

# Lawrence Berkeley National Laboratory

## Lawrence Berkeley National Laboratory

### **Title**

Exact and variational solutions of 3D Eigenmodes in high gain Free Electron Lasers

### **Permalink**

<https://escholarship.org/uc/item/0rh0j6cg>

### **Author**

Xie, M.

### **Publication Date**

1999-10-25

Peer reviewed



ERNEST ORLANDO LAWRENCE  
BERKELEY NATIONAL LABORATORY

**Exact and Variational Solutions  
of 3D Eigenmodes in High  
Gain Free Electron Lasers**

Ming Xie

**Accelerator and Fusion  
Research Division**

October 1999

Submitted to  
*Physical Review Letters*

REFERENCE COPY |  
Does Not |  
Circulate |

Lawrence Berkeley National Laboratory  
Bldg. 50 Library - Ref.

Copy 1

LBLN-44477

#### **DISCLAIMER**

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor The Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or The Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof, or The Regents of the University of California.

Ernest Orlando Lawrence Berkeley National Laboratory  
is an equal opportunity employer.

LBNL-44477  
CBP Note-327

# **Exact and Variational Solutions of 3D Eigenmodes in High Gain Free Electron Lasers**

Ming Xie

Accelerator and Fusion Research Division  
Lawrence Berkeley National Laboratory  
Berkeley, CA 94720

October 1999

Submitted to Physical Review Letters

This work was supported by the Director, Office of Energy Research, Office of High Energy and Nuclear Physics, of the U.S. Department of Energy under contract No.DE-AC03-76SF00098.



# Exact and Variational Solutions of 3D Eigenmodes in High Gain Free Electron Lasers

Ming Xie

Lawrence Berkeley National Laboratory, Berkeley, California 94720, USA

(October 11, 1999)

Exact solution and variational approximation of eigenmodes in high gain Free Electron Lasers (FELs) are presented. These eigenmodes specify transverse profiles and exponential growth rates of the laser field before saturation. They are self-consistent solutions of coupled Maxwell-Vlasov equations describing FEL interaction taking into account the effects due to energy spread, emittance and betatron oscillations of the electron beam, as well as diffraction and optical guiding of the laser field. A new formalism of scaling is introduced and based on which solutions in various limiting cases are discussed. In addition, a fitting formula is obtained from interpolating the variational solution for quick calculation of exponential growth rate of the fundamental mode.

PACS numbers: 41.60.Cr, 42.55.Vc, 52.35.Hr, 02.60.Nm

The main objective of this letter is the determination of exponential growing modes (eigenmodes) in high gain FELs, taking into account the effects due to energy spread, emittance and betatron oscillations of the electron beam, as well as diffraction and optical guiding of the laser field. To deal with all these effects simultaneously, the most effective approach for analytical investigation is through coupled Maxwell-Vlasov equations. An equation satisfied by the modes of laser field was first derived by Kim [1], but without providing a solution. The first approximate solution of the equation was obtained by Yu et al. [2] for the fundamental mode, using a variational technique first introduced by Xie et al. [3]. The approximate solution [2] assumes a waterbag model for unperturbed electron distribution in transverse phase space. Later, a special 2D case (sheet beam) of Gaussian model was considered by Hafizi et al. [4] for the fundamental mode, using also the variational technique. Taking a different approach from that of Kim [1] in handling the coupled Maxwell-Vlasov equations, Chin et al. [5] derived an equation satisfied by the mode of perturbed distribution function and obtained another approximate solution for the fundamental mode. However, this solution is known [5] to have a significant systematic error when approaching to the 1D limit.

In this letter, we present the first exact solutions of 3D FEL eigenmodes, both fundamental and higher order. The unperturbed electron distribution is assumed to be of Gaussian shape in four dimensional transverse phase space and in energy variable, but uniform in longitudinal coordinate. For the fundamental mode, a variational solution is derived and from which a fitting formula is generated for the growth rate. A new formalism of scaling

is introduced and based on which solutions are presented and discussed in various limiting cases.

The eigenmodes of laser field independent of initial condition can be determined by the equation [1]

$$\left(\frac{\partial^2}{\partial \mathbf{x}^2} + \frac{ik_r}{L_{1d}}q\right) E(\mathbf{x}) = \frac{hk_r}{4L_{1d}^3} \int_{-\infty}^0 ds \int_{-\infty}^{\infty} d^2\mathbf{p} \int_{-\infty}^{\infty} d\eta f_{\parallel}(\eta) f_{\perp}(\mathbf{x}^2 + \mathbf{p}^2/k_{\beta}^2) s e^{\Phi} E[\mathbf{x} \cos(k_{\beta}s) + (\mathbf{p}/k_{\beta}) \sin(k_{\beta}s)], \quad (1)$$

where

$$\Phi = \left[ \frac{q}{2L_{1d}} + i2k_w\eta - ik_w\Delta\nu - \frac{ik_r k_{\beta}^2}{2} (\mathbf{x}^2 + \mathbf{p}^2/k_{\beta}^2) \right] s,$$

$k_r = 2\gamma_0^2 k_w / (1 + a_w^2)$ ,  $\eta = (\gamma - \gamma_0) / \gamma_0$ ,  $\Delta\nu = (\omega - \omega_r) / \omega_r$  and  $h = (2/\sqrt{3})^3$ . The transverse profile of the slowly varying monochromatic laser field,  $E(\mathbf{x})$ , is defined by  $\mathcal{E}(\mathbf{x}, z, t) = E(\mathbf{x}) \exp[qz/2L_{1d} + i(kz - \omega t)]$ . To comply with a new scaling to be introduced later, here the complex exponential growth rate (eigenvalue),  $q$ , is scaled by the 1D power gain length,  $L_{1d} = 1/2\sqrt{3}k_w\rho$ , where  $\rho = \sqrt[3]{\pi r_e n_0 a_w^2 f_B^2 / 4k_w^2 \gamma_0^3}$  is the Pierce parameter,  $f_B = 1$  for helical wiggler,  $f_B = J_0(a_w^2/2(1 + a_w^2)) - J_1(a_w^2/2(1 + a_w^2))$  for planar wiggler,  $a_w = 0.934\lambda_w[\text{cm}]B_{rms}[\text{T}]$ ,  $n_0$  is the peak electron density on the axis, and  $r_e$  is the classical radius of electron. It is noted that the term proportional to  $\mathbf{x}^2$  was absent from the phase factor  $\Phi$  in the original equation [1] and corrected later [2].

The focusing system for the confinement of electron beam in wiggler is assumed to have a transverse gradient invariant along the beam axis. It is characterized by a constant betafunction  $\beta_f$  in both transverse planes. Thus betatron motion is governed by  $\mathbf{p} = d\mathbf{x}/dz$ ,  $d\mathbf{p}/dz = -k_{\beta}^2\mathbf{x}$ . In particular for natural wiggler focusing,  $k_{\beta} = k_w a_w / \sqrt{2}\gamma_0$ . Respectively, the unperturbed longitudinal and transverse distribution functions are normalized according to  $\int_{-\infty}^{\infty} d\eta f_{\parallel}(\eta) = 1$  and  $u(\mathbf{x} = 0) = 1$ , where  $u(\mathbf{x}) = \int_{-\infty}^{\infty} d^2\mathbf{p} f_{\perp}(\mathbf{x}^2 + \mathbf{p}^2/k_{\beta}^2)$ .

For convenience, Eq. (1) can be reduced to [2]

$$\left(\frac{\partial^2}{\partial \mathbf{x}^2} + \frac{ik_r}{L_{1d}}q\right) E(\mathbf{x}) = \int_{-\infty}^{\infty} d^2\mathbf{x}' \Gamma(\mathbf{x}, \mathbf{x}') E(\mathbf{x}'), \quad (2)$$

where

$$\Gamma(\mathbf{x}, \mathbf{x}') = \int_{-\infty}^0 ds \int_{-\infty}^{\infty} d\eta \frac{hk_r k_{\beta}^2 s}{4L_{1d}^3 \sin^2(k_{\beta}s)} e^{\Phi} f_{\parallel}(\eta) f_{\perp}(\mathbf{x}),$$

$$\chi \equiv \mathbf{x}^2 + \mathbf{p}^2/k_\beta^2 = \frac{\mathbf{x}^2 + \mathbf{x}'^2 - 2\mathbf{x}\cdot\mathbf{x}' \cos(k_\beta s)}{\sin^2(k_\beta s)}.$$

Now specify the unperturbed electron distribution as:

$$f_{\parallel}(\eta) = \frac{1}{\sqrt{2\pi}\sigma_\eta} e^{-\eta^2/2\sigma_\eta^2}, \quad (3)$$

$$f_{\perp}(\mathbf{x}^2 + \mathbf{p}^2/k_\beta^2) = \frac{1}{2\pi\sigma_x^2 k_\beta^2} e^{-(\mathbf{x}^2 + \mathbf{p}^2/k_\beta^2)/2\sigma_x^2}. \quad (4)$$

Here the transverse distribution is matched to the betatron focusing channel, giving rise to a constant beam size,  $\sigma_x$ . With Eqs.(3,4) and  $\mathbf{X} = \mathbf{x}/\sigma_x$ ,  $\tau = s/2L_{1d}$ , Eq.(2) can be expressed in a scaled form

$$\left(2\eta_d \frac{\partial^2}{\partial \mathbf{X}^2} + iq\right) E(\mathbf{X}) = \int_{-\infty}^{\infty} d^2\mathbf{X}' \Pi(\mathbf{X}, \mathbf{X}') E(\mathbf{X}'), \quad (5)$$

where

$$\begin{aligned} \Pi(\mathbf{X}, \mathbf{X}') &= \int_{-\infty}^0 \frac{\tau d\tau h}{2\pi \sin^2(2\sqrt{\eta_d \eta_\epsilon \tau})} e^{\Psi}, \\ \Psi &= (q - i\eta_\omega)\tau - 2\eta_\gamma^2 \tau^2 \\ &\quad - \frac{(1 + i\eta_\epsilon \tau)[\mathbf{X}^2 + \mathbf{X}'^2 - 2\mathbf{X}\cdot\mathbf{X}' \cos(2\sqrt{\eta_d \eta_\epsilon \tau})]}{2 \sin^2(2\sqrt{\eta_d \eta_\epsilon \tau})}. \end{aligned}$$

There are four scaling parameters [6] in Eq.(5):  $\eta_d = 1/F_d$  is a diffraction parameter, where  $F_d = 2k_r \sigma_x^2 / L_{1d}$  is a Fresnel number of the electron beam corresponding to a length scale of  $L_{1d}$ ;  $\eta_\epsilon = 4\pi(L_{1d}/\lambda_\beta)k_r \epsilon$  and  $\eta_\gamma = 4\pi(L_{1d}/\lambda_\omega)\sigma_\eta$  characterize the effective spread in longitudinal velocity due to emittance and betatron focusing and due to energy spread, respectively, where  $\lambda_\beta = 2\pi\beta_f$ ,  $\epsilon = k_\beta \sigma_x^2$  is rms beam emittance and  $\sigma_\eta$  is relative rms energy spread; finally,  $\eta_\omega = 4\pi(L_{1d}/\lambda_\omega)\Delta\nu$  is a frequency detuning parameter. The Pierce parameter can now be expressed more conveniently as  $\rho = \sqrt[3]{(I/I_A)(\lambda_\omega a_\omega f_B / 2\pi\sigma_x)^2 (1/2\gamma_0)^3}$ , where  $I$  is the peak beam current and  $I_A = 17.05$  kA is the Alfvén current.

It has been shown [2,7,8] that FEL equations can be scaled with a minimum number of scaling parameters and in different ways. The scaling formalism introduced here, termed  $L_{1d}$  scaling, differs from the previous ones in the following aspects. First, parameter  $\eta_\epsilon$  is chosen to emphasize the combined effect of emittance and betatron focusing, rather than using  $k_r \epsilon$  or  $k_\beta/k_\omega \rho$  separately. Second, by employing the scaling with  $L_{1d}$ , rather than with  $\rho$  or  $D$ , the formulation is made more transparent and elegant, and its presentation and elucidation more convenient, as it will become evident later on.

In the 1D limit without diffraction,  $\eta_d = 0$ , all modes are degenerate with the same eigenvalue and Eq.(5) becomes

$$q + ih \int_{-\infty}^0 \frac{\tau d\tau e^{f_1}}{1 + i\eta_\epsilon \tau} = 0, \quad (6)$$

where  $f_1 = (q - i\eta_\omega)\tau - 2\eta_\gamma^2 \tau^2$ . Further, if  $\eta_\epsilon = 0$  and  $\eta_\gamma = 0$ , then,  $q(q - i\eta_\omega)^2 - ih = 0$ . This is the well-known 1D cubic equation [8] which admits root with the highest growth rate,  $q = 1 + i/\sqrt{3}$ , at  $\eta_\omega = 0$ . From now on we will refer the origin,  $\{0, 0, 0, 0\}$ , in the scaled parameter space  $\{\eta_d, \eta_\epsilon, \eta_\gamma, \eta_\omega\}$  as the 1D, ideal beam limit. In this limit, the scaled growth rate,  $q_r \equiv L_{1d}/L_g$ , reaches the absolute maximum of unity, where  $L_g$  is the power gain length by definition.

Another limiting case is known as the parallel beam limit, which can be obtained from Eq.(5) with  $\eta_\epsilon = 0$

$$\left[2\eta_d \frac{\partial^2}{\partial \mathbf{X}^2} + iq - h e^{-\mathbf{X}^2/2} \int_{-\infty}^0 \tau d\tau e^{f_1}\right] E(\mathbf{X}) = 0.$$

Further, if  $\eta_\gamma = 0$ , then for axially symmetric modes

$$\left[2\eta_d \frac{d}{RdR} \left(R \frac{d}{dR}\right) + iq + \frac{h}{(q - i\eta_\omega)^2} e^{-R^2/2}\right] E(R) = 0.$$

This is the same equation systematically studied earlier by Xie et al. [3,9,10], where both exact solutions for all modes and variational approximation for the fundamental mode were obtained.

In polar coordinate  $\mathbf{X} = \{R, \phi\}$ , Eq.(5) reads

$$\begin{aligned} \left[2\eta_d \left[\frac{d}{RdR} \left(R \frac{d}{dR}\right) - \frac{m^2}{R^2}\right] + iq\right] E_m(R) \\ = \int_0^\infty R' dR' G_m(R, R') E_m(R'), \quad (7) \end{aligned}$$

where  $m$  is the azimuthal mode index and

$$\begin{aligned} G_m(R, R') &= \int_{-\infty}^0 \frac{\tau d\tau i^{-m} h}{\sin^2(2\sqrt{\eta_d \eta_\epsilon \tau})} e^U J_m(V), \\ U &= (q - i\eta_\omega)\tau - 2\eta_\gamma^2 \tau^2 - \frac{(1 + i\eta_\epsilon \tau)(R^2 + R'^2)}{2 \sin^2(2\sqrt{\eta_d \eta_\epsilon \tau})}, \\ V &= \frac{i(1 + i\eta_\epsilon \tau) \cos(2\sqrt{\eta_d \eta_\epsilon \tau}) R R'}{\sin^2(2\sqrt{\eta_d \eta_\epsilon \tau})}. \end{aligned}$$

Applying Hankel transform pair

$$\begin{aligned} E_m(Q) &= \int_0^\infty R dR J_m(QR) E_m(R), \\ E_m(R) &= \int_0^\infty Q dQ J_m(QR) E_m(Q), \end{aligned}$$

Eq.(7) can be converted into an integral equation

$$E_m(Q) = \int_0^\infty Q' dQ' T_m(Q, Q') E_m(Q'), \quad (8)$$

where

$$T_m(Q, Q') = \frac{1}{iq - 2\eta_d Q^2} \int_0^\infty R dR \int_0^\infty R' dR' J_m(QR) J_m(Q'R') G_m(R, R').$$

In explicit form

$$T_m(Q, Q') = \frac{i^{-m} h}{iq - 2\eta_d Q^2} \int_{-\infty}^0 \frac{\tau d\tau}{(1 + i\eta_\epsilon \tau)^2} e^{\Omega} J_m \left[ \frac{i \cos(2\sqrt{\eta_d \eta_\epsilon \tau}) Q Q'}{1 + i\eta_\epsilon \tau} \right],$$

where

$$\Omega = (q - i\eta_\omega)\tau - 2\eta_\gamma^2 \tau^2 - \frac{Q^2 + Q'^2}{2(1 + i\eta_\epsilon \tau)}.$$

Upon discretization in  $Q$  space, the integral equation, Eq.(8), can be casted into a matrix form:  $[\mathbf{T}_m(q) - \mathbf{I}]\mathbf{E}_m = 0$ , where  $\mathbf{I}$  is a unit matrix. Then all the eigenvalues,  $q_{nm}$ , can be determined by solving equation:  $\|\mathbf{T}_m(q) - \mathbf{I}\| = 0$ . The corresponding eigenmode,  $\mathbf{E}_{nm}$ , can be calculated subsequently given the matrix  $\mathbf{T}_m(q_{nm})$ , where  $n$  is the radial mode index.

Consider LCLS nominal case as an example with the following parameters [11]:  $\lambda_r = 1.5\text{\AA}$ ,  $\gamma_0 = 28009$ ,  $I = 3.4\text{kA}$ ,  $\gamma_0\epsilon = 1.5\text{mm-mrad}$ ,  $\sigma_\eta = 2 \times 10^{-4}$ ,  $\beta_f = 18\text{m}$ , a planar wiggler with  $\lambda_w = 3\text{cm}$  and  $\sqrt{2}a_w = 3.7$ . The scaled parameters take the values:  $\eta_d = 0.0367$ ,  $\eta_\epsilon = 0.739$  and  $\eta_\gamma = 0.248$ . For the three lowest order modes,  $E_{00}$ ,  $E_{10}$  and  $E_{01}$ , the eigenvalues and corresponding optimal detunings are, respectively,  $q_{00} = 0.4901 + i0.227$  ( $\eta_\omega = -1.161$ ),  $q_{10} = 0.125 - i0.0245$  ( $\eta_\omega = -1.52$ ) and  $q_{01} = 0.297 + i0.0662$  ( $\eta_\omega = -1.40$ ). Intensity profile of the fundamental mode is shown in Fig.(1).




FIG. 1. Intensity profile of  $E_{00}$  mode from exact solution and variational approximation, superimposed with electron density profile.

Next, we present an approximate solution for the fundamental mode,  $E_{00}$ . Similar solutions for the higher order modes,  $E_{10}$  and  $E_{01}$  will be published elsewhere.

The approximate solution derived here is, first of all, more efficient in calculation than the exact one. Secondly, it provides more physical insights, in particular on the mode profile, in a simpler manner. The solution is based on an approximation technique introduced by Xie et al. [3]. There, standard variational method [12] was first extended to treat the eigenvalue problem in which the operator of the eigenmode equation, being neither Hermitian nor self-adjoint, has a nonlinear dependence on the complex eigenvalue. The generalized variational technique, acclaimed as one of the most flexible and general approximation method [13], has later been proven effective for a variety of 2D or 3D FEL eigenvalue problems [2,4,13,14]. According to the recipe [3], a variational functional may be constructed from Eq.(7) as follows:

$$\int_0^\infty R dR E(R) \left[ 2\eta_d \frac{d}{R dR} \left( R \frac{d}{dR} \right) + iq \right] E(R) = \int_0^\infty R dR \int_0^\infty R' dR' E(R) G_0(R, R') E(R'). \quad (9)$$

Substituting into Eq.(9) a trial function of the form,  $E(R) = \exp(-\alpha R^2)$ , where  $\alpha$  is a complex variational parameter to be determined, and applying the variational condition,  $\delta q / \delta \alpha = 0$ , to the resulting equation, we obtain the following two equations from which the eigenvalue  $q$  and mode parameter  $\alpha$  can be determined,

$$F_1(q, \alpha) \equiv \frac{iq}{4\alpha} - \eta_d - \int_{-\infty}^0 \tau d\tau h \frac{e^{f_1}}{f_2} = 0, \quad (10)$$

$$F_2(q, \alpha) \equiv \frac{\partial F_1}{\partial \alpha} = -\frac{iq}{4\alpha^2} + \int_{-\infty}^0 \tau d\tau h \frac{f_3 e^{f_1}}{f_2^2} = 0, \quad (11)$$

where

$$f_2 = (1 + i\eta_\epsilon \tau)^2 + 4\alpha(1 + i\eta_\epsilon \tau) + 4\alpha^2 \sin^2(2\sqrt{\eta_d \eta_\epsilon \tau}),$$

$$f_3 = 4(1 + i\eta_\epsilon \tau) + 8\alpha \sin^2(2\sqrt{\eta_d \eta_\epsilon \tau}).$$

To take the 1D limit appropriately, a singularity is removed by introducing  $\alpha = \alpha_s(\eta_d, \eta_\epsilon, \eta_\gamma, \eta_\omega) / \sqrt{\eta_d}$ , where  $\alpha_s$  is a well-behaved, smooth function of its arguments. Then by taking  $\eta_d = 0$ , Eqs.(10,11) lead to Eq.(6) for the eigenvalue and for the mode parameter

$$\alpha_s = \frac{1}{4} \sqrt{\frac{h \int_{-\infty}^0 \tau d\tau e^{f_1}}{\eta_\epsilon h \int_{-\infty}^0 \tau^3 d\tau e^{f_1} / (1 + i\eta_\epsilon \tau)^2 - 1}}. \quad (12)$$

Therefore in the 1D limit, variational solutions are the same as the exact ones. On the other hand, in the parallel beam limit with  $\eta_\epsilon = 0$ , and furthermore with  $\eta_\gamma = 0$ , Eqs.(10,11) become

$$iq\bar{q}^2 + \eta_d \bar{q}^2 - 2\sqrt{h\eta_d} \bar{q} + h = 0, \quad (13)$$

$$\alpha = \frac{1}{4} \left( \sqrt{\frac{h}{\eta_d \bar{q}^2}} - 1 \right), \quad (14)$$



where  $\bar{q} = q - i\eta_\omega$ . These are the same equations derived earlier by Xie et al. [3]. Equation (13) is a 3D extension of the usual 1D cubic equation.

Given parameter  $\alpha$ , mode properties can be determined completely by comparing  $E(R \equiv r/\sigma_x) = \exp(-\alpha R^2)$  with the usual Gaussian mode  $E(r) = \exp(-r^2/w^2 + ik_r r^2/2R_c)$ . Thus  $w/2\sigma_x = \sqrt{1/4\alpha_r}$  and  $R_c/L_{1d} = -F_d/4\alpha_i$ , where  $w$  is the mode size and  $R_c$  the radius of phasefront curvature. Due to optical guiding,  $w$  remains constant along the wiggler and  $R_c$  is always positive (diverging phasefront) for the growing mode [3]. If such a mode is allowed to propagate in free space from a location such as the end of the wiggler, the mode will diverge with a Rayleigh length  $L_r$ , and have an apparent waist  $w_0$ , located within the wiggler at a distance  $z_0$  from the end of the wiggler, specifically:  $L_r/L_{1d} = F_d/4\alpha_r[1 + (\alpha_i/\alpha_r)^2]$ ,  $w_0/2\sigma_x = 1/\sqrt{4\alpha_r[1 + (\alpha_i/\alpha_r)^2]}$  and  $z_0/L_{1d} = -F_d/4\alpha_i[1 + (\alpha_r/\alpha_i)^2]$ . In addition, the far field divergence angle is  $\theta_d \equiv w_0/L_r = \sqrt{\alpha_r[1 + (\alpha_i/\alpha_r)^2]}(\lambda_r/\pi\sigma_x)$ . For the LCLS example, the variational method yields  $q = 0.4902 + i0.2271$  and  $\alpha_s = 0.099 - i0.11$ , optimized at  $\eta_\omega = -1.161$ . A comparison of mode profiles is shown in Fig.(1).

One of the most important FEL performance parameter is the gain length of the fundamental mode,  $L_g$ . To facilitate quick calculation of this quantity, a fitting formula is generated in a scaled form

$$\frac{L_{1d}}{L_g} \equiv q_r = \mathcal{F}(\eta_d, \eta_\epsilon, \eta_\gamma)|_{\eta_\omega^*}, \quad (15)$$

where at each point in the three dimensional parameter space  $\{\eta_d, \eta_\epsilon, \eta_\gamma\}$ , the scaled quantity,  $L_{1d}/L_g$ , is maximized at the optimal detuning  $\eta_\omega^*$ .

The function  $\mathcal{F}$  is determined by interpolating the variational solutions with the following functional form

$$\frac{L_{1d}}{L_g} = \frac{1}{1 + \Lambda}, \quad (16)$$

where

$$\begin{aligned} \Lambda = & a_1\eta_d^{a_2} + a_3\eta_\epsilon^{a_4} + a_5\eta_\gamma^{a_6} \\ & + a_7\eta_\epsilon^{a_8}\eta_\gamma^{a_9} + a_{10}\eta_d^{a_{11}}\eta_\gamma^{a_{12}} + a_{13}\eta_d^{a_{14}}\eta_\epsilon^{a_{15}} \\ & + a_{16}\eta_d^{a_{17}}\eta_\epsilon^{a_{18}}\eta_\gamma^{a_{19}}, \end{aligned}$$

and the 19 fitting parameters are given in Table 1.

**Table 1.** Fitting parameters for gain length.

$a_1 = 0.45$	$a_2 = 0.57$	$a_3 = 0.55$	$a_4 = 1.6$
$a_5 = 3$	$a_6 = 2$	$a_7 = 0.35$	$a_8 = 2.9$
$a_9 = 2.4$	$a_{10} = 51$	$a_{11} = 0.95$	$a_{12} = 3$
$a_{13} = 5.4$	$a_{14} = 0.7$	$a_{15} = 1.9$	$a_{16} = 1140$
$a_{17} = 2.2$	$a_{18} = 2.9$	$a_{19} = 3.2$	

This is the same fitting formula published before without giving the derivation [6].

In conclusions, a systematic approach is developed in three steps for the determination of 3D eigenmodes from Eq.(1). First and foremost, the exact solutions of both fundamental and higher order modes are obtained for the first time. Based on these solutions, complete information on the eigenmodes including eigenvalues and mode profiles can be extracted, examined, and used as a benchmark as well as an inspiration for approximate solutions. Secondly, a variational approximate solution of the fundamental mode is derived for the first time for Gaussian model. The solution is shown to be highly accurate in the parameter regime of interest to short wavelength FELs. It is also highly efficient and robust in calculation, and as a result, the solution has been mapped out in the entire scaled parameter space. Finally, based on the wealth of information obtained with the variational solution, a transparent and elegant fitting formula for the gain length is generated. Apart from being compared with the variational solution, the formula has been found to be in good agreement with full-blown simulations [15]. Because of its convenience and accuracy, the formula has been widely used for design and optimization of high gain FEL systems [11]. This work was supported by the U.S. Department of Energy under contract No.DE-AC03-76SF00098.

- 
- [1] K-J. Kim, Phys. Rev. Lett. **57**, 1871 (1986).
  - [2] L. Yu, S. Krinsky and R. Gluckstern, Phys. Rev. Lett. **64**, 3011 (1990).
  - [3] M. Xie and D. Deacon, Nucl. Instr. Meth. A **250**, 426 (1986).
  - [4] B. Hafzi and C. Roberson, Phys. Rev. Lett. **68**, 3539 (1992).
  - [5] Y. Chin, K-J. Kim and M. Xie, Phys. Rev. A **46**, 6662 (1992).
  - [6] M. Xie, IEEE Proc. for PAC95, No.95CH3584, 183 (1996).
  - [7] G. Moore, Nucl. Instr. Meth. A **250**, 381 (1986).
  - [8] R. Bonifacio, C. Pellegrini and L. Narducci, Opt. Comm. **50**, 373 (1984).
  - [9] M. Xie, D. Deacon and J. Madey, Nucl. Instr. Meth. A **296**, 672 (1990).
  - [10] M. Xie, D. Deacon and J. Madey, Phys. Rev. A **41**, 1662 (1990).
  - [11] LCLS Design Study Report, SLAC-R-521, (1998).
  - [12] P. Morse and H. Feshbach, *Methods of Theoretical Physics*, (McGraw-Hill, New York, 1953), p.1108.
  - [13] P. Luchini and H. Motz, *Undulators and Free-Electron Lasers*, (Clarendon Press, Oxford, 1990), p.160.
  - [14] P. Luchini and S. Solimeno, Nucl. Instr. Meth. A **272**, 311 (1988).
  - [15] H. Freund and P. O'Shea, Phys. Rev. Lett. **80**, 520 (1998).



