

UCLA

UCLA Previously Published Works

Title

OnlineStats.jl: A Julia package for statistics on data streams

Permalink

<https://escholarship.org/uc/item/28b378gm>

Journal

The Journal of Open Source Software, 5(46)

ISSN

2475-9066

Authors

Day, Josh

Zhou, Hua

Publication Date

2020

DOI

10.21105/joss.01816

Copyright Information

This work is made available under the terms of a Creative Commons Attribution License, available at <https://creativecommons.org/licenses/by/4.0/>

Peer reviewed



HHS Public Access

Author manuscript

J Open Source Softw. Author manuscript; available in PMC 2020 June 10.

Published in final edited form as:

J Open Source Softw. 2020 ; 5(46): . doi:10.21105/joss.01816.

OnlineStats.jl: A Julia package for statistics on data streams

Josh Day¹, Hua Zhou²

¹Loon Analytics, LLC

²UCLA Biostatistics

Summary

The growing prevalence of big and streaming data requires a new generation of tools. Data often has infinite size in the sense that new observations are continually arriving daily, hourly, etc. In recent years, several new technologies such as Kafka (Apache Software Foundation, n.d.-a) and Spark Streaming (Apache Software Foundation, n.d.-b) have been introduced for processing streaming data. Statistical tools for data streams, however, are under-developed and offer only basic functionality. The majority of statistical software can only operate on finite batches and require re-loading possibly large datasets for seemingly simple tasks such as incorporating a few more observations into an analysis.

OnlineStats is a Julia (Bezanson, Edelman, Karpinski, & Shah, 2017) package for high-performance online algorithms. The OnlineStats framework is easily extensible, includes a large catalog of algorithms, provides primitives for parallel computing, and offers a weighting mechanism that allows new observations have a higher relative influence over the value of the statistic/model/visualization.

Interface

Each algorithm is associated with its own type (e.g. Mean, Variance, etc.). The OnlineStats interface is built on several key functions from the OnlineStatsBase package. A new type must provide implementations of these functions in order to use the rest of the OnlineStats framework.

Updating

```
OnlineStatsBase._fit!(stat, y)
```

The `_fit!` method determines how the statistic `stat` is updated with a single observation `y`. Each `OnlineStat` is a concrete subtype of `OnlineStat{T}`, where `T` is the type of a single observation. The `fit!(stat::OnlineStat{T}, y::T)` method simply calls `_fit!`. When `fit!(stat::OnlineStat{T}, y::S)` is called (where `S` is not a subtype of `T`), `y` is iterated through and `fit!` is called on each element.

Update Weights—Many OnlineStats incorporate a weight function that determines the influence of the next observation. For example, the online update for a mean $\mu^{(t)}$ given its current state $\mu^{(t-1)}$ and new observation y_t is

$$\mu^{(t)} = (1 - \tau^{-1})\mu^{(t-1)} + \tau^{-1}y_t.$$

OnlineStats generalizes this update to use weights that are a function of t :

$$\mu^{(t)} = [1 - w(t)]\mu^{(t-1)} + w(t)y_t.$$

Therefore, for example, $w(t) = t^{-1}$ returns the analytical mean and $w(t) = \lambda$ ($0 < \lambda < 1$) returns an exponentially weighted mean.

Merging

```
OnlineStatsBase._merge!(stat1, stat2)
```

The `_merge!` function merges the state of `stat2` into `stat1` and facilitates parallel computation. This function is optional to implement, as merging is not guaranteed to be well-defined for a given statistic/algorithm. The default definition prints out a warning that no merging occurred.

Returning the State

```
OnlineStatsBase.value(stat, args...; kw...)
```

The `value` function returns the value of the estimator (optionally determined by positional arguments `args` and keyword arguments `kw`). Depending on the type, this may need to be calculated from its state. By default, this returns the first field of the type.

```
OnlineStatsBase.nobs(stat)
```

The `nobs` function returns the number of observations that the statistic has seen. By default this returns the `n` field from the algorithm's type (`stat.n`).

Example

The Mean type provides an easy-to-understand full example of how to implement a new algorithm. The update formula, as previously stated, is:

$$\mu^{(t)} = [1 - w(t)]\mu^{(t-1)} + w(t)y_t.$$

The merge formula for two means, $\mu_1^{(t)}$ and $\mu_2^{(s)}$, generalizes the above equation to:

$$\mu_{merged}^{(t+s)} = [1 - s/(t+s)]\mu_1^{(t)} + [s/(t+s)]\mu_2^{(s)}.$$

Converting these formulas into Julia code, we get the following implementation. Note that Mean is parameterized by the data type that stores the mean value so that non-standard types such as complex numbers can be used.

```
mutable struct Mean{T,W} <: OnlineStat{Number}
    : :T
    weight: :W
    n: :Int
end
function Mean(T: :Type{<:Number} = Float64; weight = inv)
    Mean(zero(T), weight, 0)
end
function _fit!(o: :Mean{T}, x) where {T}
    o.n += 1
    w = T(o.weight(o.n))
    o. += w * (x - o.)
end
function _merge!(o: :Mean, o2: :Mean)
    o.n += o2.n
    o. += (o2.n / o.n) * (o2. - o.)
end
```

References

- Apache Software Foundation. (n.d.-a). Kafka. Retrieved from <https://kafka.apache.org>
- Apache Software Foundation. (n.d.-b). Spark streaming. Retrieved from <https://spark.apache.org/streaming/>
- Bezanson J, Edelman A, Karpinski S, & Shah VB (2017). Julia: A fresh approach to numerical computing. *SIAM Review*, 59(1), 65–98. doi:10.1137/141000671