

Lawrence Berkeley National Laboratory

Recent Work

Title

STEERING MAGNETS

Permalink

<https://escholarship.org/uc/item/2ff759g7>

Author

Reimers, Richard M.

Publication Date

1979-11-01



Lawrence Berkeley Laboratory

UNIVERSITY OF CALIFORNIA, BERKELEY

Engineering & Technical Services Division


For Reference

Not to be taken from this room

RECEIVED
LAWRENCE
BERKELEY LABORATORY

MAR 24 1980

LIBRARY AND
DOCUMENTS SECTION



DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.

ENGINEERING NOTE

SC0120

M5428

1 of 1

AUTHOR

R. Reimers



DEPARTMENT

Mechanical

LOCATION

Berkeley

DATE

11/5/79

PROGRAM - PROJECT - JOB

STOCHASTIC BEAM COOLING

CALCULATIONS, GENERAL

TITLE

STEERING MAGNETS

This note describes the steering magnets installed in December at Fermilab to deflect the 200 MeV proton beam associated with the cooling ring. Another note by LBL's Don Nelson describes measurements:

Type	--	C type, solid core
Design	--	Christoph Leemann, Dick Reimers
Fabrication	--	LBL Shops
Power supply	--	FNAL, on hand
Beam energy	E	200 MeV
Particle type	--	Proton
Beam Stay Clear	BSC	2.75 inch DIA (= 69.8 mm)
Bend angle	θ	0.5 milliradians
Beam stiffness	B_p	2.1 Tesla meters (=21 kilogauss meters)
Gap field = $\theta B_p / L_{eff}$	B_g	~ 37 gauss
Gap @ beam C/L	g	6.875 inches
Efficiency est.	η	~ .95
Field quality inside	$ \Delta B/B $.024 total over 7 cm. distance
BSC		
Core length @ beam C/L	--	~ 9.3 inches
Core Weight	--	17 lbs.
Amp turns	NI	540
No. coils	--	1
Turns	N	108
Current	I	5 Amps D.C.
Coil resistance	R	~ .24 Ω
Voltage drop/coil	V	~ 1.20 volts
Conductor O.D.	d	.114 inch (#9 copper w/Formvar)
Power/magnet	P	~ 6 watts
Cooling type	--	Air convection
Maximum coil temperature	--	~ 41 deg. C (est)
Heat Loss rate	--	.06 watt/in. ²
Temperature rise	--	~ 21 deg. C (est)
Measurement		Don Nelson, Bob Main

- Dist.:
- G. Lambertson
 - C. Leemann
 - T. Chan
 - R. Avery
 - R. Main
 - D. Nelson
 - E. Gray (FNAL)
 - D. Young (FNAL)
 - F. Mills (FNAL)

This report was done with support from the Department of Energy. Any conclusions or opinions expressed in this report represent solely those of the author(s) and not necessarily those of The Regents of the University of California, the Lawrence Berkeley Laboratory or the Department of Energy.

Reference to a company or product name does not imply approval or recommendation of the product by the University of California or the U.S. Department of Energy to the exclusion of others that may be suitable.

TECHNICAL INFORMATION DEPARTMENT
LAWRENCE BERKELEY LABORATORY
UNIVERSITY OF CALIFORNIA
BERKELEY, CALIFORNIA 94720