

Lawrence Berkeley National Laboratory

Lawrence Berkeley National Laboratory

Title

FOCUSING OF HEAVY ION BEAMS ON A FUSION TARGET

Permalink

<https://escholarship.org/uc/item/3g51h852>

Author

Garren, A.

Publication Date

1981-03-01

Peer reviewed



Lawrence Berkeley Laboratory

UNIVERSITY OF CALIFORNIA

Accelerator & Fusion Research Division


Presented at the Particle Accelerator Conference,
Washington, D.C., March 11-13, 1981

FOCUSING OF HEAVY-ION BEAMS ON A FUSION TARGET

A. Garren, G. Krafft, and I. Haber

March 1981

MASTER



FOCUSING OF HEAVY ION BEAMS ON A FUSION TARGET*

A. Garren and G. Krafft
Lawrence Berkeley Laboratory
University of California
Berkeley, California 94720

I. Haber
Naval Research Laboratory
Washington, D. C. 20375

Summary

A beam line has been designed for transport between a periodic channel and a fusion target in a way intended to minimize effects of non-uniform transverse and longitudinal densities and of momentum spread. Principles used for the design are explained. The beam line is described and its performance as shown by envelope integration and particle simulation is presented.

Introduction

At a recent HIF workshop studies of beam lines for transport between the periodic cells and the target were made. One design included sextupole chromatic correction but ignored space charge¹. A second line including space charge² was derived from the first one, but it had too much chromatic sensitivity and tests using particle simulation showed that the beam behaved badly with a non-uniform distribution.³ The object of the present study is to produce a beam line without dipoles and sextupoles that represents a closer approach to a workable system, by application of certain design criteria.

The envelopes of ref. 2 have several features which seemed to be related to the high sensitivities: they are very different with and without current, there is a small intermediate beam waist and no transverse symmetry. In the next section the strategy and procedure to produce an improved line are described. The resulting system is given in scaled variables together with a table giving several possible realizations. The system is explained and its sensitivity to current and energy variations is presented. Lastly, self-consistent particle simulations with various initial distributions are described.

Design Strategy and Procedure

In order to reduce sensitivity to current variations, and to non-linear density distributions, the effect of space-charge forces should be reduced by minimizing beam radii. Small intermediate beam waists which produce large radii and gradients in adjacent quadrupoles should be avoided. The envelopes should be as smooth and symmetrical between the two transverse planes as possible.

Strategy

Three sets of quadrupole triplets are deployed, see Fig 1: Q1, Q2, Q3 produces a symmetrical waist W1, of radius comparable to those in the periodic lattice. Q7, Q8, Q9 matches the beam between the small radius waist W3 at the target and a large waist W2; also the radii are minimized and the transverse maxima are made roughly equal in this triplet. Q4, Q5, Q6 matches the beam between the waists W1 and W2.

Procedure

The computations were made with the SNCH computer program. The beam-line was designed using matrix methods and the gradients recalculated for the high current beam using envelope integration.

The gradient of the periodic cells is calculated to produce a given phase advance per cell μ_c for zero current. The corresponding beta-functions are used as initial conditions for the beam line design. The current is chosen for the desired space charge depressed phase μ . The phases were chosen to avoid instabilities due to perturbations of the space charge potential⁴, namely $\mu_0 = 60^\circ$, $\mu = 1.4^\circ$. The cell packing fraction is 1/2.

For design purposes, the beam was assumed to have the Kapchinskij-Vladimirskij (K-V) distribution⁵. In this case the envelope radii a_x, a_y , obey

$$\frac{d^2 a_{x,y}}{ds^2} \pm K a_{x,y} - \frac{\epsilon^2}{(a_{x,y})^3} - \frac{Q}{a_x a_y} = 0 \quad (1)$$

$$Q = \frac{4r_0 q^2 N}{A \beta \gamma^3} = 1.288 \times 10^{-7} \frac{q^2 I_p}{A(\beta \gamma)^3} \quad (2)$$

Here s is the path length, $K = (dB/dx)/(B_0)$, ϵ is the emittance, q the charge state, N the number of particles per unit length, A the atomic weight, β and γ the relative velocity and energy, and I_p is the particle current in amperes.

Scaling

The results are given in terms of scaled variables that make Eq. (1) dimensionless⁶. The gradient, path length, radius, and space charge parameters $\kappa, \theta, u,$ and Q' are given by

$$\begin{aligned} K &= K_C \kappa, & s &= K_C^{-1/2} \theta, \\ a &= K_C^{-1/4} \epsilon^{1/2} u, & Q &= \epsilon K_C^{1/2} Q' \end{aligned} \quad (3)$$

where K_C is the cell gradient. The value $Q' = 1.364$ corresponding to $\mu = 60^\circ$, $\mu = 24.4^\circ$ was used. Table I shows four parameter sets consistent with the designed system. Cases A - C represent scalings to the parameters of ref. 7. Case D gives the values actually used in this study and in ref. 2. All cases have the same pole-tip fields, and the maximum value is 4 Tesla.

* "This work was supported by the Director, Office of Energy Research, Office of Inertial Fusion, Research Division of the U.S. Department of Energy under Contract No. W-7405-ENG-48."




Fig. 1. Beam line design. Dashed/solid curves show zero/full current envelopes




Fig. 2. Beam envelopes near the target for variations of $\pm 1\%$ in momentum and up to $\pm 10\%$ in current.

Table I: Beam line parameters derivable from the system shown in Table II, and Figure 1, for U_{238} , cell pole-tip field $B'a = 1.061$ T, $Q' = 1.364$

		A	B	C	D	
Charge state	q	1	1	1	4	
Kinetic energy	T	5	10	10	10	GeV
Rigidity	$B\rho$	158	225	225	56	T-m
Particle current	I_p	205	519	830	208	A
Emittance	δy_e	2.7	4.5	9.1	12.2	mm-mr
Cell gradient	K_C	.436	.245	.153	.613	m ⁻²
Beam radius maxima:						
cells	a_c	1.5	1.9	3.1	3.1	cm
beam-line	a_B	11.0	13.8	22.1	22.1	cm
target	a_T	0.2	0.25	0.4	0.4	cm
Lengths:						
cell	L_C	4.7	6.3	8	4	m
beam-line	L_B	51.4	68.5	86.6	43.3	m
Q9-target	L_T	5.9	7.9	10	5	m

Beam-Line

The beam-line is presented in Table II and Fig. 1. Table II specifies the magnet gradients for the zero/full current cases. In Fig. 1, note that the envelopes show the desired smoothness, symmetry, and similarity between zero and full current. The waists $W1$ and $W3$ are symmetrical, $W2$ is not but the radii of the largest peaks near $W2$ are about equal.

Table II: Beam Line

Magnet	Exit position θ	Length $\Delta\theta$	Gradient K/K_C
QF	-2.74	0.78	1.00/1.00
QD	-1.17	0.78	1.00/1.00
QFH	0.00	0.39	1.21/1.00
Q1	3.57	0.39	1.13/1.46
Q2	4.71	0.59	2.03/1.92
Q3	5.46	0.39	2.23/1.58
Q4	20.63	0.78	0.08/0.17
Q5	22.63	1.17	0.19/0.28
Q6	24.83	0.78	0.14/0.22
Q7	26.55	0.78	0.42/0.41
Q8	28.61	1.17	0.47/0.47
Q9	30.02	0.78	0.35/0.34

The sensitivity of the system to current and momentum variations is shown in Table III and Fig. 2. In each case the initial conditions are those of a periodic envelope in the cells. The momentum acceptance corresponding to a doubling of the target spot area is $\Delta p/p = \pm 0.9\%$. For current variations of $\pm 10\%$ the spot size increases by about 10% .

Table III: Sensitivity of beam dimensions a_x/a_0 , a_y/a_0 at the target due to intensity and momentum variations.

Full Current $\Delta I/I$	$\Delta p/p$		
	-0.1	0.0	+0.1
-0.1	1.8/1.5	1.0/1.0	1.5/1.3
0	1.7/1.4	1.0/1.0	1.7/1.4
+0.1	1.6/1.3	1.0/1.0	1.8/1.5
Zero current	1.3/1.3	1.0/1.0	1.3/1.4




Fig. 3.

EA 813-8532




Fig. 4.

EL 513-8533





Fig. 5. Phase-space distributions at target spot

EL 813-8535



EL 813-8535

Particle Simulation

Simulations were performed to examine the sensitivity of the lens system to space charge aberrations caused by the non-uniform cross section. Spot degradations ranging from 30% to factors of two have been previously observed (3, 8-11). The simulations follow several thousand particles in their self-consistent electric fields. Figure 3 is a plot of the beam density as a function of radius for the initial K-V and non K-V distributions. Fig. 4 shows plots of the beam densities at the target spot resulting from these initial distributions. A small tail has formed and some hollowing of the beam at the center has occurred for the K-V case. Figs. 5 a, b show the phase-space distributions of the particles at the spot. Fig. 4 shows that for the beam that started out as a K-V distribution the statistical deviations have grown, and distorted the phase space ellipse. The target rms dimensions are listed in the first two lines of Table IV.

The non K-V distribution entering the lens system was established by slowly increasing the current in a matched low current beam which has a quadratic (water bag) main body and a linearly decreasing tail (11). The low current distribution was chosen so that the 90% emittance was the same as the design K-V distribution. The central density at the spot is actually greater than the reference K-V case. It is found that 90% of the particles are contained in a circle which has a radius of about 1.1 times the reference spot radius. Additionally, a K-V distribution with the same rms value as the non K-V system was also run. (Case 3 of Table IV.)

Conclusions

A line for focusing heavy ion beams on a target has been designed and shown by envelope integration and particle simulation to better accept non-uniform densities and variations in momentum and current.

Table IV: rms dimensions at target from particle simulations, divided by design rms values.

Distribution	X_{rms}	Y_{rms}	A/A_0
1 Ref. K-V	1.06	1.03	1.09
2 Non K-V	1.23	1.42	1.73
3 K-V	0.97	0.92	0.89

References

1. K.L. Brown and J.M. Peterson, Proc. Heavy Ion Fusion Workshop, Berkeley, 385, (1979).
2. A. Garren, *ibid.*, 397.
3. I. Haber, *ibid.*, 391.
4. L.J. Laslett and Lloyd Smith, IEEE Trans. Nucl. Sci., Vol. NS-26, No. 3, (1979).
5. I.M. Kapchinskij and V.V. Vladimirovskij, Proc. Intl. Conf. on High-Energy Accel. CERN, 274, (1959).
6. G. Lambertson, L.J. Laslett, and L. Smith, IEEE Trans. Nucl. Sci., Vol. NS-24, No.3., 993 (1977).
7. N. Marshall King, 1979 HIF Workshop Proceedings, p. 253, Table I.
8. I. Bozsik and I. Hofmann. Conf. on Charged Particle Optics, GieBen, FRG, (Sept., 1980).
9. I. Haber. Optical Society of America Washington, D. C., 68, (1980).
10. W. A. Barletta, S. S. Yu, Private Communication.
11. I. Haber. IEEE Trans. Nucl. Sci., NS-26, 3090, (1979).