Lawrence Berkeley National Laboratory

Recent Work

Title

PHOTON-PHOTON SCATTERING BETWEEN 4.2 AND 10 MeV AND THE 1S0 SHAPE DEPENDENT SCATTERING PAKAMETERS

Permalink

https://escholarship.org/uc/item/6j07t714

Authors

Slobodrian, R.J. Conzett, H.E. Shield, E. et al.

Publication Date

1966-07-01

University of California

Ernest O. Lawrence Radiation Laboratory

PROTON-PROTON SCATTERING BETWEEN 4.2 AND 10 MeV AND THE ¹S₀ SHAPE DEPENDENT SCATTERING PARAMETERS

TWO-WEEK LOAN COPY

This is a Library Circulating Copy which may be borrowed for two weeks. For a personal retention copy, call Tech. Info. Division, Ext. 5545

Berkeley, California

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.

Proceedings of the International Conference on Nuclear Physics, Gatlinburg, Tennessee, Sept. 12-17, 1966

UCRL-16991 Preprint

UNIVERSITY OF CALIFORNIA

Lawrence Radiation Laboratory Berkeley, California

AEC Contract No. W-7405-eng-48

PROTON-PROTON SCATTERING BETWEEN 4.2 AND 10 MeV AND THE $^1\mathrm{S}_\mathrm{O}$ SHAPE DEPENDENT SCATTERING PARAMETERS

R. J. Slobodrian, H. E. Conzett, E. Shield, and W. F. Tivol
July 1966

PROTON-PROTON SCATTERING BETWEEN 4.2 AND 10 MeV AND THE 150 SHAPE DEPENDENT SCATTERING PARAMETERS*

R. J. Slobodrian, H. E. Conzett, E. Shield, and W. F. Tivol

Lawrence Radiation Laboratory University of California Berkeley, California

July 1966

ABSTRACT

Proton-proton scattering angular distributions have been measured at 6.141, 8.097, and 9.981 MeV laboratory energy, in an experiment designed to achieve an absolute accuracy better than 1%. A phase shift analysis has produced preliminary values for the $^{1}S_{0}$ phase shifts, as well as split P and $^{1}D_{0}$ phase shifts. With this new information it is possible to reach substantially less ambiguous conclusions concerning the shape dependent parameters—P and Q than was possible up to date.

Work performed under the auspices of the U.S. Atomic Energy Commission.

PROTON-PROTON SCATTERING BETWEEN 4.2 AND 10 MeV AND THE SO

R. J. Slobodrian, H. E. Conzett, E. Shield, and W. F. Tivol

Lawrence Radiation Laboratory University of California Berkeley, California

July 1966

Low energy proton-proton scattering has been the object of very accurate experimental investigation, and of refined and sophisticated theoretical analyses in recent years. Particularly fruitful was the research carried out at Wisconsin, where the energy range between 1.397 MeV and 4.203 MeV (laboratory system) was covered by two separate experimental groups. 2,3 An accurate value of the $^{1}S_{0}$ phase shift was obtained recently at 0.3825 MeV through measurements of the interference minimum. 4 The $^{1}S_{0}$ phase shift at 0.3825 MeV has been used in conjunction with the KMBND data in order to attempt a determination of the shape parameter P, ⁵ in the expansion C^2 k cot $\delta_0 + \frac{1}{R} h(\eta) = -\frac{1}{a_p} + \frac{1}{2} r_e k^2$ - Pr 3 k 4 + Qr 5 k 6 + ..., where the symbols have the usual meaning. Several objections were raised concerning the certainty of the determination of P. 6,7,8 Gursky and Heller reported an attempt to produce a four parameter fit, that resulted in unreasonable values for the shape dependent parameters P and Q. 9 Additional difficulties arise due to the uncertainty of the accuracy of the vacuum polarization correction 10 for S waves, since this correction dominates the curvature of the low energy limit of the expression.

It can be shown that the WMF data reduce the ambiguities quite considerably, notwithstanding the reservations voiced by KMBND concerning some systematic errors contained in the data and the shortcomings of early analyses

of them. Between 4.203 MeV and 10 MeV there is an additional accurate experiment at 9.69 MeV, 12 consistent with the trend indicated by the WMF data, but inconsistent with a set of data that will be called $^{\circ}$ C (old cyclotron data), that range from 4.2 MeV to 8 MeV. Such OC data are inaccurate for the purpose of a determination of shape dependent parameters, but their trend could be interpreted as consistent with the KMBND data at 1.855, 2.425, and 3.037 MeV.

The present experiment and analysis was undertaken with the hope of providing clues to determine the shape parameters of the p-p interaction. It is well known that this point is relevant to the choice of a suitable shape of the potential in a Hamiltonian formulation of the interaction, or of a model in general. Clearly, the phase shifts themselves are sufficient for such purposes. Nevertheless, the parameterization provided by the expansion of k cot δ_0 is particularly suitable in order to visualize the degree of relevance of the information between 4.2 and 10 MeV, and also because predictions of $P^{1,13}$ and $Q^{1,14}$ are readily available in the literature.

The Berkeley 88-inch spiral ridge cyclotron was used to produce a beam of 6.141, 8.097, and 9.981 MeV at the center of the target, which consisted of 99.99% pure H_2 at about 0.1, 0.075, and 0.05 atmospheres, contained in a 20 inch scattering chamber. The pressure was measured to $\pm 0.1\%$ accuracy with a silicon oil manometer. The temperature was measured to $\pm 0.1\%$, and the total variation throughout the experiment was within $\pm 0.25\%$. The beam was accelerated as H_2^{-1} ions and conveyed through an analyzing magnet and quadrupole magnet lenses onto the scattering chamber. The beam was defined by Ni slits and carbon antiscatter baffles. The charge collection was accomplished with a Faraday cup and an integrating electrometer, accurate to

±0.1%. Calibrations of the integrating system were performed at regular intervals during the experiment. The beam direction was aligned to better than 2.5 minutes of arc. The beam energy was determined through its range in aluminum, and converted using Bichsel's experimental ranges 15; such energy determination should therefore be accurate to about 0.1%. The detection of the scattered protons was accomplished with two lithium-drifted silicon detectors, one on either side of the beam. The positioning was accurate to 1 minute of arc. The gas geometry factor was approximately 6.7×10^{-6} cm-sr. statistics were kept in the range of 0.3%. Dead time losses were kept below 1% and corrected by means of fast scalers. The spectra were stored in two RIDL 400 channel analyzers. Two monitor detectors were also used, one at 8° and the other at 25°, off the azimuthal plane. Their spectra were routed to a Nuclear Data 4096 channel PHA, into separate quadrants. Coincidences (prompt and delayed), between both detectors on the azimuthal plane were also recorded to obtain an indication of inelastic events. The net difference between real and accidental coincidences sets a limit on inelastic events at about 0.1% of the elastic cross sections. The background subtraction on the spectra is in the order of 1%. The peak due to impurities is separated from the proton-hydrogen peak at angles larger than 7°. The absolute error of the cross sections is 0.5%, resulting from the above mentioned sources, as well as from the geometrical factor.

A phase shift analysis was accomplished using a CDC 6600 computer and a version of the program developed by D. J. Knecht for the analyses of the KMBND data. Table I contains the results which should be considered preliminary because some more exhaustive searches will be undertaken in the future. In

view of the searches already performed no drastic changes are anticipated. The limit of error of the 1S_0 phase shift can be set at 0.2°.

A discussion of the scattering parameters that can be obtained from the experimental phase shifts, without and with extended electromagnetic structure corrections, 17 is beyond the scope of this paper. Nevertheless Fig. 1 presents a plot of the nonlinear part of the expansion $K = \sum_{i=0}^{n} A_i E^i$, where E is the laboratory energy. The nonlinear part is obtained as $\Delta K = K_{exp} - (A_0 + A_1 E)$. The function K_{exp} is calculated from the experimental phase shifts, and is corrected for vacuum polarization effects E^{10} ; E^{10} , and E^{10} were obtained through a least squares fit effected on the WMF, KMBND and our data, without performing extended electromagnetic structure corrections. The resulting shape dependent parameters are E^{10} and E^{10} and E^{10} is set equal to zero one obtains E^{10} and values may not be inconsistent with a Yukawa well. The above mentioned values are also to be understood as preliminary. Further refinements will still be made on the calculation of uncertainties of the experimental data and of the function E^{10} . Here again no important changes are anticipated.

Figure 1 illustrates the dramatic improvement over the old cyclotron data accomplished by the 88-inch variable energy cyclotron and its instrumentation.

There is an apparent discrepancy, beyond experimental error, with the phase shift obtained from the Minnesota data 11 by MacGregor (also reproduced by a calculation performed here with the CDC 6600 computer). It will require further clarification, although no relevant changes can be foreseen, as it is demonstrated in Fig. 1. It is also pertinent to note that an earlier experiment at 9.73 MeV agrees well with our data. 18

Summarizing, it is reasonable to expect that the shape dependent parameters will be restricted to a much narrower range of values. Clearly, the nonlinear terms of the k cot δ_0 expansion contribute heavily between 4 and 10 MeV, and thus the ultimate accuracy of the Wisconsin experiments is not necessary in this energy range in order to settle the problem.

Acknowledgments

It is a pleasure to thank T. Chan for his assistance in mechanical designs, John Meneghetti in the mechanical instrumentation, D. Landis with electronic circuits and B. Lothrop who made the silicon detectors.

REFERENCES AND FOOTNOTES

- Work performed under the auspices of the U.S. Atomic Energy Commission.
- 1. A summary of the work prior to 1950 is contained in J. D. Jackson and J. M. Blatt, Rev. Mod. Phys. 22, 77 (1950).
- 2. H. R. Worthington, J. N. McGruer, and D. E. Findley, Phys. Rev. <u>90</u>, 899 (1953), hereafter referred to as WMF.
- 3. D. J. Knecht, S. Messelt, E. D. Berners, and L. C. Northcliffe, Phys. Rev. 114, 550 (1959);
 - D. J. Knecht, P. F. Dahl, and S. Messelt, Phys. Rev., (to be published), hereafter referred to as KMBND.
- 4. J. E. Brolley, J. D. Seagrave, and J. D. Berry, Bull. Am. Phys. Soc. $\underline{8}$, 604 (1964).
- 5. H. P. Noyes, Phys. Rev. Letters 12, 171 (1964).
- 6. G. Breit, as quoted by D. Amati in Comptes Rendus du Congrès International de Physique Nucléaire (Centre National de la Recherche Scientifique, Paris, 1964), Vol. I, p. 60.
- 7. M. L. Gursky and L. Heller, Phys. Rev. <u>136</u>, B1693 (1964).
- 8. R. J. Slobodrian, Nuovo Cimento 40B, 443 (1965).
- 9. An inversion of curvature is induced by the point at 3.037 MeV, see refs. 8 and 11.
- 10. L. L. Foldy and E. Eriksen, Phys. Rev. <u>98</u>, 775 (1955);M. deWit and L. Durand, Phys. Rev. <u>111</u>, 1597 (1958).
- ll. R. J. Slobodrian, Nucl. Phys. (in press) and UCRL-16690 (unpublished).
- 12. L. H. Johnston and D. E. Young, Phys. Rev. <u>116</u>, 989 (1959), analyzed by M. H. MacGregor, Phys. Rev. <u>113</u>, 1559 (1959). See also ref. 18 related to an experiment performed at 9.73 MeV.

- 13. V. V. Babikov, Sov. J. Nucl. Phys. <u>1</u>, 567 (1965); J. Nucl. Phys. (USSR) <u>1</u>, 793 (1965).
- 14. L. Hulthen and M. Sugawara, Encyclopedia of Physics, Vol. 39, ed. by S. Flügge (Springer-Verlag, Berlin, 1957) and references therein.
- 15. H. Bichsel, Phys. Rev. <u>112</u>, 1089 (1958);
 H. Bichsel and E. A. Uehling, Phys. Rev. 119, 1670 (1960).
- 16. D. J. Knecht, Technical Documentary Report No. WL TDR-64-78 (unpublished).

 One of the authors of the present paper (RJS) is indebted to Dr. Knecht for sending a preprint of the second paper of ref. 3, prior to publication, and a copy of the above mentioned report.
- 17. R. J. Slobodrian, Phys. Rev. 145, 766 (1966).
- 18. B. Cork and W. Hartsough, Phys. Rev. <u>94</u>, 1300 (1954). These authors measured eight experimental points over a limited angular range starting at $\theta_{\rm CM}$ = 27.67° to about 1% accuracy.


Table I. Values of the S, P, and D phase shifts, resulting from the analysis of the experimental data.

E _{LAB} (MeV)	Phase shifts (degrees)				
	¹ s _o	3 _{P0}	3 _P 1	³ P ₂	¹ D _O
6.141	55.89	0.78	-2.22	-1.02	-1.15
8.097	57.27	2.39	-1.81	-0.13	-0.17
9.981	56.57	3.09	-2.18	-0.07	-0.15

FIGURE CAPTION

Fig. 1. Plot of $\Delta K = K_{\rm exp} - (A_0^+ A_1^- E)$ as a function of laboratory energy. The solid dots are the Wisconsin data. The open triangle is the Minnesota datum. The solid triangles are the OC data contained in ref. 1. The inverted solid triangle is the interference minimum datum. The open circles correspond to the work reported here.





MUB-11653

Fig. 1

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

- A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or
- B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

