

Lawrence Berkeley National Laboratory

Recent Work

Title

Rubber Tubing Pump

Permalink

<https://escholarship.org/uc/item/9ds4d59r>

Authors

Weigl, John W.
Stallings, Donald W.

Publication Date

1950-01-03

UNIVERSITY OF
CALIFORNIA

*Radiation
Laboratory*

TWO-WEEK LOAN COPY

*This is a Library Circulating Copy
which may be borrowed for two weeks.
For a personal retention copy, call
Tech. Info. Division, Ext. 5545*

BERKELEY, CALIFORNIA

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.

UCRL-562
Unclassified Distribution

UNCLASSIFIED

UNIVERSITY OF CALIFORNIA

Radiation Laboratory

Contract No. W-7405-eng-48

RUBBER TUBING PUMP

John W. Weigl and Donald W. Stallings

January 3, 1950

Berkeley, California

<u>INSTALLATION</u>	<u>No. of Copies</u>
Argonne National Laboratory	8
Armed Forces Special Weapons Project	1
Atomic Energy Commission, Washington	2
Battelle Memorial Institute	1
Brookhaven National Laboratory	8
Bureau of Medicine and Surgery	1
Bureau of Ships	1
Carbide & Carbon Chemicals Corp. (K-25)	4
Carbide & Carbon Chemicals Corp. (Y-12)	4
Chicago Operations Office	1
Cleveland Area Office	1
Columbia University (Dunning)	1
Columbia University (Failla)	1
Dow Chemical Company	1
General Electric Company, Richland	6
Hanford Operations Office	1
Idaho Operations Office	1
Iowa State College	2
Kansas City	1
Kellex Corporation	2
Kncils Atomic Power Laboratory	4
Los Alamos	3
Mallinckrodt Chemical Works	1
Massachusetts Institute of Technology (Gaudin)	1
Massachusetts Institute of Technology (Kaufmann)	1
Mound Laboratory	3
National Advisory Committee for Aeronautics	2
National Bureau of Standards	2
Naval Radiological Defense Laboratory	2
NEPA Project	2
New Brunswick Laboratory	1
New York Operations Office	5
North American Aviation, Inc.	1
Oak Ridge National Laboratory	8
Patent Advisor, Washington	1
Rand Corporation	1
Sandia Base	1
Sylvania Electric Products, Inc.	1
Technical Information Branch, ORE	15
U. S. Public Health Service	1
UCLA Medical Research Laboratory (Warren)	1
University of California Radiation Laboratory	5
University of Rochester	2
University of Washington	1
Western Reserve University (Friedell)	2
Westinghouse Electric Corp.	4
	<hr/>
	Total 119
Information Division	
Radiation Laboratory	
Univ. of California	
Berkeley, California	

RUBBER TUBING PUMP*

By

John W. Weigl and Donald W. Stallings

* This work was supported by the United States Atomic Energy Commission.

Although rubber tubing pumps appear to be used for gas circulation in a number of laboratories, it seems that each group has had to invent one for itself. For this reason, a brief description of a useful model is presented here.

Its mode of operation may be recognized from Figure 1. One after another, the four rollers at the corners of the square rotor compress a piece of rubber suction tubing, pushing the gas ahead of them, each roller blocking a new gas pocket before the last has been lifted off. The speed may be controlled from about 100-1500 cc/min by means of a set of step pulleys, as well as by adjustment of the hinged tubing race, and by changing the size of tubing used.

The main virtues of this type of circulating pump are the smooth flow and negligible hold-up, the lack of metal parts and lubricant in contact with the gas, its rugged construction and ability to withstand evacuation without leakage around shafts and bearings. It may be used for pushing or re-cycling gas, or for the well-controlled evacuation of a closed system to less than one millimeter pressure.

For publication in Scientific American, Laboratory and Shop Notes.




FIG. 1