

Lawrence Berkeley National Laboratory

Lawrence Berkeley National Laboratory

Title

BEAM BREAK-UP IN THE TWO BEAM ACCELERATOR

Permalink

<https://escholarship.org/uc/item/0gk6s9gw>

Author

Whittu, D.H.

Publication Date

2008-09-17

e.2



Lawrence Berkeley Laboratory

UNIVERSITY OF CALIFORNIA

Accelerator & Fusion Research Division

RESEARCH
DIVISION
OF THE
LAWRENCE BERKELEY LABORATORY

JULY 11 1989

LIBRARY AND
DOCUMENTS SECTION

Presented at the 1989 IEEE Particle Accelerator Conference,
Chicago, IL, March 20-23, 1989, and to be published in the Proceedings


Beam Break-Up in the Two Beam Accelerator

D.H. Whittum, G.A. Travish, A.M. Sessler,
G.D. Craig, and J.F. DeFord

March 1989

TWO-WEEK LOAN COPY

*This is a Library Circulating Copy
which may be borrowed for two weeks.*



e.2
LBL-26940

BEAM BREAK -UP IN THE TWO BEAM ACCELERATOR

David H. Whittum, Gil A. Travish, and Andrew M. Sessler*
Accelerator & Fusion Research Division
Lawrence Berkeley Laboratory
University of California
1 Cyclotron Road
Berkeley, California 94720

and

George D. Craig and John F. DeFord**
Lawrence Livermore National Laboratory
Livermore, CA 94550

March, 1989

*Work performed under the auspices of the U.S. Department of Energy by the Lawrence Berkeley Laboratory under contract No. DE-AC03-76SF00098.

**Work supported by the U.S. Dept. of Energy under Contract No. W-7405-ENG-48.

Beam Break-Up in the Two-Beam Accelerator

David H. Whittum, Gil A. Travish, and Andrew M. Sessler*

Lawrence Berkeley Laboratory

University of California

Berkeley, CA 94720

and

George D. Craig and John F. DeFord**

Lawrence Livermore National Laboratory

Livermore, CA 94550

Abstract

We have studied numerically beam break-up (BBU) in the drive beam of a Two-Beam Accelerator (TBA), using transverse wakes calculated numerically using the AMOS Code. We examine only cumulative BBU due to the wake of the linear induction accelerator cavities. We do not consider regenerative BBU due to the relativistic klystron (RK) cavities. We find growth lengths of order ~ 100 m for typical parameters.

Introduction

The Free Electron Laser (FEL)¹ and Relativistic Klystron (RK)² versions of the Two Beam Accelerator require the propagation of a relativistic electron beam of ~ 3 kA current, bunched on a scale of ~ 2 cm through a periodic lattice of rf structures (see Figure 1). Each period length is ~ 1 meter and at the end of each period the power generated in the rf structure (wiggler or cavity array) is extracted and fed into a parallel high gradient structure to accelerate a low current, high energy beam. Our concern in this paper is the beam break-up of the drive beam due to the transverse dipole wake of the LIA cavities that will be placed at intervals on the beamline. We briefly review the elements of the problem.

* Work supported by the Office of Energy Research, U.S. Dept. of Energy, under Contract No DE-AC03-76SF00098

** Work supported by the U.S. Dept. of Energy under Contract No. W-7405-ENG-48

A high-current rf relativistic electron beam (REB) injected off-axis into the beamline of a TBA will have a dipole moment in its charge density. The axial current associated with this dipole moment will couple to the axial electric fields of the various structures along the beamline. The structures of most concern are the resistive pipe itself, the rf input and output ports, the klystron cavities (in the case of the RK TBA) and, the subject of this paper, the LIA modules.

Each slice of the beam will excite TM_{1n0} -like modes of the LIA cavity and the associated " $v \times B$ " force will give a kick to all slices to the rear. Once a slice is kicked farther from the axis, its dipole moment excites larger fields and an instability obtains.³

If the instability is sufficiently severe, the beam will eventually scrape the beam pipe wall and "beam break-up" or "pulse-shortening" will occur. However, even a small amount of BBU growth in the TBA is undesirable, since it will reduce the intended coupling of rf and beam in the FEL or RK, and thereby diminish the power out.

The lowest-order coupling of transverse beam centroid motion and the rf fields of a particular structure may be expressed in terms of the "transverse dipole wake potential," $W(s)$.⁴

In this paper we use wakes, $W(s)$, calculated by the AMOS⁵ code for the ATA LIA cavity (see Figures 2 and 3). AMOS solves for the fields, in the time domain, of a bunch of gaussian axial profile traversing an azimuthally symmetric structure with mixed dielectric, conducting, and radiation boundary conditions.

Models for the LIA Wake

The LIA wake has been studied extensively in connection with BBU at the Advanced Test Accelerator at Lawrence Livermore National Laboratory (LLNL).⁶ We use two model numerical wakes.

The first model wake, the "exact wake," is that calculated via AMOS for the actual ATA geometry, with the approximation of azimuthal symmetry (see Figure 2).

The second model wake, the "idealized ATA cavity wake," is that calculated by AMOS for a pillbox terminated in an impedance (the "idealized ATA cavity" or "Briggs Model").^{7,8}

For analytic work, we use a third wake, the "dominant mode wake," due to a single, dominant mode of the LIA cavity⁹. It is given by

$$W(s) = W_0 \exp(-\nu s) \frac{\sin(\omega s)}{\omega}$$

where the notation is given in Table I and

$$W_0 = \frac{Z_{\perp} \omega_0^3}{Q L_{\text{gap}}}$$

Note that for long λ_{β} , an average of this wake over the TBA period is appropriate, while for short λ_{β} , the wake is felt at intervals as a discrete kick.

Basic BBU Particle Dynamics

The basic equation governing BBU is that of the motion of the center of mass of the beam slice at each s , $\xi(z, s)$, as it passes position z on the beam line. This displacement is driven by the Lorentz force associated with the fields created by the beam slices to the front at $s' < s$, and its response is governed by the focussing elements on the beam line:

$$\left(\frac{\partial}{\partial z} \gamma \frac{\partial}{\partial z} + \gamma k_{\beta}^2 \right) \xi(s, z) = H(z) \int_0^s ds' \frac{I(s')}{I_A} W(s - s') \xi(s', z)$$

where $I_A = mc^3/e = 17.05$ kA is the Alfvén current. As discussed below, we will replace the axial current profile $I(s)$ with its average value, denoted "I." The function $H(z)$ is 1 inside an LIA gap, and 0 outside.

We make several approximations. Consistent with our restriction to cumulative BBU, we assume the rf beam frequency does not excite appreciable resonances in the cavity (17 GHz is above cut-off in the beam pipe). Therefore, we may work with the average beam current.

In addition, for analytic estimates, we assume λ_{β} is constant throughout each TBA period, since γ varies by only about 5%. We also neglect spreads in λ_{β} , i.e., Landau and BNS damping.

Analytic Estimates

Using the analytic wake exhibited above, it is straightforward to solve the BBU equation up to quadrature.¹⁰ Laplace transforming in s , solving the simple harmonic oscillator initial value problem, and inverting the Laplace transform we have

$$\xi(s, z) = \frac{1}{2\pi i} \int_{-i\infty}^{i\infty} dp \frac{1}{p} \cos \left(z \sqrt{k_\beta^2 - \frac{I}{\gamma I_A} w(p)} \right)$$

where $w(p)$ is the Laplace transform of the wake averaged over a TBA period and the integral is to the right of the origin in the complex p -plane. This result may be evaluated asymptotically via steepest descents. We have taken a step initial beam perturbation. Other options include a "tickled" pulse, tuned to the resonant mode, and a delta function pulse offset.

Two regimes should be distinguished: strong focussing and weak focussing. In each regime, a sufficiently high Q results in an absolute instability, while low Q results in a convection of the peak growth down the length of the beam toward the tail.

In the strong focussing regime, λ_β is short compared to the growth length, L_g . We may compute the asymptotic behavior via steepest descents and we have, for $\tau > (z/L_g) v^{-1}$,¹¹ a convective instability characterized by peak growth along the pulse with exponent $\sim z/L_g$, where

$$L_g = L_p \frac{ck_\beta}{\omega} \frac{\gamma I_A}{I} \frac{2}{Q} \frac{1}{c Z_\perp / Q}$$

For high Q , on the other hand, such that $\tau \ll (z/L_g) v^{-1}$, we have an absolute instability characterized by growth with exponent $\sim (z/L_g)^{1/2}$ where

$$L_g = \frac{k_\beta L_p}{c\tau} \frac{c^2}{\omega^2} \frac{\gamma I_A}{I} \frac{1}{c Z_\perp / Q}$$

In the weak focussing regime, λ_β is long compared to the growth length. Again, for low Q such that $\tau > (z/L_g) v^{-1}$, the instability is convective. Growth is characterized by exponent $\sim z/L_g$, where

$$L_g = \frac{2^3}{3^{3/4}} \left(\frac{L_p c}{\omega} \frac{\gamma I_A}{I} \frac{1}{Q} \frac{1}{c Z_{\perp}/Q} \right)^{1/2}$$

For high Q , such that $\tau < (z/L_g) v^{-1}$, the instability is absolute and the growth is characterized by an exponent $\sim (z/L_g)^{2/3}$ where¹²

$$L_g = \frac{2^{7/2}}{3^{9/4}} \left(\frac{L_p}{c\tau} \frac{c^2}{\omega^2} \frac{\gamma I_A}{I} \frac{1}{c Z_{\perp}/Q} \right)^{1/2}$$

and this applies provided $\tau \gg (z/L_g) / 2\omega$.

Numerical Results

The code, "TWA", running on the MFECC Crays, makes use of a fourth order Runge-Kutta advance in z , and a fourth order gaussian integration in s , assisted by a fourth order Lagrangian interpolation of the integrand. The wake is read in as an array provided, for example, by the AMOS code.

For runs discussed in this paper, λ_{β} and γ are constant throughout the beam. The wake is turned on for one step per period and normalized accordingly. Runs were performed for the idealized ATA cell and the realistic cell, for design parameters as in Table I.

We found negligible growth in 100 m for either wake. That this should be so may be seen from a simple estimate. Using $Q \sim 6 - 8$ and $Z_{\perp}/Q \sim 8 \Omega$ for the idealized ATA cell, and the parameters of Table I, we obtain, in the strong focussing regime, a convective growth length of ~ 100 m for this example TBA design. This is in contrast to ATA parameters, which give growth lengths of order ~ 1 m.

In addition, we examined the effect of increasing I and λ_{β} beyond the values in Table I. (see Figure 3). These additional runs provided a test of the weak focussing analytic results, which are, in general not applicable to the TBA, due to the long pulse length. We observed asymptotic growth with the $z^{2/3}$ dependence in the exponent, as expected.

Conclusions

Even in the absence of Landau or BNS damping,¹³ we can expect BBU growth lengths on the order of ~100 m for typical TBA parameters and this is acceptable for a future TBA.

Future work should include: an examination of higher frequency modes not cut-off in the beam pipe (regenerative BBU); studies of BBU due to the RK cavity and the the rf input and output ports for the FEL TBA; and a BBU analysis for the SNOMAD II cavity currently the subject of experiments at ARC/LLNL.

The authors would like to thank G.J. Caporaso for helpful comments. We also found work by Y.Y. Lau particularly instructive.¹⁴

¹A.M. Sessler, E. Sternbach, and J.S. Wurtele, "A New Version of a Free Electron Laser Two-Beam Accelerator," LBL-25937

²A. M. Sessler and S. S. Yu, Phys. Rev. Lett., 58, 2439 (1987)

³R.H. Helm and G.A. Loew, "Beam Breakup", Linear Accelerators, P.M. Lapostolle and A. L. Septier, ed., Amsterdam: North Holland Pub. Co., 1970

⁴K. L. F. Bane, AIP Conf. Proc. No 153, 1987. Our "W(s)" is "W_x(s)" in the notation of this reference.

⁵J. DeFord, G. Craig, and R. McLeod, "The AMOS (Azimuthal Mode Simulation) Code, [These Conference Proceedings], (1989)

⁶G.J. Caporaso, F. Rainer, W.E. Martin, D.S. Prono, and A.G. Cole, Phys. Rev. Lett., 57, 1591 (1986)

⁷G. J. Caporaso, "The Control of Beam Dynamics in High Energy Induction Linacs," 1986 Linear Accelerator Conference Proceedings, SLAC Pub-303

⁸R.J. Briggs, D.L. Bix, G.J. Capraso, V.K. Neil, and T.C. Genoni, Part. Acc., 18, 41, (1985)

⁹See Ref. 8.

¹⁰An example of a similar calculation may be found in G.J. Caporaso, W.A. Barletta and V.K. Neil, Part. Acc. 11, 71 (1980)

¹¹V.K. Neil, L.S. Hall and R.K. Cooper, Part. Acc. 9, 213, 1979. The actual restriction on this result is $L_g \gg L_p / \sin(k_\beta L_p)$.

¹²W.K.H. Panofsky and M. Bander, Rev. Sci. Instr., 39, No. 2, 206, 1968

¹³Landau damping refers to damping due to a spread in k_β within a slice at s, z , while BNS damping refers to that due to a spread in k_β , across the beam, i.e., $k_\beta(s)$, constant within each cross-section.

¹⁴Y.Y.Lau, "Asymptotic Growth of Cumulative and Regenerative Beam Break-up Instabilities in Linear Accelerators," NRL Memo Report 6237 R, (1988)

Table I. Notation and Typical Values for TBA Parameters

L_{gap}	=LIA gap length	~ 0.0254 m
L_p	=period length	~ 1 m
τ	=pulse length	~ 50 ns
f	=beam frequency	~ 17.14 GHz
I	=average or dc current	~ 1.5 kA
γ	= beam energy /rest energy	~ 27.4
λ_β	=betatron wavelength	~ 1.5 m
ω_0	=undamped dominant mode angular frequency	
ν	=damping rate	
Q	=cavity Q value	$= \omega_0/2\nu$
ω	=damped angular frequency	$= (\omega_0^2 - \nu^2)^{1/2}$
s	=beam slice coordinate	$= t-z/v_z$
z	=axial position down beam line	
v_z	= beam axial velocity	$\sim c$
c	= speed of light	

Figure 1. The wake of the "idealized ATA cavity," a pillbox terminated in an impedance. For the figures, units of W are $V/C/m/cell$ and m for s . elsewhere units are cgs. The $W(s)$ depicted here is the $W(s)$ of the text multiplied by L_{gap} .

Figure 2. The wake of the ATA cell computed numerically via the AMOS code. Cylindrical symmetry is assumed.




Fig. 1




Fig. 2