UC Berkeley

UC Berkeley Previously Published Works

Title

Supply cost and life-cycle greenhouse gas footprint of dry and ensiled biomass sorghum for biofuel production

Permalink

<https://escholarship.org/uc/item/0gq8h8sn>

Journal

ACS Sustainable Chemistry and Engineering, 8(42)

ISSN

2168-0485

Authors

Baral, NR
Dahlberg, J
Putnam, D
et al.

Publication Date

2020-10-26

DOI

10.1021/acssuschemeng.0c03784

Peer reviewed

Supply Cost and Life-Cycle Greenhouse Gas Footprint of Dry and Ensiled Biomass Sorghum for Biofuel Production

Nawa Raj Baral,^{a,b} Jeff Dahlberg,^{a,c} Daniel Putnam,^{a,d} Jenny C. Mortimer,^{e,f} Corinne D. Scown^{*a,b,g}

^aLife-Cycle, Economics, and Agronomy Division, Joint BioEnergy Institute, 5885 Hollis Street, Emeryville, California 94608, United States

^bBiological Systems and Engineering Division, Lawrence Berkeley National Laboratory, 1 Cyclotron Road, Berkeley, California 94720, United States

^cUC-ANR Kearney Agricultural Research and Extension Center, 9240 South Riverbend Avenue, Parlier, California 93648, United States

^dDepartment of Plant Sciences, University of California, 1 Shields Avenue, Davis, California 95616, United States

^eFeedstocks Division, Joint BioEnergy Institute, 5885 Hollis Street, Emeryville, California 94608, United States

^fEnvironmental Genomics and Systems Biology Division, Lawrence Berkeley National Laboratory, 1 Cyclotron Road, Berkeley, California 94720, United States

^gEnergy Analysis and Environmental Impacts Division, Lawrence Berkeley National Laboratory, 1 Cyclotron Road, Berkeley, California 94720, United States

*Corresponding author, E-mail: cdscown@lbl.gov

Abstract

Biomass sorghum is a promising feedstock for cellulosic biorefineries because of its high yield and drought tolerance. However, the difficulty of effectively drying sorghum in some regions means it may require different handling than previously studied grassy feedstocks. This study compares the delivered cost and life-cycle greenhouse gas (GHG) footprint of field-drying and baling, module storage (wrapped, densely packed biomass), pelletizing, and ensiling. Ensiling has not been widely considered for use in bioenergy production. For farms within 66 km of the biorefinery, ensiled biomass is the lowest- cost and GHG strategy despite additional cost and energy demands for hauling wet biomass. Field-drying and baling, if feasible, is the most cost-effective option for sorghum between 66 km and 104 km, beyond which pellets are preferable. A

2000 bone-dry-metric ton (bdt)/day biorefinery can source sorghum with 18 bdt/ha yield cultivated on 5% of surrounding land at costs range from \$122 (silage) to \$167 (pellets)/bdt and a life-cycle GHG footprint of 111 (silage) to 179 kg CO₂e/bdt (pellets). With 28 bdt/ha biomass yield, 10% cultivation of surrounding land, and low fertilizer application, costs can range from \$66 (silage) to \$85 (pellets)/bdt and GHG footprint of 43 (silage) to 96 kg CO₂e (pellets)/bdt.

Keywords: Bioenergy, silage, sorghum, biomass, technoeconomic analysis, life-cycle assessment, greenhouse gas emissions

Introduction

Bioenergy sorghum (also referred to as biomass sorghum) is an important potential feedstock for future biorefineries in the United States. Sorghum [*Sorghum bicolor* (L.) Moench] is one of the few crops that can fit into all of the current bioenergy frameworks: grain-to-ethanol; sweet sorghum sugar into fuels; and as a biomass feedstock for lignocellulosic and cellulosic conversion. Sorghum lines typically considered most promising for lignocellulosic biofuel production are photoperiod-sensitive (PS), meaning they remain in a vegetative state for longer than photoperiod insensitive varieties and develop little or no grain. Brown midrib (BMR) mutants can provide additional advantages because of their relatively low lignin content and high digestibility.¹ Because biomass sorghum is an annual crop with an existing market as a forage, it may be considered a less risky dedicated bioenergy crop for farmers to cultivate relative to perennials like *Miscanthus* spp or switchgrass (*Panicum virgatum*) that have high upfront establishment costs and limited alternative markets.² Alternative markets are important to the stability of biofuel feedstock supply chains, given the limited cellulosic biorefinery capacity developed to date. Other key features of biomass sorghum are: (i) a high carbohydrate content of >70 wt%;¹ (ii) average biomass yield of 17.9 ± 3.3 bone dry tonne (bdt)/ha (Mg/ha, 0% moisture),^{1,3-9} which is roughly 4-fold more than a typical harvest rate of corn stover collected following grain harvest;¹⁰ (iii) potentially high soil carbon sequestration of -0.04 to -0.8 MgC/ha/year¹¹ (iv) tolerance to drought, disease, and heat;^{12,13} and (v) relatively high nitrogen and water use efficiencies.^{14,15}

Despite sorghum's advantages, the 60-80% moisture content^{16,17} (all moisture content values reported as a fraction of total wet weight), prior to senescence is a serious challenge for the biomass sorghum dry feedstock supply system. Stable long-term storage of biomass under aerobic conditions generally requires a moisture content around 15-20% and, for lignocellulosic biorefineries to operate at or near capacity year-round, these facilities must store feedstock for as long as one year.⁷ Many commercial sorghum varieties have been bred for delayed senescence (the stay-green phenotype) and even for non-stay-green varieties, delaying harvest until complete senescence can result in additional dry matter losses and weather-related complications.¹⁸

Ensiling wet chopped biomass, which runs counter to the conventional bioenergy strategy of dry storage, may be a viable alternative. In current practice, forage sorghum is commonly collected and chopped with a forage harvester and stored wet in a covered pit or pile (often inoculated with an organic-acid producing bacteria such as *Lactobacillus*), or in plastic tubes ('AgBags'), or anaerobic wrapped bales (baleage). Silage relies on a reduced pH and anaerobic conditions to ensure stability and quality.^{18,19} This is a common strategy in the dairy industry and farmers are familiar with silage production practices. Forage sorghums are difficult to dry in the field (especially in rainy areas), and ensiling is the most common storage method. Ensiling also enables greater flexibility with harvest timing and could be beneficial for biomass deconstruction⁶ if it is stored for a long period of time. However, the question remains as to how ensiling sorghum compares to more conventional strategies, such as baling, and how the farm-to-biorefinery distance impacts the least-cost, lowest-carbon strategy. The goal of this study is to evaluate a range of alternatives for efficient and cost-effective year-round bioenergy sorghum supply to biorefineries.

The U.S. Department of Energy *Billion Ton Study* recommends a strategy for sorghum that has similarities to ensiling, and is modeled after practices in the cotton growing industry: the wet material can be chopped as it is harvested and subsequently consolidated anaerobically into densely-packed plastic-wrapped modules (without inoculate).⁷ The direct transportation of the loose chopped-biomass (as in the case of silage) or densely-packed modules diminishes the eventual size reduction (milling) cost relative to bales but increases drying cost and energy (if downstream processing/conversion requires dry biomass).^{7,19} A rigorous technoeconomic analysis (TEA) and life-cycle greenhouse gas (GHG) inventory are essential to quantify the tradeoffs of these different approaches and identify the key cost and emissions drivers. A deeper understanding of costs and emissions is particularly crucial given the aggressive targets for delivered feedstock costs established by the U.S. Department of Energy at the pretreatment reactor throat of \$78.6/bdt (\$71.26/bone-dry short ton) to achieve biofuel prices of less than \$2.5/gallon gasoline equivalent (gge) by 2030.³⁰ A limited number of previous studies have estimated biomass sorghum supply cost in the form of bale,^{21,22} module,^{7,22} and silage,²² although these studies are limited to single point analysis and did not consider the entire supply chain including biomass production and delivery to the biorefinery gate or to the pretreatment reactor throat.

In this study, we performed a stochastic analysis of both costs and life-cycle GHG emissions for cultivating, harvesting, storing, and delivering bioenergy sorghum to biorefineries considering two different supply routes (with and without a preprocessing depot) and four different feedstock forms including chopped and ensiled biomass, modules, bales, and pellets. Any drying and densification of biomass adds cost, with the expectation that it will achieve savings in

transportation and in reduced biomass losses during storage. Thus, this study provides results as a function of transportation distance from farm to biorefinery for these potential feedstock collection and handling strategies. We also provide potential avenues to achieve the targeted feedstock supply cost at the reactor throat of \$78.6/bdt.²⁰

Methods

Bioenergy sorghum production and supply systems

Three potential supply strategies are considered in which bioenergy sorghum is delivered directly from the field to the biorefinery in the form of either chopped wet biomass (for ensiling at the biorefinery), densely packed modules, or dry bales (Figure 1). An alternative pelleting system is also considered, which is designed to accommodate longer distances between the farm and biorefinery. In the pelleting case, bioenergy sorghum is first transported from the field to the preprocessing depot (storage depot) and then pelletized²³ before being transported to the biorefinery. This analysis is based on the particle size requirements for biochemical conversion pathways. Once the biomass arrives at the biorefinery, some forms require further size reduction and others do not. Chopped ensiled biomass (particle size can be controlled by changing the knife configurations in the forage harvester) and pellets can be directly fed to the pretreatment reactor (Supporting Information (SI)-S1.2.1 and S1.5). Baled dry sorghum requires size reduction before pretreatment,²⁴ whereas modules⁷ only need to be broken apart from their compacted form.

Our analysis is based on the use of a shredder to reduce the particle size of baled biomass to <38 mm (1.5 in.) at the biorefinery,^{24,25} which is similar to the typical maximum particle size of chopped biomass produced by forage harvesters^{26,27} on the field. The resulting particle sizes will not be uniform, and forage choppers or shredders set to deliver 34 mm particles will produce many particles under 10 mm.²⁷ Modules must be broken apart with a combination of impact and shearing actions. The expected module-braking machine is not available at present; thus, energy

consumption of such machine is assumed to be 5 kWh/metric ton (half of the bale shredder), throughput is increased from 28 to 40 metric ton/h (same as the stover shredder ²⁸), and the purchase cost is assumed to be the same as the bale shredder of \$302,000 (originally reported in year 2000 dollars).²⁴

Although the impact of particle size distribution on sugar yields and downstream costs need to be further investigated at pilot or larger scales, there is evidence that many promising pretreatment processes, including steam explosion,²⁹ ammonia fiber explosion,³⁰ deacetylation and mechanical refining,³¹ and ionic liquid,³⁰ can handle these larger particle sizes without appreciable reductions in sugar yield. Biomass used to produce pellets must be milled to a smaller size than biomass supplied directly to the biorefinery. We modeled a two-stage milling process at the depot to achieve a mean particle size of 6.35 mm (¼ in.) for the optimal densification.^{23,32,33} All the feedstock forms considered in this study require a feedstock handling process prior to entering the pretreatment reactor that includes conveyors (belt/screw) and short-term storage.³⁴

Figure 1. An overview of biomass sorghum supply systems considered for analysis in this study.

Pellet production at the depot requires a series of unit operations including feedstock handling, primary milling (only required for module and bale), drying, secondary milling, conditioning and pelletizing, and steam generation units (SI-S1.5).

The logistics model was developed by using macro-enabled Microsoft Excel sheets. The process models for the preprocessing (pellet production at the storage depot) and handling at the biorefinery are developed in process modeling software (SuperPro Designer V10.2³⁵). Visual Basic code was used to integrate these modeling and analysis tools. Feedstock supply models and assumptions are consistent with previous logistics models developed for chopped biomass^{22,36,37}, module^{38,7,22}, bale,^{10,22,23,36,37,39,40} and pellets^{10,23,36,37,39,40} of different herbaceous lignocellulosic biomass feedstocks, including sorghum, corn stover, Miscanthus, and switchgrass. Previous studies^{10,22,33,41}

provided a detailed discussion about the different stages of the feedstock supply system.

Recognizing that similar operations are required for biomass sorghum,^{7,21,22} this study provides detailed discussion of these different components/stages of the biomass supply chain (Figure 1) and associated data inputs in the SI (S1.1 to S1.6 and Tables S1 to S6). We consider a standard biorefinery sized to take in 2000 bdt biomass sorghum to the pretreatment reactor throat per day in every scenario. This biorefinery size was selected based on the economies of scale achievable for ethanol, although this size is commonly used to model a wide range of biochemically-produced fuels and products.^{24,40}

The optimal biorefinery size is dependent on a number of factors, including the specifics of the conversion process and scaling factors for capital equipment, which must be weighed against the increased feedstock transportation costs for larger facilities.⁴⁰ The biorefinery is assumed to be operated 330 days per year and 24 hours per day. We allocate 12.5% of additional feedstock (for 45 days) as a safety stock to mitigate the risk of stock-outs due to inclement weather, unexpected biomass losses, and any transportation delays.⁴² Therefore, the logistics model developed in this study delivered the bone-dry biomass feedstock of 2250 t/day for the baseline scenario. Table 1 summarizes the major input parameters associated with biomass sorghum production and supply chain, including dry matter loss, harvest window, dry-down time on the field, and the fraction of land cultivated with sorghum around the biorefinery (land utilization) (Table 1). In addition to the biorefinery supply scenarios detailed in Table 1, we analyzed delivered sorghum biomass cost per bdt as a function of distance from the farm-to-biorefinery, which is independent of biorefinery scale and land utilization factor.

Dry matter loss, particularly during storage, is an important parameter for both cost and emissions, and these losses are well documented for herbaceous biomass bales.^{10,23,43} Prior work⁴² collected data from several studies and found the dry matter loss of the bale supply system in the range of 4.2 to 25% with the mean value of 11.6%. Dry matter loss in bales increases with moisture content and storage duration,⁴³ whereas the ensiling process uses anaerobic conditions and a low pH to control decomposition. Easily accessible carbohydrates (e.g. soluble starch) are converted to organic acids during the ensiling process and some initial degradation takes place before the ensiled biomass reaches a stable pH of 3.5- 4.5 and again during the feed out phase where material will again be exposed to oxygen.⁴⁴ A meta-analysis considering 43 peer-reviewed studies found the forage dry matter loss during the ensiling process in the range of 0 to 28.6% with the mean value of 6.2% and median value of 14%.⁴⁴ Wendt et al.¹⁹ found dry matter loss of 5.75% after 110 days of anaerobic storage of corn stover. Another recent study¹⁷ found 11 wt% organic acids in the ensiled biomass sorghum and 13.5% loss of total carbohydrates, although the easily accessible carbohydrate content will depend on whether the forage sorghum has a grain head. Modules systems, because they have not been widely implemented or studied for sorghum, are not well understood in terms of dry matter loss. Because relative differences in dry matter losses across different supply systems are uncertain and dependent on local conditions, we use a consistent loss factor across all scenarios and include a range of 2-30% in the uncertainty analysis (Table 1).

The sorghum harvest window impacts equipment and labor costs, and is dependent on local climate conditions. The active harvest window of sorghum for silage in the U.S. is in the range of 15 to 75 days, with the average value of 31.5 days (average of 13 different states).⁴⁵ Ensiling or

module building could allow for a wider harvesting window because these strategies do not require dry-down in the field, but extending the harvest window into the rainy season can result in soil erosion from the use of field machinery and trucks/loaders in the wet field. Therefore, we conduct our analysis using the 31.5-day average harvest window (Table 1). Dry down time on the field is also dependent on the local climate and effectiveness of biomass conditioning. Conditioning (crush and/or split the biomass sorghum stem) reduces the stiffness of the biomass, accelerates field drying, and facilitates the production of uniform and compact bales. A prior study⁴⁶ explored the impacts of using a “V” impeller, chisel impeller, and fluted roll conditioner on thin-layer drying time and found that the fluted roll conditioner reduced drying time by nearly 80% relative to the unconditioned material. Researchers at Oklahoma State University⁴⁷ have indicated that dry-down time in the field can be as low as 5 days with good conditioning and favorable weather conditions, while less effective conditioning results in 10 or more days required for dry-down. We use a minimum dry-down time of 5 days, a maximum of 21 days based on data reported by Khanchi et al.⁴⁸, and an average duration of 10 days.³⁸

The availability of biomass sorghum fields around the biorefinery (land utilization) is another important parameter because it impacts transportation costs to satisfy the facility’s needs. For the baseline scenario, we assume 5% of land surrounding the biorefinery is actively growing sorghum (meaning more land may include a sorghum rotation, but 5% of total land is producing sorghum in any given year). For comparison, the U.S. currently utilizes 1.7% of the total cropland for sorghum farming, typical land utilization for corn crops in corn-dominated regions is considerably higher (35%) whereas typical assumptions for other bioenergy crops such as switchgrass and Miscanthus are 5-10%.³ The land utilization factor could increase well beyond

5% in some regions if biomass sorghum becomes a widely used bioenergy crop.⁷ In the pelletization scenarios, preprocessing (storage) depots are assumed to be uniformly distributed around the biorefinery. With 5% land utilization, we estimated an optimal number of 13 preprocessing depots to achieve the lowest possible delivered biomass cost. This results in an average field-to-depot supply distance of 16 km (9.9 miles). Additional assumptions made in this study, descriptions of each stage in the supply chain, and the data sources used to develop the process model are provided in SI-Tables S1 to S6.

Table 1. Major input parameters for biomass sorghum supply chain

Parameter	Unit	μ	a	b	σ	Probability distribution
Biorefinery size (assumed)	bdt/day	2,000	-	-	-	None
Biorefinery working days (assumed)	days/year	330	-	-	-	None
Biomass yield ^{1,3-9,49}	bdt /ha	17.9	5.2	27.6	5.4	Lognormal
Moisture content at harvest ^{7,16,17}	%	59.7	40.0	70.0	10.7	Triangular
Safety stock ⁴²	%	12.5	8.0	25.0	8.8	Triangular
Dry matter loss (supply chain) ^{19,23,42}	%	11.6	4.2	25.0	6.6	Lognormal
Dry matter loss (forage harvester) ^{38,50}	%	2.4	0.8	4.0	-	Triangular
Harvest window ⁴⁵	days/year	31.5	15.0	75.0	14.6	Triangular
Harvesting hours ^λ	hours/day	16.0	8.0	24.0	8.0	Triangular
Fraction of land surrounding biorefinery cultivated with sorghum ^{ω,φ}	%	5.0	2.0	10.0	-	Triangular
Road winding factor ^{10,28,51,52}	-	1.5	1.1	3.5	0.4	Normal
Direct land use change impact ¹¹	tCO _{2e} /ha	-0.46	-0.04	-0.8	-	Triangular

Note: μ = average value; a = minimum value; b = maximum value; σ = standard deviation; bdt = bone dry tonnes

^λ Assumed based on the current harvesting practices of biomass sorghum.

^ω Percentage of the total area (including land, water bodies, and others) around the biorefinery.

^φ Assume the biomass sorghum field is uniformly distributed around the biorefinery.^{10,51}

Biomass sorghum production and supply costs, and greenhouse gas emissions estimates

We estimate the biomass sorghum production and supply costs using cash flow analysis, including capital investments, ownership costs (including depreciation, interest, taxes, insurance, and housing), and operating costs (including repair and maintenance, fuel, lubrication, labor, and consumable materials, such as string, tarp, and plastic wrap). For non-grain biomass feedstock, such as biomass sorghum, biomass production cost and associated GHG emissions should be allocated entirely for biomass. We calculated biomass production cost including cultivation

(except fertilizer), fertilizer, and herbicides costs. Cultivation includes such factors as land rent, establishment labor and fuel inputs, seed costs, and herbicides. Data inputs used to determine these different cost components are documented in SI-Tables S1 and S2. Detailed methods and equations used to estimate biomass production and supply costs are documented in previous studies.^{10,41,53}

In addition to the feedstock supply cost, life-cycle GHG emissions were calculated for each stage of the supply chain using a hybrid process-based/physical units input-output model as documented in our previous work.⁵⁴ The emission factors were gathered from widely used LCA databases, including GREET, Ecoinvent, and U.S. LCI database.⁵⁵⁻⁵⁷ Net emissions/sequestration of GHGs resulting from conversion of arable land for sorghum production is an important contributor and has not been well documented in previous life-cycle emissions studies for bioenergy sorghum, so we have used net GHG fluxes from direct land use change documented in recently-completed DAYCENT modeling^{11,58,59} by taking an average of net SOC impacts across all arable land in the U.S. of -0.46 tCO_{2e}/ha/year. To estimate N₂O emissions resulting from microbial nitrification and denitrification processes in the soil, we employed the standard practice of assuming 1.15% of nitrogen applied as fertilizer is released as N₂O, with a global warming potential of 298.¹¹ Further details on methods and assumptions are discussed in the SI-S2.

To capture uncertainty, we conducted a single-point sensitivity analysis for cost and GHG emissions to highlight the impacts of specific individual parameters, and separately ran stochastic simulations to develop probability distributions for the results. For the single-point

sensitivity, minimum and maximum values of influential input parameters were gathered from published literature (Table 1 and SI-Tables S1-S7). Additionally, we developed heat maps for cost and GHG emissions considering direct transportation of chopped ensiled biomass from the field to the biorefinery as a representative case, with the goal of illustrating the combined effect of varying various sets of two selected input parameters on the feedstock supply cost and GHG emissions. The stochastic Monte Carlo simulations were conducted using best-available probability distributions, including uniform, normal, triangular, and lognormal (Table 1 and SI-Tables S1-S7). The field-to-biorefinery distance is varied during two-point sensitivity analysis and Monte Carlo simulation; it is a function of biomass yield, land utilization fraction (% of surrounding land cultivated for sorghum), dry matter loss, and the road-winding factor (Table 1). The process of defining the probability distribution is consistent with the authors' recent study.⁶ The simulations were run for 10,000 Monte Carlo trials.

Results and discussion

Biomass sorghum supply cost

Figure 2a shows the delivered cost of biomass sorghum at the pretreatment reactor throat for silage, modules, and bales, with a comparison for each between direct supply versus pelletization at a storage depot. For the baseline biorefinery size of 2000 bdt/day around which 5% of land is cultivated with biomass sorghum, modules are the most expensive form of feedstock (\$146/t), followed by bales (\$125/t), and chopped ensiled biomass (\$121/t) when these are directly delivered from the field to the biorefinery. The sum of machinery, seed, herbicides, land rent, labor, and fuel,^{4,6} is responsible for, on average, 24% of the overall supply cost. While this study considered an average biomass sorghum production cost, it should be noted that these costs will

vary by location. Fertilizers account for, on average, 19% of the overall feedstock supply cost. Although not incorporated into the baseline case, sustainable farming practices, such as low- or no-till strategies and crop rotation, can reduce costs by minimizing nutrient inputs, irrigation, and use of machinery.

The major differences among the modules, bales, and silage are in the field operation and transport costs. The field operation cost is, respectively, responsible for 31%, 23%, and 9% of the overall delivered cost for modules, bales, and silage. Biomass transportation accounts for 18%, 22%, and 32% of the overall delivered cost for modules, bales, and silage, respectively. While a forage harvester can be used for harvesting and loading the chopped biomass on the truck all in a single step,²² the module-building process requires multiple field operations^{7,22} including mowing, on-field drying (to reduce moisture to 40%), chopping, module building and wrapping (using a plastic wrap), and on-field transportation or stacking at the field edge. These series of operations required for modules result in a 4X increase in field operations costs relative to the chopped ensiled biomass. The baling process also requires multiple field operations, including windrowing or mowing, on-field drying and raking (to reduce moisture to 20%), baling, and stacking at the field edge, which results in a 2.5X increase in field operations costs relative to the chopped ensiled biomass. Importantly, the time requirement for field drying entails greater risk from rain damage. However, the chopped ensiled biomass requires 49% and 43% greater transportation costs from the field to the biorefinery relative to modules and bales, respectively. This large transportation cost is mainly due to a low bulk density and high moisture content (Table 1 and SI-Table S3) relative to bales and modules.

Delivering pellets (as part of the depot system) produced from chopped ensiled biomass, modules, and bales to the biorefinery reduces the overall transportation cost by 42, 34, and 30 %, respectively, relative to their direct field-to-biorefinery transportation costs. This reduction is primarily due to the full utilization of truck payload capacity and reduction in required truck trips due to a low moisture content of pellets (10%).²³ However, the additional cost of pellet production is substantial, accounting for 20-25 % of the overall feedstock supply cost. Differences in pellet production cost depend on the level of milling and drying required, which is dependent on the form of the delivered sorghum (SI-Figure S1). Chopped ensiled biomass has already been processed in a forage harvester/chopper and thus only requires a single-stage milling process to achieve the required particle size for pelletizing of 6.35 mm,²³ whereas biomass bales require a two-stage milling process. The cost associated with the rotary steam dryer, including the onsite steam generation (using natural gas as the fuel) is responsible for 43% of the total pellet production cost from silage (Figure 2a and SI-Figure S1). Modules (40% moisture) and bales (20% moisture) require less steam for drying; the drying process makes up 37% and 15% of their pellet production cost, respectively (Figure 2a and SI-Figure S1). Despite the increased drying costs and higher field-to-depot transportation costs, the delivered cost of pellets produced from chopped ensiled biomass is lowest (\$136/t) followed closely by bales (\$147/t) and modules (\$167/t) (Figure 2a). Our results indicate that the additional drying cost, including onsite steam generation, required for the chopped ensiled biomass at the depot is offset by its lower field operation and size reduction costs relative to modules and bales (SI-Figure S1).

For comparison, the overall biomass sorghum supply costs determined in this study are comparable to the market price of biomass sorghum bales (after adjusting preprocessing cost at

the biorefinery (SI-Figure S2)) in the range of \$123 to 161/t.⁶¹ One notable difference between this study and prior work is in the estimated preprocessing cost for bales at the biorefinery (\$7/bdt), which includes material handling, size reduction, and short-term storage costs. Prior studies on corn stover bales estimated \$10.9/bdt with grinding²⁸ and \$14.3/bdt with two-stage milling¹⁰ (mean particle size of 4 mm). Our lower preprocessing costs are based on use of a shredder (consumes about 10-fold less energy than grinding^{24,28}) and larger maximum particle size (length of 38 mm, which is consistent with the module and silage systems). Recent studies indicate that these larger particle sizes do not appreciably impact performance for many commonly studied pretreatment processes including ionic liquid,⁴⁰ steam explosion,²⁹ and ammonia fiber explosion³⁰ pretreatment processes.

The biomass sorghum supply costs modeled in this study are, in addition to aligning with sorghum market values, comparable to other potential biomass feedstocks costs at the pretreatment reactor throat, including corn stover costs (\$86-132/t^{23,33,40,63}), Miscanthus (\$127-155/t^{23,40}), and switchgrass (\$79-139/t^{23,33,40}). These wide ranges are due to regional variations in on-farm resource requirements, biomass yield, land utilization surrounding the biorefinery/depot, and moisture content. Biomass yield per unit cultivated land area is a particularly key parameter because biomass yield directly alters both the costs associated with farming (e.g. land rent, fertilizer, labor, fuel, harvesting costs) and the average farm-to-biorefinery distance to deliver 2000 bdt of feedstock per day.

(a) Biomass sorghum supply cost at the pretreatment reactor throat

(b) Greenhouse gas emissions from biomass sorghum supply chain

Figure 2. Delivered cost of biomass sorghum feedstock at the pretreatment reactor throat (a) and associated greenhouse gas emissions (b). For the baseline analysis, the estimated farm-to-biorefinery distances are 57.8 km for silage and module, and 55.9 km for bale, which are dependent on the biomass yield, land utilization, dry matter loss, and the road-winding factor (Table 1). The detailed cost and carbon footprint contributions from different unit

operations associated with preprocessing at the depot and the biorefinery are documented in the SI-Figures S1 and S2. The box and whisker plots show uncertainties in costs and GHG emissions. The horizontal dashed lines represent (a) the targeted feedstock supply cost at the pretreatment reactor throat of \$78.6/bdt,³⁰ and (b) an average GHG emissions from corn stover supply chain^{42,63,64} of 76.3 kgCO_{2e}/bdt.

Greenhouse gas footprint of biomass sorghum supply system

Across all scenarios, we use an average estimated soil organic carbon (SOC) sequestration of -0.46 tCO_{2e}/ha/year for production in the U.S. (local SOC sequestration values range from 0.04 to 0.8 tCO_{2e}/ha/year¹¹). This net SOC sequestration factor reduces the GHG footprint by an average of 25% (Figure 2b). The SOC sequestration potential of biomass sorghum depends on site-specific biomass yield, nutrient application, irrigation, soil type, management history, and local climate, which we account for in the uncertainty analysis,^{11,58} but warrants further in-depth study. On-farm activities required for sorghum cultivation, excluding nutrient inputs, is responsible for an average 10% of the gross GHG emissions, comprised primarily of diesel fuel combustion in field machinery. GHG emissions associated with fertilizer application (18-27%), biomass transportation (8-30%), and pellet production (38-40%, required for the depot options) are other major contributors to the gross GHG emissions (Figure 2b). N₂O emissions resulting from nitrogen fertilizer application are responsible for, on average, 16% of the gross GHG footprint. Chopped ensiled biomass requires fewer operations for harvesting (because it is a single-pass system) and handling at the biorefinery, resulting in 4-5% lower net GHG emissions relative to the module and bale systems, respectively. Notably, many of the factors driving module-building costs do not translate into similarly elevated GHG emissions. Similar to the biomass supply cost, GHG emissions associated with biomass transportation can be cut in half by switching from the direct supply to the depot option. However, this reduction does not compensate for the increased emissions associated with drying, milling, conditioning, and pelletizing. Steam for drying the

biomass can be generated onsite using natural gas and we account for the electricity required for milling and pelletizing using the U.S. average electricity mix. Apart from drying (58% of the total preprocessing carbon footprint), carbon footprints of other preprocessing stages, specifically milling and pelletizing, are also significant (Figure 2b and SI-Figure S1). A shift toward renewable sources of electricity can reduce these emissions.

For comparison, the net GHG footprint for the baseline scenario (Figure 2b) determined in this study is similar to the GHG footprint of biomass sorghum reported in previous studies ranging from 19 kg CO₂e/bdt⁵⁷ (only includes GHG emissions associated with sorghum farming) to 132 kg CO₂e/bdt⁶⁵ (includes sorghum farming, fertilizer, N₂O emissions, and transportation). The GHG emissions from the biomass sorghum supply chain are also comparable with other biomass feedstock, including corn stover^{42,63,64} in the range of 66-97 kg CO₂e/bdt, Miscanthus^{66,67} in the range of 47-93 kg CO₂e/bdt, and switchgrass^{33,68} in the range of 52-245 kg CO₂e/bdt (high upper end due to unusually large fertilizer application during establishment). These wide ranges are due to variations in fertilizer application, biomass yield, N₂O emissions, and impacts from land use change.

Sensitivity of costs and GHG emissions to key parameters

Biomass yield is the single most influential parameter on the basis of delivered feedstock cost because it alters the land requirements, on-field operations, and average transportation distances from the farm to biorefinery (see SI-Figures S3-S8 and Figures S21-S26 for additional details). To further explore the impact of biomass yield in combination with other parameters, Figure 3 provides cost and GHG emissions results for chopped ensiled biomass across a range of biomass

yields, in combination with nitrogen application, dry matter loss, and land utilization (% land cultivated around the biorefinery). Each subset of this analysis shows an opportunity to reduce the biomass sorghum supply cost at the pretreatment reactor throat below \$100/t. A more optimistic but achievable case with biomass yield of 25 bdt/ha^{4,5,7} could reduce feedstock supply cost below \$100/t under any of the following conditions: (1) nitrogen application <100 t/ha; (2) dry matter loss of supply chain <11 wt%; (3) land utilization >5%. Achieving \$100/bdt is very challenging at lower biomass yields (Figure 3a-c). The paths to reaching a GHG footprint at or below 50 kg CO_{2e}/bdt require similarly high yields, low dry matter losses, and higher land utilization factors (Figure 3d-f). The most important difference to note is the influence of nitrogenous fertilizer application, which has a greater impact on GHG emissions than it does on delivered feedstock cost. Dry matter loss is also important, and highly uncertain for silage and modules.⁴⁴ SI-Figures S27 shows the impact of varying dry matter losses from 2 to 30% on delivered cost and carbon footprint. Similar to bales,⁴³ the dry matter losses of silage and modules can be reduced by applying the best management practices. The relative impact of additional input parameters on the delivered biomass costs and GHG emissions are presented in the SI-Figures S3 to S9 and S21 to S26, respectively.

Figure 3. Combined impacts of a set of two most influential input parameters on the biomass sorghum supply cost at the pretreatment reactor throat (a, b, and c) and greenhouse gas emissions (d, e, and f). This is a representative case considering the direct supply of chopped ensiled biomass from the field to the biorefinery.

Because logistics decisions may be made on a farm-by-farm basis, this study also explores variations in cost and GHG emissions for each supply system as a function of farm-to-biorefinery distance (Figure 4). It is most economical for biorefineries to source chopped biomass directly from the field and ensile the material next to the biorefinery if the sorghum field is located within 66 km (41 miles). Chopped ensiled biomass supply is also the least carbon-intensive option if the field-to-biorefinery supply radius is less than 80 km (50 miles). If the sorghum field is located between 66 km and 105 km (65 miles) from the biorefinery, the direct transportation of bales from the field to the biorefinery is the most economical option, assuming

dry-down in the field and baling is feasible in the local climate (Figure 4). Direct supply of bales is the least GHG-intensive option between 80 km and 248 km farm-to-biorefinery distance (Figure 4-b). Two factors drive transportation costs and emissions from the farm to biorefinery: bulk density and moisture content. The maximum payload capacity (Federal weight limits) of a five-axle flat-bed tractor-semitrailer of 22.7 t²² is still at least 7% underutilized (limited by volume) with large rectangular bales (2.42 m long, 1.17 m wide, and 0.98 m high) at a bulk density of 168 kg/m³.^{10,42}

For farm-to-biorefinery distances of 105 km or greater, we find that transportation savings justify the additional cost of pellet production and the silage/pellet system is roughly equivalent to the bale/pellet system (Figure 4-a). In terms of GHG emissions (Figure 4-b), direct supply of ensiled biomass is preferable up to 80 km, at which point direct supply of bales becomes the lowest-carbon choice. The depot system does not become the lowest-emission option until a distance of 248 km, at which point the bale/pellet system has an advantage. Figures S3 to S8 provide the results of single-point sensitivity analysis for each scenario to capture each parameter's impact on costs. Biomass yield, fertilizer application, dry matter loss, land utilization (percent land cultivated with sorghum around the biorefinery), and the road winding factor prove to be key cost drivers. For GHG emissions, the key parameters are direct land use change impacts, fertilizer application, the road winding factor, land utilization factor, moisture content at harvest, yield, fuel for cultivation and field machinery, and dry matter losses.

Figure 4. Delivered sorghum biomass costs (a) and greenhouse gas emissions (b) as a function of farm-to-biorefinery distance. Beyond 130 km, the bale/pellet depot with depot system is most economical and its advantage increases further beyond 150 km.

Potential for feedstock supply cost and GHG emissions reductions

Both the cost and GHG emissions results from our analysis suggest that ensiled sorghum warrants wider consideration as a potential bioenergy feedstock, particularly given that this system is already familiar to farmers who grow sorghum as a forage crop. An obvious extension of this work would be to model the conversion of each feedstock to biofuel and report results on a per-gallon gasoline equivalent (gge) or MJ of fuel basis. However, until experimental research can elucidate the impact of the ensiling process on downstream processing and conversion, any

results reported on a per unit fuel basis may not be accurate. Previously published results do suggest that the module and ensiling systems are both effective at retaining the quality of the moist biomass feedstock (moisture content of >20%) for further biochemical conversion.¹⁹

If sorghum becomes a more widely produced crop for bioenergy and other fiber markets, it is possible that supply systems can be improved to reduce costs and emissions. For example, the current theoretical estimate of the biomass module building process based on the existing cotton module building process^{7,38} is expensive, but a consolidated module building process could be developed in the future, combining harvesting, chopping, module building, and wrapping operations in a single pass. Field drying and baling is less likely to change substantially, and its attractiveness will remain reliant on uncontrollable natural factors such as local precipitation, relative humidity, and field conditions during the weeks following harvest. Additionally, the multi-pass harvesting techniques considered for bales and modules gather more dirt/sand³³ when compared to single-pass harvests, such as loose chopped ensiled biomass, considered in this study. These operating trade-offs and key areas of improvement among the selected biomass sorghum feedstock supply chain options show opportunities for further process optimization and intensification.

Aggressively optimizing biomass production, field operations, and biomass transportation can result in dramatic reductions in delivered cost and GHG emissions. In the most optimistic scenario, average harvested biomass increases from 17.9 to 28 bdt/ha, the road winding factor is reduced from 1.45 to 1.2, land utilization for sorghum around the biorefinery doubles from 5% to 10%, fertilizer application is minimized (see SI- Figures S31-S36), dry matter loss is cut from 11.6% to 5%, and the harvest window expands from 31 to 75 days. The result of all these factors

combined (referred to as an “optimal” case) would be a reduction in the delivered cost at the reactor throat to \$66, \$79, and \$70 per bdt as well as GHG emissions to 43, 66, 62 kg CO₂e per bdt for the direct supply of chopped ensiled biomass, modules, and bales, respectively. The combination of all these improvements should be thought of as a theoretical best-possible outcome, and unlikely to be achieved in most locations. These step by step reductions in the delivered cost and GHG emissions are presented in the SI- Figures S15-S20 and Figures S33 to S38, respectively. Our results highlight the importance of the location of biorefineries for achieving the targeted biomass supply cost at the pretreatment reactor throat of \$78.6/bdt. The optimal delivered cost of chopped ensiled biomass and bales of \$66/bdt (SI-Figure S15) and \$70/bdt (SI-Figure S19), respectively, for the improved future case overshoot the targeted cost of \$78.6/bdt. If the biomass is pelletized for longer-distance transportation, switching to the solar drying can reduce GHG emissions by 30-33% (SI-Figure S16 and S35).

Our findings suggest that, although no single logistics strategy will reliably reduce delivered biomass cost to the U.S. Department of Energy target, different systems will be preferable depending on the location of production; biomass yield, local conditions, and farm-to-biorefinery distances will be determining factors. The value of selecting strategies that are familiar to farmers must not be underestimated. Ensiling of bioenergy sorghum requires only existing equipment and is widely practiced by farmers today. The delivered cost and GHG emissions of the chopped ensiled biomass prove to be competitive in the baseline and optimal scenarios and the recent encouraging sugar yield results¹⁷ with ensiled biomass indicate that ensiled material may generate further reductions in costs per unit of biofuel produced. A combination of the

strategies presented in this study will be needed to deliver the flexibility in biomass supply needed to produce a consistent supply of competitively-priced, low-carbon biofuels.

Disclosures

The authors declare no competing financial interest.

Supporting Information

Supporting information includes detailed methods, data inputs, single-point sensitivity analysis results, detailed uncertainty results for each stage of supply chain, and optimal biomass supply cost and greenhouse gas emissions for the selected scenarios.

Acknowledgements

This work was part of the DOE Joint BioEnergy Institute ([http:// www.jbei.org](http://www.jbei.org)) supported by the U.S. Department of Energy, Office of Science, Office of Biological and Environmental Research, through contract DE-AC02-05CH11231 between Lawrence Berkeley National Laboratory and the U.S. Department of Energy. This study was also supported by the U. S. Department of Energy, Energy Efficiency and Renewable Energy, Bioenergy Technologies Office. The United States Government retains and the publisher, by accepting the article for publication, acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this manuscript, or allow others to do so, for United States Government purposes.

References

- (1) Theerarattananoon, K.; Wu, X.; Staggenborg, S.; Propheter, J.; Madl, R.; Wang, D.. Evaluation and characterization of sorghum biomass as feedstock for sugar production. *Trans. ASABE* **2010**, *53*, 509–525, DOI 10.13031/2013.2956.
- (2) Cui, X.; Kavvada, O.; Huntington, T.; Scown, C. D. Strategies for near-term scale-up of cellulosic biofuel production using sorghum and crop residues in the U.S. *Environmental Research Letters* **2018**, DOI 10.1088/1748-9326/aae6e3.
- (3) USDA. Crop Production 2018 Summary. United States Department of Agriculture, Washington, D.C., **2019**;
https://www.nass.usda.gov/Publications/Todays_Reports/reports/cropan19.pdf (accessed March 6, 2020).
- (4) A L R. Economic Analysis of Biomass Sorghum for Biofuels Production in the Texas High Plains. AgriLife Extension, Texas A&M, **2011**;
<http://amarillo.tamu.edu/files/2011/05/Biomass-Sorghum.pdf> (accessed March 5, 2020).
- (5) USDA-NASS. National Statistics for Sorghum. United States Department of Agriculture, Washington, D.C., **2019**;
https://www.nass.usda.gov/Charts_and_Maps/A_to_Z/in-sorghum.php (accessed March 5, 2020).
- (6) UCCE. Sample Costs to Produce Sorghum Silage. University of California Cooperative Extension Agriculture and Natural Resources, Agricultural Issues Center, **2016**;
https://coststudyfiles.ucdavis.edu/uploads/cs_public/c2/a9/c2a9d0ea-f089-48a9-a9b2-64ec58355b46/2016sorghumsilagesjvfinaldraftmar23.pdf (accessed Dec 30, 2019).
- (7) D O E. *2016 Billion-Ton Report: Advancing Domestic Resources for a Thriving Bioeconomy, Volume 1: Economic Availability of Feedstocks*. U.S. Department of Energy, Washington, DC, **2016**;
<https://www.energy.gov/eere/bioenergy/downloads/2016-billion-ton-report-volume-2-environmental-sustainability-effects> (accessed January 22, 2019).
- (8) Murray, S. C.; Rooney, W. L.; Mitchell, S. E.; Sharma, A.; Klein, P. E.; Mullet, J. E.; Kresovich, S. Genetic improvement of sorghum as a biofuel feedstock: II. QTL for stem and leaf structural carbohydrates. *Crop Sci.* **2008**, *48*, 2180–2193, DOI 10.2135/cropsci2008.01.0068.
- (9) Rooney, W. L.; Blumenthal, J.; Bean, B.; Mullet, J. E. Designing sorghum as a dedicated bioenergy feedstock. *Biofuels, Bioprod. Bioref.* **2007**, *1*, 147–157, DOI 10.1002/bbb.15.
- (10) Hess, J. R.; Wright, C. T.; Kenney, K. L.; Searcy, E. M.. *Uniform-Format Solid Feedstock Supply System: A Commodity-Scale Design to Produce an Infrastructure-Compatible Bulk Solid from Lignocellulosic Biomass*. Idaho National Laboratory, Idaho Falls, ID, **2009**;
<https://bioenergy.inl.gov/Reports/Uniform%20Format%20Bioenergy%20Feedstock.pdf> (accessed January 22, 2019).
- (11) Gautam, S.; Mishra, U.; Scown, C.; Zhang, Y. Sorghum biomass production in the continental United States and its potential impacts on soil organic carbon and nitrous oxide emissions. *GCB Bioenergy* **2020**, DOI:10.1111/gcbb.12736.
- (12) Sparks, D. L. *Advances In Agronomy*; 1st ed.; Elsevier, **2004**; p. 302.
- (13) Dahlberg, J.; Wolfrum, E.; Bean, B.; Rooney, W. L. Compositional and agronomic evaluation of sorghum biomass as a potential feedstock for renewable fuels. *J. Biobased*

- Mat. Bioenergy* **2011**, 5, 507–513 DOI 10.1166/jbmb.2011.1171.
- (14) TAWC. Forage Sorghum Summary. Texas Alliance for Water Conservation; <https://www.depts.ttu.edu/tawc/researchuploads/forage.pdf> (accessed March 9, 2020).
 - (15) Bean, B.; Marsalis, M. Corn and Sorghum Silage Production Considerations. 2012 High Plains Dairy Conference, Amarillo, Texas, **2012**; <http://amarillo.tamu.edu/files/2010/11/CornandSorghumSilageProductionConsiderations.pdf> (accessed Mar 9, 2020).
 - (16) Borden, D. R. Effect of Harvest Dates on Biomass Accumulation and Composition in Bioenergy Sorghum. MS Thesis, Texas A&M University, **2011**; <http://oaktrust.library.tamu.edu/bitstream/handle/1969.1/ETD-TAMU-2011-12-10401/BORDEN-THESIS.pdf?sequence=2> (accessed January 22, 2019).
 - (17) Magurudeniya, H. D.; Rodriguez, A.; Baral, N. R.; Scown, C. D.; George, A.; Simmons, B. A.; Gladden, J. M. Potential of Ensiled Sorghum Biomass as Feedstock for Bioethanol Production . 41st Symposium on Biotechnology for Fuels and Chemicals, Seattle, WA, April, 2019. <https://sim.confex.com/sim/41st/meetingapp.cgi/Paper/38528> (accessed Jul 16, 2020).
 - (18) Undersander, D. J.; Smith, L. H.; Kaminski, A. R.; Kelling, K. A.; Doll, J. D. Sorghum-Forage, **2020**; <https://hort.purdue.edu/newcrop/afcm/forage.html> (accessed Mar 9, 2020).
 - (19) Wendt, L. M.; Murphy, J. A.; Smith, W. A.; Robb, T.; Reed, D. W.; Ray, A. E.; Liang, L.; He, Q.; Sun, N.; Hoover, A. N.; Nguyen, Q. A. Compatibility of High-Moisture Storage for Biochemical Conversion of Corn Stover: Storage Performance at Laboratory and Field Scales. *Front. Bioeng. Biotechnol.* **2018**, 6, 30, DOI 10.3389/fbioe.2018.00030.
 - (20) NREL. Process Design and Economics for the Conversion of Lignocellulosic Biomass to Hydrocarbon Fuels and Coproducts: 2018 Biochemical Design Case Update. National Renewable Energy Laboratory (NREL), Golden, CO., **2018**; <https://www.nrel.gov/docs/fy19osti/71949.pdf> (accessed January 1, 2020).
 - (21) Griffith, A. P.; Haque, M.; Epplin, F. M. Cost to produce and deliver cellulosic feedstock to a biorefinery: Switchgrass and forage sorghum. *Appl. Energy* **2014**, 127, 44–54, DOI 10.1016/j.apenergy.2014.03.068.
 - (22) Butler, J.; Downing, M.; Turhollow, A. Forage harvest and transport costs. Oak Ridge National Laboratory (ORNL), Oak Ridge, TN, **1998**; <https://www.osti.gov/servlets/purl/5842> (accessed January 1, 2020).
 - (23) Roni, M. S.; Thompson, D.; Hartley, D.; Searcy, E.; Nguyen, Q. Optimal blending management of biomass resources used for biochemical conversion. *Biofuels, Bioprod. Bioref.* **2018**, 12, 624–648, DOI 10.1002/bbb.1877.
 - (24) Aden, A.; Ruth, M.; Ibsen, K.; Jechura, J.; Neeves, K.; Sheehan, J.; Wallace, B.; Montague, L.; Slayton, A.; Lukas, J. Lignocellulosic biomass to ethanol process design and economics utilizing co-current dilute acid prehydrolysis and enzymatic hydrolysis for corn stover; National Renewable Energy Lab., Golden, CO.(US), **2002**; <https://www.nrel.gov/docs/fy02osti/32438.pdf> (accessed January 22, 2019).
 - (25) Miao, Z.; Grift, T. E.; Ting, K. C. Size reduction and densification of lignocellulosic biomass feedstock for biopower, bioproducts, and liquid biofuel production. In

- Encyclopedia of agricultural, food, and biological engineering, second edition*; Heldman, D. R.; Moraru, C. I., Eds.; CRC Press, 2010; pp. 1–4, DOI: 10.1081/E-EAFE2-120051298.
- (26) Shinnars, K.; Friede, J. Energy requirements for biomass harvest and densification. *Energies* **2018**, *11*, 780, DOI 10.3390/en11040780.
 - (27) Lammers, B. P.; Buckmaster, D. R.; Heinrichs, A. J. A simple method for the analysis of particle sizes of forage and total mixed rations. *J. Dairy Sci.* **1996**, *79*, 922–928, DOI 10.3168/jds.S0022-0302(96)76442-1.
 - (28) Sokhansanj, S.; Kumar, A.; Turhollow, A. Development and implementation of integrated biomass supply analysis and logistics model (IBSAL). *Biomass and Bioenergy* **2006**, *30*, 838–847, DOI 10.1016/j.biombioe.2006.04.004.
 - (29) Liu, Z.-H.; Qin, L.; Pang, F.; Jin, M.-J.; Li, B.-Z.; Kang, Y.; Dale, B. E.; Yuan, Y.-J. Effects of biomass particle size on steam explosion pretreatment performance for improving the enzyme digestibility of corn stover. *Industrial Crops and Products* **2013**, *44*, 176–184, DOI 10.1016/j.indcrop.2012.11.009.
 - (30) Nguyen, T.-A. D.; Kim, K.-R.; Han, S. J.; Cho, H. Y.; Kim, J. W.; Park, S. M.; Park, J. C.; Sim, S. J. Pretreatment of rice straw with ammonia and ionic liquid for lignocellulose conversion to fermentable sugars. *Bioresour. Technol.* **2010**, *101*, 7432–7438, DOI 10.1016/j.biortech.2010.04.053.
 - (31) Chen, X.; Kuhn, E.; Jennings, E. W.; Nelson, R.; Tao, L.; Zhang, M.; Tucker, M. P. DMR (deacetylation and mechanical refining) processing of corn stover achieves high monomeric sugar concentrations (230 g L^{-1}) during enzymatic hydrolysis and high ethanol concentrations ($>10\% \text{ v/v}$) during fermentation without hydrolysate purification or concentration. *Energy Environ. Sci.* **2016**, *9*, 1237–1245, DOI 10.1039/C5EE03718B.
 - (32) Yancey, N. A.; Wright, C. T.; Conner, C. C.; Tumuluru, J. S. Optimization of preprocessing and densification of sorghum stover at full-scale operation. In 2011 ASABE Annual International Meeting; American Society of Agricultural and Biological Engineers, **2011**, DOI 10.13031/2013.37273.
 - (33) Jacobson, J. J.; Roni, M. S.; Lamers, P.; Cafferty, K. G. Biomass feedstock and conversion supply system design and analysis. Idaho National Laboratory, Idaho Falls, ID, **2014**; <https://inldigitallibrary.inl.gov/sites/sti/sti/6359707.pdf> (accessed January 22, 2019).
 - (34) Humbird, D.; Davis, R.; Tao, L.; Kinchin, C.; Hsu, D.; Aden, A.; Schoen, P.; Lukas, J.; Olthof, B.; Worley, M. Process design and economics for biochemical conversion of lignocellulosic biomass to ethanol: dilute-acid pretreatment and enzymatic hydrolysis of corn stover; National Renewable Energy Laboratory (NREL), Golden, CO., **2011**; <https://www.nrel.gov/docs/fy11osti/47764.pdf> (accessed January 22, 2019).
 - (35) Intelligen. SuperPro Designer ; Intelligen, 2018.
 - (36) Sokhansanj, S.; Mani, S.; Turhollow, A.; Kumar, A.; Bransby, D.; Lynd, L.; Laser, M. Large-scale production, harvest and logistics of switchgrass (*Panicum virgatum* L.) -

- current technology and envisioning a mature technology. *Biofuels, Bioprod. Bioref.* **2009**, 3, 124–141, DOI 10.1002/bbb.129.
- (37) Sokhansanj, S.; Mani, S.; Tagore, S.; Turhollow, A. F. Techno-economic analysis of using corn stover to supply heat and power to a corn ethanol plant – Part 1: Cost of feedstock supply logistics. *Biomass Bioenergy* **2010**, 34, 75–81, DOI 10.1016/j.biombioe.2009.10.001.
 - (38) An, H.; Searcy, S. W. Economic and energy evaluation of a logistics system based on biomass modules. *Biomass and Bioenergy* **2012**, 46, 190–202, DOI 10.1016/j.biombioe.2012.09.002.
 - (39) Idaho National Laboratory (INL). Feedstock supply system design and economics for conversion of lignocellulosic biomass to hydrocarbon fuels. Idaho National Laboratory, Idaho Falls, ID, **2013**; <https://bioenergy.inl.gov/Reports/Design%20Case%202017.pdf> (accessed January 22, 2019).
 - (40) Baral, N. R.; Davis, R.; Bradley, T. H. Supply and value chain analysis of mixed biomass feedstock supply system for lignocellulosic sugar production. *Biofuels, Bioprod. Bioref.* **2019**, 13(3), 635–659, DOI 10.1002/bbb.1975.
 - (41) ORNL. Development of the Integrated Biomass Supply Analysis and Logistics Model (IBSAL). Oak Ridge National Laboratory, Oak Ridge, TN, **2008**; <https://pdfs.semanticscholar.org/fb01/c190bcb71a9a1657d5fafddb66beb5f19b41.pdf> (accessed March 9, 2020).
 - (42) Baral, N. R.; Quiroz-Arita, C.; Bradley, T. H. Uncertainties in corn stover feedstock supply logistics cost and life-cycle greenhouse gas emissions for butanol production. *Appl. Energy* **2017**, 208, 1343–1356, DOI 10.1016/j.apenergy.2017.09.020.
 - (43) Sahoo, K.; Mani, S. Techno-economic assessment of biomass bales storage systems for a large-scale biorefinery. *Biofuels, Bioprod. Bioref.* **2017**, 11, 417–429, DOI 10.1002/bbb.1751.
 - (44) Goeser, J. P.; Heuer, C. R.; Crump, P. M. Forage fermentation product measures are related to dry matter loss through meta-analysis. *The Professional Animal Scientist* **2015**, 31, 137–145, DOI 10.15232/pas.2014-01356.
 - (45) USDA. Field Crops Usual Planting and Harvesting Dates. United States Department of Agriculture, Washington, D.C., **2010**; <https://downloads.usda.library.cornell.edu/usda-esmis/files/vm40xr56k/dv13zw65p/w9505297d/planting-10-29-2010.pdf> (accessed March 10, 2020).
 - (46) Miller, E. A.; Buser, M. D.; Huhnke, R. L.; Taylor, R. K. Machine Power and Drying Rate Relationships for High Energy Forage Sorghum. In *2013 ASABE Annual International Meeting*; American Society of Agricultural and Biological Engineers, **2013**; 1–21, DOI 10.13031/aim.20131618668.
 - (47) OSUBioenergy. Conditioning and Baling Sorghum-Developing a Sustainable Biomass Production System, Oklahoma State University, **2012**, <https://www.youtube.com/watch?v=YyYoMGTKUz8> (accessed Aug 25, 2020).

- (48) Khanchi, A.; Jones, C. L.; Sharma, B. Characteristics and compositional variation in round and square sorghum bales under different storage conditions. In 2009 ASABE Annual International Meeting; American Society of Agricultural and Biological Engineers, 2009, DOI 10.13031/2013.27801.
- (49) Huntington, T.; Cui, X.; Mishra, U.; Scown, C. D. Machine learning to predict biomass sorghum yields under future climate scenarios. *Biofuels, Bioprod. Bioref.* **2020**, DOI 10.1002/bbb.2087.
- (50) Turhollow, A. The economics of energy crop production. *Biomass and Bioenergy* **1994**, 6, 229–241, DOI 10.1016/0961-9534(94)90077-9.
- (51) Thompson, J. L.; Tyner, W. E. Corn stover for bioenergy production: Cost estimates and farmer supply response. *Biomass and Bioenergy* **2014**, 62, 166–173, DOI 10.1016/j.biombioe.2013.12.020.
- (52) Gutesa, S. Using GIS and Intelligent Transportation Tools for Biomass Supply Chain. Master thesis, Iowa State University, **2013**;
<https://lib.dr.iastate.edu/cgi/viewcontent.cgi?article=4393&context=etd> (accessed March 10, 2020).
- (53) ORNL. Cost Methodology for Biomass Feedstocks: Herbaceous Crops and Agricultural Residues. Oak Ridge National Laboratory, Oak Ridge, TN, **2009**;
<https://pdfs.semanticscholar.org/3f28/acdff5d254d9a31ce6ccfee66afd0abfb0a.pdf> (accessed Dec 31, 2019).
- (54) Neupane, B.; Konda, N. V. S. N. M.; Singh, S.; Simmons, B. A.; Scown, C. D. Life-Cycle Greenhouse Gas and Water Intensity of Cellulosic Biofuel Production Using Cholinium Lysinate Ionic Liquid Pretreatment. *ACS Sustain. Chem. Eng.* **2017**, 5, 10176–10185, DOI 10.1021/acssuschemeng.7b02116.
- (55) NREL. U.S. Life Cycle Inventory Database. National Renewable Energy Laboratory (NREL): Golden, CO, **2011**; <https://www.nrel.gov/lci/> (accessed Mar 10, 2020).
- (56) ECOINVENT. Ecoinvent LCI database. **2017**; <https://www.ecoinvent.org/> (accessed Jul 22, 2019).
- (57) A N L. Argonne GREET Model. Argonne National Laboratory: Lemont, IL, **2018**;
<https://www.anl.gov/es> (accessed Jul 20, 2019).
- (58) U.S. Department of Energy (DOE). 2016 Billion-Ton Report, Volume 2: Environmental Sustainability Effects of Select Scenarios from Volume 1. U.S. Department of Energy, Washington, DC, **2016**; <https://www.energy.gov/eere/bioenergy/downloads/2016-billion-ton-report-volume-2-environmental-sustainability-effects> (accessed January 22, 2019).
- (59) Dou, F.; Wight, J. P.; Wilson, L. T.; Storlien, J. O.; Hons, F. M. Simulation of biomass yield and soil organic carbon under bioenergy sorghum production. *PLoS ONE* **2014**, 9, e115598, DOI 10.1371/journal.pone.0115598.
- (60) Baral, N. R.; Kavvada, O.; Mendez-Perez, D.; Mukhopadhyay, A.; Lee, T. S.; Simmons, B. A.; Scown, C. D. Techno-economic analysis and life-cycle greenhouse gas mitigation

- cost of five routes to bio-jet fuel blendstocks. *Energy Environ. Sci.* **2019**, *12*, 807–824, DOI 10.1039/C8EE03266A.
- (61) A M S. Hay Reports. United States Department of Agriculture, Washington, D.C., **2020**; <https://www.ams.usda.gov/market-news/hay-reports> (accessed Mar 11, 2020)..
- (62) Christopher T. Wright; Peter A. Pryfogle; Nathan A. Stevens; J. Richard Hess; Corey W. Radtke. Value of distributed preprocessing of biomass feedstocks to a bioenergy industry. In *2006 Portland, Oregon, July 9-12, 2006*; American Society of Agricultural and Biological Engineers: St. Joseph, MI, 2006, DOI 10.13031/2013.21517.
- (63) Kaliyan, N.; Morey, R. V.; Tiffany, D. G. Economic and environmental analysis for corn stover and switchgrass supply logistics. *Bioenerg. Res.* **2015**, *8*, 1433–1448, DOI 10.1007/s12155-015-9609-y.
- (64) Canter, C. E.; Dunn, J. B.; Han, J.; Wang, Z.; Wang, M. Policy implications of allocation methods in the life cycle analysis of integrated corn and corn stover ethanol production. *Bioenerg. Res.* **2016**, *9*, 77–87, DOI 10.1007/s12155-015-9664-4.
- (65) Cai, H.; Dunn, J. B.; Wang, Z.; Han, J.; Wang, M. Q. Life-cycle energy use and greenhouse gas emissions of production of bioethanol from sorghum in the United States. *Biotechnol. Biofuels* **2013**, *6*, 141, DOI 10.1186/1754-6834-6-141.
- (66) Wang, S.; Wang, S.; Hastings, A.; Pogson, M.; Smith, P. Economic and greenhouse gas costs of Miscanthus supply chains in the United Kingdom. *Glob. Change Biol. Bioenergy* **2012**, *4*, 358–363, DOI 10.1111/j.1757-1707.2011.01125.x.
- (67) Shemfe, M. B.; Whittaker, C.; Gu, S.; Fidalgo, B. Comparative evaluation of GHG emissions from the use of Miscanthus for bio-hydrocarbon production via fast pyrolysis and bio-oil upgrading. *Appl. Energy* **2016**, *176*, 22–33, DOI 10.1016/j.apenergy.2016.04.113.

Table of Contents (TOC) graphic (For Table of Contents Use Only)

A cost and life-cycle greenhouse gas comparison of baling, module-building, and ensiling for direct-transport and depot-based biomass sorghum supply systems.