Lawrence Berkeley National Laboratory

Lawrence Berkeley National Laboratory

Title

HYDROLYZED WOOD SLURRY FLOW MODELING

Permalink

<https://escholarship.org/uc/item/17b963p7>

Author

Wrathall, Jim

Publication Date

1979-11-01

Lawrence Berkeley Laboratory

UNIVERSITY OF CALIFORNIA

ENERGY & ENVIRONMENT DIVISION

HYDROLYZED WOOD SLURRY FLOW MODELING

Jim Wrathall and Sabri Ergun

November 1979

RECEIVED
LAWRENCE
BERKELEY LABORATORY

MAR 14 1980

LIBRARY AND
DOCUMENTS SECTION

TWO-WEEK LOAN COPY

*This is a Library Circulating Copy
which may be borrowed for two weeks.
For a personal retention copy, call
Tech. Info. Division, Ext. 6782.*

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.

HYDROLYZED WOOD SLURRY FLOW MODELING

Jim Wrathall and Sabri Ergun

Lawrence Berkeley Laboratory
University of California
Berkeley, California 94720

Prepared for
Thermochemical Conversion Contractors' Meeting
Rolla, Missouri
7 November, 1979

Contract No. W-7405-ENG-48 U.S. Department of Energy

INTRODUCTION

Our project involves catalytic conversion of hydrolyzed wood slurry to fuel oil. Based on our experience at the Albany PDU (operated by Rust Engineering), we have designed a process to convert Douglas Fir chips into a pumpable fuel at costs comparable to current spot prices for Middle Eastern crude oil. Part of our task includes overcoming operating difficulties that have developed at the Albany pilot plant, one of which is production and handling of a pumpable, non-clogging hydrolyzed slurry as feedstock for a liquefaction process.

We have set up a flow system to investigate the properties of the hydrolyzed slurry in hopes of acquiring proficiency in control of slurry flow and development of conditions and correlations that will be of general usefulness to the chemical engineering community. We expect to issue operating directives based on our research which will be of value in solving some of the problems encountered at the Albany facility.

DISCUSSION OF SLIDES 1 - 5

As is shown in slide 1, our slurry flow modeling system consists of a hold tank, recirculating pump, high pressure pump, and a glass coil, and is designed to simulate a system of similar size that incorporates a fired tubular reactor in place of the glass coil.

The coil itself is a 3/8" outer diameter pyrex tube with a coil diameter of 14.5" and coil spacing of 1", making it 27" high. The internal diameter of the coil is 5 mm. As is seen from the data in slide 2, the laminar flow pressure drop for the coil is only 10 - 15% higher than that for a straight tube of equal length, indicating that the coiling has no serious effect on flow resistance.

The high pressure pump is a reciprocating pump (Bran-Lubbe) with stroke adjustable to 30 mm. Volumetric displacement (flow) is linear with stroke, as is seen in slide 3. The range of flow attainable with this pump corresponds quite well with our proposed residence times for both 1-litre and 4-litre tubular reactors.

Our experimental feedstock is a hydrolyzed wood slurry infused with gas. The stirred hold tank and recirculating pump (Moyno progressive cavity design) serve to homogenize the 3-phase slurry and push it to the high-pressure pump. The slurry itself presents the problems of settling (at low flow rates) and high viscosity. Proper homogenization eliminates settling but increases viscosity. The relationship between viscosity and concentration at constant gas volume percent is shown in slide 4.

Visual observation of the slurry flow shows it to be strictly laminar; in other words, there is absolutely no radial or axial mixing. Infused gas bubbles retain their size, shape and position in the flowing slurry. As seen in slide 5, for a given flow rate, pressure drop increases with concentration. Application of the Hagen-Poiseuille equation shows, in addition, that apparent viscosity decreases with increasing linear velocity, an effect confirmed by use of a spindle viscometer. This information indicates that the slurry is a pseudoplastic fluid similar in behavior to a polymer solution or a colloidal suspension.

CONCLUSION

In the course of these preliminary investigations we have encountered no problems of settling or clogging that have plagued the Albany facility on earlier occasions. Our success in handling the slurry in a reproducible manner suggests that it will present no roadblock in the overall process development.

Future work will involve careful development of pumping procedures for startup, process conditions, and shutdown. We will develop correlations of interest involving the several variables of pressure, stirring shear and power, gas volume, recirculation and recycle rates, viscosity, and concentration. We will attempt to develop a numerical or theoretical treatment of the previously uncharacterized three-phase hydrolyzed wood slurry, in close cooperation with the U.C. Chemical Engineering Department. Thus, our results will not only be of general usefulness to us in developing and perfecting our process, but will also be of interest to researchers studying fluids of a similar nature.

Slurry Flow - Modeling System

XBL 7912 - 13391

Figure 2

XBL 7912 - 13395

Figure 3

Figure 4

XBL 7912 - 13392

XBL 7912 - 13393

Figure 5