

Lawrence Berkeley National Laboratory

LBL Publications

Title

A STUDY OF THE INTERACTION OF NO₂ WITH CARBON PARTICLES

Permalink

<https://escholarship.org/uc/item/2pg3103s>

Authors

Gundel, L.A.
Guyot-Sionnest, N.S.
Novakov, T.

Publication Date

1988-04-01

c.2



Lawrence Berkeley Laboratory

UNIVERSITY OF CALIFORNIA

APPLIED SCIENCE DIVISION

RECEIVED
LAWRENCE
BERKELEY LABORATORY

JUN 23 1988


LIBRARY AND
DOCUMENTS SECTION

Presented at the Third International Conference on
Carbonaceous Particles in the Atmosphere,
Berkeley, CA, October 5-8, 1987

A Study of the Interaction of NO₂ with Carbon Particles

L.A. Gundel, N.S. Guyot-Sionnest, and T. Novakov

April 1988



APPLIED SCIENCE
DIVISION

TWO-WEEK LOAN COPY
*This is a Library Circulating Copy
which may be borrowed for two weeks.*

c.2
LBL-24704

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.

A STUDY OF THE INTERACTION OF NO₂ WITH CARBON PARTICLES*

L.A. Gundel, N.S. Guyot-Sionnest, and T. Novakov

Applied Science Division
Lawrence Berkeley Laboratory
University of California
Berkeley, California 94720

Abstract

The interaction of NO₂ in air (0.5-35 ppm) with carbon particles led to three products: NO gas, and NO₂⁻ and NO₃⁻, removed from the particles by water extraction. At 4 ppm or below, in dry or humid air, the product distribution, in relative molar amounts, was NO₃⁻ = 2NO₂⁻ = 2NO. At 20 ppm and above, the relative amounts of products depended on the presence of water vapor. In dry air NO = 3NO₃⁻ = 6NO₂⁻. In humid air NO = NO₂⁻ = 2NO₃⁻. For carbon slurries in water, [NO₂⁻] = 6[NO₃⁻] at an input concentration of NO₂ of 4 ppm. In comparison to carbon, alumina particles and glass beads removed NO₂ ineffectively. These results indicate that NO₂ oxidized the carbon particles while it was reduced to NO. NO₂ adsorbed at oxidized sites on the particles formed a surface species that was analyzed as nitrate. At high enough concentration of NO₂ (20 ppm and above), the interaction of NO and water vapor with the surface nitrate produced NO₂⁻. In slurries NO, generated from interaction of NO₂ with carbon, reacted with surface nitrate or nitric acid in solution to form the relatively large quantities of nitrite. This work suggests that NO_x reactions with carbon in droplets or on wet surfaces could be important sources for the production of nitrous acid in the environment.

*This work was supported by the Director, Office of Energy Research, Office of Health and Environmental Research, Division of Physical and Technological Research of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Introduction

This study examines the interaction of activated carbon particles with NO_2 in air. Its aim is to identify heterogeneous reactions involving NO_x species that may be important in the atmosphere and in indoor environments. Earlier work indicates that carbon can react quickly and irreversibly with NO_2 . Charcoal led a group of more than a dozen kinds of particles in ability to decompose NO_2 in a flow reactor (Judeikis et al., 1979). In an indoor air quality study, Girman (1986) added activated carbon to a room and observed simultaneous decreases in NO_2 and increases in NO concentrations. Akhter et al. (1984) found that NO_2 reacted rapidly with hexane soot, resulting in the formation of surface species C—ONO and C—NO_2 . Indoor surfaces such as wallboard and carpet can also act as sinks for NO_2 (Spicer et al., 1986, 1987) and as substrates for the conversion of NO_2 to NO (D'Octavio and Dietz, 1985; Nishimura et al., 1986; Yanagisawa et al., 1987).

Recent studies indicate that heterogeneous reactions involving NO_2 and water may be responsible for the formation of significant amounts of HONO in nighttime polluted air (Harris et al., 1982; Pitts et al., 1984a). Measurements of the rate of formation of HONO on the walls of environmental (smog) chambers (Sakamaki et al., 1983; Pitts et al., 1984b; Svensson et al., 1987) and in a simulated indoor environment (Pitts et al., 1985) support this interpretation. Apparently HNO_3 was also formed in these experiments, but it remained on the walls. Because the measured rates cannot account for all the observed ambient HONO (Heikes and Thompson, 1983), other as yet undiscovered processes, possibly involving ambient particles, may be important, as suggested by Sakamaki et al. (1983). Modeling studies of the fate of NO_2 and other pollutants indoors by Nazaroff and Cass (1986) also pointed to the potential importance of heterogeneous NO_x reactions.

This work concentrates on the interaction of ppm levels of NO_2 with carbon particles and compares the relative activities of activated carbon, alumina, and glass to convert NO_2 to NO , NO_2^- , and NO_3^- . The influence of both water vapor and liquid water on product distributions has also been studied.

Experimental Details

Experiments were performed with gas-particle and gas-liquid water-particle systems. Figure 1 shows a schematic diagram of the apparatus used for two-phase experiments (NO_2 + particles in air). NO_2 (500 ppm in N_2 , obtained from Scott-Marrin, Inc., Riverside, California) and clean dry air passed through mass flow controllers, mixed, and entered glass impingers that contained 20 mg activated carbon particles (ground RB1, from American Norit Company) or alumina (chromatographic activity grade 1, from ICN Pharmaceuticals). All experiments were conducted at room temperature. The particles were dispersed among 20 ml 3-mm diameter glass beads by vigorous shaking. Blank measurements were performed using glass beads alone. The activated carbon for these experiments has been chosen because in previous studies of the rate of oxidation of SO_3^- (Gundel et al., 1985), this carbon (RB1) was found to be the most active.

A Thermo-Electron Model 14D/E Chemiluminescent $\text{NO-NO}_2\text{-NO}_x$ Analyzer monitored NO and NO_2 concentrations downstream of the reaction vessel. Upstream NO_2 concentration ranged from 0.5 to 35 ppm, with a typical total flow of 1 liter/min at atmospheric pressure through the reaction vessel. Before the start of experiments, NO_2 in air at about 20 ppm passed through the tubing leading to the apparatus for an hour. With this preconditioning, NO was always less than 2% of NO_2 ; otherwise, up to 10% of the total NO_x was NO .

In some experiments humidified air entered the system just upstream of the reaction vessel, after passing through a temperature-controlled impinger that contained 10 ml water. The resulting relative humidity was 50% as measured by a dew point hygrometer (General Eastern Model 1200 AP). For dry experiments this auxiliary flow line was kept dry, but air passed through it at the same rate. Flow rates were measured with a calibrated wet-test meter.

After a 10-minute exposure to NO_2 , the sample of particles was sonicated in 20 ml deionized water and filtered through pre-extracted 0.22- μm pore size cellulose acetate filters (Millipore Corp.) before determining NO_2^- and NO_3^- by ion chromatography (IC) (Dionex Auto-Ion System 12 Analyzer). Because

the eluent was basic ($[\text{HCO}_3^-] = 3.0 \text{ mM}$ and $[\text{CO}_3^{2-}] = 2.4 \text{ mM}$), this analytical method could not distinguish between HNO_2 (nitrous acid) and NO_2^- (nitrite ion) or between HNO_3 (nitric acid) and NO_3^- (nitrate ion). Freshly prepared NaNO_2 and NaNO_3 solutions were used as standards. Background concentrations of nitrite and nitrate on the particles were determined by passing air alone through loaded reaction vessels for 10 min and then extracting as usual. pH measurements were performed on some of the filtered extracts after IC analysis.

The effects of varying flow rate through the reaction vessel were not investigated extensively. Future studies will vary the flow rate to determine whether the contact time between NO_2 and particles influences observed product distributions.

Three-phase experiments were conducted using the apparatus shown in Fig. 2. NO_2 (1 to 25 ppm) in air passed through 10-ml aliquots of water slurries of particles (1 mg/ml). To assure that NO_2 could dissolve in water during its residence time in the reaction vessel (Schwartz and White, 1981), a lower flow rate was used, typically 0.15 liter/min. This resulted in a residence time of 4 sec. After 10 minutes the slurries were filtered and analyzed by IC.

Particles were precleaned before use. A batch of about 10 g carbon was ground in an agate ball mill overnight and then washed three times in boiling deionized water, filtered through porous glass, dried overnight at 110°C , and reground in a small agate mortar. Earlier work with this type of activated carbon showed that this heating had no effect on its ability to oxidize SO_3^- (Gundel et al., 1985). The principal contaminant measured after this treatment was SO_4^{2-} , at about $2 \mu\text{moles/g C}$. Alumina was ground by hand in an agate mortar to a fine powder before extraction in boiling water. Filtration and air drying at 110°C followed. Glass beads, filters, and syringes were sonicated in deionized water and dried before use.

Results

Carbon. Figure 3 shows the amounts of NO , NO_2^- , and NO_3^- generated when NO_2 passed through carbon particles for initial NO_2 concentrations between 0.5 and 35 ppm. The results are expressed in

micromoles per gram C. These units adjust for differences in flow rates between experiments. The upper part of the figure contains data for NO_2 in dry air; the lower part shows the product distribution for humid air.

In dry air a significant part of the initial NO_2 was converted to NO. Above an upstream concentration of about 100 $\mu\text{moles NO}_2/\text{g C}$, NO was the principal product; but at all concentrations of NO_2 , the particles contained significant amounts of NO_2^- and NO_3^- . About half as much nitrite was formed as nitrate. A saturation effect occurred for each product: for the ionic species, the slope flattened above 80 $\mu\text{moles/g C}$; for NO the saturation did not appear until the initial NO_2 concentration was over 400 $\mu\text{moles/g C}$.

When the air stream contained water vapor at 50% relative humidity, the relative amounts of the products differed from the distribution in dry air. Throughout the concentration range of the experiments, approximately equal amounts of NO and NO_2^- were formed. Compared to carbon particles in dry air, this was an increase in production of nitrite at the expense of NO. At low NO_2 concentrations, nitrate was most abundant, as in dry air. Above 80 $\mu\text{moles NO}_2/\text{g C}$, the yield of nitrate remained constant, while NO_2^- and NO continued to increase with increasing initial NO_2 . About half as much nitrate was formed as in the dry NO_2 air mixture.

Figure 4 shows the amounts of NO_2^- and NO_3^- found in carbon slurries vs. amounts of NO_2 that entered the reaction vessel. Data are expressed in micromoles per gram C. Figure 5 contains data in micromoles per liter for experiments in which NO_2 passed through pure water in the impinger. Because the carbon concentration was 1 g/liter for the data shown in Fig. 4, the units of these figures are equivalent. The input NO_2 concentrations ranged from 1 to 25 ppm in these experiments.

About a third more NO_2 was trapped in carbon slurries than in pure water, and for carbon most of this was detected as nitrite. At 24 $\mu\text{moles NO}_2/\text{g C}$ (4 ppm) $[\text{NO}_2^-]$ was about 6 times $[\text{NO}_3^-]$. Above 100 $\mu\text{moles NO}_2/\text{g C}$ (~ 16 ppm), 95% of the NO_x^- was NO_2^- . Water alone contained equal amounts of nitrite and nitrate after NO_2 passed through it. The slopes of curves drawn in Figs. 4 and 5 decreased as initial

NO₂ increased, indicating saturation effects occurred, even in pure water.

Mass balance. At 40 μmoles NO₂/g C, the products and unreacted NO₂ accounted for 81% of the amount entering the reaction vessel. At 730 μmoles/g C, only about 20% of the input NO₂ could be accounted for. Slightly lower recoveries were observed for experiments conducted in humid air. The missing species may have reacted at or been adsorbed on the tubing walls downstream of the reaction vessel. Another possibility is conversion to nitrogenous species that were not detected or that remained on the carbon surface after extraction. Mass balance calculations could not be made for slurries because the NO_x sampling port was upstream of the reaction vessel in those experiments.

Alumina. Figure 6 shows the results for the interaction of NO₂ with alumina particles for both dry and humid air streams. No NO was produced, and for all values of entering NO₂ concentration, approximately equal amounts of NO₂⁻ and NO₃⁻ were found on the particles. Unreacted NO₂ was detected in large amounts downstream of the reaction vessel. The sum of nitrite, nitrate, and downstream NO₂ concentrations accounted for between 93 and 108% of the NO₂ that entered the impinger. At high NO₂ concentrations, the presence of water vapor depressed the ability of alumina to trap NO₂⁻ and NO₃⁻ by about a factor of three.

Alumina slurries trapped NO₂ only slightly more efficiently than water. Figure 7 shows amounts of nitrite and nitrate found, along with a comparison with water, for low levels of NO₂. No experiments were done with alumina at NO₂ concentrations higher than 50 μmoles/g alumina. Although NO₂⁻ concentrations were somewhat higher than NO₃⁻, the differences were not so pronounced as in carbon slurries, where NO₂⁻ clearly dominated.


Glass beads. Below 80 μmoles NO₂ per liter of beads (equivalent to 80 μmoles/g of particles because 20 mg of particles were dispersed among 20 ml of glass beads), the beads contained no nitrite or nitrate above blank values. This was true for dry and humid gas streams. In dry and humid air, above 400 μM NO₂/liter about 0.3% and 0.7% respectively of the NO₂ was extracted from the beads as equal amounts of NO₂⁻ and NO₃⁻. This represents less than 2% of the amounts removed from carbon, and 10 to

50% of the amounts removed from alumina.

Comparison. To enable comparison of the interaction of NO₂ with various substrates, Table 1 contains data for two-phase experiments at 4 ppm (about 75 μmoles NO₂/g) and three-phase experiments at 8 ppm (about 50 μmoles NO₂/g). For carbon in dry or humid air, about twice as much NO₃⁻ was formed as NO₂⁻, and amounts of NO equalled amounts of NO₂⁻. Carbon trapped about 6 times as much NO₂ as alumina. Glass beads were inert. Carbon slurries contained 9 times as much nitrite as nitrate. At 8 ppm NO₂, the total NO_x⁻ in solution was twice that in alumina slurries or water alone.

Discussion

Both alumina and glass beads trapped small amounts of NO₂ that appeared as equal amounts of nitrite and nitrate in water extracts. The same behavior appeared in alumina and pure water slurries. Observation of equal amounts of NO₂⁻ and NO₃⁻ suggests that reactive dissolution of NO₂ occurred according to reaction (1) (Schwartz and White, 1981):




Here the alumina or beads adsorbed some NO₂, which then reacted with water during extraction. The alumina and glass surfaces did not influence the ratio of nitrite to nitrate, and no NO was generated. Water vapor competed with NO₂ for adsorption sites on alumina, and the total amount of NO₂ trapped declined when water vapor was present. For both alumina and glass beads, most of the NO₂ passed through the reaction vessel unchanged. Adding alumina to water did not lead to increased amounts of nitrite and nitrate, compared to water alone, suggesting that the alumina surface was inactive in water.

In contrast to the behavior seen on alumina and glass surfaces, chemical reactions occurred on carbon particles. NO resulted from the reduction of NO₂ as it oxidized the surface. If an oxidized site C_xO was created, reaction (2), it could oxidize NO₂ and cause nitrate ion to appear in the water extract, reaction (3):






The relatively high yields of NO_3^- found at low NO_2 concentrations may also reflect the formation of the oxidized species by reaction (3) on previously formed C_xO sites, i.e. those already present on the particles before exposure to NO_2 . At high concentrations of NO_2 , another surface reaction could occur when water vapor was present in the gas stream -- the interaction of NO with NO_2 to form nitrous acid:



The homogeneous version of reaction (4) is too slow to be important in the gas phase (Heikes and Thompson, 1983; Pitts et al., 1984b). Nitric oxide could also react with the oxidized nitrogen already formed on the carbon surface to yield more nitrous acid:



The indicated stoichiometry of this reaction is probably not too meaningful. Both reactions (4) and (5) require NO and water at the surface, and they explain the observed dominance of nitrite formation on carbon in the presence of water vapor. When the NO_2 concentration was high enough to generate sufficient NO, appreciable amounts of nitrous acid could be formed by these reactions. Reaction (5) is somewhat similar to a reaction that can occur on the walls of smog chambers (Besemer and Nieboer, 1985):



Here the surface is not carbon but the Teflon wall, and the surface species is adsorbed nitric acid, shown in (6) as $\text{s}\cdot\text{HNO}_3$. In carbon slurries surface-generated NO may react with surface nitrate, reaction (5), or with nitrate in solution:



Reaction (7) can explain the observed prevalence of NO_2^- in carbon slurries.

Comparison to Other Work

The mechanism proposed here to explain the generation of NO from the carbon surface does not require the presence of water. This contrasts with the reaction scheme proposed by Nishimura et al.


(1986) and by Yanagasawa et al. (1987), who explained the source of NO in their experiments as decomposition of HNO₂ in a study of the interaction of NO₂ with indoor materials such as rush mats and gypsum wall board. These authors suggested that the HNO₂ was formed from reaction (1) and decomposed in the reverse of reaction (4).

Adsorption of NO₂ on carbon particles without reaction probably also occurred because some nitrite was formed even with no water vapor present. The source of this HNO₂ was reactive dissolution of adsorbed NO₂, reaction (1).

In studies of the reaction of NO₂/N₂O₄ with hexane soot, Akhter et al. (1984) found infrared evidence for formation of C-NO₂ and C-ONO groups on the soot surface. Absorbance for each species grew at the same rate. The C-ONO group may correspond to a surface product or intermediate whose decomposition leads to formation of NO in our work:



The C-NO₂ group may correspond to adsorbed NO₂ on the surface, which decomposes in water to form equal amounts of nitrite and nitrate:



The results of this study cannot be extrapolated directly to atmospheric chemistry because activated carbon particles may not simulate the behavior of combustion soot, and ambient NO₂ levels are much lower than those used here (parts per billion rather than parts per million).

Conclusions

This work identifies a new pathway for transformation of NO₂: reaction at the surface of carbon particles to produce NO, nitrite, and nitrate. The results of this study indicate that all these products can form easily and quickly on activated carbon particles, although no rates of generation were measured.

References

- Akhter, M.S., Chughtai, A.R., and Smith, D.M. (1984). *J. Phys. Chem.* 88:5334-5342.
- Besemer, A.C., and Nieboer, H. (1985). *Atmos. Environ.* 19:507-513.
- D'Ottavio, T.W., and Dietz, R.N. (1985). *Multizone NO₂ Reactivity in a Single Family Home*.
Brookhaven National Laboratory Report BNL 37497.
- Girman, J. (1986). Personal communication.
- Gundel, L.A., Benner, W.H., and Novakov, T. (1985). In *Symposium on Heterogeneous Processes in Source-Dominated Atmospheres, Preliminary Proceedings*. Lawrence Berkeley Laboratory Report LBL-20261, Paper 14.
- Harris, G.W., Carter, W.P.L., Winer, A.M., Pitts, Jr., J.N., Platt, U., and Perner, D. (1982). *Environ. Sci. Technol.* 16:414-419.
- Heikes, B.G., and Thompson, A.M. (1983). *J. Geophys. Res.* 88:10883-10895.
- Judeikis, H.S., Siegel, S., Stewart, T.B., Hedgpeth, H.R., and Wren, A.G. (1979). In *Nitrogenous Air Pollutants, Chemical and Biological Implications* (D. Grosjean, ed.) Ann Arbor Science, Ann Arbor, pp. 83-109.
- Nazaroff, W.W., and Cass, G.R. (1986). *Environ. Sci. Technol.* 20:924-934.
- Nishimura, H., Hayamizu, T., and Yanagisawa, Y. (1986). *Environ. Sci. Technol.* 20:413-416.
- Pitts, Jr., J.N., Bierman, H.W., Atkinson, R., and Winer, A.M. (1984a). *Geophys. Res. Lett.* 11:557-560.
- Pitts, Jr., J.N., Sanhueza, E., Atkinson, R., Carter, W.P.L., Winer, A.M., Harris, G.W., and Plum, C.N. (1984b). *Int. J. Chem. Kin.* 16:919-939.
- Pitts, Jr., J.N., Wallington, T.W., Bierman, H.W., and Winter, A.T. (1985). *Atmos. Environ.* 19:763-767.
- Sakamaki, F., Hatakeyama, S., and Akimoto, H. (1983). *Int. J. Chem. Kin.* 15:1013-1029.
- Schwartz, S.E., and White, W.H. (1981). In *Trace Atmospheric Constituents: Properties, Transforma-*

tions, and Fates (S.E. Schwartz, ed.). Wiley, New York, pp. 1-116.

Spicer, C., Coutant, R.W., and Ward, G.F. (1986). *Investigation of Nitrogen Dioxide Removal from Indoor Air*. GRI Report GRI-86/0303.

Spicer, C.W., Coutant, R.W., Gaynor, A.J., and Billick, I.H. (1987). In *Proceedings of the 4th International Conference on Indoor Air Quality and Climate, Berlin (West), 17-21 August 1987*. Institute for Water, Soil and Air Hygiene, Berlin, Vol. 1, pp. 371-375.

Svensson, R., Ljungström, E., and Lindquist, O. (1987). *Atmos. Environ.* 21:1529-1539.

Yanagisawa, Y., Fasano, A.M., Spengler, J.D., and Billick, I.H. (1987). In *Proceedings of the 4th International Conference of Indoor Air Quality and Climate, Berlin (West), 17-21 August 1987*. Institute for Water, Soil and Air Hygiene, Berlin, pp. 376-380.

Table 1. Comparison of the interactions of NO₂ with carbon, alumina, glass, and water.

	Condition ^a	NO ₂ (in) ppm	NO ₂ (in)	NO ₂ (out) μmoles/g	NO	NO ₂ ⁻	NO ₃ ⁻	Sum/NO ₂ (in) %
Carbon	Dry	4	80.1	2.7	14.6	12.2	22.7	65
	Humid	4	73.4	2.3	11.5	10.7	21.3	62
	Slurry	8	51.6	b	b	6.5	0.76	-
Alumina	Dry	4	75.4	72.6	c	4.8	4.2	108
	Humid	4	75.4	67.8	c	4.1	4.0	101
	Slurry	8	49.6	b	b	2.2	1.8	-
Glass beads	Dry	4	75.4	75.4	c	c	c	100
	Humid	4	75.4	75.4	c	c	c	100
Liquid water	Liquid ^d	8	48.8	b	b	2.1	1.9	-

^a Averaged data from duplicate experiments, when available.

^b No data available.

^c Below the limit of detection.

^d Micromoles per liter.

Figure Captions

Figure 1. Schematic diagram of the apparatus used to study the interaction of NO_2 with carbon and alumina particles. For experiments in dry air, the auxiliary line was used as shown, but the humidifier vessel was empty.

Figure 2. Schematic diagram of the apparatus used to study the interaction of NO_2 with carbon and alumina particles in water.


Figure 3. Amounts of nitrogenous species resulting from the interaction of NO_2 with carbon particles in two-phase experiments vs. initial amount of NO_2 . Upper: NO_2 in dry air; lower: NO_2 in humid air (50% relative humidity). Solid line and \square , NO ; dashed line and cross, NO_2^- ; dotted line and ∇ , NO_3^- ; hexagon - NO_2 measured downstream of the reaction vessel.

Figure 4. Amounts of NO_2^- and NO_3^- determined in carbon slurries vs. amount of NO_2 . Dashed line and \circ , NO_2^- ; dotted line and ∇ , NO_3^- ; solid line and \square , $\text{NO}_2^- + \text{NO}_3^-$.

Figure 5. Amounts of NO_2^- and NO_3^- determined in water vs. initial amount of $\text{NO}_2(\text{g})$. Dashed line and \circ , NO_2^- ; dotted line and ∇ , NO_3^- ; solid line and \square , $\text{NO}_2^- + \text{NO}_3^-$.


Figure 6. Amounts of nitrogenous species resulting from the interaction of NO_2 with alumina particles in two-phase experiments vs. amount of $\text{NO}_2(\text{g})$. Upper: NO_2 in dry air; lower: NO_2 in humid air (50% relative humidity). \square - NO ; cross - NO_2^- ; ∇ - NO_3^- .

Figure 7. Upper: amounts of NO_2^- and NO_3^- in alumina slurries (1 g/liter) vs. amount of NO_2 . Dashed line and \circ , NO_2^- ; dotted line and ∇ , NO_3^- ; solid line and \square , $\text{NO}_2^- + \text{NO}_3^-$. Lower: Amounts of NO_2^- and NO_3^- in pure water vs. amount of NO_2 .



XBL 8712-5307


Figure 1




XBL 8712-5308

Figure 2

Carbon + NO₂ in Dry Air




Carbon + NO₂ in Humid Air



XBL 981 8806A


Figure 3



XBL 881-9515


Figure 4

Water



XBL 881-8802


Figure 5




XBL 881-8807

Figure 6

Alumina Particles in Water



Water



XBL 881 3802 A

Figure 7

LAWRENCE BERKELEY LABORATORY
TECHNICAL INFORMATION DEPARTMENT
UNIVERSITY OF CALIFORNIA
BERKELEY, CALIFORNIA 94720