UC Berkeley

UC Berkeley Previously Published Works

Title

Readout rebalancing for near-term quantum computers

Permalink

<https://escholarship.org/uc/item/3db9m67x>

Journal

Physical Review A, 103(2)

ISSN

2469-9926

Authors

Hicks, R
Bauer, CW
Nachman, B

Publication Date

2021-02-01

DOI

10.1103/PhysRevA.103.022407

Peer reviewed

Readout rebalancing for near-term quantum computers

Rebecca Hicks,^{1,*} Christian W. Bauer^{2,†} and Benjamin Nachman^{2,‡}

¹*Department of Physics, University of California, Berkeley, Berkeley, California 94720, USA*

²*Physics Division, Lawrence Berkeley National Laboratory, Berkeley, California 94720, USA*

Readout errors are a significant source of noise for near-term intermediate-scale quantum computers. Mismeasuring a qubit as $|1\rangle$ when it should be $|0\rangle$ occurs much less often than mismeasuring a qubit as $|0\rangle$ when it should have been $|1\rangle$. We make the simple observation that one can improve the readout fidelity of quantum computers by applying targeted X gates prior to performing a measurement. These X gates are placed so that the expected number of qubits in the $|1\rangle$ state is minimized. Classical postprocessing can undo the effect of the X gates so that the expectation value of any observable is unchanged. This protocol is designed to have no effect when readout errors are symmetric. We show that the statistical uncertainty following readout error corrections is smaller when using readout rebalancing. The statistical advantage is circuit and computer dependent and is demonstrated for the W state, a Grover search, and for a Gaussian state. The benefit in statistical precision is most pronounced (and nearly a factor of 2 in some cases) when states with many qubits in the excited state have high probability.

I. INTRODUCTION

Quantum computers hold great promise for a variety of scientific and industrial applications. However, existing noisy intermediate-scale quantum (NISQ) computers [1] introduce significant errors that must be mitigated before achieving useful output. Error mitigation on a quantum computer [2–6] is significantly different than classical error mitigation because quantum bits (“qubits”) cannot be copied [7–9]. Full quantum error correction requires significant overhead in the additional number of qubits and gates. This has been demonstrated for simple quantum circuits [10–19] but is infeasible on NISQ hardware due to limited qubit counts and circuit depths. Instead, a variety of schemes have been proposed to mitigate—without completely eliminating—errors. There are two types of errors that are targeted by these schemes: Those that affect the preparation of the quantum state [20–25] and those that affect the measurement of the prepared state [10, 26–42]. This paper focuses on the latter type—called readout errors—and how one can modify the quantum state prior to readout in order to reduce these errors.

Readout errors typically arise from two sources: (1) Measurement times are significant in comparison to decoherence times and, thus, a qubit in the $|1\rangle$ state¹ can decay to the $|0\rangle$ state during a measurement, and (2) probability distributions of measured physical quantities that correspond to the $|0\rangle$ and $|1\rangle$ states have overlapping support, and there

is a small probability of measuring the opposite value. The first of these sources results in asymmetric errors: Incorrectly measuring state $|0\rangle$ as $|1\rangle$ occurs much less frequently than incorrectly measuring state $|1\rangle$ as $|0\rangle$. The goal of this paper is to introduce a method that addresses this asymmetry to reduce readout errors. In particular, we propose to use quantum (classical) X gates before (after) making a measurement to essentially relabel qubits that are likely to be in the $|1\rangle$ state. This *Readout rebalancing* must be combined with additional readout corrections to unfold the migrations. Previous studies have proposed symmetrizing the readout with targeted X gates [43, 44], but we are unaware of any proposal to introduce asymmetric rebalancing. Symmetrizing has the advantage that it is independent of the measured state and improves the fidelity of qubits that are more often in the $|1\rangle$ state. However, symmetrizing will necessarily reduce the fidelity for qubits that are more often in the $|0\rangle$ state (this is a state-dependent statement).

This paper is organized as follows. Section II introduces readout rebalancing and briefly reviews readout error mitigation. Numerical results are presented in Sec. III, and the paper ends with conclusions and outlook in Sec. IV.

II. METHOD

To motivate the rebalancing technique, we start with an illustrative example. Suppose that there is a two-qubit system with measurement errors $\Pr(|0\rangle_i \rightarrow |1\rangle_i) = 0$ and $\Pr(|1\rangle_i \rightarrow |0\rangle_i) = q_i$ for $i \in \{0, 1\}$ with no nontrivial multiqubit readout errors. When $q_i \rightarrow 0$, there are no readout errors. For simplicity, assume that $q_i \ll 1$ so that terms of $O(q_i^2)$ can be neglected. The readout corrections are estimated by inverting the 4×4 matrix encoding the transition probabilities between any possible true state and any possible observed

*rebecca_hicks@berkeley.edu

†cwbauer@lbl.gov

‡bpnachman@lbl.gov

¹We consider two-state systems and denote the excited state as $|1\rangle$ and the ground state as $|0\rangle$.

FIG. 1. An illustration of the readout rebalancing protocol. Here U_{circuit} represents the state preparation that must happen for each measurement and the readout error mitigation represented by an inverted response matrix R^{-1} (in practice, a more sophisticated readout error mitigation scheme may be used) is performed on an ensemble of measured states. From the measured values of the qubits of the first circuit which uses a small fraction of the total number of runs one then determines which qubits have $\langle q_i \rangle > 0.5$ and should, therefore, be flipped (the first and fifth in our example). One then runs the remaining large fraction of the runs on the modified second circuit.

state. Suppose this is used to correct readout errors and that the state is measured N times. Define $N_{|ij\rangle}$ as the number of true counts in state $|ij\rangle$ and $\hat{N}_{|ij\rangle}$ is the number of reconstructed counts in state $|ij\rangle$ following readout error corrections. By construction, $\mathbb{E}[\hat{N}_{|ij\rangle}] = N_{|ij\rangle}$. One can show that the variance of the counts after readout correction are given by (for details, see Appendix A)

$$\text{Var}[\hat{N}_{|ij\rangle}] = N_{|ij\rangle} \left(1 - \frac{N_{|ij\rangle}}{N}\right) + \Delta \text{Var}[\hat{N}_{|ij\rangle}], \quad (1)$$

with

$$\begin{aligned} \Delta \text{Var}[\hat{N}_{|00\rangle}] &= q_0 N_{|10\rangle} + q_1 N_{|01\rangle} + O(q^2) \\ \Delta \text{Var}[\hat{N}_{|11\rangle}] &= (q_0 + q_1) N_{|11\rangle} + O(q^2). \end{aligned} \quad (2)$$

In particular, if $N = N_{|11\rangle}$ (i.e., the other states have zero true counts), one finds $\text{Var}[\hat{N}_{|00\rangle}] = 0$, whereas $\text{Var}[\hat{N}_{|11\rangle}] \neq 0$ for nonvanishing q_i . On the other hand, if $N = N_{|00\rangle}$, both $\text{Var}[\hat{N}_{|00\rangle}] = 0$ and $\text{Var}[\hat{N}_{|11\rangle}] = 0$ vanish. This suggests that if one is trying to measure a state dominated by $|11\rangle$, it would be more effective to first invert $0 \leftrightarrow 1$, perform the measurement, and then swap back the classical bits afterward.

The readout rebalancing protocol is illustrated in Fig. 1. First, the probability mass function $\text{Pr}(x)$ over states x is estimated using a small fraction of the total number of intended

measurements.² Then, a rule is used to determine which qubits should be flipped prior to being measured with the goal of switching those qubits that are predominantly in the $|1\rangle$ state. There are multiple possible rules, and in this paper, we use a simple and effective approach. In this approach one first computes the average value of qubit i , $\langle q_i \rangle = \frac{1}{N} \sum_j q_{i,j}$, where N is the number of measurements and $q_{i,j} \in \{0, 1\}$ is the observed value for qubit i on measurement j . If this value is greater than 0.5, the qubit i is set to be flipped, and otherwise it is untouched. A modified circuit is then prepared where single qubit X gates are applied at the end of the circuit to the qubits set to be flipped. Using this modified circuit one then performs the intended measurements. These data are then corrected for biases introduced from readout errors and then postprocessed with classical X gates to undo the quantum X gates. Further information about the bias correction for readout errors is provided below.

As stated earlier, the reason that the readout rebalancing protocol is expected to be effective is that errors are asymmetric. Although we are not aware of other proposals for biased (circuit-specific) rebalancing, Google AI Quantum [43] (through its software CIRQ [45]), and Rigetti (through its software PYQUIL [44]) have proposed symmetric rebalancing whereby the result from a circuit is averaged with a version of its complement that uses some predetermined (non-state-specific) set of X gates. This approach improves the fidelity of qubits that are mostly in the one state, but it degrades the performance of measuring states where a qubit is mostly in the zero state. We will compare to a version of symmetrized readout where measurements are averaged using a nominal circuit and a circuit with all X gates.

There are many options for readout error corrections, indicated by R^{-1} in Fig. 1. Let m and t represent the raw and true probability mass functions of the state, respectively. Furthermore, $R_{ij} = \text{Pr}(m = i | t = j)$ is an estimate of the response matrix. This is typically extracted by performing $2^{n_{\text{qubit}}}$ measurements, one for each state prepared with a series of X gates and then measured without other circuitry. Note that this scales exponentially with the number of qubits, but a number of subexponential approximations have been proposed [31–33, 41, 46] (any of these could be combined with the readout rebalancing protocol). The simplest readout error correction approach is simply $\hat{t}_{\text{matrix}} = R^{-1}t$. For a variety of reasons, this may be suboptimal, and so, multiple alternative methods have been proposed [35, 37, 38]. In particular, $R^{-1}t$ need not be non-negative and amplifies statistical fluctuations when R has large off-diagonal components. In this paper, we will use iterative Bayesian unfolding (IBU) [47–49] as described in the context of quantum computing in Ref. [38].

²The dependence on the number of initial measurements is studied in Appendix B. These initial measurements could also enhance the final precision, but if they are a small fraction of the measurement budget, then their impact will be subleading. It may even be possible to adaptively adjust the maps as measurements are performed. When the average qubit value is far from 0.5, the potential gains are small.

This iterative procedure starts with $\hat{t}_i^0 = \Pr(m = i) = 1/2^n$ qubits and then,

$$\hat{t}_i^{n+1} = \sum_j \Pr(t = i | m = j) m_j \quad (3)$$

$$= \sum_j \frac{R_{ji} \hat{t}_i^n}{\sum_k R_{jk} \hat{t}_k^n} m_j. \quad (4)$$

We will use 100 iterations and label $\hat{t} \equiv \hat{t}^{100}$, but the results do not depend strongly on this number. IBU is a form of regularized matrix inversion that converges to the maximum likelihood estimate. It results in a strictly non-negative result which preserves unitarity. Furthermore, using a large but finite number of iterations damps oscillations from amplified statistical fluctuations.

The next session will illustrate readout rebalancing for several example states by combining it with IBU.

III. RESULTS

To demonstrate readout error corrections, we utilize the software package QISKIT by IBM [50]. States are measured 10^5 times for each setting, and 10^6 measurements are used to determine readout rebalancing maps.³ Readout errors from the IBM Q Tokyo machine (see Ref. [38]) are imported for illustrating the impact of readout rebalancing. The corresponding response matrix is presented in Fig. 2. Most of the probability mass in the response matrix is along the diagonal, which represents the probability for a particular state to be correctly measured. However, there are significant off-diagonal terms, which are more pronounced in the lower right part of the matrix. To illustrate this feature, the bottom plot in Fig. 2 shows the probability for a state to be correctly measured organized by the number of 0's in the state bitstring. As advertised earlier, more 1's in the bitstring correlate with a lower probability of being measured correctly.

The first example to demonstrate readout rebalancing uses a circuit U_{circuit} producing the inverted W state,

$$\psi_{W,I} = \frac{1}{\sqrt{5}}(|01111\rangle + |10111\rangle + \dots + |11110\rangle). \quad (5)$$

Measured counts from sampling $\psi_{W,I}$ are shown in the top plot of Fig. 3. The true distribution has five spikes corresponding to the five states with nonzero amplitude in Eq. (5). The raw data have nontrivial probability mass for other states due to readout errors (the off-diagonal elements in Fig. 2). Readout error corrections successfully morph the raw data m into $\hat{t}$ which closely resembles the true distribution t .

The impact of our method can be seen by comparing the statistical uncertainty of a particular expectation value obtained with and without readout rebalancing. Statistical uncertainties are determined by repeating the above procedure many (1000) times and then computing the mean and standard deviation. To be concrete, we choose the average value of the

FIG. 2. Top: An example response matrix for the IBM Q Tokyo machine with five qubits. Bottom: the probability to measure the correct string (diagonal elements of the top plot) as a function of the number of 0's in the bitstring.

integer obtained from the bitstring,

$$\langle O \rangle = \frac{1}{N} \sum_s n_s (s_0 + 2s_1 + 4s_2 + 8s_3 + 16s_4), \quad (6)$$

as a representative observable. Here $s_i \in \{0, 1\}$ is the value of the i th qubit in state s , n_s is the number of times the state is measured to be in state s , and $N = \sum_s n_s$ is the total number of measurements in one iteration of the procedure. For the inverted W state, the exact value of this observable is given by $\langle O \rangle = 124/4 = 24.8$. Computing the average value of $\langle O \rangle$ from repeating the procedure 1000 times reproduces this result with and without readout symmetrization and readout rebalancing. This is expected since the postprocessing step should not affect the central value. In contrast, the standard deviation across the 1000 runs of the procedure depends on the level of fidelity improvement one applies. Without any fidelity improvement, the standard deviation is given by 0.0232 ± 0.0005 with a symmetrized readout, it is 0.0214 ± 0.0005 , whereas for readout rebalancing one finds a standard deviation of 0.0189 ± 0.004 . This means that one can use fewer

³In practice, we advocate using far fewer measurements to determine the rebalancing maps. The difference for the examples presented in this section is negligible as shown in Appendix B.

FIG. 3. The inverted W state (top) and Grover state with the 11111 oracle (bottom) for the truth counts (t), the raw counts (m), and the readout corrected counts ($\hat{t}$).

measurements with readout rebalancing to achieve the same statistical precision as the nominal approach or for the same number of measurements; the statistical uncertainty is smaller with readout rebalancing included. In particular, reducing the statistical uncertainty by 20% is equivalent to having 50% more measurements (since $\sqrt{1.5} \sim 1.2$).

As a second example we use Grover's algorithm [51], shown in the bottom plot of Fig. 3. In general, given an oracle, Grover's algorithm is able to find the inputs that produce a particular output value. In our case, the oracle is the Boolean function $(x_0 \vee x_1 \vee x_2 \vee x_3 \vee x_4)$ where the input to x_i would be the i th bit of our bitstring. For this function to equal 1 our desired input would be state $|11111\rangle$, so instead of Eq. (6), we use the counts in the $|11111\rangle$ state as our observable for 10^5 measurements. As with the previous example, all three

TABLE I. Table summarizing the three examples given in the text. We show the fraction of events needed to obtain the same statistical power as for readout correction without any readout fidelity improvements.

	Symmetrized (%)	Rebalanced (%)
Inverted W	(85 ± 6)	(66 ± 5)
Grover	(78 ± 5)	(58 ± 5)
Gaussian ($\mu = -0.11$)	(98 ± 6)	(56 ± 5)
Gaussian ($\mu = 0.78$)	(80 ± 6)	(41 ± 4)

approaches achieve the consistent central values (2.57×10^4). However, the standard deviations are 210 ± 4 (default), 185 ± 4 (symmetrized readout), and 160 ± 4 (readout rebalancing). This 30% improvement in precision is equivalent to a 70% larger number of measurements (since $\sqrt{1.7} \sim 1.3$).

A third example is a one-dimensional Gaussian state, which arises in the context of a $(0 + 1)$ -dimensional noninteracting scalar quantum field theory (as the ground state of the harmonic oscillator) [52–59]. In order to illustrate the impact of readout rebalancing, a Gaussian random variable with mean μ and standard deviation 0.1 is digitized with five bits where $|00000\rangle \mapsto -1$ and $|11111\rangle \mapsto 1$, where μ ranges from -1 to 1. Probability mass functions of these Gaussian states are presented in the top plot of Fig. 4.

The mean and standard deviation of $\langle O \rangle$ are shown in the middle and bottom plots of Fig. 4, respectively. As expected, $\langle O \rangle$ increases monotonically with μ and is the same with and without readout rebalancing. However, due to the larger number of 1's on the right side of the digitized domain of the Gaussian, readout rebalancing results in a smaller statistical uncertainty than the nominal approach. Readout rebalancing results in a relatively constant statistical precision as a function of μ with a slight increase in the middle of the domain due to a balanced number of 0's and 1's. With readout rebalancing, the right side of the domain is equivalent to the left side. For μ close to one, the improvement in the statistical uncertainty is nearly a factor of 2.

We summarize the results of the three examples in Table I. This table shows the fraction of events that are required to achieve the same statistical power compared with the case where no rebalancing is performed before readout error correction. One can see that the Rebalanced approach proposed in this paper outperforms the Symmetrized result and that by performing readout rebalancing one can save about a factor of 2 in the number of measurements required.

IV. CONCLUSIONS

We have introduced a modification to readout error mitigation that can be combined with other approaches to readout error corrections. Although the benefit of this readout rebalancing scheme is circuit dependent and may be modest, there is minimal computational cost and when states with many 1's are frequent, the gain in statistical precision can be significant.

The code for Readout Rebalancing can be found in Ref. [60].

FIG. 4. Top: the true counts for the truncated Gaussian states with fixed variance and shifted means. Middle (right): the average value (standard deviation) of the state when converting the bitstring to base 10 as a function of the Gaussian mean. $\langle O \rangle$ is computed over a particular set of measurements, and then this procedure is repeated 1000 times to compute the mean and standard deviation. Error bars represent statistical uncertainties.

ACKNOWLEDGMENTS

We would like to thank M. Freytsis, B. de Jong, and M. Urbanek for useful discussions and feedback on the paper. This work was supported by the U.S. Department of Energy, Office of Science under Contract No. DE-AC02-05CH11231. In particular, support comes from Quantum Information Science Enabled Discovery (QuantISED) for High Energy Physics (Grant No. KA2401032) and the Office of Advanced Scientific Computing Research (ASCR) through the Accelerated Research for Quantum Computing Program. This research used resources of the Oak Ridge Leadership Computing Facility, which is a DOE Office of Science User Facility supported under Contract No. DE-AC05-00OR22725.

APPENDIX A: DETAILED DERIVATION OF AN ANALYTIC EXAMPLE

Given a state containing two qubits there are four possible states $|00\rangle$, $|01\rangle$, $|10\rangle$, and $|11\rangle$. Prior to readout error corrections (PRC), the measured count for a state $|ij\rangle$ is given by $\hat{N}_{|ij\rangle}^{\text{PRC}}$. The expectation values $\mathbb{E}[\hat{N}_{|ij\rangle}^{\text{PRC}}] = \hat{N}_{|ij\rangle}^{\text{PRC}}/N$ of those counts are related to the expectation values of the true counts via

$$\mathbb{E}[\hat{N}_{|00\rangle}^{\text{PRC}}] = \mathbb{E}[N_{|00\rangle}] + q_0 \mathbb{E}[N_{|10\rangle}] + q_1 \mathbb{E}[N_{|01\rangle}], \quad (\text{A1})$$

$$\mathbb{E}[\hat{N}_{|01\rangle}^{\text{PRC}}] = (1 - q_1) \mathbb{E}[N_{|01\rangle}] + q_0 \mathbb{E}[N_{|11\rangle}] \quad (\text{A2})$$

$$\mathbb{E}[\hat{N}_{|10\rangle}^{\text{PRC}}] = (1 - q_0) \mathbb{E}[N_{|10\rangle}] + q_1 \mathbb{E}[N_{|11\rangle}], \quad (\text{A3})$$

$$\mathbb{E}[\hat{N}_{|11\rangle}^{\text{PRC}}] = (1 - q_0 - q_1) \mathbb{E}[N_{|11\rangle}] + O(q^2). \quad (\text{A4})$$

One can, therefore, obtain the expectation values of the true counts by computing the reconstructed counts from the measured counts as

$$\hat{N}_{|00\rangle} = \hat{N}_{|00\rangle}^{\text{PRC}} - q_1 \hat{N}_{|01\rangle}^{\text{PRC}} - q_0 \hat{N}_{|10\rangle}^{\text{PRC}} + O(q^2), \quad (\text{A5})$$

$$\hat{N}_{|01\rangle} = \hat{N}_{|01\rangle}^{\text{PRC}} (1 + q_1) - q_0 \hat{N}_{|11\rangle}^{\text{PRC}} + O(q^2), \quad (\text{A6})$$

$$\hat{N}_{|10\rangle} = \hat{N}_{|10\rangle}^{\text{PRC}} (1 + q_0) - q_1 \hat{N}_{|11\rangle}^{\text{PRC}} + O(q^2), \quad (\text{A7})$$

$$\hat{N}_{|11\rangle} = (1 + q_0 + q_1) \hat{N}_{|11\rangle}^{\text{PRC}} + O(q^2). \quad (\text{A8})$$

and requiring $\mathbb{E}[\hat{N}_{|ij\rangle}] = \mathbb{E}[N_{|ij\rangle}]$.

The variance of $\hat{N}_{|ij\rangle}$ determines how many overall runs are required to obtain $\mathbb{E}[N_{|ij\rangle}]$ with a given accuracy. One way of viewing $\hat{N}_{|ij\rangle}^{\text{PRC}}$ is as a multinomial random variable with total number N and probabilities given by Eqs. (A1)–(A4) via $p_{ij} = \mathbb{E}[\hat{N}_{|ij\rangle}^{\text{PRC}}]/N$. Therefore,

$$\text{Var}[\hat{N}_{|ij\rangle}^{\text{PRC}}] = p_{ij}(1 - p_{ij})N, \quad (\text{A9})$$

$$\text{Cov}[\hat{N}_{|ij\rangle}^{\text{PRC}}, \hat{N}_{|i'j'\rangle}^{\text{PRC}}] = -p_{ij}p_{i'j'}N. \quad (\text{A10})$$

Using the fact that

$$\text{Var}[aX + bY] = a^2 \text{Var}(X) + b^2 \text{Var}(Y) + 2ab \text{Cov}(X, Y),$$

FIG. 5. The probability that the rebalancing map m is optimal $= (1, 1, 1, 1, 1)$ as a function of the number of initial measurements reserved for determining the rebalancing map. The probability is determined by averaging over 20 runs.

one can derive

$$\text{Var}[\hat{N}_{ij}] = N_{ij} \left(1 - \frac{N_{ij}}{N}\right) + \Delta \text{Var}[\hat{N}_{ij}], \quad (\text{A11})$$

with

$$\Delta \text{Var}[\hat{N}_{00}] = q_0 N_{10} + q_1 N_{01}, \quad (\text{A12})$$

$$\Delta \text{Var}[\hat{N}_{01}] = q_0 N_{11} + q_1 N_{01}, \quad (\text{A13})$$

$$\Delta \text{Var}[\hat{N}_{10}] = q_1 N_{11} + q_1 N_{10}, \quad (\text{A14})$$

$$\Delta \text{Var}[\hat{N}_{11}] = (q_0 + q_1) N_{11}, \quad (\text{A15})$$

where Eqs. (A12)–(A15) have all been expanded to linear order in q_i and, therefore, have corrections of order q_i^2 .

APPENDIX B: STATISTICS OF THE REBALANCING MAPS

This Appendix explores how the dependence on the number of measurements on the rebalancing maps. A rebalancing map $m \in \{0, 1\}^{n_{\text{qubit}}}$ where a 0 in the i th entry means that the i th qubit is untouched by the map and otherwise if the value is 1, then the qubit is flipped.

Figure 5 presents the probability that the rebalanced map is optimal for the W inverted state. In this case, the optimal map is $(1, 1, 1, 1, 1)$ (all qubits are flipped) so the probability is $\text{Pr}[m = (1, 1, 1, 1, 1)]$. Bit strings selected uniformly at random would have a $\frac{1}{2^5} \approx 3\%$ chance of yielding the optimal map. This probability grows to approximately 100% by only 100 measurements.

Rebalancing maps for the Gaussian state are investigated in Fig. 6 for $\mu = -0.75$ and $\mu = 0.75$. Except for the first

FIG. 6. The average rebalancing map value for each of the five qubits and for $\mu = -0.75$ (top) and $\mu = 0.75$ (bottom). A value of 0 means that the qubit is untouched and a value of 1 represents a qubit that is flipped. The probability is determined by averaging over 20 runs, and error bands represent the standard error.

qubit, the maps converge after about 1000 measurements, far below the total budget used for the main measurements presented in the body of the paper (10^4). In both cases, the first qubit map requires much longer to converge because the average value of the qubit is close to 0.5. In particular, the average qubit values in the $\mu = -0.75$ case are approximately $(0.498, 0.481, 0.588, 0.010, 0.001)$ and in the $\mu = 0.75$ case, the average values are approximately $(0.499, 0.520, 0.411, 0.986, 0.997)$. For the cases when $\langle q \rangle \approx 0.5$, there is no change in the variance if the qubit is flipped or not, and so the long convergence times for these maps

is irrelevant. The practical gains from rebalancing are most important when there are qubits with $\langle q \rangle$ far from 0.5 and

these maps converge rapidly with a precision that scales with the inverse square root of the number of initial measurements.

-
- [1] J. Preskill, Quantum computing in the NISQ era and beyond, *Quantum* **2**, 79 (2018).
 - [2] D. Gottesman, An introduction to quantum error correction and fault-tolerant quantum computation, [arXiv:0904.2557](#).
 - [3] S. J. Devitt, W. J. Munro, and K. Nemoto, Quantum error correction for beginners, *Rep. Prog. Phys.* **76**, 076001 (2013).
 - [4] B. M. Terhal, Quantum error correction for quantum memories, *Rev. Mod. Phys.* **87**, 307 (2015).
 - [5] D. A. Lidar and T. A. Brun, *Quantum error correction* (Cambridge University Press, 2013).
 - [6] M. A. Nielsen and I. L. Chuang, *Quantum Computation and Quantum Information: 10th Anniversary Edition*, 10th ed. (Cambridge University Press, New York, 2011).
 - [7] J. L. Park, The concept of transition in quantum mechanics, *Found. Phys.* **1**, 23 (1970).
 - [8] W. K. Wootters and W. H. Zurek, A single quantum cannot be cloned, *Nature (London)* **299**, 802 (1982).
 - [9] D. Dieks, Communication by epr devices, *Phys. Lett.* **92A**, 271 (1982).
 - [10] M. Urbanek, B. Nachman, and W. de Jong, Quantum error detection improves accuracy of chemical calculations on a quantum computer, *Phys. Rev. A* **102**, 022427 (2020).
 - [11] J. R. Wootton and D. Loss, Repetition code of 15 qubits, *Phys. Rev. A* **97**, 052313 (2018).
 - [12] R. Barends, J. Kelly, A. Megrant, A. Veitia, D. Sank, E. Jeffrey, T. C. White, J. Mutus, A. G. Fowler, B. Campbell, Y. Chen, Z. Chen, B. Chiaro, A. Dunsworth, C. Neill, P. O'Malley, P. Roushan, A. Vainsencher, J. Wenner, A. N. Korotkov, A. N. Cleland, and J. M. Martinis, Superconducting quantum circuits at the surface code threshold for fault tolerance, *Nature (London)* **508**, 500 (2014).
 - [13] J. Kelly, R. Barends, A. G. Fowler, A. Megrant, E. Jeffrey, T. C. White, D. Sank, J. Y. Mutus, B. Campbell, Y. Chen, Z. Chen, B. Chiaro, A. Dunsworth, I.-C. Hoi, C. Neill, P. J. J. O'Malley, C. Quintana, P. Roushan, A. Vainsencher, J. Wenner, A. N. Cleland, and J. M. Martinis, State preservation by repetitive error detection in a superconducting quantum circuit, *Nature (London)* **519**, 66 (2015).
 - [14] N. M. Linke, M. Gutierrez, K. A. Landsman, C. Figgatt, S. Debnath, K. R. Brown, and C. Monroe, Fault-tolerant quantum error detection, *Sci. Adv.* **3**, e1701074 (2017).
 - [15] M. Takita, A. W. Cross, A. D. Córcoles, J. M. Chow, and J. M. Gambetta, Experimental Demonstration of Fault-Tolerant State Preparation with Superconducting Qubits, *Phys. Rev. Lett.* **119**, 180501 (2017).
 - [16] J. Roffe, D. Headley, N. Chancellor, D. Horsman, and V. Kendon, Protecting quantum memories using coherent parity check codes, *Quantum Sci. Technol.* **3**, 035010 (2018).
 - [17] C. Vuillot, Is error detection helpful on IBM 5Q chips?, *Quantum Inf. Comput.* **18**, 0949 (2018).
 - [18] D. Willsch, M. Willsch, F. Jin, H. De Raedt, and K. Michielsen, Testing quantum fault tolerance on small systems, *Phys. Rev. A* **98**, 052348 (2018).
 - [19] R. Harper and S. T. Flammia, Fault-Tolerant Logical Gates in the IBM Quantum Experience, *Phys. Rev. Lett.* **122**, 080504 (2019).
 - [20] A. Kandala, K. Temme, A. D. Córcoles, A. Mezzacapo, J. M. Chow, and J. M. Gambetta, Error mitigation extends the computational reach of a noisy quantum processor, *Nature (London)* **567**, 491 (2019).
 - [21] E. F. Dumitrescu, A. J. McCaskey, G. Hagen, G. R. Jansen, T. D. Morris, T. Papenbrock, R. C. Pooser, D. J. Dean, and P. Lougovski, Cloud Quantum Computing of an Atomic Nucleus, *Phys. Rev. Lett.* **120**, 210501 (2018).
 - [22] Y. Li and S. C. Benjamin, Efficient Variational Quantum Simulator Incorporating Active Error Minimization, *Phys. Rev. X* **7**, 021050 (2017).
 - [23] K. Temme, S. Bravyi, and J. M. Gambetta, Error Mitigation for Short-Depth Quantum Circuits, *Phys. Rev. Lett.* **119**, 180509 (2017).
 - [24] S. Endo, S. C. Benjamin, and Y. Li, Practical Quantum Error Mitigation for Near-Future Applications, *Phys. Rev. X* **8**, 031027 (2018).
 - [25] A. He, B. Nachman, W. A. de Jong, and C. W. Bauer, Zero-noise extrapolation for quantum-gate error mitigation with identity insertions, *Phys. Rev. A* **102**, 012426 (2020).
 - [26] R. C. Bialczak, M. Ansmann, M. Hofheinz, E. Lucero, M. Neeley, A. D. O'Connell, D. Sank, H. Wang, J. Wenner, M. Steffen, A. N. Cleland, and J. M. Martinis, Quantum process tomography of a universal entangling gate implemented with Josephson phase qubits, *Nat. Phys.* **6**, 409 (2010).
 - [27] M. Neeley, R. C. Bialczak, M. Lenander, E. Lucero, M. Mariantoni, A. D. O'Connell, D. Sank, H. Wang, M. Weides, J. Wenner, Y. Yin, T. Yamamoto, A. N. Cleland, and J. M. Martinis, Generation of three-qubit entangled states using superconducting phase qubits, *Nature (London)* **467**, 570 (2010).
 - [28] A. Dewes, F. R. Ong, V. Schmitt, R. Lauro, N. Boulant, P. Bertet, D. Vion, and D. Esteve, Characterization of a Two-Transmon Processor with Individual Single-Shot Qubit Readout, *Phys. Rev. Lett.* **108**, 057002 (2012).
 - [29] E. Magesan, J. M. Gambetta, A. D. Córcoles, and J. M. Chow, Machine Learning for Discriminating Quantum Measurement Trajectories and Improving Readout, *Phys. Rev. Lett.* **114**, 200501 (2015).
 - [30] S. Debnath, N. M. Linke, C. Figgatt, K. A. Landsman, K. Wright, and C. Monroe, Demonstration of a small programmable quantum computer with atomic qubits, *Nature (London)* **536**, 63 (2016).
 - [31] C. Song, K. Xu, W. Liu, C.-p. Yang, S.-B. Zheng, H. Deng, Q. Xie, K. Huang, Q. Guo, L. Zhang, P. Zhang, D. Xu, D. Zheng, X. Zhu, H. Wang, Y.-A. Chen, C.-Y. Lu, S. Han, and J.-W. Pan, 10-Qubit Entanglement and Parallel Logic Operations with a Superconducting Circuit, *Phys. Rev. Lett.* **119**, 180511 (2017).
 - [32] M. Gong, M.-C. Chen, Y. Zheng, S. Wang, C. Zha, H. Deng, Z. Yan, H. Rong, Y. Wu, S. Li, F. Chen, Y. Zhao, F. Liang, J. Lin, Y. Xu, C. Guo, L. Sun, A. D. Castellano, H. Wang, C. Peng, C.-Y. Lu, X. Zhu, and J.-W. Pan, Genuine 12-Qubit Entanglement on

- a Superconducting Quantum Processor, *Phys. Rev. Lett.* **122**, 110501 (2019).
- [33] K. X. Wei, I. Lauer, S. Srinivasan, N. Sundaresan, D. T. McClure, D. Toyli, D. C. McKay, J. M. Gambetta, and S. Sheldon, Verifying multipartite entangled GHZ states via multiple quantum coherences, *Phys. Rev. A* **101**, 032343 (2020).
- [34] V. Havlicek, A. D. Córcoles, K. Temme, A. W. Harrow, A. Kandala, J. M. Chow, and J. M. Gambetta, Supervised learning with quantum enhanced feature spaces, *Nature (London)* **567**, 209 (2019).
- [35] Y. Chen, M. Farahzad, S. Yoo, and T.-C. Wei, Detector tomography on IBM 5-qubit quantum computers and mitigation of imperfect measurement, *Phys. Rev. A* **100**, 052315 (2019).
- [36] M.-C. Chen, M. Gong, X.-S. Xu, X. Yuan, J.-W. Wang, C. Wang, C. Ying, J. Lin, Y. Xu, Y. Wu, S. Wang, H. Deng, F. Liang, C.-Z. Peng, S. C. Benjamin, X. Zhu, C.-Y. Lu, and J.-W. Pan, Demonstration of Adiabatic Variational Quantum Computing with a Superconducting Quantum Coprocessor, *Phys. Rev. Lett.* **125**, 180501 (2020).
- [37] F. B. Maciejewski, Z. Zimborás, and M. Oszmaniec, Mitigation of readout noise in near-term quantum devices by classical post-processing based on detector tomography, *Quantum* **4**, 257 (2020).
- [38] B. Nachman, M. Urbanek, W. A. de Jong, and C. W. Bauer, Unfolding quantum computer readout noise, *npj Quantum Inf.* **6**, 84 (2020).
- [39] K. E. Hamilton and R. C. Pooser, Error-mitigated data-driven circuit learning on noisy quantum hardware, *arXiv:1911.13289*.
- [40] P. J. Karalekas, N. A. Tezak, E. C. Peterson, C. A. Ryan, M. P. da Silva, and R. S. Smith, A quantum-classical cloud platform optimized for variational hybrid algorithms, *Quantum Sci. Technol.* **5**, 024003 (2020).
- [41] M. R. Geller and M. Sun, Efficient correction of multiqubit measurement errors, *arXiv:2001.09980*.
- [42] M. R. Geller, Rigorous measurement error correction, *Quantum Sci. Technol.* **5**, 03LT01 (2020).
- [43] M. P. Harrigan *et al.*, Quantum approximate optimization of non-planar graph problems on a planar superconducting processor, *arXiv:2004.04197*.
- [44] Rigetti Forest Software Development Kit, Source code for pyquil.noise, <http://docs.rigetti.com/en/stable/noise.html>.
- [45] The Cirq Contributors, Cirq, a python framework for creating, editing, and invoking Noisy Intermediate Scale Quantum (NISQ) circuits, <https://github.com/quantumlib/Cirq> (2020).
- [46] K. E. Hamilton, T. Kharazi, T. Morris, A. J. McCaskey, R. S. Bennink, and R. C. Pooser, Scalable quantum processor noise characterization, *arXiv:2006.01805*.
- [47] G. D'Agostini, A Multidimensional unfolding method based on Bayes' theorem, *Nucl. Instrum. Methods Phys. Res., Sect. A* **362**, 487 (1995).
- [48] L. B. Lucy, An iterative technique for the rectification of observed distributions, *Astron. J.* **79**, 745 (1974).
- [49] W. H. Richardson, Bayesian-based iterative method of image restoration, *J. Opt. Soc. Am.* **62**, 55 (1972).
- [50] IBM Research, QISKIT, <https://qiskit.org> (2019).
- [51] L. K. Grover, A fast quantum mechanical algorithm for database search, in *Proceedings of the Twenty-Eighth Annual ACM Symposium on Theory of Computing, STOC '96* (ACM, New York, 1996), pp. 212–219.
- [52] S. P. Jordan, H. Krovi, K. S. M. Lee, and J. Preskill, BQP-completeness of scattering in scalar quantum field theory, *Quantum* **2**, 44 (2018).
- [53] S. P. Jordan, K. S. M. Lee, and J. Preskill, Quantum computation of scattering in scalar quantum field theories, *Quant. Inf. Comput.* **14**, 1014 (2014).
- [54] S. P. Jordan, K. S. M. Lee, and J. Preskill, Quantum algorithms for quantum field theories, *Science* **336**, 1130 (2012).
- [55] S. P. Jordan, K. S. M. Lee, and J. Preskill, Quantum algorithms for fermionic quantum field theories, *arXiv:1404.7115*.
- [56] R. D. Somma, Quantum simulations of one dimensional quantum systems, *Quantum Inf. Comput.* **16**, 1125 (2016).
- [57] A. Macridin, P. Spentzouris, J. Amundson, and R. Harnik, Electron-Phonon Systems on a Universal Quantum Computer, *Phys. Rev. Lett.* **121**, 110504 (2018).
- [58] A. Macridin, P. Spentzouris, J. Amundson, and R. Harnik, Digital quantum computation of fermion-boson interacting systems, *Phys. Rev. A* **98**, 042312 (2018).
- [59] N. Klco and M. J. Savage, Digitization of scalar fields for quantum computing, *Phys. Rev. A* **99**, 052335 (2019).
- [60] <https://github.com/LBNL-HEP-QIS/ReadoutRebalancing>.