Lawrence Berkeley National Laboratory

Recent Work

Title

Imaging and quantification of spreading and trapping of carbon dioxide in saline aquifers using meter-scale laboratory experiments

Permalink

<https://escholarship.org/uc/item/3fv5v9rr>

Journal

Water Resources Research, 53(1)

ISSN

0043-1397

Authors

Trevisan, L
Pini, R
Cihan, A
et al.

Publication Date

2017

DOI

10.1002/2016WR019749

Peer reviewed

**Imaging and quantification of spreading and trapping of carbon dioxide in saline aquifers
using meter-scale laboratory experiments**

Luca Trevisan^{1,2}, Ronny Pini^{3,4}, Abdullah Cihan⁵, Jens T. Birkholzer⁵, Quanlin Zhou⁵, Ana
Gonzalez-Nicolas^{1,5}, Tissa H. Illangasekare¹

¹Center for Experimental Study of Subsurface Environmental Processes (CESEP), Department of
Civil and Environmental Engineering, Colorado School of Mines, Golden, Colorado, USA

²Now at Gulf Coast Carbon Center, Bureau of Economic Geology, Jackson School of Geosciences,
University of Texas at Austin, Austin, Texas, USA

³Department of Petroleum Engineering, Colorado School of Mines, Golden, Colorado, USA

⁴Now at Department of Chemical Engineering, Imperial College, London, UK

⁵Energy Geosciences Division, Lawrence Berkeley National Laboratory, University of California,
Berkeley, California, USA

Corresponding author: Luca Trevisan (luca.trevisan@gmail.com)

Abstract

The role of capillary forces during buoyant migration of CO₂ is critical towards plume immobilization within the post-injection phase of a geological carbon sequestration operation. However, the inherent heterogeneity of the subsurface makes it very challenging to evaluate the effects of capillary forces on the storage capacity of these formations and to assess in-situ plume evolution. To overcome the lack of accurate and continuous observations at the field scale and to mimic vertical migration and entrapment of realistic CO₂ plumes in the presence of a background hydraulic gradient, we conducted two unique long-term experiments in a 2.44 m × 0.5 m tank. X-ray attenuation allowed measuring the evolution of non-wetting phase (NWP) saturation, thus providing direct insight into capillarity- and buoyancy-dominated flow processes occurring under successive drainage and imbibition conditions. The comparison of saturation distributions between two experimental campaigns suggests that layered-type heterogeneity plays an important role on NWP migration and trapping, because it leads to (i) longer displacement times (3.6 months vs. 24 days) to reach stable trapping conditions, (ii) limited vertical migration of the plume (with center of mass at 39% vs. 55% of aquifer thickness), and (iii) immobilization of a larger fraction of injected NWP mass (67.2% vs. 51.5% of injected volume) as compared to the homogenous scenario. While these observations confirm once more the role of geological heterogeneity in controlling buoyant flows in the subsurface, they also highlight the importance of characterizing it at scales that are below seismic resolution.

Keywords: surrogate fluids; sandbox experiments; migration and trapping; injection schemes; geological carbon storage

37 **Highlights:**

- 38 • We present a set of m-scale sandbox experiments designed to replicate field scale CO₂
39 injection configuration and contrast in fluid properties
- 40 • Multiple injection events, each followed by longer imbibition, are used to achieve larger
41 plume footprints, higher trapping efficiency, and larger total mass trapped
- 42 • X-ray attenuation is used for accurate quantification of CO₂-analog saturation and mass
43 balance calculations
- 44 • Time scales associated with stabilization of the plume are greatly enhanced by
45 heterogeneity

46

1. Introduction

Geological Carbon Storage (GCS) has the potential to stabilize and eventually reduce anthropogenic emissions of CO₂ to the atmosphere, thus facilitating the transition from fossil energy production to an extensive use of renewables. For GCS to considerably reduce global carbon emissions, large volumes of CO₂ have to be stored underground. This can be accomplished by taking advantage of the heterogeneous nature of deep brine-bearing sedimentary formations and by designing appropriate injection schemes. The heterogeneous nature of geological media plays a critical role in controlling the migration and entrapment of injected CO₂ by affecting the efficiency of both dissolution [Agartan *et al.*, 2015; Farajzadeh *et al.*, 2011] and capillary trapping [Bryant *et al.*, 2008; Trevisan *et al.*, 2015]. Hence, it becomes crucial to consider the influence of natural heterogeneity on storage capacity and efficiency whenever candidate reservoirs are identified [Kopp *et al.*, 2009]. Assuming that most candidate reservoirs are inherently heterogeneous, we can expect a persistent presence of so-called capillary barriers that possess variable spatial continuity and that lead to the plume concentrating in high permeability streaks and pooling behind less permeable layers. Because characterizing deep reservoirs' heterogeneity and assessing in-situ plume behavior (by means of e.g. preferential flow and fluid saturation evolution) is practically difficult, intermediate scale (dm-m) immiscible displacement experiments represent a convenient method for studying the influence of heterogeneity on macroscale migration and trapping phenomena. A further advantage of synthetic aquifers is the ability to test injection schemes that have potential applications in real storage scenarios. In the context of this work, we investigate the role of capillary forces during buoyant migration of CO₂ as a critical factor towards plume immobilization during post-injection of carbon storage in deep saline aquifers.

In general, the action of capillarity on immiscible fluid displacement manifests itself via two major phenomena, namely hysteresis and capillary barrier, causing occurrence of non-wetting phase (NWP) at different saturations across the porous medium. The importance of these phenomena has been pointed out by several numerical modeling studies focusing on a variety of specific aspects at the field scale [Bryant *et al.*, 2008; Deng *et al.*, 2012; Doughty and Pruess, 2004; Flett *et al.*, 2007; Saadatpoor *et al.*, 2010] and at the sub-meter scale [Kuo and Benson, 2015; Li and Benson, 2015; Ritzi *et al.*, 2016; Trevisan *et al.*, under review]. For example, spatial correlation of the permeability (k) field as well as interconnectivity of high- k preferential flow pathways have a critical impact on CO₂ migration and trapping in saline aquifers [Gershenzon *et al.*, 2015; Han *et al.*, 2010; Ide *et al.*, 2007; Lengler *et al.*, 2010; Tian *et al.*, 2016]. The modeling approach has also been followed, either numerically [Buscheck *et al.*, 2012; Gasda *et al.*, 2008; Goater *et al.*, 2013; Yamamoto *et al.*, 2009] or analytically [Gunn and Woods, 2011; Hesse *et al.*, 2006; MacMinn *et al.*, 2010; Zimoch *et al.*, 2011], to understand the behavior of a CO₂ plume in concomitance with regional groundwater flow and sloping caprock. Injection strategies aimed at enhancing the storage capacity and efficiency of saline formations have also been explored by means of numerical models [Buscheck *et al.*, 2012; Cameron and Durlofsky, 2012; Cihan *et al.*, 2015; Gonzalez-Nicolas *et al.*, under review; Huber *et al.*, 2016; Rasmusson *et al.*, 2016].

While numerical simulations have shed light on the influence of some of the geological and engineering aspects that control CO₂ trapping mechanisms, validation by means of experiments is still lacking. Hereby, the difficulty in carrying out controlled field experiments has always involved uncertainty related to the rigorous application of boundary conditions and the exact distribution of sandstone rock types. Most of the work to date has focused on non-aqueous phase liquid (NAPL) migration observed in sandbox experiments [e.g. Barth *et al.*, 2003; Fagerlund *et*

al., 2007; *Glass et al.*, 2000; *Kueper and Frind*, 1991], while studies that specifically address GCS are quite scarce and are limited to cm-to-m observations of immiscible [Pini et al 2012; *Polak et al.*, 2015; *Trevisan et al.*, 2014; *Werner et al.*, 2014; *Zhao et al.*, 2014] and miscible displacements [Agartan et al., 2015; *Neufeld et al.*, 2010]. A dimensional analysis approach has also been proposed to reconcile laboratory- and field-scales [Cinar et al., 2009; *Polak et al.*, 2015; *Trevisan et al.*, 2014; *Werner et al.*, 2014]. In this context, physical models prove to be very useful, because they enable a systematic evaluation of flow regimes and heterogeneity contrasts in terms of e.g., strength and correlation length of a permeability field. However, while studies so far have integrated heterogeneity in a simplified fashion, it has been long recognized that the complex geometrical arrangement of typical sedimentary facies plays a major role in capillary trapping [Mikes and Bruining, 2006; *Pickup et al.*, 2000; *Ringrose et al.*, 1993; *van Lingen et al.*, 1996].

To address the lack of geological realism of prior experimental studies, as well as the limited dimensional size available for long-term observation of migration and trapping phenomena, a set of sandbox experiments is performed in this study on a larger (2.44 m × 0.5 m) system. The setup is unique as it enables introducing realistic subsurface conditions, thus including the presence of a) a background hydraulic gradient, b) significant buoyant forces, and c) a wider continuum of heterogeneity scale. Results from two experiments are presented that have performed with surrogate fluids at ambient pressure-temperature (P - T) conditions. The first experiment is conducted in a homogeneous configuration, while the second represents a more realistic heterogeneous scenario. The scope of this experimental analysis is twofold. On the one hand, we present a bench-scale demonstration of injection schemes controlling the migration and immobilization of a surrogate CO₂ plume with and without the influence of heterogeneity. On the other hand, we provide an explicit characterization of the permeability field and boundary

conditions, as well as quantification of fluid saturation distribution, for future comparison with continuum-based numerical simulations. The uniqueness of these experiments lies in the ability to reproduce and observe those large-scale phenomena that control plume migration while hinting at the time scale for immobilization involved with geological heterogeneity.

2. Experimental approach and methods

Two experiments are presented in this study: a homogeneous setup using #50 Granusil sand and a spatially correlated, facies-based heterogeneous scenario with equivalent geometric mean μ_{lnk} of $3.86 \times 10^{-11} \text{ m}^2$ and a variance σ^2_{lnk} of 1.69. The two experiments presented in this study are carried out in a larger tank setup with respect to the studies by *Trevisan et al.* [2014] and *Trevisan et al.* [2015], offering the ability to recreate realistic plume spreading behavior through longer periods.

2.1 Experimental fluids

The experiments were conducted at ambient conditions with a pair of surrogate fluids that mimic the density and viscosity contrasts of scCO₂ and brine at reservoir P - T conditions, as reported in Table 1. However, these fluids are insoluble and do not allow for study of mixing and dissolution processes. Specifically, isoparaffinic oil (Soltrol 220) and a glycerol-water mixture (80:20 w/w) were chosen to represent the injected NWP and resident wetting-phase fluid (WP), respectively. Soltrol 220 was dyed red with Sudan IV (Fisher Scientific) and doped with 10% w/w Iodoheptane (Alfa Aesar) to allow for direct visualization of the fluid flow and to increase x-ray attenuation contrast between the two phases.

Table 1 Summary of density (ρ), viscosity (μ), and interfacial tension (IFT) of surrogate fluids at experimental P - T conditions and actual fluids of scCO₂ and brine at reservoir conditions.

phase	ρ (kg/m ³)	μ (mPa·s)	μ_{nw}/μ_w	ρ_{nw}/ρ_w	IFT (mN/m)
Soltrol 220	860	4.9	0.072	0.71	15
Glycerol-water	1210	61			
scCO₂	266-733 ^a	0.023-0.0611 ^a	0.026-0.20 ^a	0.22-0.75 ^a	19.8 ^b
	(760 ^c)	(0.06 ^c)			
Brine	945-1230 ^a	0.195-1.58 ^a	(0.075 ^c)	(0.745 ^c)	
	(1020 ^c)	(0.8 ^c)			

^a estimates from *Nordbotten et al.* [2005], T = 35-155°C, P = 10.5-31.5 MPa

^b measurement from *Bennion and Bachu* [2006], T = 43°C, P = 20 MPa, brine salinity = 2.7% wt.

^c estimates from *Singh et al.* [2010] for Sleipner field

2.2 Experimental aquifer tank

Both homogeneous and heterogeneous scenarios are performed in a sand pack enclosed by a Plexiglas and aluminum tank with internal dimensions (L × W × H) of (244 × 5 × 80.8) cm³. Each experiment consists of four stages: two NWP injection events separated by as many fluid redistribution (gravity relaxation) stages, during which the plume is allowed to reach hydrostatic equilibrium. Figure 1 illustrates the geometry of the tank setup and the sand arrangement for the homogeneous configuration (#50 sand for the aquifer, #8 sand for injection well and boundary layers, a fine sand mixture for the bottom and top aquitards, and a clay layer as caprock). The aquifer has a 5% slope (3° dip angle) achieved by tilting the setup during packing and a constant background WP flow is maintained in the updip direction by two constant head reservoirs connected to the coarse sand boundaries. The injection well consists of a 10-cm-high acrylic pipe (internal diameter, I.D.=4.5 cm) filled with #8 sand. The well is open at the top and supplied with NWP through the bottom from a constant pressure reservoir (a Mariotte's bottle) sitting on an electronic scale at 50 cm above the potentiometric surface. Since this is an inclined surface, the height difference is calculated with respect to the center of the tank. This pressure-controlled injection method was adopted for its easy implementation. However, as it will be shown in the

Discussion section, the injection flowrate resulting from this constant pressure potential condition shows fluctuations due to the influence of 1) the relative permeability of the NWP and 2) the intrinsic permeability of the sands intersected by the plume.

Figure 1 Schematic of the flow cell. Injection of NWP takes place from a well placed at the bottom of the aquifer. The aquifer has a gentle slope (3°) in the direction of the ambient flow (right to left). Coarse #8 sand is packed along upstream and downstream boundaries to equally constrain constant head conditions. Electronic scales continuously track NWP inflow and WP outflow masses.

2.3 Design of the heterogeneous setup

To explicitly represent a sedimentary structure with a correlated permeability field in a synthetic aquifer we follow the experimental approaches of *Barth et al.* [2001] and *Fernandez-Garcia et al.* [2004]. Six different sieve sizes are used to approximate a target log-normal distribution of the facies-based permeability field and populate a two-dimensional rectangular array of 122 by 25 cells with dimensions $(2 \times 2) \text{ cm}^2$. The six categories (or facies) correspond to Granusil silica sands #16, #20, #30, #50, #70, and #110, from coarsest to finest, spatially arranged

as shown in Figure 2A (see Table 2 for physical properties of the sands). Figure 2B shows the target histogram of $\ln k$ values for the six facies populating the permeability field (except for #8 sand used for boundaries and wells). Their volumetric fractions are: 3%, 11.4%, 19.5%, 30.8%, 24.6%, and 10.7%, respectively, following the log-normal distribution of permeability. The moderate permeability contrast of the experimental setup is used to shorten the experimental time by facilitating faster plume migration compared to actual reservoirs.

In order to compare the degree of heterogeneity of the synthetic reservoir with cases of practical interest, we estimate the permeability variation using the Dykstra-Parson coefficient V_{DP} [Craig, 1993]:

$$V_{DP} = \frac{k_{50} - k_{84.1}}{k_{50}} = 1 - e^{-\sigma} \quad (1)$$

where k_{50} is the mean permeability and $k_{84.1}$ is the mean permeability plus one standard deviation; for a homogeneous reservoir V_{DP} approaches zero, while for an extremely heterogeneous reservoir V_{DP} would approach one. For this study, V_{DP} is 0.73, which is in agreement with values reported in the literature [Behzadi and Alvarado, 2012; Farajzadeh et al., 2011; Kumar et al., 2005; Saadatpoor et al., 2010; Tchelepi and Orr, 1994; Tian et al., 2016]. Another metric often considered is the variance of $\ln k$ ($\sigma^2_{\ln k}$). In this study, a variance of 1.69 is selected, falling in the range of values (0.2 to 5) reported by a number of modeling studies relevant to GCS [Cameron and Durlofsky, 2012; Deng et al., 2012; Flett et al., 2004; Han et al., 2010; Lengler et al., 2010].

Capillary pressure $P_c(S)$ drainage curves of the sands cover a range of capillary entry pressures between 0.28 kPa and 2.04 kPa (Figure 2C). These values define the ability of NWP to invade a given sand, while the final saturation in each sand is controlled by the so-called buoyancy pressure,

P_b , exerted by the height difference H between the injected NWP and the resident WP during the injection (50 cm).

$$P_b = (\rho_w - \rho_{nw})gH \quad (2)$$

where ρ_w and ρ_{nw} are the densities of WP and NWP, respectively, and g is the gravitational constant. For simplicity, equation 2 defines P_b at the injection point, where it takes a value of 1.7 kPa, which is estimated using $H=50$ cm. Since this is in an open system, as the plume moves upwards, this initial buoyancy pressure will dissipate proportionally to its vertical location.

The spatial sand distribution is designed to mimic a layered structure that recreates a permeability field in agreement with most reservoir simulations [e.g., *Deng et al.*, 2012; *Flett et al.*, 2007; *Han et al.*, 2010; *Saadatpoor et al.*, 2010; *Tian et al.*, 2016]. The Sequential Indicator Simulation (SIS) algorithm [*Journel and Alabert*, 1990] combined with the open source program SGeMS [*Remy et al.*, 2009] is used to generate 20 equiprobable realizations based on an exponential variogram (equation 3).

$$\gamma(h_i) = c_0 \left[1 - \exp\left(-\frac{3h_i}{a_{0,i}}\right) \right] \quad (3)$$

where c_0 is the sill, h_i is the lag distance in the i direction (x, z), and $a_{0,i}$ is the range. The correlation length is defined as $\lambda_i = a_{0,i}/3$. The layered structure is built by assigning long horizontal (100/3 cm) and shorter vertical (4/3 cm) correlation lengths as input parameters for SIS simulations. Figure 2D shows the experimental variograms along the flow direction for 20 SIS realizations (gray symbols), highlighting the theoretical variogram (red line) and realization #18 (black symbols).

Figure 2 A) spatial arrangement of the six sand categories in SIS realization #18, with highlighted high- k clusters (dashed line represents x-ray detection edge); B) target histograms for the six sands representing a $\ln k$ distribution (k in m^2); C) characteristic $P_c(S)$ drainage curve for each sand, including #8 sand used for lateral boundaries and wells; D) theoretical (red line) and experimental (symbols) variograms for 20 realizations of the permeability field; the black variogram represents the realization selected for the packing setup (#18).

Table 2 Physical properties of the silica sand grades used in the experiments from *Sakaki and Illangasekare* [2007].

Material ID	Sieve size	k (m^2)	$\ln k$	ϕ_{avg} (-)	d_{50} (mm)	d_{60}/d_{10} (-)
1	#16	5.62×10^{-10}	-21.3	0.397	0.88	1.72
2	#20	2.14×10^{-10}	-22.3	0.41	0.7	
3	#30	1.23×10^{-10}	-22.8	0.433	0.5	1.50
4	#50	3.37×10^{-11}	-24.1	0.4	0.3	1.94
5	#70	1.43×10^{-11}	-25.0	0.44	0.2	1.86
6	#110	5.21×10^{-12}	-26.0	0.38	0.12	~2.0

Prior to injection, the porosity variation of the sand pack was determined for both homogeneous and heterogeneous packing configurations by measuring x-ray attenuation across the flow domain (supporting information Figure S1). Since the sands have all similar porosity (~ 0.4), their spatial distribution is not distinguishable from this contour plot; however, the evidence of an inclined stratification, as well as of the clay layer confining the aquifer (porosity > 0.5) is clear. The higher average porosity observed in the heterogeneous case is due to the looser packing carried out to minimize the mixing of finer and coarser sands.

2.4 Boundary conditions

A constant pressure ($P_b = 1.7$ kPa) boundary condition is applied at the injection well (see Figure 1). The target volume for each injection is 1 L, corresponding to approximately 0.044 pore volumes (estimated using extents of the aquifer multiplied by average porosity; $229 \text{ cm} \times 5 \text{ cm} \times 50 \text{ cm} \times 0.4$). Interestingly, despite both experiments share the same injected volume, the injections exhibit variable flowrate and therefore different duration. This behavior is further discussed in Section 4.3.

Prior to NWP injection, different background hydraulic gradients were tested to mimic the effect of regional groundwater flow through deep saline aquifers [Larkin, 2010], as shown in Figure 3. For the heterogeneous scenario, a 4.5-cm head difference across the domain was selected, resulting in a WP flow discharge of 0.56 ml/min at the left boundary and corresponding to a 2% hydraulic gradient. The latter was increased to 4.5% in the homogeneous scenario to maintain a similar WP flow discharge. This comparison shows the direct manifestation of the presence of high permeability layers channeling the flow in the heterogeneous setting, as the estimated

effective permeability for the heterogeneous case is $9.34 \times 10^{-11} \text{ m}^2$ and twice of the permeability for the homogeneous case ($4.28 \times 10^{-11} \text{ m}^2$).

Figure 3 Correlation between background hydraulic gradient and outflow rate Q (dashed line represents the 0.56 ml/min wetting phase flow discharge applied to both experiments).

2.5 Successive drainage and imbibition experiments

For each sand-packed large tank (homogeneous or heterogeneous), the experiment includes the first injection event with a target NWP volume of 1L, the first redistribution (or imbibition) event with no injection, the second injection event with the same volume, and the second redistribution event. Each of the redistribution events stops when no further movement of the plume is observed along horizontal and vertical directions. The design of these experiments aims to assess long-term migration and trapping of NWP in the meter-scale system. To the best knowledge of the authors, the long-term m-scale experiments conducted in this study are the first of the kind, providing a necessary dataset for understanding field-scale processes of scCO_2 migration and trapping. The reservoir thickness used in this study is only one order of magnitude smaller than that for some pilot and demonstration GCS projects. For example, the Frio C sand used for CO_2 injection in the Frio pilot test is ~ 5 meter thick.

Central to the experimental approach is the use of x-ray attenuation to measure the spatial and temporal distribution of the phase saturations in the sand pack non-invasively and with high spatial resolution (one measure every 15 mm in x and z directions). The saturation measurements represent a depth-average along the second horizontal axis (y) and an areal average over a sampling volume determined by the radius of the collimated x-ray beam (1 mm). Further details about the x-ray attenuation device, both hardware- and software-wise, as well as the procedure for x-ray data conversion into actual phase path-lengths can be found in *Trevisan et al.* [2014] and *Trevisan* [2015]. In conjunction with x-ray attenuation measurements, photographic images of the transparent walls of the flow cell are continuously gathered in order to discard any preferential flow of NWP along the vertical walls.

3. Experimental results

To show the effect of known heterogeneity structures on migration and trapping of NWP fluid, we present experimental observations for both homogeneous and heterogeneous setups in a similar fashion. Figure 4 and Figure 5 illustrate the development of NWP plumes qualitatively, with photography, and quantitatively, with saturation contours gathered via x-ray attenuation, for these experiments. For the sake of conciseness, only plume snapshots acquired at the end of the injection and redistribution stages are presented, while a more complete set of results at additional times is available as supplementary materials (Figure S.I.1 and Figure S.I.2). The tables embedded in Figure 4 and Figure 5 summarize the NWP mass balance corresponding to each snapshot. The NWP volumes are broken down into inflow, outflow, detected plume (above $z=0$), and undetected plume (below $z=0$) volumes within the sandbox. As a comparative measure between the two scenarios, we introduce a trapping efficiency factor, $\varepsilon = V_{plume}/V_{inflow}$, to represent the fraction

of NWP (detected and undetected) that remains in the domain with respect to the total amount injected. Additionally, we introduce the perimeter-to-area ratio (P/A) as an indicator of plume surface available for dissolution and chemical reactions.

3.1 Homogeneous scenario

The homogeneous experiment is designed to represent the simplest setting for a buoyant plume to migrate through a porous domain. The purpose of this fairly simplistic setup is twofold: 1) to observe plume behavior during successive drainage and imbibition events, which could be used in the future for testing two-phase flow models considering the effect of hysteresis, and 2) to provide a control experiment to compare with a more complex permeability field. To facilitate the comparison between both scenarios, we analyze each of the four stages separately.

First Injection Stage (0 to 22.05 hours, Figure 4, top row): early evolution of the plume appears to be controlled by buoyancy force, showing a chimney-like structure, which gradually develops into an asymmetrical shape, driven by the background WP flow from right to left. Since the plume reaches the caprock at the same time the injection is halted, the influence of aquifer dip on plume geometry is minimal during this stage. Also, towards the completion of this stage, the displacement front shows some unstable behavior characterized by several short-range fingers, possibly due to the buildup of the injection flow rate, causing viscous forces to dominate over capillary forces. The plume at the end of this stage is referred to “early plume”, and the saturation (i.e., maximum initial saturation for later imbibition) in this plume under drainage is relatively high.

First Fluid Redistribution Stage (22.05 to 327.27 hours, Figure 4, second row): once the first injection is complete, the plume is allowed to redistribute until it approaches equilibrium, which is considered when no further movement of the plume is observed along horizontal and vertical

directions (as shown in the Discussion section). During this buoyancy-dominated relaxation process, the plume (i.e., the post-injection plume) develops predominantly along a thin layer underneath the caprock and leaves behind a trail of residual saturation. Approximately 11 days after the injection ends, 35% of the injected mass has escaped out of the aquifer and the post-injection plume takes an average NWP saturation of 17%. Interestingly, this residually-trapped saturation is not homogeneously distributed within the plume, as shown by the x-ray contour maps, where values range between 5% and 20%. The highest saturation of trapped NWP occurs in the footprint of the early plume event and can be attributed to the high initial saturation within this footprint. Out of this footprint, the post-injection plume experiences drainage and imbibition during the redistribution period, and has much smaller initial maximum saturation (than that in the early plume at the end of the first injection event) that results in even smaller saturation of trapped NWP. These results indicate that the observed behavior of trapped NWP may be represented by existing empirical [e.g., *Land*, 1968] or non-empirical trapping models [e.g., *Cihan et al.*, 2014; *Cihan et al.*, under review]. The irregular saturation distribution within the footprint of the early plume probably results from the imperfect nature of the sand packing causing water encroachment to occur by non-uniform displacement/imbibition, as shown in pore network experiments by *Chang et al.* [2016]. Although the behavior observed here has been predicted at the reservoir scale by several continuum-based multiphase flow models [*Flett et al.*, 2007; *Kumar et al.*, 2005; *Lengler et al.*, 2010], no experimental evidence has been yet reported with such detailed characterization of the saturation distribution.

Second Injection Stage (327.27 to 350.65 hours, Figure 4, third row): during early times of the second injection event, the plume follows the path established by the previous injection event. However, before the target injection volume is reached, the lateral spreading of the plume increases

resulting in a wider footprint than the early plume, as well as larger median plume saturation (0.46 vs. 0.38), as shown in Figure 7. The larger spreading and higher saturation are most likely due to 1) the presence of trapped NWP in the early plume that has a detrimental effect on relative WP permeability as compared to the nearby NWP-free regions, 2) right-to-left background WP flow that results in the skewness of the plume, and 3) the dynamic evolution with additional injection that would occur for the same continuously injected volume of 2 L. All these effects cannot be distinguished by the only one dataset without comparison.

Second Fluid Redistribution Stage (350.65 to 590 hours, Figure 4, bottom row): the positive impact of a second injection event is revealed by the area occupied by the plume after the 2nd redistribution, which is 23% larger than the area occupied after the 1st injection and redistribution. Consequently, a larger footprint enables a 58% increase in residually stored mass. On the other hand, this experiment shows the principal disadvantage of fairly homogeneous and isotropic reservoirs, where gravity segregation causes the plume to bypass a large fraction of the reservoir. From the NWP saturation contour maps obtained with x-ray attenuation, a concave region of lower saturation surrounded by relatively higher saturation can be observed, as a possible effect of the background WP flow on plume trapping. Similar effects on the inhomogeneity of the trapped saturation distribution as for the first redistribution, but the region with higher residual saturations seems to be larger.

Note that the plume is always continuous in its footprint at the different stages of the experiment. The trapping efficiency factor after the second redistribution stage is 51.5%, smaller than 65% after the end of the first redistribution stage. However, a NWP volume of 1030 ml is trapped within a wider plume, larger than the total trapped volume of 650 ml after the first redistribution stage.

Figure 4 Homogeneous base case experiment: plume snapshots taken via photography (left) and x-ray attenuation (right) at the end of each stage: 1st injection (1st row), 1st redistribution (2nd row), 2nd injection (3rd row), and 2nd redistribution (4th row). Total NWP volumes corresponding to each snapshot are listed in the table.

3.2 Heterogeneous scenario

First Injection Stage (0 to 27.3 hours, Figure 5, top row): as opposed to the homogenous scenario, where the plume freely migrates upward and reaches the caprock by the end of the first

injection event, the presence of capillary and permeability barriers of finer sands in the heterogeneous scenario leads to a considerable reduction in vertical migration distance. The injected NWP fluid migrates into a cluster of connected coarse sands (#16, #20, #30) that is immediately above the injection well and bounded by fine #110 sand from the left and right sides and by #70 sand from the top of the cluster (see Figure 2A). With time, the injected NWP fluid accumulates in this high-permeability cluster, pools under the overlying less permeable #70 sand, and migrates downward to the left side following the structure of the coarse sands. This results in an increase in plume thickness and thus NWP pressure at the top of this NWP pool. When the NWP pressure at the bottom of #70 sand is higher than its entry capillary pressure (~ 1.2 kPa), the capillary barrier is broken and NWP starts to migrate upward through the #70 sand into the second cluster of coarse sands to form the second pool of NWP. Clearly, the plume includes two separate pools connected by a flow path through #70 sand where NWP saturation is small. However, it is this low-saturation flow path that supplies all NWP mass in the second, upper pool. The second cluster consists of #30 sand and #16 sand to the left and is bounded from the top by a continuous layer of #70 sand crossing over the entire sandbox length. At the end of this stage, the second pool is filled by NWP only in the #30 sand portion of this cluster. This accumulation-penetration-breakthrough phenomenon was simulated for stratified intra-formation layers for the Illinois Basin [Birkholzer and Zhou, 2009; Zhou et al., 2010], but this phenomenon is shown the first time in a laboratory experiment with sufficient aquifer thickness.

First Fluid Redistribution Stage (27.3 to 262.42 hours, Figure 5, second row): at the end of this stage, all injected NWP mass is trapped within the two pools by capillary barriers of the surrounding finer sands and local residual saturation in the two clusters of coarse sands. With time, the first, lower pool shrinks a little bit and its saturation decreases, leading to the reduction in NWP

pressure at the top of the pool. The reduced NWP mass from the lower pool migrates through the #70 sand flow path into the second, upper pool. At the end of this stage, the flow through this path ceases because at the bottom of this path, the continuous reduction in the NWP pressure and saturation leads to the balance between capillary force of the finer sand and buoyancy force from the lower pool. The capillary barrier of the fine #70 sand is recovered from its broken condition, trapping large amount of NWP mass in the lower pool with higher saturation than local residual saturation (~20%). With continuous inflow from the lower pool and redistribution in the upper pool, NWP fluid migrates updip to the left side and fills in a new branch of #16 sand facies. At the end of this stage, the saturation distribution in the upper pool follows the balance between capillary and buoyancy forces at any location of the pool. Due to the updip feature of the cluster and the pool, buoyancy-induced NWP pressure is the highest at the upper end of the pool on the left and lowest on the lower end of the pool on the right, resulting in the saturation variability in the pool.

The entire upper pool is trapped by the capillary barrier of the overlying continuous #70 sand layer, as the highest NWP pressure at the upper-left end of the pool is still lower than the entry capillary pressure of #70 sand. The upper pool is also surrounded by finer #50 sand on its left side and #50 and #70 sands on the right side of the pool. This phenomenon of a NWP pool of high saturation trapped in a “pocket-shaped” cluster of high-permeability sands by surrounding lower-permeability sands or shales on all sides (at least top and updip) except one in-flow side is referred to as “pocket” trapping. The in-flow side can be the downdip or bottom side through which NWP fluid or scCO₂ is supplied. The pocket trapping is caused by capillary and permeability barrier effects along the semi-closed boundary of the trapped NWP pool. This trapping is similar to the dead-end effect in contaminant transport [Coats and Smith, 1964] and hydrocarbon trapping in anticlines.

Second Injection Stage (262.42 to 293.42 hours, Figure 5, third row): the lower cluster of coarse sands and the lower NWP pool is additionally charged by injected NWP fluid, leading to an increase in NWP saturation in this pool. The increased saturation leads to higher capillary pressure at the top of the pool and the bottom of inter-pool #70 sand, breaking the capillary barrier again. Once the inter-pool flow path is reactivated for flow, the NWP pressure at the top of the upper pool increases sharply because the entire plume (i.e., the two pools and the inter-pool flow path) is connected, leading to much higher NWP columns. This higher NWP pressure drives NWP upward migration into the #50 sand facies overlying the #30 sand in the downdip portion and overlying the #16 sand in the updip portion of the upper pool.

Second Fluid Redistribution Stage (293.42 to 2400 hours, Figure 5, bottom row): with time of redistribution, NWP migrates updip further in the #50 sand from the #16 branch to expand the second pool. Meanwhile, the NWP pressure is sufficiently high at the updip ends of the pool, and thus breaks the capillary barrier of the continuous #70 sand layer at two locations. The newly-created two flow paths through #70 sand facilitate upward migration of NWP to form the third pool in the third cluster of #20, 30, and #50 sand. The same accumulation-penetration-breakthrough process continues to create the fourth and the fifth NWP pool. The fifth pool is connected to the left-side boundary, resulting in outflow of 35.7% of the injected mass from the sandbox. .

This last stage takes 2.9 months to reach quasi-hydrostatic equilibrium. 64.3% of the injected NWP is immobilized within the aquifer, a 12.8% increase with respect to the homogeneous scenario. Another significant feature of the plume is its specific surface area, represented by the P/A ratio, showing a tenfold increase with respect to the end of the first redistribution stage, and a

37-fold increase with respect to the end of the second redistribution stage for the homogeneous scenario.

Note that the contrasts of permeability and entry capillary pressure among the six sand facies are chosen to show all the physical processes and phenomena, including pooling under finer facies and capillary barrier effect, breakthrough of capillary barriers caused by buoyancy-enhanced NWP pressure, start and cessation of inter-pool NWP flow, and cyclic drainage and imbibition. These contrasts are also chosen to show residual trapping, hysteresis caused by cyclic drainage and imbibition, and pocket trapping that mainly depends on the heterogeneity structures. These chosen contrasts make this unique experiment feasible at the time scale of 100 days and the spatial scale of $244\text{ cm} \times 80.8\text{ cm} \times 5\text{ cm}$. The physical processes and phenomena and the trapping mechanisms demonstrated in the experiment are relevant to the field-scale GCS reservoirs that have much higher contrasts of permeability and entry capillary pressure. The higher contrasts will facilitate some phenomena, such as pocket trapping.

Time (h)	Inflow (ml)	Outflow (ml)	Above $z=0$ (ml)	Below $z=0$ (ml)	ε (%)	P/A (cm^{-1})
27.3	1000	0	353	647	100	0.082
255.17	1000	0	601	399	100	0.082
293.4	2000	0	1250	750	100	0.062
2400	2000	714	900	386	64.3	0.672

Figure 5 Heterogeneous experiment: plume snapshots taken via photography (left) and x-ray attenuation (right) at the end of each stage: 1st injection (1st row), 1st redistribution (2nd row), 2nd injection (3rd row), and 2nd redistribution (4th row). Total NWP volumes corresponding to each snapshot are listed in the table.

4. Discussion

Some important observations made in the homogeneous experiment include: 1) the linear increase in injection flowrate with time under the constant injection pressure condition, and the subsequent development of displacement front instabilities, 2) the absence of remobilized NWP during the second injection and the larger footprint achieved afterwards, and 3) the non-uniform NWP saturation distribution within the early plume footprint. The heterogeneous experiment provides the following observations: 1) the absence of CO₂ outflow after the first fluid redistribution, and 2) the longer time of plume redistribution (2.8 months). Some of these observations in the two experiments cannot be predicted by the state-of-the-art mathematical models, thus offering an opportunity to improve these models.

4.1 Spatial moment analysis

Besides visual observations and quantitative measurement of plume saturation via x-ray attenuation, we assess the spreading of the plume throughout the various stages of the experiments via analysis of spatial moments [Eichel *et al.*, 2005; Fagerlund *et al.*, 2007; Han *et al.*, 2010; Kueper and Frind, 1991]. For an immiscible plume, the zeroth moment, M_{000} , is defined in a similar manner as for a solute concentration [Freyberg, 1986]:

$$M_{000}(t) = \sum_i \varphi^i(x, y, z) S_{NW}^i(x, y, z, t) V^i \quad (4)$$

where φ^i is the porosity (space-dependent) and S_{NW}^i is the space- and time-dependent NWP saturation for the i^{th} gridblock with volume V^i . The first moments in the x- and z-direction normalized by the total NWP volume present in the domain (M_{000}) define the coordinates of the plume centroid:

$$x_c(t) = \frac{M_{100}}{M_{000}} = \frac{\sum_i x^i \varphi^i(x, y, z) S_{NW}^i(x, y, z, t) V^i}{\sum_i \varphi^i(x, y, z) S_{NW}^i(x, y, z, t) V^i} \quad (5)$$

$$z_c(t) = \frac{M_{001}}{M_{000}} = \frac{\sum_i z^i \varphi^i(x, y, z) S_{NW}^i(x, y, z, t) V^i}{\sum_i \varphi^i(x, y, z) S_{NW}^i(x, y, z, t) V^i} \quad (6)$$

4.1.1 Zeroth moment

A critical problem related to the long-term containment of CO₂ in deep reservoirs and recently tackled by tracer tests is the assessment of the amount that is being retained under residual saturation conditions [LaForce *et al.*, 2014; Myers *et al.*, 2015; Rasmusson *et al.*, 2014]. In fact, any part of the plume occurring at saturations higher than residual is considered mobile and susceptible to further displacement, unless additional trapping mechanisms, such as dissolution trapping and pocket trapping, get underway. The controlled laboratory experiments in conjunction with a refined x-ray scanning grid allow for accurate quantification of the total NWP volume

present in the tank using zeroth moment calculations. To evaluate the effects of capillary barriers and sequential injections on the retention of NWP we selected a cut-off value of 0.22 to differentiate mobile and residual fractions of a saturation at local scale. This cut-off value represents the maximum residual NWP saturation of the homogeneous experiment; however, this cut-off value is higher than actual residual saturation values owing to the hysteretic behavior of the $P_c(S)$ relationship [Cihan *et al.*, under review], and may result in slight over-prediction of the immobile volume and under-prediction of the mobile volume.

As shown in Figure 6, both experiments reach an apparent hydrostatic equilibrium at the end of the experiments as no further changes in the trapped NWP mass (mobile and immobile) are observed. The final residually-trapped volumes are similar for the homogeneous and heterogeneous cases, 595 ml and 657 ml, respectively. However, the final mobile volume (243 ml) in the heterogeneous case is significantly larger than that (34 ml) in the homogeneous case, because of local structural “pocket” trapping caused by heterogeneity structures and capillary barrier effects. In addition, the heterogeneity elongates the time (3.6 months) needed for plume stabilization after two injection events, much longer than that (24 days) for the homogeneous cases.

Figure 6 Zeroth moment evolution representing total plume volume (detected by x-ray scanning) during both experiments (black squares). Orange circles and blue triangles differentiate mobile and residual portions of the plume, respectively. Dashed lines delineate the two injection events.

Additionally to the analysis of total plume volume, assessing the range of NWP saturations measured at the end of each stage provides information about the trapping capacity of each scenario (Figure 7). At the end of both injection stages (stages A and C), capillary barriers have a dominant effect on plume migration in the heterogeneous scenario, leading to the highest saturations after the second injection. After the first fluid redistribution (stage B), the mobile NWP fluid exists over 70% of the plume footprint under pocket trapping in the heterogeneous case, while a residual (immobile) saturation state has been reached in 99% of the plume footprint in the homogeneous case. Finally, at the experiment completion (stage D), the main difference in terms of saturation distribution between both scenarios is the presence, although scattered, of high saturation areas in the heterogeneous case.

Figure 7 NWP saturation distributions measured at the end of each stage for both experiments (black for homogeneous, gray for heterogeneous). A) end of 1st injection; B) end of 1st redistribution; C) end of 2nd injection; D) end of 2nd redistribution.

4.1.2 First moment

The analysis of first spatial moments allows tracking the position of plume's centroid in the x-z plane during the temporal evolution of the NWP plume. As shown in Figure 8, whenever the plume breaks through at the outflow boundary, the center of mass reverses its original migration direction (both horizontally and vertically) and starts moving countercurrent with respect to the dipping angle of the aquifer and the background flow. This characteristic behavior is observed in both scenarios and during both injection events. In the homogeneous scenario, the observed behavior is essentially identical during the two injection events. In the heterogeneous scenario (right column in Figure 8), however, an overall equilibrium is quickly attained after the first injection, both horizontally and vertically, while after the second injection event, a slower upward, left-bound movement of the plume centroid takes place for approximately two months, culminating with the breakthrough into the outflow boundary.

Another interesting observation is that in the homogeneous scenario the plume remains very close to the caprock, as compared to the heterogeneous scenario. This behavior could have important implications in actual field conditions, where avoiding a prolonged seal exposure to CO₂ may prevent mineral reaction that can undermine its geological integrity.

Figure 8 Temporal evolution of the horizontal (squares, top row) and vertical (circles, bottom row) coordinates of the plume center of mass during both experiments. The intervals shown by the vertical dashed lines represent the duration of the injection events. X-coordinates decrease towards the left (outflow) boundary of the domain. Z-coordinates of caprock vary from 300 mm (right boundary) to 400 mm (left boundary).

4.2 Assessment of flow regimes

As the primary objective of this type of experiments is to mimic flow behavior of a scCO_2 plume through a brine-saturated aquifer, the injection flowrate was maintained inside the limits of capillary/buoyancy-dominated flow regime. Evidence from laboratory [England *et al.*, 1987] and field observations [Cavanagh and Haszeldine, 2014] suggest that for capillary number (Ca) $< 10^{-5}$, buoyant fluids such as oil or CO_2 move across the porous medium via gravity-driven ganglia and therefore can be modeled with numerical methods that neglect viscous forces, such as invasion percolation [Frette *et al.*, 1992; Meckel *et al.*, 2015]. For the experiments presented here we estimate capillary numbers with two different methods: 1) from NWP velocity (flowrate/well area)

during the injection and 2) from plume's center of mass velocity (length/time) during the fluid redistribution stages. The evolution of the capillary number presented in Figure 9 points toward similar injection flow regimes for both experiments and higher influence of capillary forces (smaller Ca) during gravity relaxation for the heterogeneous scenario.

Figure 9 Evolution of the capillary number during homogeneous (left) and heterogeneous (right) experiments. Calculations of NWP velocity are based on injection flowrate (continuous lines) and average displacement of plume centroid (circles). Shaded areas represent injection periods. For visualization purposes, the length of the heterogeneous plot was reduced from 2500 to 1000 hours.

4.3 Injection flow rate evolution

For the homogeneous experiment (Figure 10, left column), the first and second injection events take 22 hours and 23 hours to complete the target injection volume of 1 L. For both injection events, the flow rate rose monotonically from 0.31 ml/min to 1.16 ml/min. This behavior could be explained by near-well enhanced NWP relative permeability caused by saturation increase with time and by the growth of the plume in both length and width.

For the heterogeneous experiment (Figure 10, right column), the injection duration extends to 27 and 30 hours during the first and second injection events. During the first injection, the flow rate shows several rapid changes indicating a strong influence of the permeability structure. The higher rate during the first 10 hours indicates easy injection into the first cluster of high-

permeability sand facies (see Figure 2A) with the lower plume pool as shown in the first row of Figure 5. The later behavior of the injection rate with a decrease and then a gradual increase indicates the impact of low-permeability sand (#70) that is broken through by NWP to form the upper plume pool. The smaller fluctuations of the injection rate show the impacts of smaller-scale structures of permeability within each cluster. For the second injection event, the injection rate decreases sharply and then increases gradually, showing a smoother evolution. This behavior of the injection rate clearly shows the control of the low-permeability sand between the two clusters of high-permeability sands. The quick reduction can be attributed to this structure because the high saturation in the lower pool remains stable during the first redistribution stage and thus does not change the relative permeability significantly. At later time of injection, the rate is similar for both injection events because the flow paths connecting the two pools are also stable in terms of saturation and relative permeability. Overall, the evolution of the injection rate depends on the absolute permeability, saturation-dependent relative permeability and the structure of absolute permeability that controls the pools of plume. It will be very interesting to use numerical modeling to match the observed flow rates with all known heterogeneity structures and plume evolution with quantified high-resolution saturation.

Figure 10 Evolution of cumulative inflow volume (top row) and flow rate (bottom row) of Soltrol 220 for the homogeneous (left column) and heterogeneous (right column) experiment. Target injected volume (1000 ml for each injection event) is highlighted by horizontal dashed lines for cumulative volumes.

4.4 Comparison with small-tank experiments

The immiscible displacement experiments, referred to as large tank experiments, performed in the 2.4 m $\times$ 0.5 m sandbox represent the last iteration of the experimental analysis on capillary trapping that originated from smaller (0.7 m $\times$ 0.16 m) and less complex setups [Trevisan *et al.*, 2015; Trevisan *et al.*, 2014]. With respect to previous small tank experiments, the progression to the current large tank system involves four main additional features: 1) a larger influence of buoyancy forces, enabled by a lower aspect ratio of the aquifer; 2) the implementation of a background hydraulic gradient; 3) the sequential injection scheme and cyclic drainage and imbibition; 4) a larger variability of the permeability field. These features, in addition to the meter-scale system and long-term monitoring, make some of the observations discussed above unique and first of the kind.

5. Concluding remarks

The large tank experiments show the asymptotic values of trapping and storage efficiency factors with multiple cycles of drainage and imbibition under an ideal homogeneous scenario and a more realistic heterogeneous one. The trapping efficiency factor reduces from 65% after the first redistribution stage to 51.5% after the second redistribution stage in the homogeneous experiment, while it reduces from 100% to 64.3% from the first to the second redistribution stage in the heterogeneous experiment. The enhanced trapping efficiency in the heterogeneous case can be attributed to the local structural trapping, i.e., pocket trapping, which is caused by combined heterogeneity structure and capillary barrier effect. For the homogeneous case, all trapped NWP mass is due to combined residual saturation and hysteresis caused by cyclic drainage and imbibition. Even though the beneficial effects of sequential injections cannot be fully tested due to unfeasibility to perform a benchmark experiment with one single 2L-injection, such schemes are being increasingly scrutinized and often advocated by numerical studies [Huber *et al.*, 2016; Rasmusson *et al.*, 2016; Shamshiri and Jafarpour, 2012].

The observations of these large tank sandbox experiments allow to draw the following conclusions:

1. When performed in relatively homogeneous systems, subsequent NWP injections can enhance the reservoir space occupied by the plume, increase NWP mass trapped by capillary forces, and achieve higher residual saturations by hysteresis caused by drainage/imbibition cycles. Under constant injection pressure, the injection rate for the two injection events linearly increases with time following the same trend.

2. For the heterogeneous case, injected NWP accumulates in clusters of high-permeability sand facies to form plume pools of with higher saturation trapped under the capillary barrier effect in addition to hysteresis and residual saturation. Connecting these separate plume pools are low-permeability sand facies through which NWP has to break under buoyancy to achieve high storage and trapping efficiency.

3. The constant NWP injection pressure in the heterogeneous case results in fluctuations in the injection rate, reflecting the effect of permeability structure, the evolution of plume clusters, and NWP migration through low-permeability facies that connecting these pools. This observation can be relevant to field situations where formation injectivity can show significant variations in time.

4. Layer-type heterogeneity exerts a major control on the migration and trapping of the plume, leading to longer displacement times to reach stable trapping conditions, dampened vertical migration, and immobilization of larger fraction of injected mass within coarser sand zones.

The outcomes presented in this study highlight the convenience of sandbox experiments for mimicking a realistic aquifer configuration and interplay of governing forces. As part of the continuing effort to improve numerical predictions of storage capacity and efficiency, these surrogate systems are instrumental to identify the relevant migration and trapping phenomena that need to be considered by mathematical models. For instance, given their capillary-dominated flow regime, these experiments lend themselves to benchmark the performance of existing and new two-phase flow simulators.

Acknowledgements

Funding for this research is provided by the U.S. Department of Energy through the National Energy Technology Laboratory's CO₂ sequestration R&D Program under grant DE-FE0004630 and National Science Foundation Award no. EAR-1045282 through the Hydrologic Sciences Program. Supporting information is included as three Figures in an S.I. file and as one Excel spreadsheet; any additional data may be obtained from Luca Trevisan (email: luca.trevisan@gmail.com). LT thanks Tip Meckel and Susan Hovorka for insightful discussions and acknowledges additional funding from the Bureau of Economic Geology.

638 **References**

- 639 Agartan, E., L. Trevisan, A. Cihan, J. Birkholzer, Q. Zhou, and T. H. Illangasekare (2015),
640 Experimental study on effects of geologic heterogeneity in enhancing dissolution trapping of
641 supercritical CO₂, *Water Resour Res*, 51(3), 1635-1648.
- 642 Barth, G. R., T. H. Illangasekare, and H. Rajaram (2003), The effect of entrapped nonaqueous
643 phase liquids on tracer transport in heterogeneous porous media: laboratory experiments at the
644 intermediate scale, *J Contam Hydrol*, 67(1-4), 247-268.
- 645 Barth, G. R., M. C. Hill, T. H. Illangasekare, and H. Rajaram (2001), Predictive modeling of
646 flow and transport in a two-dimensional intermediate-scale, heterogeneous porous medium,
647 *Water Resour Res*, 37(10), 2503-2512.
- 648 Behzadi, H., and V. Alvarado (2012), Upscaling of upward CO₂ migration in 2D system, *Adv*
649 *Water Resour*, 46, 46-54.
- 650 Bennion, D. B., and S. Bachu (2006), Dependence on Temperature, Pressure, and Salinity of the
651 IFT and Relative Permeability Displacement Characteristics of CO₂ Injected in Deep Saline
652 Aquifers, in *2006 SPE Annual Technical Conference and Exhibition*, edited, Society of
653 Petroleum Engineers, San Antonio, Texas, U.S.A.
- 654 Birkholzer, J. T., and Q. Zhou (2009), Basin-scale hydrogeologic impacts of CO₂ storage:
655 Regulatory and capacity implications, *International Journal of Greenhouse Gas Control* 3 (6),
656 745–756.
- 657 Bryant, S. L., S. Lakshminarasimhan, and G. A. Pope (2008), Buoyancy-Dominated Multiphase
658 Flow and Its Effect on Geological Sequestration of CO₂, *Spe J.*, 13(4), 447-454.
- 659 Buscheck, T. A., Y. Sun, M. Chen, Y. Hao, T. J. Wolery, W. L. Bourcier, B. Court, M. A. Celia,
660 S. J. Friedmann, and R. D. Aines (2012), Active CO₂ reservoir management for carbon storage:
661 Analysis of operational strategies to relieve pressure buildup and improve injectivity,
662 *International Journal of Greenhouse Gas Control*, 6, 230-245.
- 663 Cameron, D. A., and L. J. Durlofsky (2012), Optimization of well placement, CO₂ injection
664 rates, and brine cycling for geological carbon sequestration, *International Journal of Greenhouse*
665 *Gas Control*, 10, 100-112.
- 666 Cavanagh, A. J., and R. S. Haszeldine (2014), The Sleipner storage site: Capillary flow modeling
667 of a layered CO₂ plume requires fractured shale barriers within the Utsira Formation,
668 *International Journal of Greenhouse Gas Control*, 21, 101-112.
- 669 Chang, C., Q. Zhou, T. J. Kneafsey, M. Oostrom, T. W. Wietsma, and Q. Yu (2016), Pore-scale
670 supercritical CO₂ dissolution and mass transfer under imbibition conditions, *Adv Water Resour*,
671 92, 142-158.

672 Cihan, A., J. T. Birkholzer, and M. Bianchi (2015), Optimal well placement and brine extraction
673 for pressure management during CO₂ sequestration, *International Journal of Greenhouse Gas*
674 *Control*, 42, 175-187.

675 Cihan, A., J. T. Birkholzer, L. Trevisan, A. Gonzalez-Nicolas, and T. H. Illangasekare (under
676 review), Investigation of representing hysteresis in macroscopic models of two-phase flow in
677 porous media using intermeditate scale experimental data.

678 Cinar, Y., A. Riaz, and H. A. Tchelepi (2009), Experimental Study of CO₂ Injection Into Saline
679 Formations, *Spe J.*, 14(4), 588-594.

680 Coats, K. H. & Smith, B. D. (1964) Dead-end pore volume and dispersion in porous media. SPE
681 Journal 4(1), 73–84, doi:0.2118/647-PA.

682 Craig, F. F. (1993), *The reservoir engineering aspects of waterflooding*, 134 p. pp., Henry L.
683 Doherty Memorial Fund of AIME, Richardson, Tex.

684 Deng, H. L., P. H. Stauffer, Z. X. Dai, Z. S. Jiao, and R. C. Surdam (2012), Simulation of
685 industrial-scale CO₂ storage: Multi-scale heterogeneity and its impacts on storage capacity,
686 injectivity and leakage, *International Journal of Greenhouse Gas Control*, 10, 397-418.

687 Doughty, C., and K. Pruess (2004), Modeling supercritical carbon dioxide injection in
688 heterogeneous porous media, *Vadose Zone J*, 3(3), 837-847.

689 Eichel, H., R. Helmig, I. Neuweiler, and O. A. Cirpka (2005), Upscaling of Two-Phase Flow
690 Processes in Porous Media, in *Upscaling Multiphase Flow in Porous Media: From Pore to Core*
691 *and Beyond*, edited by D. B. Das and S. M. Hassanizadeh, pp. 237-257, Springer Netherlands.

692 England, W. A., A. S. Mackenzie, D. M. Mann, and T. M. Quigley (1987), The Movement and
693 Entrapment of Petroleum Fluids in the Subsurface, *J Geol Soc London*, 144, 327-347.

694 Fagerlund, F., T. H. Illangasekare, and A. Niemi (2007), Nonaqueous-phase liquid infiltration
695 and immobilization in heterogeneous media: 1. Experimental methods and two-layered reference
696 case, *Vadose Zone J*, 6(3), 471-482.

697 Farajzadeh, R., P. Ranganathan, P. L. J. Zitha, and J. Bruining (2011), The effect of
698 heterogeneity on the character of density-driven natural convection of CO₂ overlying a brine
699 layer, *Adv Water Resour*, 34(3), 327-339.

700 Fernandez-Garcia, D., T. H. Illangasekare, and H. Rajaram (2004), Conservative and sorptive
701 forced-gradient and uniform flow tracer tests in a three-dimensional laboratory test aquifer,
702 *Water Resour Res*, 40(10).

703 Flett, M., R. Gurton, and I. Taggart (2004), The Function of Gas-Water Relative Permeability
704 Hysteresis in the Sequestration of Carbon Dioxide in Saline Formations, in *SPE Asia Pacific Oil*
705 *and Gas Conference and Exhibition*, edited, Society of Petroleum Engineers, Perth, Australia.

706 Flett, M., R. Gurton, and G. Weir (2007), Heterogeneous saline formations for carbon dioxide
707 disposal: Impact of varying heterogeneity on containment and trapping, *J Petrol Sci Eng*, 57(1-
708 2), 106-118.

709 Frette, V., J. Feder, T. Jossang, and P. Meakin (1992), Buoyancy-Driven Fluid Migration in
710 Porous-Media, *Phys Rev Lett*, 68(21), 3164-3167.

711 Freyberg, D. L. (1986), A Natural Gradient Experiment on Solute Transport in a Sand Aquifer
712 .2. Spatial Moments and the Advection and Dispersion of Nonreactive Tracers, *Water Resour*
713 *Res*, 22(13), 2031-2046.

714 Gasda, S. E., M. A. Celia, and J. M. Nordbotten (2008), Upslope plume migration and
715 implications for geological CO₂ sequestration in deep, saline aquifers, *The IES Journal Part A:*
716 *Civil & Structural Engineering*, 1(1), 2-16.

717 Gershenzon, N. I., R. W. Ritzi, D. F. Dominic, M. Soltanian, E. Mehnert, and R. T. Okwen
718 (2015), Influence of small-scale fluvial architecture on CO₂ trapping processes in deep brine
719 reservoirs, *Water Resour Res*, 51(10), 8240-8256.

720 Glass, R. J., S. H. Conrad, and W. Peplinski (2000), Gravity-destabilized nonwetting phase
721 invasion in macroheterogeneous porous media: Experimental observations of invasion dynamics
722 and scale analysis, *Water Resour Res*, 36(11), 3121-3137.

723 Goater, A. L., B. Bijeljic, and M. J. Blunt (2013), Dipping open aquifers—The effect of top-
724 surface topography and heterogeneity on CO₂ storage efficiency, *International Journal of*
725 *Greenhouse Gas Control*, 17, 318-331.

726 Gonzalez-Nicolas, A., L. Trevisan, T. H. Illangasekare, A. Cihan, and J. T. Birkholzer (under
727 review), Enhancing trapping effectiveness through proper time scheduling of injection of
728 supercritical CO₂ in heterogeneous formations.

729 Gunn, I., and A. W. Woods (2011), On the flow of buoyant fluid injected into a confined,
730 inclined aquifer, *J Fluid Mech*, 672, 109-129.

731 Han, W. S., S. Y. Lee, C. A. Lu, and B. J. McPherson (2010), Effects of permeability on CO₂
732 trapping mechanisms and buoyancy-driven CO₂ migration in saline formations, *Water Resour*
733 *Res*, 46, W07510.

734 Hesse, M., H. A. Tchelepi, and F. M. Orr (2006), Scaling Analysis of the Migration of CO₂ in
735 Saline Aquifers.

736 Huber, E. J., A. D. Stroock, and D. L. Koch (2016), Analysis of a time dependent injection
737 strategy to accelerate the residual trapping of sequestered CO₂ in the geologic subsurface,
738 *International Journal of Greenhouse Gas Control*, 44, 185-198.

739 Ide, S. T., K. Jessen, and F. M. Orr (2007), Storage of CO₂ in saline aquifers: Effects of gravity,
740 viscous, and capillary forces on amount and timing of trapping, *International Journal of*
741 *Greenhouse Gas Control*, 1(4), 481-491.

742 Journal, A. G., and F. Alabert (1990), New Method for Reservoir Mapping, *J Petrol Technol*,
743 42(2).

744 Kopp, A., H. Class, and R. Helmig (2009), Investigations on CO₂ storage capacity in saline
745 aquifers-Part 2: Estimation of storage capacity coefficients, *International Journal of Greenhouse*
746 *Gas Control*, 3(3), 277-287.

747 Kueper, B. H., and E. O. Frind (1991), Two-phase flow in heterogeneous porous media: 2.
748 Model application, *Water Resour Res*, 27(6), 1059-1070.

749 Kumar, A., M. Noh, G. A. Pope, K. Sepehrnoori, S. Bryant, and L. W. Lake (2005), Reservoir
750 Simulation of CO₂ Storage in Deep Saline Aquifers, *Spe J.*, 10(3), 336-348.

751 Kuo, C. W., and S. M. Benson (2015), Numerical and analytical study of effects of small scale
752 heterogeneity on CO₂/brine multiphase flow system in horizontal corefloods, *Adv Water Resour*,
753 79, 1-17.

754 LaForce, T., J. Ennis-King, C. Boreham, and L. Paterson (2014), Residual CO₂ saturation
755 estimate using noble gas tracers in a single-well field test: The CO₂CRC Otway project,
756 *International Journal of Greenhouse Gas Control*, 26, 9-21.

757 Land, C. (1968), Calculation of Imbibition Relative Permeability for Two- and Three-Phase
758 Flow From Rock Properties, *Spe J.*, 8(2), 149-156.

759 Larkin, R. (2010), Hydrodynamic Trapping of CO₂ Geosequestered in Saline Aquifers, in *SPE*
760 *Improved Oil Recovery Symposium*, edited, Tulsa, Oklahoma, USA.

761 Lengler, U., M. De Lucia, and M. Kuhn (2010), The impact of heterogeneity on the distribution
762 of CO₂: Numerical simulation of CO₂ storage at Ketzin, *International Journal of Greenhouse*
763 *Gas Control*, 4(6), 1016-1025.

764 Li, B. X., and S. M. Benson (2015), Influence of small-scale heterogeneity on upward CO₂
765 plume migration in storage aquifers, *Adv Water Resour*, 83, 389-404.

766 MacMinn, C. W., M. L. Szulczewski, and R. Juanes (2010), CO₂ migration in saline aquifers.
767 Part 1. Capillary trapping under slope and groundwater flow, *J Fluid Mech*, 662, 329-351.

768 Meckel, T. A., S. L. Bryant, and P. R. Ganesh (2015), Characterization and prediction of CO₂
769 saturation resulting from modeling buoyant fluid migration in 2D heterogeneous geologic
770 fabrics, *International Journal of Greenhouse Gas Control*, 34, 85-96.

771 Mikes, D., and J. Bruining (2006), Standard flow cells to incorporate small-scale heterogeneity
772 (crossbedding) in a reservoir model, *Mar Petrol Geol*, 23(9-10), 979-993.

773 Myers, M., L. Stalker, T. La Force, B. Pejic, C. Dyt, K.-B. Ho, and J. Ennis-King (2015), Field
774 measurement of residual carbon dioxide saturation using reactive ester tracers, *Chem Geol*, 399,
775 20-29.

776 Neufeld, J. A., M. A. Hesse, A. Riaz, M. A. Hallworth, H. A. Tchelepi, and H. E. Huppert
777 (2010), Convective dissolution of carbon dioxide in saline aquifers, *Geophys Res Lett*, 37.

778 Nordbotten, J. M., M. A. Celia, and S. Bachu (2005), Injection and storage of CO₂ in deep saline
779 aquifers: Analytical solution for CO₂ plume evolution during injection, *Transp. Porous Media*,
780 58(3), 339-360.

781 Pickup, G., P. S. Ringrose, and A. Sharif (2000), Steady-State Upscaling: From Lamina-Scale to
782 Full-Field Model, *Spe J.*, 5(2).

783 Pini, R., Krevor, S. C., & Benson, S. M. (2012), Capillary pressure and heterogeneity for the
784 CO₂/water system in sandstone rocks at reservoir conditions. *Advances in Water Resources*, 38,
785 48-59.

786 Polak, S., Y. Cinar, T. Holt, and O. Torsaeter (2015), Use of low- and high-IFT fluid systems in
787 experimental and numerical modelling of systems that mimic CO₂ storage in deep saline
788 formations, *J Petrol Sci Eng*, 129, 97-109.

789 Rasmusson, K., M. Rasmusson, Y. Tsang, and A. Niemi (2016), A simulation study of the effect
790 of trapping model, geological heterogeneity and injection strategies on CO₂ trapping,
791 *International Journal of Greenhouse Gas Control*, 52, 52-72.

792 Rasmusson, K., M. Rasmusson, F. Fagerlund, J. Bensabat, Y. Tsang, and A. Niemi (2014),
793 Analysis of alternative push-pull-test-designs for determining in situ residual trapping of carbon
794 dioxide, *International Journal of Greenhouse Gas Control*, 27, 155-168.

795 Remy, N., A. Boucher, and J. Wu (2009), *Applied geostatistics with SGeMS : a user's guide*, xix,
796 264 p. pp., Cambridge University Press, Cambridge, UK ; New York.

797 Ringrose, P. S., K. S. Sorbie, P. W. M. Corbett, and J. L. Jensen (1993), Immiscible flow
798 behaviour in laminated and cross-bedded sandstones, *J Petrol Sci Eng*, 9(2), 103-124.

799 Ritzi, R. W., J. T. Freiburg, and N. D. Webb (2016), Understanding the (co) variance in
800 petrophysical properties of CO₂ reservoirs comprising sedimentary architecture, *International*
801 *Journal of Greenhouse Gas Control*, 51, 423-434.

802 Saadatpoor, E., S. L. Bryant, and K. Sepehrnoori (2010), New Trapping Mechanism in Carbon
803 Sequestration, *Transp. Porous Media*, 82(1), 3-17.

804 Sakaki, T., and T. H. Illangasekare (2007), Comparison of height-averaged and point-measured
805 capillary pressure-saturation relations for sands using a modified Tempe cell, *Water Resour Res*,
806 43(12).

807 Shamshiri, H., and B. Jafarpour (2012), Controlled CO₂ injection into heterogeneous geologic
808 formations for improved solubility and residual trapping, *Water Resour Res*, 48(2).

809 Singh, V., A. Cavanagh, H. Hansen, B. Nazarian, M. Iding, and P. Ringrose (2010), Reservoir
810 Modeling of CO₂ Plume Behavior Calibrated Against Monitoring Data From Sleipner, Norway,
811 in *SPE Annual Technical Conference and Exhibition*, edited, Florence, Italy.

812 Tchelepi, H. A., and F. M. Orr (1994), Interaction of Viscous Fingering, Permeability
813 Heterogeneity, and Gravity Segregation in Three Dimensions, *SPE Reservoir Engineering*,
814 9(04), 266-271.

815 Tian, L., Z. Yang, F. Fagerlund, and A. Niemi (2016), Effects of permeability heterogeneity on
816 CO₂ injectivity and storage efficiency coefficient, *Greenhouse Gases: Science and Technology*,
817 6(1), 112-124.

818 Trevisan, L. (2015), Study of trapping mechanisms of supercritical carbon dioxide in deep
819 heterogeneous geological formations through intermediate-scale testing and modeling, PhD
820 thesis, 189 pp, Colorado School of Mines, Golden, CO.

821 Trevisan, L., P. G. Krishnamurthy, and T. A. Meckel (under review), Impact of 3D capillary
822 heterogeneity and bedform architecture at the 1 sub-meter scale on CO₂ saturation for buoyant
823 flow in clastic aquifers.

824 Trevisan, L., R. Pini, A. Cihan, J. T. Birkholzer, Q. Zhou, and T. H. Illangasekare (2015),
825 Experimental analysis of spatial correlation effects on capillary trapping of supercritical CO₂ at
826 the intermediate laboratory scale in heterogeneous porous media, *Water Resour Res*, 51(11),
827 8791-8805.

828 Trevisan, L., A. Cihan, F. Fagerlund, E. Agartan, H. Mori, J. T. Birkholzer, Q. Zhou, and T. H.
829 Illangasekare (2014), Investigation of mechanisms of supercritical CO₂ trapping in deep saline
830 reservoirs using surrogate fluids at ambient laboratory conditions, *International Journal of*
831 *Greenhouse Gas Control*, 29, 35-49.

832 van Lingen, P. P., J. Bruining, and C. P. J. W. van Kruijsdijk (1996), Capillary Entrapment
833 Caused by Small-Scale Wettability Heterogeneities, *SPE Reservoir Engineering*, 11(02), 93-100.

834 Werner, M., D. Sutter, A. Krattli, O. Lafci, R. Mutschler, P. Oehler, J. Winkler, and M. Mazzotti
835 (2014), A physical model for geological CO₂ storage - Replacing misconceptions by visual
836 explanation, *International Journal of Greenhouse Gas Control*, 25, 42-53.

837 Yamamoto, H., K. Zhang, K. Karasaki, A. Marui, H. Uehara, and N. Nishikawa (2009),
838 Numerical investigation concerning the impact of CO₂ geologic storage on regional groundwater
839 flow, *International Journal of Greenhouse Gas Control*, 3(5), 586-599.

840 Zhao, B. Z., C. W. MacMinn, H. E. Huppert, and R. Juanes (2014), Capillary pinning and
841 blunting of immiscible gravity currents in porous media, *Water Resour Res*, 50(9), 7067-7081.

842 Zhou, Q., J. T. Birkholzer, E. Mehnert, Y.-F. Lin, and K. Zhang (2010), Modeling basin- and
843 plume-scale processes of CO₂ storage for full-scale deployment, *Ground Water*, 48(4), 494-514.

844 Zimoch, P. J., J. A. Neufeld, and D. Vella (2011), Leakage from inclined porous reservoirs, *J*
845 *Fluid Mech*, 673, 395-405.