UCLA

UCLA Previously Published Works

Title

Comparison of stormwater biofiltration systems in Southeast Australia and Southern California

Permalink

<https://escholarship.org/uc/item/3hj6r735>

Journal

WIREs Water, 2(2)

ISSN

2049-1948

Authors

Ambrose, Richard F
Winfrey, Brandon K

Publication Date

2015-03-01

DOI

10.1002/wat2.1064

Peer reviewed

Article type: Focus Article

Article title: Comparison of Stormwater Biofiltration Systems in Southeast Australia and Southern California

Authors:

First author
Richard F. Ambrose ^{1,2*}
Second author
Brandon K. Winfrey ¹

¹Department of Environmental Health Sciences

and

²Institute of the Environment and Sustainability

University of California, Los Angeles

Los Angeles, CA 90095-1771

*Correspondence to: rambrose@ucla.edu

Abstract

Stormwater biofilters (also called rain gardens, bioretention systems, and bioswales) are used to manage stormwater runoff in urbanized environments. Some benefits of biofilters include flood prevention, stormwater runoff water quality improvement, and wildlife habitat. This technology has been implemented on a larger scale in southeast Australia, but cities and counties in southern California just beginning to construct biofilter systems to manage stormwater runoff. Biofilters tend to be larger in southern California than in southeast Australia. Differences in rainfall patterns likely affect biofilter function. Southern California has much longer periods between rain events than southeast Australia, providing challenges to establishing and maintaining vegetation in biofilters. The use of biofilters for restoring pre-development flow regimes has been studied in a peri-urban watershed in southeast Australia, but flow regime restoration is not likely in highly urbanized locations in both Australia and southern California. However, stormwater runoff treatment and harvesting in decentralized biofilters could substantially reduce storm flows and improve water quality in receiving waters while improving urban water supply and extending the life of existing stormwater management infrastructure.

Keywords: stormwater biofilters, water quality, stormwater harvesting, green infrastructure, low impact development, rain garden, bioswale, urban runoff

1 Introduction

2 Urban stormwater management is important for controlling pollution and flooding
3 associated with runoff from impervious surfaces following rain events but has often been at the
4 cost of important ecosystem services and functioning in urban streams (i.e., the urban stream
5 syndrome)¹. Low Impact Development or Green Infrastructure stormwater systems that infiltrate
6 water through a vegetated filter media can be used to capture and treat urban stormwater runoff
7 and re-establish pre-development flow patterns². In this paper, we will refer to these systems as
8 stormwater biofilters, but recognize that they also capture and treat dry-weather runoff not
9 associated with storms. There are many similarities in design criteria of bioswales, vegetated
10 strips, rain gardens, and bioretention or biofiltration systems; we are considering the term
11 “biofilter” to encompass all systems that filter stormwater runoff through a vegetated filter media
12 and convey treated stormwater into perforated pipes leading to a discharge pipe and/or percolate
13 into the underlying soil. Biofilters remove pollutants such as metals, solids, oils and grease,
14 nutrients, and pathogens through a myriad of physical, physicochemical, and biological
15 processes. All of these processes occur as a result of gravity-fed hydraulics, filter media
16 characteristics, and capturing sunlight through photosynthesis, making these systems low-energy
17 options for stormwater management. Biofilters are employed in stormwater management in a
18 variety of regimes. Currently, many cities in the United States and Australia offer rebate
19 programs and guidance documents to design and construct biofilters at residents’ homes.
20 Government and non-profit organizations are also building biofilters at the single project- and
21 neighborhood-scale. Typically, single projects capture runoff from parking lots or a large
22 commercial or industrial development; these projects are commonly constructed by private
23 companies who own the lots from which stormwater is collected. Neighborhood-scale projects
24 aim to manage larger catchments and often include several types of stormwater management
25 technologies; these projects are commonly constructed by government agencies, often in
26 collaboration with other organizations, and are more extensive and expensive.

27 Comparing US and Australian stormwater management infrastructure is useful because
28 both developed countries are mitigating the effects of urban stormwater runoff on aquatic
29 ecosystems using low impact development³. In this paper, we compare the implementation of
30 stormwater biofilters in southeast Australia and southern California. Although stormwater
31 biofilters have been constructed in both of these regions, they differ in the motivations behind
32 their construction. We discuss these motivations as well as differences in the climates of the two
33 regions, design and maintenance of biofilters, and the ecology of biofiltration systems. We show
34 how the different environmental settings could influence optimal implementation in each region,
35 although little work has been done so far to identify the optimal implementations.

36 IMPETUS FOR IMPLEMENTATION

37 In southeast Australia, a major impetus for the construction of stormwater biofilters was
38 water conservation in response to the so-called Millennium drought⁴. Additionally, stormwater
39 biofiltration was recognized as an effective method to prevent nitrogen from reaching Port
40 Phillip Bay because these systems can handle the variable concentrations and flows of runoff
41 events^{5, 6}. The major water purveyor, Victorian state statutory authority Melbourne Water,
42 adopted policies and incentives to encourage large-scale implementation of stormwater biofilters.
43 Melbourne Water programs include a “Ten Thousand Rain Garden” program. In addition,

studies by Melbourne scientists had demonstrated an adverse effect of stormwater runoff from urbanized watersheds¹. Besides the active support of Melbourne Water, regulatory requirements encourage the construction of stormwater biofilters. New developments and redevelopments are required to manage stormwater according to Clause 56.07-4 of the Victoria Planning Provisions (http://planningschemes.dpcd.vic.gov.au/schemes/vpps/56_07.pdf). The involvement of academic scientists in Melbourne is also noteworthy. The Water for Liveability Centre at Monash University has played a central role developing the scientific foundations for biofilter construction and the implementation of actual projects. The Little Stringybark Creek Project is a collaborative research program where researchers from Monash University and University of Melbourne have investigated the potential of watershed-scale impact of managing stormwater runoff with biofilters and rainwater harvesting. This project is the largest of its kind in the world and has so far resulted in the construction of dozens of biofilters.

In southern California, the impetus for stormwater biofilter implementation has been control of water pollution under the federal Clean Water Act. Initially, the State Water Resources Control Board (SWRCB) promulgated regulations requiring stormwater be retained on new construction sites. Under the 2009-0009-DWQ Construction General Permit, stormwater runoff originating in new developments in California was recognized as point source pollution and regulated under the Clean Water Act. The Clean Beach Initiative, a fund under California's SWRCB, provided funding to projects aimed at reducing fecal indicator bacteria (FIB) loads to California's beaches from urban runoff⁷. Stormwater biofilters were suggested as a best management practice (BMP) to preserve drainage in urban areas and prevent FIB from reaching beaches. These stormwater biofilters (among other techniques for retaining stormwater) were largely constructed by permittees on private property. More recently, Municipal Separate Storm Sewer System (MS4) regulations have led to broader adoption of stormwater biofilters. Stormwater biofilters constructed by government agencies are typically larger, more expensive, and may include other stormwater management techniques such as infiltration galleries and pervious pavement. Most neighborhood-scale systems have been built by local government agencies. The Elmer Avenue Green Street project, coordinated by a consortium including the City of Los Angeles, the Council for Watershed Health and TreePeople (non-profit organizations), mitigated flooding in a Sun Valley neighborhood by capturing runoff in a large infiltration gallery installed beneath Elmer Avenue⁸. This project also included the construction of 24 street-side biofilters and rainwater harvesting tanks. The California Department of Transportation (CalTrans) constructed a biofilter in 2006 as part of a pilot project to investigate the suitability of using this technology as a BMP for stormwater management. Monitoring of the treatment performance and maintenance requirements of the CalTrans biofilter is ongoing. There has been limited engagement with the academic community in the role of biofilter implementation in southern California.

DIFFERENCE IN CLIMATE

Southeast Australia and southern California also differ in their climate, which may have a substantial impact on biofilter performance. Southeast Australia is considered a temperate climate while southern California has a Mediterranean climate. Temperatures are similar, with mean monthly high temperatures in Melbourne and Los Angeles varying from 15-27°C and mean monthly low temperatures varying from 7-17°C (Figure 1). Los Angeles is slightly warmer, with both average high and low temperatures about 4°C higher in the winter and average

low temperatures about 2°C higher in the summer. Los Angeles also has slightly more consistent monthly mean high temperatures, with a 6°C difference between winter and summer compared to a 12°C difference in Melbourne.

In contrast to relatively consistent temperature patterns, the rainfall patterns of southeast Australia and southern California differ dramatically. Mean monthly rainfall in Melbourne varies only between 4 and 6 cm (Figure 2). In contrast, mean monthly rainfall in Los Angeles varies between 0 and 12 cm, with 80% of the rain falling in December to March. As a result, there are much longer periods without rain in Los Angeles. This difference is apparent in the frequency of antecedent dry days (ADD), defined as the number of days preceding a rain event over 1 mm/day. Between 1994 and 2013, periods of ADD over 30 days occurred 51 times in Los Angeles but only 3 times in Melbourne (Figure 3). In Melbourne, the pattern of ADD was similar in the driest and wettest years over the 20-year period examined, even though rainfall differed by a factor of two. In contrast, the driest and wettest years in Los Angeles had distinctly different ADD distributions, with widely spaced rainfall during the driest year. The more consistent rainfall in southeast Australia means shorter periods of dry weather, which can influence biofilters performance. Besides longer periods of dry weather in Los Angeles, there are larger differences from year to year, meaning that there are more years when biofilters would receive only sporadic rainfall. Nitrogen and metals removal efficiencies are reduced by biofilter drying^{9, 10}. In addition, a saturated or submerged zone, which can improve nitrogen and metals removal¹⁰, would be easier to maintain consistently with regular rainfall. Because of the extended dry periods, a saturated zone likely could only be maintained year-round in southern California if there was considerable dry-weather runoff or if it was replenished with potable water. Although biofilter drying generally reduces pollutant removal efficiency for many pollutants and can challenge the maintenance of a biofilter, prolonged dry periods enhanced the removal of micropollutants¹¹.

Stormwater pollutant loads differ somewhat between southeast Australia and southern California, and this could influence biofilter performance or which design would be optimal in each location. In both regions, pollutant loads range widely for every constituent (Table 1), although there are some general patterns. Nutrients tended to be higher in southern California stormwater. Although there was broad overlap, total suspended solids ranged higher in southeast Australia stormwater. Lead and *E. coli* also ranged higher in southeast Australia stormwater. These data reflect stormwater runoff, which reflect inflow after rain events but may not represent dry weather runoff pollutant loads.

DESIGN SPECIFICATIONS AND MAINTENANCE

There are differences in key design characteristics of stormwater biofilters in southeast Australia and southern California. We compared 13 Victoria and 13 southern California stormwater biofilters (Table 2). These biofilters represent various ages, sizes, and designs of the major neighborhood-scale biofilters found in Victoria and southern California. Most biofilters in southern California were constructed in the past four years, while Victoria biofilters have been built steadily over the past ten years. The biofilters in both regions cover a wide size range, but southern California biofilters were not as small as many of the Victoria biofilters, and three of the southern California biofilters were larger than any of the Victoria biofilters. The mean biofilter size in southern California was 646 m² while the mean size in Victoria was 160 m².

Catchment areas also differed somewhat between the two regions. Eight of the 13 Victoria biofilters drained catchments of less than 1 ha compared to only one southern California biofilter. Both regions included one project greater than 50 ha. The mean catchment areas of southern California and Victoria biofilters were 10 ha and 7 ha, respectively, while the median areas were 5.0 ha and 0.43 ha. Catchment ratio (biofilter area/impervious catchment area) has been used as an indicator of biofilter effectiveness on a catchment scale, with Australian researchers suggesting that biofilters should cover 2% of the impervious catchment area for optimal performance¹². Southern California BMP guidelines suggest designing biofilters to infiltrate the runoff from a 2-cm (3/4-in) storm event within the drainage area within 48 hours¹³. Sizing calculations include percolation rates of filter media and underlying soils, impervious surface area, and the runoff coefficients for drainage areas¹³. Four Victoria and four southern California biofilters reach the Australian catchment ratio target. All but one of the Victoria biofilters were located in residential areas (the exception is located in an industrial and commercial area, while seven southern California biofilters were in commercial districts (two combined with industrial and one combined with residential, Table 2).

Biofilters designed for infiltration are not lined with an impermeable layer, allowing treated water to flow vertically to the underlying soil, potentially recharging groundwater. Biofilters with underdrains can be lined or unlined. These biofilters contain slotted or perforated pipes plumbed to flow to the adjacent stormwater conveyance system or receiving stream (or potentially to be captured for use in irrigation or other purposes). Underdrains can be designed with outflows at an elevation higher than the bottom of the biofilter in order to retain water between inflow events, which results in a submerged zone. Almost all biofilters in both regions were designed for infiltration (Table 2). In Los Angeles, three biofilters had underdrains as well as infiltration, and again two were underdrain alone. In Melbourne, seven biofilters had underdrains as well as infiltration, and two were underdrain alone. Hereford Road Raingarden has both types of flow regimes, providing groundwater recharge via infiltration during most rain events and flood protection with underdrains during larger rain events by preventing high ponding (Sidebar 1).

We classified biofilters as curb cutouts or standalone systems to make comparisons between their immediate surroundings. Curb cutout biofilters are systems located adjacent to the street and sidewalk (Figure 4a). These biofilters may be required to adhere to certain regulations set by transportation agencies regarding visibility, safety, and connectivity to the stormwater conveyance system. The City of Los Angeles provides standard plans that identify plant type, ponding depth, and dimensions required to comply with local regulations^{13, 14}. Similarly, Melbourne Water provides engineering plans for biofilters and other green infrastructure that provides guidance to comply with local regulations¹⁵. Standalone biofilters refer to systems not located between a street and sidewalk. These systems are typically in public parks or easements (Figure 4b). Typically, standalone biofilters have more flexibility in design, but could have restrictions based on safety if they are located in a public area, particularly regarding plant type and ponding depth. One of the Ballona Creek Rain Gardens is located between a bike path and residential area (Sidebar 2). This biofilter infiltrates runoff that would otherwise flow directly into Ballona Creek. This long, narrow design would not likely be possible with other types of stormwater management systems. Both Melbourne and Los Angeles had 7 curb cutout biofilters. Only Los Angeles had parking lot biofilters (2), with the remainder in both regions being standalone.

1 A submerged (saturated) zone can lead to more consistent biofilters performance.
2 Maintaining a submerged zone led to stable hydraulic performance during prolonged wet and dry
3 periods, while the outflow rate of biofilters with no submerged zone was reduced during
4 prolonged wet periods¹¹. Submerged zones have been shown to enhance removal of nitrogen¹⁶⁻¹⁹
5 and heavy metals²⁰. Theoretically, a submerged zone could increase plant survivorship by
6 allowing plant roots to have access to water for an extended period of time. However, we are not
7 aware of any studies documenting this potential, nor evaluating its importance for different
8 species. The presence of a submerged zone could influence the plant species used in a biofilter,
9 both in terms of pollutant removal and long-term maintenance. Again, we know of no studies
10 evaluating these aspects; the major study evaluating the influence of plant traits on biofilter
11 performance²¹ did not evaluate submerged zones. Because of the difference in the frequency of
12 antecedent dry days, submerged zones would be easier to maintain in southeast Australia than in
13 southern California. In southern California, submerged zones would likely require supplemental
14 water to maintain them through the dry season unless dry-weather runoff was substantial. In
15 some settings, such as golf courses, it might be possible to direct runoff to biofilters to maintain
16 submerged zones. Similarly, greywater from commercial or residential buildings could be
17 treated using biofilters while providing water for maintaining submerged zones. Alternatively,
18 submerged zones could be allowed to dry out and then be re-established following storm events.
19 Submerged zones are beginning to be incorporated into stormwater biofilters in Melbourne, but
20 are not currently being used in southern California.

21 Plants represent critical features of stormwater biofilters, but there are relatively few
22 design guidelines available. In both regions, native plants are recommended^{13, 15}. In Los
23 Angeles, standard plans for curb cutout biofilters include only plants with mature heights below
24 91 cm (3 ft) in order to maintain sight lines, but offer no guidance on planting densities¹⁴. In
25 southern California, plants are often (but not always) selected by landscape architects, apparently
26 with little knowledge of their performance in stormwater biofilters. In southeast Australia,
27 research on the biofilter performance of native plants²¹ has provided some information for plant
28 selection, though this has not necessarily been followed. For example, the single species with
29 the best pollutant removal performance, *Carex appressa*, is rarely used in Melbourne stormwater
30 biofilters, possibly because of its sharp leaves. There is a need for more information about the
31 performance of native species, especially in California, more complete consideration of all
32 relevant plant traits, including aesthetics and maintenance considerations as well as pollutant
33 removal, and better incorporation of these considerations into the selection of plants for a
34 particular biofilter system.

35 In southern California, larger systems are typically maintained by the agency responsible
36 for construction. Procedures include removing undesired vegetation, trash and debris,
37 accumulated sediments, and residue from oils and grease; replanting desired vegetation as
38 needed; re-leveling eroded areas and filling rutted areas with gravel; and observing performance
39 under wet conditions¹³. Biofilters in southeast Australia are similarly maintained with the
40 exception of irrigation following plant establishment. Additionally, the top 2 – 5 cm of filter
41 media is scraped off every few years in some Australian biofilters in order to maintain hydraulic
42 conductivity and remove heavy metals, as suggested by Hatt et al.²². Responsibility for the
43 maintenance of smaller systems in southern California, such as curb cutouts, is less clear. Initial
44 maintenance may be performed by the agency constructing the biofilters, with subsequent
45 maintenance the responsibility of the landowner. Transferring maintenance responsibility might

be attractive to government agencies; however, distributing responsibility among many parties can be problematic because differing levels of maintenance can occur.

Because of the large number of variables influencing stormwater biofilter performance, specifying a single optimal design would be difficult. One study from Melbourne specifically addressed this problem, concluding that the optimally designed biofilter is at least 2% of its catchment area and possesses a sandy loam filter media planted with *Carex appressa* or *Melaleuca ericifolia*¹². Although a good start, this study has limitations, including the fact that it was conducted in laboratory columns and did not evaluate the performance of species combinations. No similar study evaluating optimum biofilter design has been conducted for southern California. Besides the need to evaluate California native plant species, there may be other differences between southeast Australia that need to be considered in southern California biofilter design. For example, Australian plants are adapted to low levels of soil nutrients, particularly phosphorus, so sandy loam may be more suitable there than other regions¹². In other areas with different design criteria, catchment coverage of 5% to 10% has been estimated to be required to meet phosphorus reduction targets based on modeling studies²³. There have been very few field-based evaluations of biofilter performance in southeast Australia (but see^{9, 24-26}) or southern California. Most field studies of biofilter performance have been undertaken in North Carolina²⁷⁻³² and Maryland³³⁻³⁶.

Although biofilters have the potential to harvest stormwater (or other runoff) to increase water supply, few biofilters in southeast Australia or southern California have been constructed to take advantage of this potential. One exception is Edinburgh Gardens biofilter in Fitzroy North, VIC, AU. Stormwater runoff is collected from the surrounding the residential area, filtered through the 600-m² biofilter, and stored in an underground tank. Harvested and treated runoff provides 50% of the water needed for irrigating this 24-ha park (<http://www.yarracity.vic.gov.au/environment/Parks-and-reserves/Edinburgh-Gardens/Proposed-Raingarden/>).

ECOLOGY OF BIOFILTRATION SYSTEMS

A biofilter ecosystem consists of the physical elements, plants, animals, and microbial community. Most studies of stormwater biofilters have focused on physical elements, particularly the media used and its arrangement within the biofilter. Much less has been published about the biological elements of biofilters. Of these, by far the most work has been done on plants. Vegetated biofilter mesocosms removed more nutrients than unvegetated mesocosms^{37, 38}. Read et al. have examined the role of different plant traits in stormwater biofilter performance using laboratory mesocosms²¹. The strongest contributors to N and P removal were related to root extent, with the plants associated with the highest pollutant removal, e.g., *Carex appressa*, combining these root traits with high growth rates. Assimilation by plants has been shown to be the primary mechanism for removing nitrate under typical stormwater conditions³⁹. Plants can be important in maintaining hydraulic conductivity in stormwater biofilters⁹. Le Coustumer et al. found that species with thick roots, such as *Melaleuca* spp., were able to maintain high hydraulic conductivity over time; they argue that the choice of plant species is a key design element because of the potential maintenance of system hydraulics⁴⁰.

1 Studies to date have focused on plant species from southeast Australia. Although general
2 plant traits (such as extensive root systems or thick roots) may lead to similar stormwater
3 biofilter performance in southern California, this has yet to be tested; we are currently
4 conducting mesocosm experiments to evaluate these factors using native southern California
5 plants. Although the results of these experiments are not yet available, there are some
6 differences between southeast Australia and southern California that are apparent. It is critical
7 that plant species used in stormwater biofilters be well adapted to the local conditions, and as
8 noted above the precipitation regimes are markedly different between southeast Australia and
9 southern California. Because of frequent rainfall throughout the year, plants in southeast
10 Australia stormwater biofilters can more easily survive without supplemental water, particularly
11 if a submerged zone is incorporated into the biofilter design. In contrast, plants in southern
12 California biofilters should be able to withstand an extended dry period; although it is possible to
13 provide supplemental irrigation, this is not desirable, particularly with the current and projected
14 shortage of water in southern California⁴¹. Although wetland plants are frequently considered
15 for planting in biofilters, in southern California biofilters will be “wet” for only a relatively short
16 period of time, so plants will need to tolerate saturated conditions separated by dry conditions⁴².
17 Therefore, native terrestrial plants (from chaparral, coastal sage scrub, or grasslands) might be
18 more appropriate for southern California biofilters, although these species have not yet been
19 evaluated. In their review, Houdeshel et al. suggest planting deep-rooted shrubs that do not
20 require irrigation following establishment in arid climates but do not provide information on
21 biofilter performance⁴³.

22 To date, very few of the plant species native to southeast Australia and southern
23 California have been tested for biofilter performance, or even planted in biofilters. Both of these
24 regions have rich native flora, with more than 800 endemic plant species in southern California⁴⁴
25 and more than 1800 indigenous plant species in the Melbourne area⁴⁵. The most extensive
26 investigation to date of plants for use in biofilters evaluated 20 plant species²¹, so clearly there
27 are many candidate species that have not yet been studied. Both regions also include many non-
28 native invasive plant species. Biofilters in both regions could be particularly prone to
29 colonization of invasive species due to the higher moisture and nutrient content than surrounding
30 soils and receiving seeds from runoff. Managers of biofilters in both regions have noted that
31 weed suppression has a high maintenance cost.

32 Besides the identity of species planted, southeast Australia and southern California may
33 have different planting schemes, particularly in the mix of species planted in individual
34 biofilters. However, no studies have systematically evaluated the plant communities in
35 stormwater biofilters in either region. We are currently conducting these studies.

36 In contrast to the number of studies on the role of plants in stormwater biofilters, very
37 little work has been done on animals and microbes. Earthworms and other burrowing terrestrial
38 macroinvertebrates have the potential to affect the hydrology by creating macropores in the filter
39 media⁴⁶. These animals could also affect nutrient cycling by providing an anaerobic
40 environment in their guts capable of denitrification of soil nitrate and through providing a
41 conduit to the surface through macropores⁴⁶. Additionally, the interaction between plants and
42 animals in biofilters and the consequences in function have not been examined⁴⁷.

The role of the microbial community in stormwater performance is acknowledged, but few details have been studied. For nitrogen removal, the importance of microbially mediated denitrification is recognized⁴⁸, and conditions supporting increased denitrification, particularly a submerged zone, identified^{17, 19}. Although some studies of specific microbes, or expressed genes, have been conducted, these focus narrowly on nitrogen transformations⁴⁹ rather than a broader ecological roles of the microbial community (e.g., mycorrhizae supporting plant growth and diversity, competition between denitrifying bacteria and plant roots for nitrate).

As biological elements in an urbanized landscape, biofilters can provide important ecological values and ecosystem services. This benefit of biofilters has received little attention, but particularly as more biofilters are constructed in a catchment, their ecological influence will become more important. Stormwater biofilters are explicitly designed to provide several important ecosystem services, including flood attenuation, groundwater recharge and water quality improvement. However, they may also provide other ecosystem services for which they have not been explicitly designed (at least to date). One documented ecosystem service provided by stormwater biofilters is the support of biodiversity. Stormwater biofilters support a higher diversity of aboveground terrestrial invertebrates than surround gardens and lawns⁵⁰. Kazemi and co-workers have argued that transitioning from traditional urban landscapes such as lawns to biofilters would enhance urban biodiversity^{10, 50, 51}. Few studies have evaluated stormwater biofilter characteristics that would increase the support of biodiversity, but Kazemi et al. have suggested that greater leaf/plant litter depth and higher plant species richness contribute to increased biodiversity in biofilters⁵². Kazemi's studies were conducted in Melbourne; although the results may apply to southern California, no similar studies have yet been conducted there.

Other ecosystem services that may be performed by stormwater biofilters include carbon sequestration⁵³, pollinator habitat⁵⁰, aesthetics, and potentially water supply². Constructing biofilters with underdrains connected to stormwater harvesting tanks or infiltration-type (unlined) biofilters could help restore pre-development flow regimes in smaller watersheds². Biofilters can artificially recharge groundwater when underlying soils have adequately high infiltration rates⁵⁴. This recharge could be beneficial if the biofilter area is sufficient, soil pollution and depth to groundwater are low, and the increased water table does not adversely affect infrastructure belowground.

Sidebar 1: The Hereford Road Raingarden

The Hereford Road Raingarden was constructed in 2010 to replace a stormwater retention basin in an area adjacent to Hereford Rd. and a petrol station. This 100-m² stormwater biofilter treats runoff from a 9,300-m² drainage area in residential Mt. Evelyn, VIC, AU. A sand transition layer and gravel drainage layer allow water to infiltrate into underlying soils or is collected in perforated pipes flowing first to an

overflow pit, then to Little Stringybark Creek. The loamy sand layer is the filter media where most plant roots occupy. Hereford Road Raingarden is planted with species that have been reported to promote high treatment performance: *Carex appressa*, *Juncus flavidus*, and *Melaleuca* sp. This biofilter was constructed as part of a catchment-scale effort to restore the Little Stringybark Creek (LSC) stream ecosystem through flow-regime management. Infiltration and collection pipes prevent stormwater runoff from entering Little Stringybark Creek directly during low-flow events and provide flood protection during high flow events.

Sidebar 2: The Ballona Creek Raingardens.

The Ballona Creek Raingardens were constructed in 2012 to filter runoff from residential, commercial, and industrial areas in Culver City, CA, US before infiltrating into the underlying soil. Two biofilters (810 m² and 1,900 m²) were constructed to filter runoff from 5 ha of residential area (810-m² biofilter) and 5 ha of industrial/commercial area (1,900-m² biofilter). Biofilters were sized to capture and infiltrate 2.5 cm of rain over 24 hours. Stormwater runoff enters a debris trap before flowing over a rock-lined channel into the 8-m wide biofilters filled with a sandy loam filter media sloped at a 3:1 ratio to pond water and channel flow. Overflow pipe conveys water to Ballona Creek. Grasses and sedges are the dominate the plant community in these rain

gardens. Volunteers from the community remove non-native species annually. The debris filter will be cleaned every 3 years.

Box 1: Key differences between biofilters in southeast Australia and southern California.

- Climatic differences dictate vegetation choice and hydraulic design. More drought tolerant plant species are expected in southern California biofilters. Ponding zones are generally deeper in southern California biofilters.
- Most southern California systems are curb cutouts or located in parking lots. More biofilters in southeast Australia are standalone systems. This could be due to higher development pressure and urban density in southern California, where most systems are retrofitted to existing developments.
- Most biofilters in southern California infiltrate to the groundwater exclusively (e.g., Sidebar 2). In southeast Australia, many systems collect outflow via an underdrain as well as infiltrate (e.g., Sidebar 1).
- Varying types of filter media tends to be layered and contain transition zones in southeast Australia (e.g., Sidebar 1). Very little information was available on filter media in southern California, but the Stormwater Best Management Practice Design and Maintenance Manual for Publicly Maintained Storm Drain Systems provide desired particle size distribution for filter media.

CONCLUSIONS

Biofiltration is a promising approach to managing stormwater runoff in urban areas with temperate and Mediterranean climates. While this technology is implemented on a large scale in southeast Australia, southern California is still in the early stages of constructing a system of

biofilters as a BMP to control urban runoff. There are notable differences in biofilter design between southeast Australia and southern California, most notably the larger average size of southern California biofilters and higher diversity of drainage type in southeast Australia biofilters. The most striking difference with regards to stormwater management in these two locations is the greater seasonality of rainfall in southern California, with extended dry periods between rain events, even in the wet season. This climatological difference undoubtedly affects the function of biofilters in the Mediterranean climate of southern California. More research is needed to optimize biofilter design in this climate. One interesting design aspect worth investigation is the treatment of greywater using biofilters. Greywater can supply a continuous flow of water to maintain submerged zones during dry periods, potentially maintaining plant life and an anaerobic zone for denitrification.

The benefits of biofilters are rarely seen at the watershed level with the exception of projects like Little Stringybark Creek in Mt. Evelyn, VIC, where the strategic implementation of infiltrating biofilters and rainwater harvest tanks at the watershed scale have worked towards restoring the pre-development flow regime². Due to the importation of water from northern California and the Colorado River to southern California, a pre-development flow regime in southern California watersheds may not be possible, especially in highly urbanized areas with high impervious cover. Nonetheless, southern California biofilters with underdrains and saturated zones used to harvest and treat stormwater runoff could substantially reduce storm flows and improve water quality in receiving waters. Biofilters, along with other low impact development strategies, can be used to improve and extend the life of existing stormwater management infrastructure.

Acknowledgments

This project was supported by U.S. National Science Foundation Partnerships in International Research and Education (PIRE) grant OISE-1243543 to the University of California, Irvine (UCI). We appreciate discussions we have had with PIRE team members, especially Stan Grant of UCI and Ana Deletic and Belinda Hatt of Monash University. We also thank stormwater managers and others in Melbourne and California including Tim Fletcher, Chris Walsh and Matt Burns of University of Melbourne, Wing Tam, Susie Santilena and Deborah Deets of the City of Los Angeles Bureau of Sanitation, and Bhaskar Joshi and Mark Keisler of California Department of Transportation. The authors declare no conflict of interest.

References

1. Walsh CJ, Roy AH, Feminella JW, Cottingham PD, Groffman PM, Morgan RP. The urban stream syndrome: current knowledge and the search for a cure. *Journal of the North American Benthological Society* 2005, 24:706-723.
2. Burns MJ, Fletcher TD, Walsh CJ, Ladson AR, Hatt BE. Hydrologic shortcomings of conventional urban stormwater management and opportunities for reform. *Landscape and Urban Planning* 2012, 105:230-240.
3. Roy A, Wenger S, Fletcher T, Walsh C, Ladson A, Shuster W, Thurston H, Brown R. Impediments and Solutions to Sustainable, Watershed-Scale Urban Stormwater Management: Lessons from Australia and the United States. *Environmental Management* 2008, 42:344-359.
4. Grant SB, Fletcher TD, Feldman D, Saphores J-D, Cook PLM, Stewardson M, Low K, Burry K, Hamilton AJ. Adapting Urban Water Systems to a Changing Climate: Lessons from the Millennium Drought in Southeast Australia. *Environmental Science & Technology* 2013, 47:10727-10734.
5. Taylor GD, Fletcher TD, Wong THF, Breen PF, Duncan HP. Nitrogen composition in urban runoff—implications for stormwater management. *Water Research* 2005, 39:1982-1989.
6. Brown RR, Clarke JM. *Transition to water sensitive urban design: The story of Melbourne, Australia*. Melbourne, Australia: Facility for Advancing Water Biofiltration, Monash University; 2007.
7. Dorsey JH. Improving water quality through California's Clean Beach Initiative: an assessment of 17 projects. *Environmental Monitoring and Assessment* 2010, 166:95-111.
8. Belden E, Antos, M, Morris, K, Steele, NLC. Sustainable Infrastructure: The Elmer Avenue Neighborhood Retrofit. *Urban Coast* 2012, 3:92-100.
9. Hatt BE, Fletcher TD, Deletic A. Hydrologic and pollutant removal performance of stormwater biofiltration systems at the field scale. *Journal of Hydrology* 2009, 365:310-321.
10. Blecken G-T, Zinger Y, Deletić A, Fletcher TD, Viklander M. Influence of intermittent wetting and drying conditions on heavy metal removal by stormwater biofilters. *Water Research* 2009, 43:4590-4598.
11. Zhang K, Randelovic A, Page D, McCarthy DT, Deletic A. The validation of stormwater biofilters for micropollutant removal using in situ challenge tests. *Ecological Engineering* 2014, 67:1-10.
12. Bratieres K, Fletcher TD, Deletic A, Zinger Y. Nutrient and sediment removal by stormwater biofilters: A large-scale design optimisation study. *Water Research* 2008, 42:3930-3940.
13. County of Los Angeles Department of Public Works. Stormwater Best Management Practice Design and Maintenance Manual for Publicly Maintained Storm Drain Systems. 2009. Available at: <http://dpw.lacounty.gov/ldd/publications/Stormwater%20BMP%20Design%20and%20Maintenance%20Manual.pdf>.
14. City of Los Angeles Department of Public Works. Vegetated Stormwater Curb Extension Standard Plan S-484-0. 2010. Available at: <http://eng.lacity.org/techdocs/stdplans/s-400/s-484-0.pdf>.

- 1 15. Melbourne Water. *Water Sensitive Urban Design Engineering Procedures: Stormwater*.
2 Collingwood, VIC, AU: CSIRO Publishing; 2005.
- 3 16. Kim H, Seagren EA, Davis AP. Engineered bioretention for removal of nitrate from
4 stormwater runoff. *Water Environment Research* 2003, 75:355-367.
- 5 17. Gilchrist S, Borst M, Stander EK. Factorial study of rain garden design for nitrogen
6 removal. *Journal of Irrigation and Drainage Engineering* 2014, 140.
- 7 18. Zinger Y, Blecken G-T, Fletcher TD, Viklander M, Deletić A. Optimising nitrogen
8 removal in existing stormwater biofilters: Benefits and tradeoffs of a retrofitted saturated
9 zone. *Ecological Engineering* 2013, 51:75-82.
- 10 19. Payne EG, Pham T, Cook PL, Fletcher TD, Hatt BE, Deletic A. Biofilter design for
11 effective nitrogen removal from stormwater—influence of plant species, inflow hydrology
12 and use of a saturated zone. *Water Science & Technology* 2014, 69:1312-1319.
- 13 20. Blecken G-T, Zinger Y, Deletić A, Fletcher TD, Viklander M. Impact of a submerged
14 zone and a carbon source on heavy metal removal in stormwater biofilters. *Ecological*
15 *Engineering* 2009, 35:769-778.
- 16 21. Read J, Fletcher TD, Wevill T, Deletic A. Plant Traits that Enhance Pollutant Removal
17 from Stormwater in Biofiltration Systems. *International Journal of Phytoremediation*
18 2009, 12:34-53.
- 19 22. Hatt BE, Fletcher TD, Deletic A. Hydraulic and Pollutant Removal Performance of Fine
20 Media Stormwater Filtration Systems. *Environmental Science & Technology* 2008,
21 42:2535-2541.
- 22 23. Hurley SE, Forman RTT. Stormwater ponds and biofilters for large urban sites: Modeled
23 arrangements that achieve the phosphorus reduction target for Boston's Charles River,
24 USA. *Ecological Engineering* 2011, 37:850-863.
- 25 24. Le Coustumer S, Fletcher TD, Deletic A, Barraud S, Lewis JF. Hydraulic performance of
26 biofilter systems for stormwater management: Influences of design and operation.
27 *Journal of Hydrology* 2009, 376:16-23.
- 28 25. Deletic A, Fletcher TD. Performance of grass filters used for stormwater treatment—a
29 field and modelling study. *Journal of Hydrology* 2006, 317:261-275.
- 30 26. Glaister BJ, Cook PLM, Fletcher TD, Hatt BE. Long-term phosphorus accumulation in
31 stormwater biofiltration systems at the field scale. In: *Water Sensitive Urban Design*
32 *2013: WSUD 2013*. Barton, ACT: Engineers Australia; 2013.
- 33 27. Brown RA, Birgand F, Hunt WF. Analysis of Consecutive Events for Nutrient and
34 Sediment Treatment in Field-Monitored Bioretention Cells. *Water, Air, & Soil Pollution*
35 2013, 224:1-14.
- 36 28. Hathaway J, Hunt W, Graves A, Wright J. Field Evaluation of Bioretention Indicator
37 Bacteria Sequestration in Wilmington, North Carolina. *Journal of Environmental*
38 *Engineering* 2011, 137:1103-1113.
- 39 29. Hunt W, Jarrett A, Smith J, Sharkey L. Evaluating Bioretention Hydrology and Nutrient
40 Removal at Three Field Sites in North Carolina. *Journal of Irrigation and Drainage*
41 *Engineering* 2006, 132:600-608.
- 42 30. Hunt W, Smith J, Jadlocki S, Hathaway J, Eubanks P. Pollutant Removal and Peak Flow
43 Mitigation by a Bioretention Cell in Urban Charlotte, N.C. *Journal of Environmental*
44 *Engineering* 2008, 134:403-408.

- 1 31. Passeport E, Hunt W, Line D, Smith R, Brown R. Field Study of the Ability of Two
2 Grassed Bioretention Cells to Reduce Storm-Water Runoff Pollution. *Journal of*
3 *Irrigation and Drainage Engineering* 2009, 135:505-510.
- 4 32. Wardynski B, Hunt W. Are Bioretention Cells Being Installed Per Design Standards in
5 North Carolina? A Field Study. *Journal of Environmental Engineering* 2012, 138:1210-
6 1217.
- 7 33. Davis AP. Field Performance of Bioretention: Water Quality. *Environmental Engineering*
8 *Science* 2007, 24:1048-1064.
- 9 34. Davis A. Field Performance of Bioretention: Hydrology Impacts. *Journal of Hydrologic*
10 *Engineering* 2008, 13:90-95.
- 11 35. DiBlasi CJ, Li H, Davis AP, Ghosh U. Removal and Fate of Polycyclic Aromatic
12 Hydrocarbon Pollutants in an Urban Stormwater Bioretention Facility. *Environmental*
13 *Science & Technology* 2009, 43:494-502.
- 14 36. Li H, Davis A. Urban Particle Capture in Bioretention Media. I: Laboratory and Field
15 Studies. *Journal of Environmental Engineering* 2008, 134:409-418.
- 16 37. Henderson C, Greenway M, Phillips I. Removal of dissolved nitrogen, phosphorus and
17 carbon from stormwater by biofiltration mesocosms. *Water Science & Technology* 2007,
18 55.
- 19 38. Barrett M, Limouzin M, Lawler D. Effects of Media and Plant Selection on Biofiltration
20 Performance. *Journal of Environmental Engineering* 2013, 139:462-470.
- 21 39. Payne EGI, Fletcher TD, Russell DG, Grace MR, Cavagnaro TR, Evrard V, Deletic A,
22 Hatt BE, Cook PLM. Temporary Storage or Permanent Removal? The Division of
23 Nitrogen between Biotic Assimilation and Denitrification in Stormwater Biofiltration
24 Systems. *PLoS ONE* 2014, 9:e90890.
- 25 40. Le Coustumer S, Fletcher TD, Deletic A, Barraud S, Poelsma P. The influence of design
26 parameters on clogging of stormwater biofilters: A large-scale column study. *Water*
27 *Research* 2012, 46:6743-6752.
- 28 41. Ault TR, Cole JE, Overpeck JT, Pederson GT, Meko DM. Assessing the risk of persistent
29 drought using climate model simulations and paleoclimate data. *Journal of Climate* 2014,
30 27:7529-7549.
- 31 42. Houdeshel C, Pomeroy C. Plant Selection for Bioretention in the Arid West. In: *Low*
32 *Impact Development 2010*: American Society of Civil Engineers; 2010, 1475-1485.
- 33 43. Houdeshel CD, Pomeroy CA, Hultine KR. Bioretention Design for Xeric Climates Based
34 on Ecological Principles 1. *JAWRA Journal of the American Water Resources*
35 *Association* 2012, 48:1178-1190.
- 36 44. Stebbins GL, Major J. Endemism and Speciation in the California Flora. *Ecological*
37 *Monographs* 1965, 35:1-35.
- 38 45. Royal Botanic Gardens Melbourne, The Australian Research Centre for Urban Ecology.
39 *Biodiversity of Metropolitan Melbourne*. Melbourne, VIC, AU: Victorian Environmental
40 Assessment Council; 2009.
- 41 46. Mehring AS, Levin LA. Can animals improve the efficiency of water-sensitive urban
42 design? In review.
- 43 47. Levin LA, Mehring AS. Optimization of Bioretention Systems Through Application of
44 Ecological Theory. *WIREs Water* Accepted.

48. Payne EGI, Fletcher TD, Cook PLM, Deletic A, Hatt BE. Processes and Drivers of Nitrogen Removal in Stormwater Biofiltration. *Critical Reviews in Environmental Science and Technology* 2014, 44:796-846.
49. Chen X, Peltier E, Sturm BSM, Young CB. Nitrogen removal and nitrifying and denitrifying bacteria quantification in a stormwater bioretention system. *Water Research* 2013, 47:1691-1700.
50. Kazemi F, Beecham S, Gibbs J. Streetscape biodiversity and the role of bioretention swales in an Australian urban environment. *Landscape and Urban Planning* 2011, 101:139-148.
51. Kazemi F, Beecham S, Gibbs J. Streetscale bioretention basins in Melbourne and their effect on local biodiversity. *Ecological Engineering* 2009, 35:1454-1465.
52. Kazemi F, Beecham S, Gibbs J, Clay R. Factors affecting terrestrial invertebrate diversity in bioretention basins in an Australian urban environment. *Landscape and Urban Planning* 2009, 92:304-313.
53. Pataki DE, Carreiro MM, Cherrier J, Grulke NE, Jennings V, Pincetl S, Pouyat RV, Whitlow TH, Zipperer WC. Coupling biogeochemical cycles in urban environments: ecosystem services, green solutions, and misconceptions. *Frontiers in Ecology and the Environment* 2011, 9:27-36.
54. Bouwer H. Artificial recharge of groundwater: hydrogeology and engineering. *Hydrogeology Journal* 2002, 10:121-142.
55. Bureau of Meteorology. Climate Data Online- Daily Rainfall. Available at: <http://www.bom.gov.au/climate/data/>. (Accessed 2014)
56. Western Regional Climate Center (WRCC). Summary of Day Data Lister (SOD-TD3200). Available at: <http://www.wrcc.dri.edu/cgi-bin/cliMAIN.pl?ca5115>. (Accessed 2014)
57. Lau S-L, Khan E, Stenstrom MK. Catch basin inserts to reduce pollution from stormwater. *Water Science & Technology* 2001, 44:23-34.
58. Ackerman D, Weisberg S. Relationship between rainfall and beach bacterial concentrations on Santa Monica Bay beaches. *Journal of Water and Health* 2003, 1:85-89.
59. Stein ED, Ackerman D. Dry Weather Water Quality Loadings in Arid, Urban Watersheds of the Los Angeles Basin, California, USA1. *JAWRA Journal of the American Water Resources Association* 2007, 43:398-413.
60. Han Y, Lau S, Kayhanian M, Stenstrom M. Correlation analysis among highway stormwater pollutants and characteristics. *Water Science & Technology* 2006, 53:235-243.
61. Duncan H. *Urban Stormwater Quality: A Statistical Overview*. Clayton, Victoria AUS: Cooperative Research Centre for Catchment Hydrology; 1999.
62. McCarthy DT, Deletic A, Mitchell VG, Fletcher TD, Diaper C. Uncertainties in stormwater E. coli levels. *Water Research* 2008, 42:1812-1824.

Figure captions

Figure 1. Mean monthly temperatures for Melbourne and Los Angeles. Data for 1994-2013: Melbourne⁵⁵ and Los Angeles⁵⁶.

- 1 Figure 2. Precipitation patterns for Melbourne and Los Angeles. Data for 1994-2013:
- 2 Melbourne⁵⁵ and Los Angeles⁵⁶.
- 3 Figure 3. Distribution of antecedent dry days for Melbourne and Los Angeles. Inset:
- 4 Distributions of antecedent dry days for Melbourne and Los Angeles during Driest and Wettest
- 5 Years. Data for 1994-2013: Melbourne⁵⁵ and Los Angeles⁵⁶.
- 6 Figure 4. Examples of typical stormwater biofilter settings. (a) Curb cutout biofilter located in
- 7 Culver City, CA, US on Baldwin Avenue; and (b) standalone biofilter located in Mt. Evelyn,
- 8 VIC, AU in Morrison Reserve.
- 9

Tables

Table 1. Typical concentrations of constituents in stormwater runoff in southern California and southeast Australia.

Constituent	Unit	Southern California*	Southeast Australia**
Total Suspended Solids	mg/L	30 - 70	40 - 150
Total Nitrogen	mg/L	2 - 10	1 - 3
Total Phosphorus	mg/L	0.2 - 0.9	0.1 - 0.4
Cadmium	µg/L	2 - 5	4 - 5
Copper	µg/L	8 - 100	10 - 60
Lead	µg/L	2 - 30	10 - 140
Zinc	µg/L	80 - 500	100 - 300
<i>E. coli</i>	MPN/100mL	360 - 1,800	600 - 31,000

*Data from ⁵⁷⁻⁶⁰. **Data from ^{5, 9, 61, 62}.

Table 2. Characteristics of biofilters in Victoria and southern California. Where biofilter size varied within a site, averages were calculated based on the smallest size. Biofilter systems were identified and described using information gathered from Internet keyword searches for terms "rain garden," "biofilter," "stormwater biofilter," "stormwater biofiltration," and "stormwater LID" preceded by locations of interest (Los Angeles, Culver City, Irvine, San Diego, Orange County, or Melbourne). Additionally, websites of local watershed protection agencies and personal communication with agency personnel were used to determine site locations. The selected sites do not represent a random sample of all existing biofilters in each region, but biofilters were not selected to represent any particular characteristic(s), except that Victoria biofilters were selected to represent a range of ages.

<u>Site Name</u>	<u>Age (yrs)</u>	<u>Size (m²)</u>	<u>Catchment (ha)</u>	<u>Catchment Ratio</u>	<u>Catchment Land Use</u>	<u>Drainage Type</u>	<u>Setting</u>
<i>Southern California</i>							
Elmer Avenue (Multiple)	4	12 – 24	16	-	res	Infiltration	Curb cutout
Riverdale Avenue	4	12 – 20	5.7	-	res	Infiltration/Underdrain	Curb cutout
Oros Street	7	12 – 20	2.0	-	res	Infiltration/Underdrain	Curb cutout
Bicknell Avenue (Multiple)	5	12 – 20	not avail.	-	res	Infiltration	Curb cutout
Baldwin Avenue (Multiple)	2	120	2.2	0.5%	res	Infiltration	Curb cutout
Ballona Creek East	3	1,900	5	3.8%	ind/comm	Infiltration	Standalone
Ballona Creek West	3	810	5	1.6%	res	Infiltration	Standalone
Hope Street	4	10-15	not avail.	-	comm	Infiltration	Curb cutout
Woodman Ave (multiple)	0.5	2,500	51	0.5%	res/comm	Infiltration	Curb cutout
Chatsworth Station (multiple)	2	Varies	15	-	comm	Underdrain	Parking Lot
LA Zoo Parking Lot (multiple)	3	1,400	5.5	2.5%	ind/comm	Infiltration	Parking Lot
Irvine- CalTrans	9	810	1.6	5.0%	comm	Underdrain	Standalone
Scripps Institution of Oceanography	4	150	0.7	2.3%	comm	Infiltration/Underdrain	Standalone
Average	4	646	10	2.3%			
<i>Victoria</i>							
Hereford Rd	4	100	0.9	1.1%	res	Infiltration/Underdrain	Standalone
Spring Street	2	14	0.1	1.3%	res	Infiltration/Underdrain	Standalone
Stringybark Blvd South	3	70	0.4	1.5%	res	Infiltration/Underdrain	Standalone
Fernhill Rd (multiple)	1	5-15	Varies	-	res	Infiltration	Curb cutout
Morrison Reserve	1	500	16	0.3%	res	Infiltration	Standalone

Otter St (multiple)	6	105	1	0.9%	res	Infiltration/Underdrain	Curb cutout
Napier and Kerr (multiple)	7	24	0.4	0.6%	res	Infiltration	Curb cutout
Cremorne St (multiple)	9	85	0.1	6.4%	ind/comm	Infiltration/Underdrain	Curb cutout
Parker St (multiple)	9	33	0.1	4.7%	res	Infiltration/Underdrain	Curb cutout
Avoca Crescent (multiple)	9	13	0.1	2.5%	res	Infiltration/Underdrain	Curb cutout
Clifton Hill (multiple)	6	200	3	0.7%	res	Underdrain	Standalone
Alleyne Ave (multiple)	8	76	0.1	15%	res	Infiltration	Curb cutout
Edinburgh Gardens	3	700	60	0.1%	res	Underdrain	Standalone
Average	5	160	7	2.9%			

Related Articles

DOI	Article title
	Levin LA, Mehring AS. Optimization of Bioretention Systems Through Application of Ecological Theory