

# **UC Berkeley**

## **SEMM Reports Series**

### **Title**

Creep of Concrete for Turkey Point Containment Vessel

### **Permalink**

<https://escholarship.org/uc/item/3xs09039>

### **Author**

Al-Alusi, Hesham

### **Publication Date**

1972-03-01

UNIVERSITY OF CALIFORNIA, BERKELEY

BERKELEY • DAVIS • IRVINE • LOS ANGELES • RIVERSIDE • SAN DIEGO • SAN FRANCISCO

SANTA BARBARA • SANTA CRUZ



COLLEGE OF ENGINEERING  
DEPARTMENT OF CIVIL ENGINEERING  
DIVISION OF STRUCTURAL ENGINEERING  
AND STRUCTURAL MECHANICS

BERKELEY, CALIFORNIA 94720

February 22, 1972

Bechtel Corporation  
190 Shady Grove Road  
P.O. Box 607  
Gaithersburg, Maryland 20760

Attention: Mr. N. K. Bhatia

Gentlemen:

RE: Creep of Concrete for Turkey Point Containment  
Vessel - 1972

Transmitted herewith is the final report entitled, "Creep of Concrete for Turkey Point Containment Vessel - 1972," which gives results from creep studies on concrete cast at Berkeley and at the job site. Concrete specimens were under load for approximately one year.

Sincerely yours,

A handwritten signature in black ink, appearing to read "David Pirtz".

David Pirtz  
Professor of Civil Engineering

DP:ib  
Enclosure

Final Report

STUDIES OF CONCRETE FOR TURKEY POINT  
NUCLEAR CONTAINMENT VESSEL

TEST PROGRAM

The purpose of the testing program is to establish some of the mechanical and thermal properties of the concrete using 3/4-in. maximum size aggregate to be used in the construction of the Turkey Point Nuclear Power Plant's containment structure.

The test program comprises of the evaluation of the properties of the concrete:

- a. Compressive Strength to be determined on sealed concrete specimens stored at 73° F at ages of 3, 7, and 28 days on three each of 6-in. x 12-in. cylinders.
- b. Modulus of Elasticity and Poisson's Ratio to be determined on sealed concrete specimens stored at 73° F at age of 28 days on three each of 6-in. x 12-in. cylinders.
- c. Creep characteristic of sealed concrete specimens to be determined at a sustained load of 1530 psi initially applied at 28 days. The creep tests shall be run on specimens cast at Berkeley and specimens that were cast on the job site and shipped to Berkeley. The creep tests shall be carried out on two frames containing 2 each 6-in. x 18-in. cylinders per frame at 73° F.

CONCRETE MIX

The mix design for both the Berkeley and job site specimens are shown in Table A. The casting data for specimens made in Berkeley are shown in

Table B. In Table B the weight of cement, water, sand, and 3/4-in. aggregate per cu. yd. of concrete was computed using the measured unit weight of the concrete and the batch weights of each material. The concrete at the job site had a slump of 2 1/2 inches and a temperature at time of casting of 63° F.

The aggregates used in the casting of the Turkey Point specimens were shipped to Davis Hall on the University of California campus at Berkeley. The aggregates were placed in steel drums and soaked for 24 hours then air dried and blended to about saturated surface dry conditions (sand +5.02%, 3/4-in. agg. -0.90%). Bulk specific gravities and absorption capacities of the aggregates as determined at Berkeley are shown in Table C.

The concrete was mixed at Berkeley in a 2 cu. ft. capacity pan-type mixer with each batch making approximately 1.70 cu. ft. of concrete.

Hand-held internal vibrators were used in the casting to insure proper compaction of the concrete.

#### MANUFACTURE OF SPECIMENS

Creep specimens were cast in 6-in. diameter by 20-in. long 16-gage sheet metal molds which were lined inside with a 1/16-in. thick seamless butyl rubber sleeve. The butyl rubber sleeve was bonded to a 2-in. thick steel base plate and then the 16-gage sheet metal mold was slipped over the rubber sleeve and banded with a large hose clamp to the base plate. The purpose of the outer steel mold is to assure that the outer surface of the creep specimen will be kept uniform during casting. A 10-in. Carlson Strain Meter was centered on the axis of the mold with its lead wire being brought out through a hole in the center of the base plate which has a "O" ring seal for the lead wire. A 1/8-in. by 8-in. metal rod was placed diametrically across the top of the mold

to serve as support for a wire which held the meter in an axial position during casting. After casting, the wire was cut off and the rod removed.

The creep specimens cast at Berkeley were allowed about five hours time for the bleeding water to rise to the surface, and then a conical-shaped layer of mortar made from the original mix was formed on the top of each cylinder. The 2-in. thick steel top-plates were then worked back and forth into position until the mortar appeared to be spread uniformly between the plate and the specimen. A square was used to assure that each top-plate was normal to the axis of the specimen. The creep specimens were then moved to the 73° F. constant temperature room. Sheet metal molds were stripped from the creep specimens at the age of one day, and the top two inches of the butyl rubber sleeve was then bonded and banded with a large hose clamp to the top plate to assure that the specimens would be internally sealed.

Molds for the creep specimen to be cast at the job site were prepared at Berkeley and shipped to the job site. Creep specimens were cast on the job site with concrete taken from the truck after two-thirds of the load had been discharged. The concrete was allowed about two hours time for the bleeding water to rise to the surface, the bleeding water was removed and a thin layer of mortar applied to provide a smooth surface for the top plate. The top two inches of butyl rubber sleeve was bonded and banded with a large hose clamp to the top plate to assure that the specimens would be internally sealed. Specimens were allowed to stand overnight and then moved to the civil office where the temperature remains about 70° F.

Compressive strength specimens cast at Berkeley were cast in 6-in. by 12-in. metal cans provided with lids to internally seal the specimen. Compressive strength specimens remained in the fog room until just prior

to testing, at which time they were stripped, capped, and covered with saran wrapping to ensure water retention through the test period. Compressive strength specimens cast on the job site were cured at 70°F in water tanks until tested.

#### TEST PROCEDURES AND RESULTS

##### Compressive Strength and Elastic Properties

Compressive strength at Berkeley was determined at the ages of 3, 7 and 28 days. Each strength determination represents the average obtained for three 6-in. by 12-in. cylinders. The same three 6-in. by 12-in. concrete cylinders were used in the determination of compressive strength, modulus or elasticity (E), and Poisson's ratio ( $\mu$ ) for the 28-day-old concrete. The modulus of elasticity and Poisson's ratio were determined by use of an XYY' recorder employing differential transformers. This arrangement produces a continuous plot of both longitudinal stress vs. longitudinal strain and longitudinal stress vs. lateral strain from which both the modulus of elasticity and Poisson's ratio were computed. The loading rate used was 60,000 lbs. per minute which is equivalent to 36 psi/sec., for the 6-in. diameter specimens.

Compressive strengths, modulus of elasticity, and Poisson's ratio for sealed concrete specimens stored at 73°F in Berkeley are shown in Table D. Compressive strengths for concrete cast at the job site <sup>are</sup> and shown in Table D.

Splitting tensile strengths were determined on three 6-in. x 12-in. concrete cylinders by A.S.T.M. C496-66 method.

##### Creep Tests

Creep characteristics for the concrete were determined on sealed 6-in. by 18-in. cylinders with centrally embedded Carlson Strain Meters. Two

specimens each were initially loaded at the ages of 28 days for specimens cast at Berkeley and 31 days for specimens cast at the job site all at a temperature of 73° F.

A stress level of 1530 psi was applied to all loaded creep specimens by a hydraulic system with an automatic controller which was used to maintain a constant stress level.

Sustained modulus of elasticity, creep characteristics, and autogenous strains for sealed concrete specimens stored at 73° F are shown in Table E for concrete cast at Berkeley and in Table F for concrete cast at the job site. The total load was applied within 30 seconds and the first strain reading taken within another 30 seconds or 1 minute after the load was started to be applied. Specimens cast at Berkeley have been under stress for 418 days and those cast at the job site have been under stress for 282 days. Sustained modulus of elasticity was computed by dividing the applied stress of 1530 psi by the sum of the elastic, creep, and autogenous strains at 1 minute after the load was started to be applied and at various other times. Creep plus autogenous strains starting from one minute and minutes after load was applied are shown. Creep plus autogenous strains per psi of stress starting from 10 minutes after load was applied are shown.

Elastic, creep, plus autogenous strains and creep plus autogenous strains from 10 minutes after load was applied are all shown plotted vs log of time for the average of two sealed concrete specimens stored at 73° F in Figure 1 for specimens cast at Berkeley and at the job site.

The complete computer calculations for determining the strains due to loading the sealed concrete specimens are shown in Tables G and H for specimens cast at Berkeley and Tables I and J for specimens cast at the job site.

**TABLES**

TABLE A  
MIX DESIGN FOR TURKEY POINT CONCRETE  
PENNSUCO AGGREGATES - 1970

<u>Material</u>	<u>Source</u>
Cement: Type II	Florida Portland Cement
Sand:	Pennsuco, Oolite, Florida Rock and Sand
3/4-in. Gravel:	Pennsuco, Oolite, Florida Rock and Sand
WRA Admixture:	Retardwell - Union Carbide
AEA Admixture:	Airecon - Union Carbide

Specifications

f'c (at 28 days)	5000 psi
Slump:	2 to 3 inches
Air:	4 percent

One Cubic Yard Batch, SSD Weights as given by Mr. D. E. Graham, Bechtel Corporation (San Francisco Office).

<u>Mix No.</u>	<u>2P6</u>
Cement, lbs.	635
Sand, lbs.	1254
3/4-in. Aggregate, lbs.	1630
Water, lbs.	260
WRA, oz.	27
AEA, oz.	1.6

TABLE B  
CASTING DATA  
PENNSUCO AGGREGATES

Date	November 20, 1970	
Specimens Cast	2 - 6x18-in. creep specimens 6 - 6x12-in. compressive strength cylinders 3 - 6x12-in. compressive strength, Young's Modulus, and Poisson's ratio cylinders 3 - 6x12-in. splitting tension cylinders	
Batch No. <sup>(a)</sup>	1	2
Cement, pcy	639	638
Water, pcy	279	277
Sand, pcy S.S.D.	1263	1257
3/4-in. aggregate, pcy S.S.D.	1636	1636
Unit wt.,pcf	141.6	141.0
Slump, inches	2 1/2	2 3/4
Air, % by Vol.	3.8	3.8
AEA, oz. pcy	1.6	1.6
WRA, oz. pcy	27.2	27.1
Temp. °F	69	69

(a) Each batch approximately 1.70 cu. ft.

TABLE C  
TURKEY POINT NUCLEAR CONTAINMENT VESSEL CONCRETE  
BULK SPECIFIC GRAVITY AND ABSORPTION CAPACITY

Aggregate	BULK SPECIFIC GRAVITY - Saturated surface dry	ABSORPTION CAPACITY percent
Pennsuco sand	2.50	2.49
Pennsuco 3/4-in. aggregate	2.40	5.10

TABLE D  
MECHANICAL PROPERTIES

Age, Days		Specimens Cast at	
		Berkeley	Job Site
3	Compressive strength, (a) psi	6,590	-
7	" " "	7,330	5,340
28	" " "	8,470	6,690
90	" " "	-	7,120
28	Poisson's Ratio	0.24	-
28	Modulus of elasticity, (a) psi x 10 <sup>6</sup>	4.4	-
28	" " " (b) "	4.7	-
28	Splitting tensile strength, (a) psi	570	-

(a) Average of three 6 x 12-in. cylinders.

(b) Average of two creep specimens.

TABLE E  
TURKEY POINT NUCLEAR CONTAINMENT VESSEL CONCRETE  
PENNSUCO AGGREGATE - 1972  
ELASTIC, CREEP, AND AUTOGENOUS STRAINS

Specimen cast: At Berkeley, California  
 Maximum size of aggregate: 3/4-in.  
 Specimen size: 6-in. by 18-in. (Sealed)  
 Temperature:  $73 \pm 3^{\circ}\text{F}$   
 Age at loading: 28 days  
 Applied stress: 1530 psi  
 Compressive strength: 8470 psi at age 28 days  
 Fine aggregate: Pennsuco  
 Coarse aggregate: Pennsuco 3/4-in.

Time under Stress, days	Sustained Modulus of Elasticity psi $\times 10^6$ (a)	Elastic Creep plus Autogenous Strains	Micro-strain		
			One minute after load applied	Ten minutes after load applied	per psi
0	-	0			
0.0007	4.71	-325	0		
0.0035	4.61	-333	-8		
0.0069	4.55	-336	-11	0	0
0.021	4.44	-345	-20	-9	-0.0058
1.04	3.85	-398	-73	-62	-0.0406
2	3.69	-415	-90	-79	-0.0516
3	3.60	-425	-100	-89	-0.0584
4	3.53	-434	-109	-98	-0.0640
10	3.24	-465	-140	-129	-0.0843
15	3.12	-489	-165	-153	-0.100
18	3.09	-496	-170	-160	-0.104
25	2.99	-512	-178	-176	-0.115
31	2.94	-520	-195	-184	-0.121
37	2.87	-533	-208	-197	-0.128
53	2.71	-555	-230	-219	-0.143
69	2.68	-571	-246	-235	-0.153
81	2.65	-578	-253	-242	-0.158
92	2.59	-590	-265	-254	-0.166
109	2.57	-595	-270	-259	-0.169
130	2.53	-605	-280	-269	-0.176
144	2.50	-613	-288	-277	-0.181
158	2.47	-619	-294	-283	-0.185
172	2.44	-628	-303	-292	-0.191
186	2.42	-633	-308	-297	-0.194
200	2.40	-637	-312	-301	-0.197
214	2.40	-638	-313	-302	-0.197

TABLE E, Continued

TURKEY POINT NUCLEAR CONTAINMENT VESSEL CONCRETE

PENNSUCO AGGREGATE - 1972

ELASTIC, CREEP, AND AUTOGENOUS STRAINS

Specimen cast: At Berkeley, California

Maximum size of aggregate: 3/4-in.

Specimen size: 6-in. by 18-in. (Sealed)

Temperature: 73 + 3°F

Age at loading: 28 days

Applied stress: 1530 psi

Compressive strength: 8470 psi at age 28 days

Fine aggregate: Pennsuco

Coarse aggregate: Pennsuco 3/4-in.

Time under Stress, days	Sustained Modulus of Elasticity psi x 10 <sup>6</sup> (a)	Elastic Creep plus Autogenous Strains	Micro-strain		
			Creep plus Autogenous Strains	One minute after load applied	Ten minutes after load applied per psi
228	2.37	-645	-320	-309	-0.202
242	2.35	-650	-325	-314	-0.205
256	2.34	-653	-328	-317	-0.207
271	2.32	-658	-333	-322	-0.210
284	2.32	-660	-335	-324	-0.212
301	2.31	-663	-338	-327	-0.214
311	2.30	-666	-341	-330	-0.216
328	2.29	-669	-344	-333	-0.218
350	2.27	-673	-348	-337	-0.220
380	2.27	-674	-349	-338	-0.220
418	2.24	-682	-357	-346	-0.226

- (a) Sustained Modulus of Elasticity computed as follows:  
 1530 psi divided by sum of elastic, creep, and  
 autogenous strains.

TABLE F  
TURKEY POINT NUCLEAR CONTAINMENT VESSEL CONCRETE  
PENNSUCO AGGREGATE - 1972  
ELASTIC, CREEP, AND AUTOGENOUS STRAINS

Specimen cast: At Berkeley, California  
 Maximum size of aggregate: 3/4-in.  
 Specimen size: 6-in. by 18-in. (Sealed)  
 Temperature:  $73 + 3^{\circ}\text{F}$   
 Age at loading: 31 days  
 Applied stress: 1530 psi  
 Fine aggregate: Pennsuco  
 Coarse aggregate: Pennsuco 3/4-in.

Time under Stress, days	Sustained Modulus of Elasticity psi $\times 10^6$ (a)	Micro-strain			
		Elastic Creep plus Autogenous Strains	Creep plus Autogenous Strains		
			One minute after load applied	Ten minutes after load applied	per psi
0	-	0			
0.0007	4.16	-368	0		
0.0035	4.05	-378	-10		
0.0069	3.97	-385	-17	0	0
0.014	3.87	-375	-27	-10	-0.0065
0.035	3.79	-404	-36	-19	-0.0124
0.333	3.53	-433	-65	-48	-0.0313
0.472	3.40	-450	-82	-65	-0.0424
0.881	3.35	-457	-89	-72	-0.0476
1	3.33	-460	-92	-75	-0.0490
7	2.85	-536	-168	-151	-0.0986
14	2.66	-575	-206	-189	-0.124
22	2.57	-595	-227	-210	-0.137
36	2.44	-627	-259	-242	-0.158
50	2.34	-655	-287	-270	-0.176
64	2.28	-671	-303	-286	-0.187
78	2.23	-685	-317	-300	-0.196
92	2.19	-698	-330	-313	-0.204
106	2.15	-711	-343	-326	-0.213
120	2.13	-720	-352	-335	-0.220
135	2.09	-732	-364	-347	-0.227
148	2.08	-736	-368	-351	-0.229
165	2.05	-745	-377	-360	-0.235
175	2.04	-751	-383	-366	-0.239
192	2.02	-757	-389	-372	-0.243
214	2.00	-764	-396	-379	-0.248
244	1.98	-772	-404	-387	-0.253
282	1.95	-784	-416	-399	-0.261

(a) Sustained Modulus of Elasticity computed as follows:  
 1530 psi divided by sum of elastic, creep and autogenous strains.

## STRAIN METER NO. L290

PROJECT TURKEY POINT  
LOCATION DAVIS HALL ROOM 360A

CAST 11-20-70

CALIBRATIONS  
 METFP RESISTANCE AT 0.0 DEGREES F. 53.38 OHMS  
 CHANGE IN TEMP. PER OHM CHANGE IN RESIS. 9.68 DEGREES F.  
 USEFUL RANGE 96.8-101.9 RATIO IN PERCENT  
 ORIGINAL CALIBRATION CONSTANT 3.15 MICROSTRAIN PER 0.01  
 PERCENT RATIO CHANGE  
 CALIBRATION CONSTANT CORR. FOR LEAD 3.15 MICROSTRAIN PER 0.01  
 PERCENT RATIO CHANGE  
 TEMPERATURE CORRECTION 5.5 MICROSTRAIN PER DEGREE F.  
 CONCRETE EXPANSION 7.5 MICROSTRAIN PER DEGREE F.

DATE	TIME*	METER *	TEMP. *	RESIST. *	CHANGE *	TOTAL *	MICROSTRAIN TEMPERATURE CORRECTED					
							*IN RATIO*	MICRO-*	TIME AFTER LOADING	0 * 1 MIN.* 1 MIN.* 10 MIN.* 10 MIN.	*1530 PSI*	1 PSI *1530 PSI*
11-12-70	915*	61.43	77.9	99.865	*	0.	*	*	*	*	*	*
11-25-70	1740*	60.95	73.4	99.882	* .017	-20.	*	14.	*	*	*	*
12-9-70	1625*	60.94	73.2	99.865	* 0.	-26.	*	9.	*	*	*	*
12-18-70	1530*	60.90	72.8	99.861	* -.004	-29.	*	9.	*	*	*	*
12-18-70	1531*	60.90	72.8	98.846	* -1.019	-349.	*	-311.	*	-320.	*	0. * 0.
12-18-70	1535*	60.90	72.8	98.824	* -1.041	-356.	*	-318.	*	-327.	*	-7. * -.0045
12-18-70	1540*	60.94	73.2	98.819	* -1.046	-356.	*	-320.	*	-329.	*	-9. * -.0061
12-19-70	1600*	60.95	73.3	98.791	* -1.074	-364.	*	-329.	*	-338.	*	-18. * -.0120
12-19-70	1630*	60.93	73.1	98.626	* -1.239	-417.	*	-381.	*	-390.	*	-70. * -.0457
12-20-70	1605*	60.93	73.1	98.570	* -1.295	-435.	*	-398.	*	-407.	*	-88. * -.0572
12-21-70	1615*	60.91	72.9	98.537	* -1.328	-446.	*	-408.	*	-417.	*	-98. * -.0637
12-22-70	1620*	60.92	73.0	98.511	* -1.354	-454.	*	-417.	*	-426.	*	-106. * -.0692
12-28-70	940*	60.90	72.8	98.409	* -1.456	-487.	*	-448.	*	-457.	*	-138. * -.0900
1-2-71	945*	60.94	73.2	98.332	* -1.533	-509.	*	-473.	*	-482.	*	-163. * -.1063
1-5-71	1715*	60.93	73.1	98.316	* -1.549	-515.	*	-478.	*	-487.	*	-168. * -.1095
1-12-71	1530*	60.95	73.3	98.262	* -1.603	-531.	*	-496.	*	-505.	*	-185. * -.1209
1-18-71	955*	60.93	73.1	98.233	* -1.632	-541.	*	-504.	*	-513.	*	-194. * -.1266
1-24-71	1410*	60.96	73.4	98.192	* -1.673	-552.	*	-518.	*	-527.	*	-207. * -.1354
2-9-71	1210*	60.98	73.6	98.125	* -1.740	-572.	*	-539.	*	-548.	*	-229. * -.1495
2-25-71	1030*	60.98	73.6	98.079	* -1.786	-587.	*	-554.	*	-563.	*	-243. * -.1589
3-9-71	1410*	60.98	73.6	98.053	* -1.812	-595.	*	-562.	*	-571.	*	-251. * -.1643
2-23-71	1440*	61.01	73.9	98.021	* -1.844	-603.	*	-573.	*	-582.	*	-262. * -.1712
4-6-71	930*	60.99	73.7	98.002	* -1.863	-610.	*	-578.	*	-587.	*	-268. * -.1749
4-27-71	1000*	60.98	73.6	97.974	* -1.891	-620.	*	-587.	*	-596.	*	-276. * -.1805
5-11-71	1350*	60.96	73.4	97.941	* -1.924	-631.	*	-597.	*	-606.	*	-286. * -.1871
5-25-71	1500*	60.98	73.6	97.927	* -1.938	-634.	*	-602.	*	-611.	*	-291. * -.1902
5-8-71	920*	61.02	74.0	97.897	* -1.968	-642.	*	-612.	*	-621.	*	-301. * -.1969
5-22-71	1410*	61.00	73.8	97.884	* -1.981	-647.	*	-616.	*	-625.	*	-305. * -.1993
7-6-71	1340*	61.01	73.9	97.870	* -1.995	-651.	*	-620.	*	-629.	*	-310. * -.2023
7-20-71	1015*	61.00	73.8	97.864	* -2.001	-653.	*	-622.	*	-631.	*	-311. * -.2034
8-7-71	1510*	61.01	73.9	97.848	* -2.017	-658.	*	-627.	*	-636.	*	-316. * -.2069
8-17-71	850*	61.03	74.1	97.834	* -2.031	-661.	*	-632.	*	-641.	*	-321. * -.2100
8-21-71	1410*	61.02	74.0	97.823	* -2.042	-665.	*	-635.	*	-644.	*	-325. * -.2121
9-15-71	1610*	61.04	74.1	97.807	* -2.058	-669.	*	-641.	*	-650.	*	-330. * -.2157
9-27-71	1415*	61.03	74.1	97.799	* -2.066	-672.	*	-643.	*	-652.	*	-332. * -.2172
10-14-71	1400*	61.01	73.9	97.792	* -2.073	-675.	*	-645.	*	-654.	*	-334. * -.2184
10-24-71	1440*	61.03	73.8	97.780	* -2.085	-680.	*	-648.	*	-657.	*	-338. * -.2207
11-11-71	1400*	60.98	73.6	97.772	* -2.093	-683.	*	-651.	*	-660.	*	-340. * -.2221
12-1-71	1410*	60.99	73.7	97.759	* -2.106	-687.	*	-655.	*	-664.	*	-344. * -.2249
1-3-71	1420*	60.96	73.4	97.753	* -2.112	-690.	*	-656.	*	-665.	*	-345. * -.2258
2-10-72	1420*	60.97	73.5	97.727	* -2.138	-698.	*	-665.	*	-674.	*	-354. * -.2313

TABLE G

## STRAIN METER NO. L291

PROJECT TURKEY POINT  
LOCATION DAVIS HALL ROOM 360A

CAST 11-20-70

## CALIBRATIONS

METER RESISTANCE AT 0.0 DEGREES F. 53.51 OHMS

CHANGE IN TEMP. PER OHM CHANGE IN RESIS. 9.65 DEGREES F.

USEFUL RANGE 96.8-101.9 RATIO IN PERCENT

ORIGINAL CALIBRATION CONSTANT 3.16 MICROSTRAIN PER 0.01

PERCENT RATIO CHANGE

CALIBRATION CONSTANT CORR. FOR LEAD 3.16 MICROSTRAIN PER 0.01

PERCENT RATIO CHANGE

TEMPERATURE CORRECTION 5.5 MICROSTRAIN PER DEGREE F.

CONCRETE EXPANSION 7.5 MICROSTRAIN PER DEGREE F.

DATE	TIME*	METER *	TEMP. *	RESIST. *	CHANGE *	TOTAL *	MICROSTRAIN TEMPERATURE CORRECTED											
							* RESIST.*	F. *	RATIO *IN RATIO*	MICRO- *	TIME AFTER LOADING							
*	*	*	*	*	*	*	*	*	*	*								
*****										*****								
11-12-70	* 915*	61.52	*	77.3	*	99.852	*	0.	*	0.	*	*	*	*	*			
11-25-70	* 1740*	61.14	*	73.6	*	99.862	*	.010	*	-17.	*	10.	*	*	*			
12-9-70	* 1625*	61.12	*	73.4	*	99.848	*	-.004	*	-22.	*	6.	*	*	*			
12-18-70	* 1530*	61.13	*	73.2	*	99.842	*	-.010	*	-25.	*	5.	*	*	*			
12-18-70	* 1531*	61.19	*	73.2	*	98.794	*	-1.058	*	-357.	*	-326.	*	-331.	*	0.	*	0.
12-18-70	* 1535*	61.17	*	73.2	*	98.770	*	-1.082	*	-364.	*	-334.	*	-339.	*	-8.	*	-.0050
12-18-70	* 1540*	61.14	*	73.6	*	98.758	*	-1.094	*	-366.	*	-338.	*	-343.	*	-12.	*	-.0079
12-18-70	* 1600*	61.14	*	73.6	*	98.730	*	-1.122	*	-375.	*	-347.	*	-352.	*	-21.	*	-.0137
12-19-70	* 1630*	61.08	*	73.1	*	98.553	*	-1.299	*	-434.	*	-402.	*	-407.	*	-76.	*	-.0495
12-20-70	* 1605*	61.06	*	72.9	*	98.501	*	-1.351	*	-451.	*	-418.	*	-423.	*	-92.	*	-.0600
12-21-70	* 1615*	61.06	*	72.9	*	98.467	*	-1.385	*	-462.	*	-429.	*	-434.	*	-103.	*	-.0670
12-22-70	* 1620*	61.08	*	73.1	*	98.441	*	-1.411	*	-469.	*	-437.	*	-442.	*	-111.	*	-.0727
12-28-70	* 940*	61.04	*	72.7	*	98.342	*	-1.510	*	-503.	*	-468.	*	-473.	*	-142.	*	-.0926
1-7-71	* 945*	61.09	*	73.1	*	98.270	*	-1.582	*	-523.	*	-492.	*	-497.	*	-165.	*	-.1081
1-6-71	* 1715*	61.08	*	73.1	*	98.245	*	-1.607	*	-531.	*	-499.	*	-504.	*	-173.	*	-.1131
1-17-71	* 1530*	61.10	*	73.2	*	98.195	*	-1.657	*	-546.	*	-516.	*	-520.	*	-189.	*	-.1237
1-18-71	* 955*	61.04	*	72.7	*	98.166	*	-1.686	*	-558.	*	-524.	*	-528.	*	-197.	*	-.1289
1-24-71	* 1410*	61.09	*	73.1	*	98.131	*	-1.721	*	-567.	*	-535.	*	-540.	*	-209.	*	-.1367
2-9-71	* 1210*	61.13	*	73.5	*	98.061	*	-1.791	*	-587.	*	-558.	*	-563.	*	-232.	*	-.1518
2-25-71	* 1030*	61.13	*	73.5	*	98.012	*	-1.840	*	-602.	*	-574.	*	-579.	*	-248.	*	-.1619
3-0-71	* 1410*	61.12	*	73.4	*	97.987	*	-1.865	*	-611.	*	-582.	*	-587.	*	-255.	*	-.1669
3-23-71	* 1440*	61.16	*	73.8	*	97.952	*	-1.900	*	-620.	*	-593.	*	-598.	*	-267.	*	-.1747
4-6-71	* 930*	61.05	*	72.8	*	97.931	*	-1.921	*	-632.	*	-598.	*	-603.	*	-272.	*	-.1776
4-27-71	* 1000*	61.13	*	73.5	*	97.899	*	-1.953	*	-638.	*	-610.	*	-615.	*	-283.	*	-.1852
5-11-71	* 1350*	61.12	*	73.4	*	97.878	*	-1.974	*	-645.	*	-616.	*	-621.	*	-290.	*	-.1894
5-25-71	* 1500*	61.14	*	73.6	*	97.859	*	-1.993	*	-650.	*	-622.	*	-627.	*	-296.	*	-.1936
6-8-71	* 920*	61.15	*	73.7	*	97.834	*	-2.018	*	-657.	*	-631.	*	-635.	*	-304.	*	-.1989
6-22-71	* 1410*	61.15	*	73.8	*	97.816	*	-2.036	*	-662.	*	-636.	*	-641.	*	-310.	*	-.2027
7-6-71	* 1340*	61.17	*	73.9	*	97.801	*	-2.051	*	-667.	*	-641.	*	-646.	*	-315.	*	-.2060
7-20-71	* 1015*	61.12	*	73.4	*	97.797	*	-2.055	*	-671.	*	-642.	*	-647.	*	-315.	*	-.2062
8-3-71	* 1510*	61.17	*	73.9	*	97.776	*	-2.076	*	-675.	*	-649.	*	-654.	*	-323.	*	-2111
8-17-71	* 850*	61.18	*	74.0	*	97.761	*	-2.091	*	-679.	*	-654.	*	-659.	*	-328.	*	-2144
8-31-71	* 1410*	61.17	*	73.9	*	97.751	*	-2.101	*	-682.	*	-657.	*	-662.	*	-331.	*	-2163
9-15-71	* 1610*	61.13	*	74.0	*	97.735	*	-2.117	*	-687.	*	-662.	*	-667.	*	-336.	*	-2197
9-27-71	* 1415*	61.15	*	73.7	*	97.727	*	-2.125	*	-691.	*	-664.	*	-669.	*	-338.	*	-2210
10-14-71	* 1400*	61.16	*	73.8	*	97.717	*	-2.135	*	-694.	*	-668.	*	-673.	*	-341.	*	-2232
10-24-71	* 1440*	61.16	*	73.8	*	97.707	*	-2.145	*	-697.	*	-671.	*	-676.	*	-345.	*	-2253
11-11-71	* 1400*	61.14	*	73.6	*	97.697	*	-2.155	*	-701.	*	-674.	*	-679.	*	-347.	*	-2271
12-1-71	* 1410*	61.14	*	73.6	*	97.685	*	-2.167	*	-705.	*	-677.	*	-682.	*	-351.	*	-2296
1-3-71	* 1420*	61.09	*	73.1	*	97.680	*	-2.172	*	-709.	*	-678.	*	-683.	*	-352.	*	-2300
2-10-72	* 1420*	61.10	*	73.2	*	97.659	*	-2.193	*	-715.	*	-685.	*	-690.	*	-359.	*	-2344



PROJECT TURKEY POINT FS 7151 STRAIN METER NO. L287  
 LOCATION 200M 360A DAVIS TALL CAST ON JOB  
 USEFUL RANGE LOADED TO 1530 PSI

CALIBRATIONS  
 METER RESISTANCE AT 0.0 DEGREES F. 52.95 OHMS  
 CHANGE IN TEMP. PFR OHM CHANGE IN RESIS. 9.75 DEGREES F.  
 USEFUL RANGE 96.7-101.9 RATIO IN PERCENT  
 ORIGINAL CALIBRATION CONSTANT 3.17 MICROSTRAIN PER 0.01  
 CALIBRATION CONSTANT CORR. FOR LEAN 3.17 MICROSTRAIN PER 0.01  
 PERCENT RATIO CHANGE 5.2 MICROSTRAIN PER DEGREE F.  
 TEMPERATURE CORRECTION 5.7 MICROSTRAIN PER DEGREE F.  
 CONCRETE EXPANSION

DATE	TIME*	METER *	TEMP *	RESIST. *	CHANGE *	TOTAL *	MICROSTRAIN TEMPERATURE CORRECTED		
							* RESIST.*	F. *	% IN RATIO*
4-22-71	*	1425*	59.07	99.826	*	0.	*	0.	*
5-3-71	*	1538*	60.36	99.682	*	-144.	*	20.	*
5-3-71	*	1539*	60.36	98.565	*	-1.261	*	-406.	*
5-3-71	*	1541*	60.36	98.550	*	-1.276	*	-339.	*
5-3-71	*	1543*	60.36	98.539	*	-1.287	*	-411.	*
5-3-71	*	1548*	60.41	98.519	*	-1.307	*	-343.	*
5-3-71	*	1608*	60.41	98.487	*	-1.339	*	-357.	*
5-3-71	*	1638*	60.41	98.463	*	-1.363	*	-364.	*
5-3-71	*	2207*	60.40	98.373	*	-1.453	*	-393.	*
5-4-71	*	755*	60.40	98.320	*	-1.506	*	-410.	*
5-4-71	*	1255*	60.40	98.297	*	-1.529	*	-417.	*
5-4-71	*	1538*	67.40	98.288	*	-1.538	*	-420.	*
5-11-71	*	1350*	60.43	98.048	*	-1.778	*	-495.	*
5-17-71	*	1630*	60.46	97.926	*	-1.900	*	-532.	*
5-25-71	*	1500*	50.43	97.867	*	-1.959	*	-552.	*
5-8-71	*	920*	60.45	97.765	*	-2.061	*	-583.	*
6-2-71	*	1410*	61.48	97.693	*	-2.133	*	-554.	*
7-6-71	*	1340*	60.48	97.635	*	-2.191	*	-623.	*
7-20-71	*	1015*	60.51	97.591	*	-2.235	*	-635.	*
8-3-71	*	1510*	60.49	97.552	*	-2.274	*	-649.	*
8-17-71	*	850*	60.51	97.515	*	-2.311	*	-660.	*
9-31-71	*	1410*	60.51	97.477	*	-2.342	*	-659.	*
9-15-71	*	1710*	60.52	97.44	*	-2.375	*	-676.	*
9-27-71	*	1415*	60.47	97.3*	*	-2.392	*	-687.	*
10-14-71	*	1400*	60.51	97.410	*	-2.416	*	-693.	*
10-24-71	*	1440*	60.46	97.390	*	-2.436	*	-702.	*
11-11-71	*	1400*	60.45	97.371	*	-2.455	*	-708.	*
12-1-71	*	1410*	60.44	97.347	*	-2.479	*	-716.	*
1-3-71	*	1420*	50.41	97.322	*	-2.504	*	-726.	*
2-10-72	*	1427*	60.43	97.288	*	-2.538	*	-736.	*

TABLE J

**FIGURE**




FIG. I

FIG. I