Lawrence Berkeley National Laboratory

Recent Work

Title

Numerical Solution of the Steady Stokes Equations

Permalink

<https://escholarship.org/uc/item/43z843w5>

Journal

Journal of computational physics, 99(2)

Author

Tau, E.-Y.

Publication Date

1990

Lawrence Berkeley Laboratory

UNIVERSITY OF CALIFORNIA

Physics Division

Mathematics Department

To be submitted for publication.

Numerical Solution of the Steady Stokes Equations

E.Y. Tau

January 1990

Prepared for the U.S. Department of Energy under Contract Number DE-AC03-76SF00098.

! LOAN COPY !
! Circulates !
! for 2 weeks !

Bldg. 50 Library.
Copy 2

LBL-28441

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.

NUMERICAL SOLUTION OF THE STEADY STOKES EQUATIONS*

Eric Yu Tau

Lawrence Berkeley Laboratory
and
Department of Mathematics
University of California
Berkeley, California 94720

January 1990

* This work was supported in part by the Applied Mathematical Sciences Subprogram of the Office of Energy Research, U.S. Department of Energy, under Contract Number DE-AC03-76SF000098.

Numerical Solution of the Steady Stokes Equations

Abstract

In this paper we present a fast numerical technique for finding solutions of the steady-state Stokes equations on both two and three dimensional domains. We implement the method on a special staggered grid for a rectangular (cubic) domain, and obtain a solution in an order of $O(N \log N)$ operations for both two and three dimensional cases, where N is the number of grid points in the domain. The main idea is to derive from the Stokes equations an equation for the pressure p , $Ap = b$, where the matrix A is semi-positive definite and very well conditioned on the orthogonal complement of its null space.

1 Introduction

For simplicity, we describe the problem in the two dimensional case. The Stokes equations have the following form:

$$-\frac{1}{R}\Delta \mathbf{u} + \nabla p = \mathbf{f} \quad (1)$$

$$\nabla \cdot \mathbf{u} = 0 \quad (2)$$

where $\mathbf{u} = (u, v)$ is the velocity field, p is the pressure, $\mathbf{f} = (f_x, f_y)$ is the body force and R is the Reynolds number. Let Ω be a rectangular domain. We assume the following boundary condition on $\mathbf{u}$:

$$\mathbf{u}(x, y) = \mathbf{u}_b(x, y), \quad (x, y) \in \partial\Omega. \quad (3)$$

$\mathbf{u}_b$ must satisfy

$$\int_{\partial\Omega} \mathbf{u}_b \cdot \mathbf{n} dS = 0, \quad (4)$$

where $\mathbf{n}$ is the outer unit normal to $\partial\Omega$. It is well known that we need not prescribe the boundary condition on p .

Most of the work done before on this problem begins with replacing Eqs. (1) and (2) by the system

$$-\frac{1}{R}\Delta \mathbf{u} + \nabla p = \mathbf{f}$$

$$\Delta p = \nabla \cdot \mathbf{f}$$

and then trying to solve the Laplace equation for p . The lack of boundary condition on p causes some difficulty. Much work has been done to determine the correct boundary condition for p (see, e.g., discussion in Strikwerda (1984)). Work using the original system (1) and (2) has also been done, but it still requires some additional conditions for p near the boundary (Harlow and Welch (1965), Strikwerda (1984)).

Chorin (1968) proposed a projection method for the more general Navier-Stokes equations that determines p without any artificial conditions on p . The method is based on the use of the equation $\nabla \cdot \mathbf{u} = 0$ instead of $\Delta p = \nabla \cdot \mathbf{f}$ to find p . Here we present a method based on the evaluation of p for the Stokes equations that requires no artificial conditions on p either. The idea is to use consistent finite difference operators to discretize Eqs. (1) and (2). It will be shown later in this section that the resulting system of equations is semi-definite if the difference operators satisfy a discrete analogue of the condition $(\mathbf{u}, \nabla p) = -(\nabla \cdot \mathbf{u}, p)$ (see Chorin (1969) for the discrete form of this condition). We eliminate $\mathbf{u}$ to form an equation $Ap = b$ which uniquely determines p (up to a constant, of course). Since it is computationally inefficient to express $\mathbf{u}$ in terms of p explicitly, we shall only have to evaluate Ap , i.e. given a p , we can find Ap , where A is not written out (as in the iterative implementation of Chorin's projection method (1968)). It turns out that for some properly chosen operators the matrix A is semi-positive definite and very well conditioned on the orthogonal complement of its null space, so we can use the conjugate-gradient method to get the solution for p .

Assume the domain Ω is covered by some uniform grid of mesh size h . Following the notations of Anderson (1989), we approximate Eqs. (1) and (2) by finite difference equations,

$$-\frac{1}{R}\Delta_h \mathbf{u} + (\nabla_x^h, \nabla_y^h)p = \mathbf{f}, \quad (5)$$

$$D_x^h u + D_y^h v = 0, \quad (6)$$

where Δ_h is an approximation to the Laplacian, ∇_x^h and ∇_y^h to the derivatives in the gradient operator, D_x^h and D_y^h to the derivatives in the divergence operator. Notice that near the boundary $\Delta_h \mathbf{u}$ and $D_x^h u + D_y^h v$ contain velocity values on the boundary which are known. If we move those known terms to the right hand side of equations, we can rewrite Eqs. (5) and (6) as

$$-\frac{1}{R}\tilde{\Delta}_h \mathbf{u} + (\nabla_x^h, \nabla_y^h)p = \mathbf{f} + \mathbf{g}(\mathbf{u}_b) \quad (7)$$

$$\tilde{D}_x^h u + \tilde{D}_y^h v = h(\mathbf{u}_b) \quad (8)$$

where

$$\mathbf{g}(\mathbf{u}_b) = \frac{1}{R}\Delta_h \mathbf{u} - \frac{1}{R}\tilde{\Delta}_h \mathbf{u}$$

and

$$h(\mathbf{u}_b) = \tilde{D}_x^h u + \tilde{D}_y^h v - (D_x^h u + D_y^h v).$$

In other words, the operators with tilde's differ from the original operators only near the boundary, and they are the parts of the operators

Δ_h , D_x^h , D_y^h that operate only on unknown values of the velocity. We will show how to calculate them once Δ_h , D_x^h , and D_y^h are defined in section (2) (see also Anderson (1989)).

Put Eqs. (7) and (8) in block matrix form. We have

$$\begin{pmatrix} -\frac{1}{R}\tilde{\Delta}_h & 0 & \nabla_x^h \\ 0 & -\frac{1}{R}\tilde{\Delta}_h & \nabla_y^h \\ \tilde{D}_x^h & \tilde{D}_y^h & 0 \end{pmatrix} \begin{pmatrix} u \\ v \\ p \end{pmatrix} = \begin{pmatrix} f_x + g_x(\mathbf{u}_b) \\ f_y + g_y(\mathbf{u}_b) \\ h(\mathbf{u}_b) \end{pmatrix} \quad (9)$$

Consider the quadratic form

$$(u, v, p) \begin{pmatrix} -\frac{1}{R}\tilde{\Delta}_h & 0 & \nabla_x^h \\ 0 & -\frac{1}{R}\tilde{\Delta}_h & \nabla_y^h \\ \tilde{D}_x^h & \tilde{D}_y^h & 0 \end{pmatrix} \begin{pmatrix} u \\ v \\ p \end{pmatrix}$$

$$= -\frac{1}{R}[(u, \tilde{\Delta}_h u) + (v, \tilde{\Delta}_h v)] + (u, \nabla_x^h p) + (v, \nabla_y^h p) + (\tilde{D}_x^h u, p) + (\tilde{D}_y^h v, p).$$

It is positive semi-definite provided

$$(u, \nabla_x^h p) + (v, \nabla_y^h p) = -((\tilde{D}_x^h u, p) + (\tilde{D}_y^h v, p)) \quad (10)$$

and

$$(u, \tilde{\Delta}_h u) \leq 0, \quad (v, \tilde{\Delta}_h v) \leq 0 \quad (11)$$

Conditions (11) are satisfied for most reasonable difference approximations to the Laplacian while condition (10) is just a discrete analogue of the condition $(\mathbf{u}, \nabla p) = -(\nabla \cdot \mathbf{u}, p)$.

We can formally eliminate u and v in Eq. (9) to form a equation for p as follows:

From Eq. (7) we obtain

$$u = R\{\tilde{\Delta}_h^{-1}\nabla_x^h p - \tilde{\Delta}_h^{-1}(f_x + g_x(\mathbf{u}_b))\}$$

and

$$v = R\{\tilde{\Delta}_h^{-1}\nabla_y^h p - \tilde{\Delta}_h^{-1}(f_y + g_y(\mathbf{u}_b))\}$$

Substitution of these expressions into Eq. (8) gives

$$\begin{aligned} & (\tilde{D}_x^h \tilde{\Delta}_h^{-1} \nabla_x^h + \tilde{D}_y^h \tilde{\Delta}_h^{-1} \nabla_y^h) p \\ &= \tilde{D}_x^h \tilde{\Delta}_h^{-1} (f_x + g_x(\mathbf{u}_b)) + \tilde{D}_y^h \tilde{\Delta}_h^{-1} (f_y + g_y(\mathbf{u}_b)) + \frac{1}{R} h(\mathbf{u}_b) \end{aligned}$$

or simply

$$Ap = F^1 + F^2 \tag{12}$$

$$\text{where } A = \tilde{D}_x^h \tilde{\Delta}_h^{-1} \nabla_x^h + \tilde{D}_y^h \tilde{\Delta}_h^{-1} \nabla_y^h \tag{12a}$$

$$F^1 = \tilde{D}_x^h \tilde{\Delta}_h^{-1} (f_x + g_x(\mathbf{u}_b)) + \tilde{D}_y^h \tilde{\Delta}_h^{-1} (f_y + g_y(\mathbf{u}_b))$$

$$F^2 = \frac{1}{R} h(\mathbf{u}_b)$$

If we can solve Eq. (12) for p , then we can use Eq. (7) to obtain solutions for u and v .

Of course we do not have to find $\tilde{\Delta}_h^{-1}$ explicitly, but rather given a p (and $\mathbf{u}_b$), we can solve Eq. (7) for u and v then use Eq. (8) to form Ap . It turns out that for some properly chosen operators $\Delta_h, D_x^h, D_y^h, \nabla_x^h$

and ∇_y^h the matrix A is semi-positive definite, so we can use the conjugate-gradient method to solve Eq. (12).

Recall that $\tilde{\Delta}_h$, $\tilde{D}_x^h$, $\tilde{D}_y^h$ are different from Δ_h , D_x^h , D_y^h only near the boundary, so if we choose

$$\Delta_h = D_x^h \nabla_x^h + D_y^h \nabla_y^h \quad (13)$$

which is just a discrete analogue of the definition of Laplacian. We will have

$$\tilde{\Delta}_h = \tilde{D}_x^h \nabla_x^h + \tilde{D}_y^h \nabla_y^h$$

on all grid points except those near the boundary. By looking at the structure of matrix A in (12a), it is reasonable to believe that A is close to the identity matrix, and that the conjugate-gradient method will converge in a few steps. We shall see that this is indeed the case by numerical examples.

2 Discretization of the Domain and Choice of D^h , ∇^h , Δ_h

We now implement the method for a special case of a staggered grid. Assume Ω is a unit square. Let $h = 1/n$. Define meshes (see *Fig. 1*)

$$U = \{(ih, (j + \frac{1}{2})h) \mid i = 0, \dots, n; j = 0, \dots, n-1\}$$

$$V = \{((i + \frac{1}{2})h, jh) \mid i = 0, \dots, n-1; j = 0, \dots, n\}$$

$$P = \{((i + \frac{1}{2})h, (j + \frac{1}{2})h) \mid i, j = 0, \dots, n-1\}$$

$$\bullet \in U \quad \blacksquare \in V \quad + \in P$$

Figure 1: Discretization of Domain

$$U^0 = U - U \cap \partial\Omega \quad V^0 = V - V \cap \partial\Omega$$

and define u on U , v on V and p on P .

The operators are defined as follows:

$$D_x^h : U \rightarrow P \text{ by } (D_x^h u)_{i+\frac{1}{2}, j+\frac{1}{2}} = (u_{i+1, j+\frac{1}{2}} - u_{i, j+\frac{1}{2}}) / h$$

$$D_y^h : V \rightarrow P \text{ by } (D_y^h v)_{i+\frac{1}{2}, j+\frac{1}{2}} = (v_{i+\frac{1}{2}, j+1} - v_{i+\frac{1}{2}, j}) / h$$

$$\nabla_x^h : P \rightarrow U^0 \text{ by } (\nabla_x^h p)_{i, j+\frac{1}{2}} = (p_{i+\frac{1}{2}, j+\frac{1}{2}} - p_{i-\frac{1}{2}, j+\frac{1}{2}}) / h$$

$$\nabla_y^h : P \rightarrow V^0 \text{ by } (\nabla_y^h p)_{i, j+\frac{1}{2}} = (p_{i+\frac{1}{2}, j+\frac{1}{2}} - p_{i+\frac{1}{2}, j-\frac{1}{2}}) / h$$

and we define $\Delta_h u$ on U_0 , $\Delta_h v$ on V_0 by the standard five point approximation to Laplacian except near the boundary where we use a first order approximation, for instance, we put

$$\frac{\partial^2 u}{\partial y^2} \approx \frac{u_{i,\frac{3}{2}} - 3u_{i,\frac{1}{2}} + 2u_{1,0}}{h^2}$$

at $j = 1$. Similarly for $j = n$ and $\frac{\partial^2 u}{\partial x^2}$. With those choices of the operators, it can be checked that relation (13) is satisfied on all grid points except those near the boundary.

Now the operators D^h etc. are defined. We can obtain the corresponding $\tilde{D}^h$ as follows: if $D_x^h u$ doesn't involve u_b , put $\tilde{D}_x^h u = D_x^h u$; if it does, just put all $u_b = 0$ in $D_x^h u$ to get $\tilde{D}_x^h u$. For instance

$$(\tilde{D}_x^h u)_{\frac{1}{2}, j+\frac{1}{2}} = \frac{u_{1, j+\frac{1}{2}}}{h}.$$

If we define the inner product on U^0 , V^0 and P by

$$(\phi, \psi)_{U^0} = \sum_{i=1}^{n-1} \sum_{j=1}^n \phi_{i, j-\frac{1}{2}} \psi_{i, j-\frac{1}{2}}$$

$$(\phi, \psi)_{V^0} = \sum_{i=1}^n \sum_{j=1}^{n-1} \phi_{i-\frac{1}{2}, j} \psi_{i-\frac{1}{2}, j}$$

and

$$(\phi, \psi)_P = \sum_{i=1}^n \sum_{j=1}^n \phi_{i-\frac{1}{2}, j-\frac{1}{2}} \psi_{i-\frac{1}{2}, j-\frac{1}{2}}$$

then it is easy to check that

$$(\tilde{D}_x^h u + \tilde{D}_y^h v, p)_P = -(\nabla_x^h p, u)_{U^0} - (\nabla_y^h p, v)_{V^0}.$$

Moreover, since

$$-\tilde{\Delta}_h = \begin{pmatrix} 5 & -1 & & & -1 & 0 & -1 \\ -1 & 4 & -1 & & & -1 & 0 & -1 \\ \cdot & \cdot & & & & & \cdot & \cdot \\ \cdot & \cdot & & & & & \cdot & \cdot \\ \cdot & \cdot & & & & & \cdot & \cdot \\ \cdot & \cdot & & & & & \cdot & \cdot \\ \cdot & \cdot & & & & & \cdot & \cdot \\ & & -1 & 0 & -1 & & -1 & 5 \end{pmatrix}$$

we have by Gerschgorin's theorem

$$-(u, \tilde{\Delta}_h u)_{U^0} \geq 0$$

and

$$-(v, \tilde{\Delta}_h v)_{V^0} \geq 0.$$

Thus the matrix in Eq. (9) is indeed semi-positive definite and our numerical experiment shows that the matrix A is also semi-positive definite.

With the discretization and the choice of operators made here, Eq. (12) has a non-trivial null space which is a constant pressure field. For the equation to have a solution the right hand side must be orthogonal to the null space. In this case, this condition turns out to be

$$\sum_{i,j} (F_{i,j}^1 + F_{i,j}^2) = 0$$

The terms denoted by $F_{i,j}^1$ are obtained by multiplying the reduced discrete divergence operator by a known vector. It can be verified that

$$\sum_{i,j} F_{i,j}^1 = 0$$

The second part of the sum, $\sum_{i,j} F_{i,j}^2$, is just a midpoint rule approximation to the condition $\int_{\partial\Omega} \mathbf{u}_b \cdot \mathbf{n} dS = 0$ (see Anderson (1989)).

The above description can be naturally extended to the three dimensional case and all the conclusions remain true.

3 Solution of the Equations

In this section, we specify the routines we used in our numerical examples. The goal is to solve Eq. (7) for $\mathbf{u}$ quickly with a given p . In the two dimensional case there is a fast solver for this equation, namely, the subroutine BLKTRE from the NCAR set of routines FISHPACK. In the three dimensional case, however, there is no fast solver available. We can apply the fast fourier transform (FFT) technique to reduce the problem to a two dimensional problem (see, e.g., Swarztrauber (1977)). For instance, consider the equation for u ,

$$\frac{1}{R} \tilde{\Delta}_h u = \nabla_x^h p + f_x + g_x(\mathbf{u}_b).$$

The grid is defined by $x = (i - 1)h$, $y = (j - 0.5)h$, $z = (k - 0.5)h$. We use FFT in the x-direction to reduce the problem to (n-1) two dimensional systems on the staggered grid $y = (j - 0.5)h$, $z = (k - 0.5)h$. Since u is specified on the boundary, only sine functions are needed in the FFT. For the resulting two dimensional systems, we use the subroutine HSTCRT from the NCAR set of routines FISHPACK.

To solve equation $Ap = b$, we use the standard conjugate-gradient method. Since there is a non-trivial null space, care must be taken to eliminate components in the null space. Let $\mathbf{c}$ denote the null vector of the matrix (which

is a constant vector in this case) and $(\cdot, \cdot)$ the inner product on p defined in section (2). The conjugate-gradient method algorithm is as follows:

$$r^0 = b - Ap^0 \quad p^0 \text{ initial guess}$$

For $k = 0, 1, 2, \dots$

$$r^k = r^k - \frac{(r^k, c)}{(c, c)} c$$

$$\beta^k = \frac{(r^k, r^k)}{(r^{k-1}, r^{k-1})} \quad k \geq 1 \quad \beta^0 = 0$$

$$z^k = r^k + \beta^k z^{k-1}$$

$$\alpha^k = \frac{(r^k, r^k)}{(z^k, Az^k)}$$

$$p^{k+1} = p^k + \alpha^k z^k$$

$$r^{k+1} = r^k - \alpha^k Az^k$$

The computational work in each iteration step of the conjugate-gradient method is done mostly to form Ap , everything else is just some vector products which requires labor of order $O(N)$ (where N is the number of points in the domain). The formation of Ap requires solutions to two Laplace equations in the two dimensional case or three Laplace equations in the three

dimensional case which cost $O(N \log N)$. Our solution to the steady Stokes equations thus requires work of order $2MN \log N$ or $3MN \log N$ where M is the number of iterations in the conjugate-gradient method. We will see from our numerical examples that M is very small even for very large N in the three dimensional case.

We first give an example in the two dimensional case. As a test problem, we take $\mathbf{f} = (3 \cos(x) \sin(y), -\sin(x) \cos(y))$, $R = 1$, $u_b = \cos(x) \sin(y)$, $v_b = -\sin(x) \cos(y)$ and $\Omega = \{x, y | 0 \leq x \leq 2\pi, 0 \leq y \leq \pi\}$. In this case the exact solution is known to be

$$u = \cos(x) \sin(y), \quad v = -\sin(x) \cos(y),$$

$$\frac{\partial p}{\partial x} = \cos(x) \sin(y), \quad \frac{\partial p}{\partial y} = \sin(x) \cos(y).$$

In table 1 we display the results of the calculation. We use the residual r of the pressure equation (12) as our computation criterion, i.e., the iteration stops when $\max(r_{i,j})$ is less than 1×10^{-7} . We should mention that by our construction this residual is exactly the divergence of the velocity field, i.e., we have

$$r_{i,j} = (D_x^h u + D_y^h v)_{i,j}$$

We denote by $e(u), e(v), e(p_x)$ and $e(p_y)$ the errors of u, v, p_x and p_y , i.e., the absolute value of the differences between the exact solutions and our numerical solutions, respectively. All the errors are measured in the L^∞ norm.

For the case of three dimensions, we choose the test problem to be:

$$u_b = \sin(x) \cos(y) \cos(2z)$$

Table 1: Numerical results in 2-D case

Grid size	20×10	40×20	80×40	160×80
Iterations	8	10	10	11
L^∞ norm of r	9.50×10^{-8}	8.84×10^{-9}	7.71×10^{-8}	9.06×10^{-8}
$e(u)$	1.21×10^{-3}	2.92×10^{-4}	7.23×10^{-5}	1.80×10^{-5}
$e(v)$	5.06×10^{-4}	1.17×10^{-4}	2.87×10^{-5}	7.13×10^{-6}
$e(p_x)$	2.07×10^{-2}	5.68×10^{-3}	1.48×10^{-3}	3.77×10^{-4}
$e(p_y)$	1.49×10^{-2}	4.58×10^{-3}	1.26×10^{-3}	3.30×10^{-4}

$$v_b = \cos(x) \sin(y) \cos(2z)$$

$$w_b = -\cos(x) \cos(y) \sin(2z)$$

$$\mathbf{f} = (0, 0, -18 \cos(x) \cos(y) \sin(2z))$$

$$R = 1, \text{ and } \Omega = \{x, y, z | 0 \leq x \leq \pi, 0 \leq y \leq \pi, 0 \leq z \leq \pi/2\}.$$

We also have the exact solution as:

$$u = \sin(x) \cos(y) \cos(2z)$$

$$v = \cos(x) \sin(y) \cos(2z)$$

$$w = -\cos(x) \cos(y) \sin(2z)$$

$$p = 6 \cos(x) \cos(y) \cos(2z).$$

Table 2 shows our numerical results for this problem.

We can see from the numerical results that we achieved second order accuracy for the velocity in both cases despite the fact that we used a first order approximation for the Laplacian operator near the boundary. The calculation for the pressure is less accurate, which is expected. The number of iterations grows very slightly as the mesh size increases both in the two

Table 2: Numerical results in 3-D case

Grid size	20×20×10	40×40×20	80×80×40	160×160×80
Iterations	13	16	18	19
L^∞ norm of r	9.82×10^{-9}	1.48×10^{-8}	5.18×10^{-8}	8.47×10^{-8}
$e(u)$	9.47×10^{-3}	2.66×10^{-3}	7.07×10^{-4}	1.83×10^{-4}
$e(v)$	9.47×10^{-3}	2.66×10^{-3}	7.07×10^{-4}	1.83×10^{-4}
$e(w)$	1.02×10^{-2}	2.64×10^{-3}	6.66×10^{-4}	1.67×10^{-4}
$e(p_x)$	0.105	5.54×10^{-2}	2.81×10^{-2}	1.41×10^{-2}
$e(p_y)$	0.105	5.54×10^{-2}	3.72×10^{-2}	1.41×10^{-2}
$e(p_z)$	0.202	0.100	6.71×10^{-2}	2.52×10^{-2}

and three dimensional cases. There is no substantial increase of the number of iterations from two dimensions to three dimensions. This makes our method particularly suitable for three dimensional calculations.

One should note that for the conjugate-gradient method to converge in a few iterations, it is very important that relation (13) in section (2) be satisfied. To show the importance of this, we make another calculation with a different discretization of the domain and different choices of the operators. We take the same test problem in two dimensions. This time the two components of the velocity are defined on the same set of grid points defined by $x, y = ih, i = 0, \dots, n$. The pressure p is defined on the same grid as before. The operators are defined as:

$$\begin{aligned}
 (D_x^h u)_{i+\frac{1}{2}, j+\frac{1}{2}} &= \frac{1}{2h} [(u_{i+1, j+1} - u_{i, j+1}) + (u_{i+1, j} - u_{i, j})] \\
 (D_y^h v)_{i+\frac{1}{2}, j+\frac{1}{2}} &= \frac{1}{2h} [(v_{i+1, j+1} - v_{i+1, j}) + (v_{i, j+1} - v_{i, j})] \\
 (\nabla_x^h p)_{i, j} &= \frac{1}{2h} [(p_{i+\frac{1}{2}, j+\frac{1}{2}} - p_{i-\frac{1}{2}, j+\frac{1}{2}}) + (p_{i+\frac{1}{2}, j-\frac{1}{2}} - p_{i-\frac{1}{2}, j-\frac{1}{2}})] \\
 (\nabla_y^h p)_{i, j} &= \frac{1}{2h} [(p_{i+\frac{1}{2}, j+\frac{1}{2}} - p_{i+\frac{1}{2}, j-\frac{1}{2}}) + (p_{i-\frac{1}{2}, j+\frac{1}{2}} - p_{i-\frac{1}{2}, j-\frac{1}{2}})]
 \end{aligned}$$

Table 3: Iterations needed for a different discretization

Grid size	20×10	40×20	80×40	160×80
Iterations	31	45	48	49
L^∞ norm of r	7.98×10^{-8}	9.49×10^{-8}	9.12×10^{-8}	9.25×10^{-8}

and Δ_h by the standard five point approximation to Laplacian. These definitions satisfy (10) (see Stephens et al. (1984)) and (11) but not (13).

Table (3) shows the results of this calculation. We see that it requires about four times the iterations needed for the previous one.

4 Conclusions

We have presented a fast numerical technique for solving the steady-state Stokes equations which requires no artificial conditions for the pressure near the boundary. Our numerical experiments show that the method is of second order accuracy for the velocity. The key idea of the method is to use some consistent difference operators to approximate the Stokes equations and then derive a equation $Ap = b$ for the pressure such that the matrix A is semi-positive definite and very well conditioned on the orthogonal complement of its null space. Therefore it is very efficient to use the standard conjugate-gradient method to solve the pressure equation. We implemented our method on a staggered grid for rectangular (cubic) domains and showed that the conjugate-gradient method converged in a very few iterations even for a very large number of grid points in the three dimensional case. The method is certainly applicable to more general domains as long as we can solve the Laplace equations on those domains.

Acknowledgement

The author would like to thank Professor Alexandre Chorin for many fruitful suggestions and very patient help during the preparation of this paper.

References

- [1] C. R. Anderson, "Derivation and Solution of the Discrete Pressure Equations for the Incompressible Navier-Stokes Equations," Lawrence Berkeley Laboratory Report LBL-26353, 1988.
- [2] A. J. Chorin, *Math. Comp.*, **22** (1968), 745.
- [3] A. J. Chorin, *Math. Comp.*, **23** (1969), 341.
- [4] F. H. Harlow and J. E. Welch, *Physics of Fluids*, **8** (1965), 2182.
- [5] A. B. Stephens, J. B. Bell, J. M. Solomon, and L. B. Hackerman, *J. Comp. Phys.*, **53** (1984), 152.
- [6] J. Strikwerda, *SIAM J. Sci. Stat. Comput.*, **5**(1984), 56.
- [7] P. N. Swarztrauber, *SIAM Review*, **19** (1977), no. 3, 490.

LAWRENCE BERKELEY LABORATORY
UNIVERSITY OF CALIFORNIA
INFORMATION RESOURCES DEPARTMENT
1 CYCLOTRON ROAD
BERKELEY, CALIFORNIA 94720