

Lawrence Berkeley National Laboratory

Recent Work

Title

A study of flow and transport through a fault embedded in fractured rock

Permalink

<https://escholarship.org/uc/item/4fk415zw>

Authors

Salve, Rohit
Hudson, David
Liu, Hui-Hai
[et al.](#)

Publication Date

2003-10-02

A STUDY OF FLOW AND TRANSPORT THROUGH A FAULT EMBEDDED IN FRACTURED ROCK

Rohit Salve¹, David Hudson², Hui-Hai Liu¹, and Joseph S.Y. Wang¹

¹Lawrence Berkeley National Laboratory

²U.S. Geological Survey

Contact: Rohit Salve, 510/486-6416, r_salve@lbl.gov

RESEARCH OBJECTIVES

The objective of this investigation is to study flow and transport through a 20 m vertical section of a fault located in the fractured welded tuff of the Topopah Spring welded tuff unit at Yucca Mountain, Nevada (Figure 1), the proposed site for a high-level nuclear waste geologic repository.

APPROACH

This investigation involved the release of approximately 82,000 liters of water along a horizontal section of the fault, under ponded conditions, over a period of 13 months; and then under reduced fluxes for another 6 months. When quasi-steady-state seepage was observed at the lower end of the test bed, two tracers with different molecular diffusion coefficients were introduced into the ponded water infiltrating the fault. After tracer-laced water had been released into the fault, more tracer-free water was released. As water was released into the fault, changes in moisture content were monitored in the formation, while a large cavity excavated below the test bed was visually inspected for seepage. Water percolating through the fault and into the excavated cavity was continuously monitored with an automated, remotely accessed water collection system.

ACCOMPLISHMENTS

We observed that water (introduced along the fault) followed the fault as the primary vertical flow path, while the adjacent fractured matrix served to move water laterally and vertically. Unlike primary flow paths along the fault, flow was not persistent along the secondary flow paths under similar boundary conditions. The field experiment showed the existence of a capillary barrier and confirmed the dynamic nature of flow through the fault. Further, observations of bromide concentrations in seepage water during the early stages of the experiment, and of bromide and pentafluoride benzoic acid concentrations in the seepage water, indicate the significant influence of matrix diffusion on transport through a fault embedded in fractured, nonwelded rock.

SIGNIFICANCE OF FINDINGS

Field tests involving both flow and transport within a fault under unsaturated conditions are rare. This test has provided insights into mechanisms that come into play when water with tracers is introduced into a fault located in this unsaturated environment. This information is being used to develop conceptual models of flow and transport through Yucca Mountain.

RELATED PUBLICATIONS

- Salve, R., Hudson, D., Liu, H. H. and J. S Y. Wang, Development of a wet plume following liquid release along a fault. Berkeley Lab Report LBNL-52711, Berkeley, California, 2003; Water Resources Research, 2003 (submitted).
- Liu, H. H., R. Salve, J. S Y. Wang , G. S. Bodvarsson, and D. Hudson, Field investigation into unsaturated flow and transport in a fault: Model analysis. Berkeley Lab Report LBNL-52823; Journal of Contaminant Hydrology, 2003 (submitted).
- Salve, R., A passive-discrete water sampler for monitoring seepage. Berkeley Lab Report LBNL-51203, Berkeley, California; Groundwater, 2003 (submitted).

ACKNOWLEDGMENTS

This work was supported by the Director, Office of Civilian Radioactive Waste Management, U.S. Department of Energy, through Memorandum Purchase Order EA9013MC5X between Bechtel SAIC Company, LLC, and the Ernest Orlando Lawrence Berkeley National Laboratory (Berkeley Lab). The support is provided to Berkeley Lab through the U.S. Department of Energy Contract No. DE-AC03-76SF00098.