

# Lawrence Berkeley National Laboratory

## Recent Work

**Title**

A Broad View of Model Validation

**Permalink**


<https://escholarship.org/uc/item/5c5306wb>

**Author**

Tsang, C.F.

**Publication Date**

1989-10-01



# Lawrence Berkeley Laboratory

UNIVERSITY OF CALIFORNIA

## EARTH SCIENCES DIVISION

Presented at the International Symposium on the  
Safety Assessment of Radioactive Repositories,  
Paris, France, October 9-13, 1989, and  
to be published in the Proceedings

### A Broad View of Model Validation

C.-F. Tsang

October 1989



1 LOAN COPY 1  
1 CIRCULATES 1  
1 FOR 2 WEEKS 1

Bldg. 50 Library.  
COPY 2

LBL-28094

## **DISCLAIMER**

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.

## **A Broad View of Model Validation**

*Chin-Fu Tsang*

Earth Sciences Division  
Lawrence Berkeley Laboratory  
1 Cyclotron Road  
Berkeley, California 94720

October 1989

This work was supported by the Director, Office of Energy Research, Office of Basic Energy Sciences, Engineering and Geosciences Division, and by the Director, Office of Civilian Radioactive Waste Management, Office of Systems Integration and Regulation, Licensing and Compliance Division, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Invited Paper, International Symposium on the  
Safety Assessment of Radioactive Waste Repositories,  
Paris, France, October 9-13, 1989

## A BROAD VIEW OF MODEL VALIDATION

*Chin-Fu Tsang*

Earth Sciences Division  
Lawrence Berkeley Laboratory  
1 Cyclotron Road  
Berkeley, California 94720

### ABSTRACT

The safety assessment of a nuclear waste repository requires the use of models. Such models need to be validated to ensure, as much as possible, that they are a good representation of the actual processes occurring in the real system. In this paper we attempt to take a broad view by reviewing step by step the modeling process and bringing out the need to validating every step of this process. Thus model validation includes not only comparison of modeling results with data from selected experiments, but also evaluation of procedures for the construction of conceptual models and calculational models as well as methodologies for studying data and parameter correlation. The need for advancing basic scientific knowledge in related fields, for multiple assessment groups, and for presenting our modeling efforts in open literature to public scrutiny is also emphasized.

## Introduction

The safety assessment of a nuclear waste geologic repository demands much more of the scientists and engineers and their modeling results than the safety evaluation of any civil constructions such as dams, or resource evaluation of petroleum or geothermal reservoirs. The extra demands are mainly due to two factors:

- (a) The safety assessment usually involves the estimation of low probability (low concentration) of radionuclides transported over kilometers and extrapolated thousands of years into the future.
- (b) Data characterizing the rock mass at the repository site are necessarily sparse, since too many data-collecting boreholes may adversely impact the integrity of the rock mass. Thus, there may be much uncertainties in our knowledge of the geometric structures, boundary conditions and relevant processes present at the site.

There is much interest and concern in all the countries with a nuclear waste management program on the question of model validity. A number of recent international cooperative efforts, e.g., Hydrocoin (1987), Intraval (Andersson, 1989), and others, have been devoted to the validation of models. Model validation was also extensively discussed in recent and upcoming symposia, such as GEOVAL87 (1987) and GEOVAL90 which will be held in April 1990. Some general comments on model validation were given by Tsang (1987). Additionally, there is a wealth of literature on validation in the field of system engineering and operations research which may be useful for our consideration. Examples include Balci (1988, 1989), Balci and Sargent (1984), Gass (1983), Gass and Thompson (1980), Oren (1981), Sargent (1984, 1988), Schruben (1980) and Zeigler (1976).

The present paper gives a broad view of model validation specifically for the safety assessment of a nuclear waste repository. We shall begin by giving a few definitions to establish common understanding of several key terms for the subsequent part of the paper. Then we shall describe a detailed step-by-step process for model predictions. Validation is not narrowly involved in only one step but is needed broadly for all the steps of the modeling process. Thus the section following will discuss possible validation issues associated with each step of the modeling process. Three miscellaneous, through important, remarks conclude the paper.

## A Few Definitions and Comments

There have been a number of definitions on validation. Schlesinger et al. (1979) defined it as meaning "substantiation that a computerized model within its domain of applicability possesses a satisfactory range of accuracy consistent with the intended application of the model." The International Atomic Energy Agency (IAEA, 1982) defines validation as follows: "A conceptual model and the computer code derived from it are validated when it is confirmed that the conceptual model and the computer code provide a good representation of the actual processes occurring in the real system."

In the context of this paper we shall understand model as the combination of conceptual model and computer code with the relevant field and laboratory data and information. Only with the combination of all these elements is it possible to perform modeling studies whose results may be used as a representation of the actual processes occurring in the real system.

The computer code is a computer program that solves a given set of equations with given inputs by numerical manipulations. Thus computer codes should be certified, which means that the code is properly verified and properly documented. In other words, it is mathematically correct in the formulation and solution, and properly documented on its function, accuracy, required discretization and ranges of applicability. However, one should not be talking about code validation, since validation questions the appropriateness of the mathematical equations and input data and conditions, which are assumed and taken for granted in a code.

Model calibration is the process by which certain unknown parameters to be used in a code are determined by comparing modeling results with part of the observed data, which the model is required to simulate. For safety assessment of nuclear waste repositories, the models are expected to predict data for thousands of years into the future, and calibration is done to estimate parameters with short-term data. In this paper we assume this kind of calibration to be part of site characterization activities, where tests and analyses (which may well include modeling calculations) are done to determine the needed model parameters for assessment of repository safety for thousands of years.

By conceptual model we mean two main components: structure and processes. Structure refers to the geometric structure of the system, such as stratigraphy, faults, heterogeneity, fracture density and lengths, and other geometric and geologic characteristics. Processes are physical and chemical phenomena such as buoyancy flow, colloidal transport, matrix diffusion, and dissolution and precipitation. Structure is site-specific and scale-dependent and usually appears in modeling study as calculational mesh designs and input data. Processes, on the other hand, are usually described by mathematical equations being solved in a computer code and can often be studied in the laboratory. In practice, there are often cases where processes and structure are intimately coupled.

Based on the above discussion it may be apparent that almost by definition one can never have a validated computer model without further qualifying phrases. In our view one can say that a model, including the conceptualization and the code, is validated with respect to (a) a process or (b) a site-specific system. For (a), a process is first identified (e.g., buoyancy convective flow) and then conceptualized (e.g., as temperature-dependent density and viscosity) and coding is performed on this conceptualization. The model, composing of conceptualization and code, is then applied to a buoyancy experiment and its results compared with measurements. Then we can say that the model is validated with respect to this specific process. Model validation with respect to various processes should be a significant element in any national nuclear waste management program because it establishes our capability in predicting the effects of these processes occurring at a site. This is indeed the subject of a number of current international projects.

For (b), a site-specific system may be composed of a number of processes and structures, which form the building blocks of the system. Of course it is an important and not-so-easy

problem to identify the building blocks. Once the building blocks are identified, a model or group of models may be used to simulate the system and results can be compared with field observations. If successful, the group of models is said to be validated with respect to this particular site, within a range of applications determined by the range of field observations studied.

Hence, there is no such thing as a validated model in the generic sense. However we can say that "a model is validated with respect to a given process," or that "a model or group of models are validated with respect for a given site." Ranges of applicability should be stated with these statements. Though model validation with respect to processes is an important subject currently under study by many groups, in what follows we shall only address model validation with respect to a given site, since this is more relevant to the definitions of Schlesinger et al. (1979) and IAEA (1982).

### **The Modeling Process**

In this section we shall itemize and discuss the steps in a site-specific modeling exercise. We call this a modeling process, which is distinct from the physical and chemical processes referred to in the last section.

The first step in the modeling process (see Table 1) is review and evaluation of available data. This is more than searching the data base to obtain numbers that we need for a given modeling exercise. A good modeler studies the complete data base to obtain as good as possible an overall picture of the site and relevant processes occurring there. Of particular interest is an evaluation of data correlation. Data correlation is of two types. The first is the spatial or temporal correlation. This is often studied by statistical methods. The second which may be of more importance is the parameter correlation, which limits the range of values one parameter can have because of a chosen value of another parameter. For example, Wang and Narasimhan (1989) pointed out that there is such a correlation between the saturated conductivity and air-entry pressure (or radius) for the unsaturated zone at the Yucca Mountain site. Earlier studies have coupled too large a saturated conductivity value with too small an air-entry radius value as inputs to a modeling calculation, and such inputs are unphysical.

The second step is the development of a conceptual model and potential scenarios. This is to abstract the essence of the data base to construct the structure of the geometric model and to identify relevant physical and chemical processes involved in the system. Sometimes the data may be uncertain or even internally inconsistent and some subjective judgement will be required. Possible scenarios in time also have to be identified and evaluated according to their probabilities of occurrence.

The establishment of performance criteria is the third step. This is related to "domain of applicability" or "range of application" in the definition of validation according to Schlesinger et al. (1979). Performance criteria are the quantities of interest that the model is asked to predict. There is the possibility that a performance criterion could be defined in such a way that the quantity of interest can never be predicted with sufficient accuracy because of intrinsic uncertainties in data. For example, in a highly heterogeneous fractured porous medium, it is probably impossible to predict tracer concentration at a particular point in space and time.



Thus one has to modify the performance criterion to something more plausible yet still acceptable for the problem at hand. In the same example, instead of requiring the prediction of a point value of tracer concentration, we can ask for an integrated tracer concentration over a period of time and region of space (Tsang, 1989). In safety assessment of nuclear waste repository, perhaps that is all that is needed.

The fourth step of the modeling process is the construction of calculational models and the determination of the associated lumped parameters. Conceptual models are usually complex and are by definition three-dimensional so that simplification is always needed before modeling can proceed. We call these simplified models the calculational models. Often it is convenient that different simplification procedures are used for the calculation of different quantities of interest. Thus a very simple calculational model is perhaps needed for thermal field calculation, while finer features need to be added to calculate tracer transport. By lumped parameters we mean not only those averaged over space blocks, but also those combining several more elementary parameters. For spatially lumped parameters, there needs to be much consideration how they should be defined especially in the case of strongly heterogeneous systems. I believe it is still an open question how to define permeability and dispersivity for such media. An example of a lumped parameter incorporating elementary parameters is the relative permeability function for an unsaturated fractured porous medium, where it is shown (Pruess et al., 1989) that an equivalent porous medium with a specialized relative permeability function is adequate to calculate flow in the system, instead of the detailed parameters associated with liquid and gas flows in fracture networks and matrix blocks. The choice of calculational models and their associated lumped parameters is strongly dependent on the computer codes that are available. For example, if the code is able only to perform two-dimensional calculations, the calculational model has to be two-dimensional.

After the decision on calculational models, calculations can proceed. Computer runs are made to yield tables of results or graphical outputs. There is a need to study the sensitivity of these results on parameter or data uncertainties. Many times stochastic modeling techniques have to be used and results may then be given as probability distribution functions. If ergodicity condition can be assumed, spatially averaged quantities can perhaps be predicted.

The final step is to evaluate the calculational results. For the safety assessment of nuclear waste repositories, these results have to be evaluated according to the performance criteria. Uncertainties in these results have to be established. These uncertainties may arise not only from data uncertainties, but also from every step of the modeling process discussed above. For example, a particular choice of calculational model may introduce considerable uncertainties. One could ask the question, how well can a two-dimensional model simulate a three-dimensional model? The outcome of such evaluations of results would be to redo the modeling process to better determine or reduce uncertainties, or to define further data needs for measurements and site investigations.

### **The Broad View of Model Validation**

Since the goal of model validation is to ensure that the modeling results provide a good representation of the actual processes occurring in the real system (IAEA, 1982), validation should be applied to every step of the modeling process as discussed above.

Thus for the first step of data review and evaluation the methodologies of evaluation of data (spatial or temporal) correlation should be studied, understood and validated. The process of evaluating parameter correlation has to be defined and properly carried out. The latter depends much on the scientific experience and knowledge of the personnel involved in the work and in the peer review process.

Construction of the conceptual model and evaluation of various possible scenarios requires much expertise and practice. One way to provide some confidence in this process is to involve more than one group of hydrogeologists, geochemists, geophysicists and geologists to perform this step. Cross-checking of the final results and understanding the differences between the outputs from the different groups may be extremely valuable.

The step of simplification of the complex conceptual models to calculational models and their associated lumped parameters has been often overlooked in model validation. It would be useful to put this on a proper scientific basis. Each modeling team should evaluate the uncertainties involved by alternative simplifications to arrive at alternative calculational models. Sensitivity of final results on the alternative models as well as on parameter uncertainties should also be studied.

Currently the most common validation approach used by many workers in this field involves the following. First a field or laboratory experiment is selected. Then the experimental conditions are specified, which include both the initial conditions and boundary conditions. Often not all boundary conditions are known. Then model computations are made and predictions are checked against field or laboratory data. Sargent (1984) presented a list of validation methods which includes other methods in addition to this approach:

- (1) *Event validity*. This represents an initial validation test of a qualitative nature, in which events or occurrences of the simulation model are compared with those of the real system.
- (2) *Face validity*. This may be considered as part of peer review, involving asking people knowledgeable of the field whether the model is reasonable. The model flowchart may be checked for its correctness, and model input-output relationship may be checked for its reasonableness.
- (3) *Traces*. The behavior of the different elements or entities of a model are traced or followed through the numerical model to determine if the logic and the program are correct and if the necessary accuracy is maintained.
- (4) *Historical methods*. A historical method may consist of three steps: (a) examining the model's assumptions on theory, observations, general knowledge and intuition; (b) validating each of the model's assumptions, where possible, by empirically testing them; and (c) comparing the input-output relationship of the model to field behavior.
- (5) *Internal validity*. This is particularly important in the validation of stochastic models or models with statistical inputs. Several realizations of a stochastic model are used to determine the amount of stochastic variability in the model. A high degree of variability may cause the model's results to be questionable and may require a redefinition of appropriate quantity of interest, i.e., appropriate

performance measure.

- (6) *Historical data validation.* If historical data exist for a given site, part of the data may be used to construct and calibrate the model and the remaining data are used to check against calculated results from the model.
- (7) *Predictive validation.* The model is used to provide predictions for a given field or laboratory test and further measurements are made to check these predictions.
- (8) *Turing tests.* This may also be considered a part of the peer review and is particularly important for stochastic models. Here people knowledgeable about the field are asked if they can discriminate between model output and field observations.

It is of interest to note that historical data validation and predictive validation are only two out of a number of validation methods. We should apply all the above list of validation methods, wherever possible, to all steps of the modeling process. For example, the methods of traces and face validity have not been much used up to now in our field. Often we depend on model developers and model users to ensure the correctness of model logic and accuracy. Sometimes this is not adequate.

### **Need for Multiple Assessment Groups**

As mentioned in the last section, some of the modeling steps, such as the design of conceptual models and the construction of calculational models, will be difficult to validate in a non-subjective way, since their validation depends on the depth and breadth of scientific knowledge of the modelers involved. One approach for validation is the use of multiple assessment groups. Two or more groups studying the same geologic system independently may come up with different scenarios, different conceptual models and different simplifications in the construction of calculational models. Discussions among these groups will clarify the reasons of the differences and stimulate new considerations and better understanding of the system to be modeled. Thus, such interactions not only cross-verify each others' work, but also promote cross-fertilization to arrive at a more "correct" solution. We may define this multiple assessment group approach as one of the possible validation methods. Modeling results arrived at through the study and interaction of independent groups have a better chance of being correct and will probably have credibility among the scientific community and the public.

Multiple assessment groups do not necessarily imply multiple requirements of budgetary and personnel resources for the national waste management program. First of all, the repository safety assessment modeling studies represent only a small component of the national program. Secondly if budgetary and personnel resources are really a problem, the multiple-group approach can be applied only to the early steps of modeling where usual validation methods cannot be used easily. The later steps of carrying out detailed computations and presentation of results can be performed by one major group. International cooperation will also be helpful.

The multiple assessment group approach is very much needed and cannot be replaced by the expert peer review approach. Usually experts are requested to serve on a limited time period to study a problem, and their comments may focus on the technical procedures and

methodologies used by the modelers involved. More likely than not they do not have time to study the primary site-specific data and come up with an independent view. Thus in most cases it is hard for them to become site-specific experts. On the other hand, the multiple assessment group approach allows each group to study and consider primary data in detail and develop the model unbiased by the views of other groups. Then interaction and discussions among the groups will be in depth with fruitful results. Some experiences of this nature may be found in the international cooperative projects such as Hydrocoin and IntraVal.

### **Need for Basic Research and Public Scrutiny**

If one examines the modeling steps and various validation methods as discussed above, one quickly comes to the realization that how well modeling results can predict behavior of real systems depends very much on the state of our knowledge of various physical and chemical processes that take place in complex geological systems which can be characterized only in a limited way. It also depends on the state of field testing technologies and analysis methodologies. We should advance our state of knowledge and methodologies by short-term laboratory and field experiments and long-term natural analog studies. Without proper understanding of physical and chemical processes and the system structure involved there could be no validation. One can say that a thorough understanding represents the major part of validation. Thus a percentage of our nuclear waste management effort should be devoted to such basic studies to add to the general geoscience state of the knowledge and methodologies.

One of the best ways to draw on the reservoir of available knowledge is not only by the various validation methods indicated in the last section but also by having our modeling work published in the open literature. This should be done in parallel to the usual peer review process. Open-literature publications receive the benefits of anonymous technical review and public scrutiny. Sometimes an error may be pointed out by scientists from a different but related field of research. Positively, a study whose results are in the open literature examined by and maybe used by the general scientific community over a number of years has a much better chance of being correct. Eventually the decision if a model is valid is not made only by those doing the modeling studies. The model is valid in a given case if the modelers have done the studies correctly and has convinced other knowledgeable persons of this. Thus in the end it is the general scientific community that will decide the validity of models and whether they are correctly used in the right context.

### **Acknowledgements**

The paper contains ideas that have developed over the last few years in discussions with a large number of colleagues in the U.S., Europe and Japan. I have benefited greatly from presentations by participants of the INTRAVAL project at various meetings. In particular I would like to acknowledge the inspiration of Drs. Kjell Andersson and Johan Andersson of the Secretariat of the INTRAVAL project and the inputs from members of the Validation Overview and Integration Committee, Drs. Jesus Carrera, Neil Chapman, David Hodgkinson, Ivars Neretnieks, Shlomo Neuman, and Tom Nicholson, whose reactions and discussions have caused me much trouble but have helped me to crystallize many ideas. Acknowledgements are also due to Dr. Don Alexander and others of the U.S. Department of Energy, Office of Civilian Radioactive Waste Management for their continual support and encouragement. The

work is supported jointly by Director, Office of Energy Research, Office of Basic Energy Sciences, Engineering and Geosciences Division, and by the Director, Office of Civilian Radioactive Waste Management, Office of Systems Integration and Regulations, Licensing and Compliance Division, through the U.S. Department of Energy Contract No. DE-AC03-76SF00098.

## References

- Balci, O.: "Credibility Assessment of Simulation Results: The State of the Art, Methodology and Validation," *Simulation Series*, 19, No. 1, The Society for Computer Simulation, pp. 19-25, 1988.
- Balci, O.: "How to Assess the Acceptability and Credibility of Simulation Results," *Proceedings of the 1989 Winter Simulation Conference*, edited by E. MacNair, K. Musselman, and P. Heidelberger, Washington, DC, 1989.
- Balci, O., and R. G. Sargent: "A Bibliography on the Credibility, Assessment and Validation of Simulation and Mathematical Models," *Simuletter*, 15, No. 3, pp. 15-27, 1984a.
- Gass, S. I.: "Decision-Aiding Models: Validation, Assessment, and Related Issues for Policy Analysis," *Operations Research*, 31, 4, pp. 601-663, 1983.
- Gass, S. I. and B. W. Thompson: "Guidelines for Model Evaluation: An Abridged Version of the U.S. General Accounting Office Exposure Draft," *Operations Research*, 28, 2, pp. 431-479, 1980.
- GEOVAL87: "Proceedings of Symposium on Verification and Validation of Geosphere Performance Assessment Models," Stockholm, Sweden, April 7-9, 1987, Published by Swedish Nuclear Power Inspectorate, Stockholm, Sweden, 1987.
- HYDROCOIN: "Hydrocoin Progress Report," Swedish Nuclear Power Inspectorate, Stockholm, Sweden; also, Grundfelt, B., *The Hydrocoin Project - Overview and Results from Level One*, Proceedings of International GEOVAL-87 Symposium, Stockholm, Sweden, April 7-9, 1987.
- Oren, T.: "Concepts and Criteria to Assess Acceptability of Simulation Studies," *A Frame of Reference*, *Communication of the ACM*, 24, 4, pp. 180-189, 1981.
- Pruess, K., J. S. Y. Wang, and Y. W. Tsang: "On Thermohydrological conditions New High-Level Nuclear Wastes Emplaced in Partially Saturated Fractured Tuff, Part 2. Effective Continuum Approximation," *Water Resources Research*, to be published, 1989.
- Sargent, R. G.: "Simulation Model Validation, Simulation and Model-Based Methodologies," *An Integrative View*, edited by Oren, et al., Springer-Verlag, 1984.
- Sargent, R. G.: "A Tutorial on Validation and Verification of Simulation Models," *Proceedings of 1988 Winter Simulation Conference*, edited by M. Abrams, P. Haigh, and J. Comfort, pp. 33-39, 1988.

Schlesinger, et al.: "Terminology for Model Credibility," *Simulation*, 32, 3, pp. 103-104, 1979.

Schruben, L. W.: "Establishing the Credibility of Simulations," *The Art and the Science*, Prentice-Hall, 1980.

Tsang, C. F.: "A New Approach to Tracer Transport Analysis: From Fracture Systems to Strongly Heterogeneous Porous Media," Keynote address presented at the International Workshop on "Appropriate Methodologies for Development and Management of Groundwater Resources in Developing Countries," Hyderabad, India, February 28-March 4, 1989.

Wang, J. S. Y., and T. N. Narasimhan: "Processes, Mechanisms, Parameters and Modeling Approaches for Partially Saturated Flow in Soil and Rock Media," Lawrence Berkeley Laboratory Report, LBL-26224, 1989.

Zeigler, B. P.: "Theory of Modelling and Simulation," John Wiley and Sons, Inc., New York, 1976.

**Table 1. Steps of the modeling process and their validation.**

<b>The Modeling Process</b>	<b>Examples of Issues Requiring Validation</b>
1. Data Review and Evaluation	Spatial correlation and parameter correlation.
2. Conceptual Model and Scenarios	Accuracy of conceptual model and probability of scenarios.
3. Performance Criteria	Appropriate choice of quantities of interest.
4. Calculational Models and Lumped Parameters	Simplification procedures and determination of lumped parameters from data.
5. Modeling Calculations and Sensitivity Studies	Uncertainties to data and to calculational model choices.
6. Results Evaluation and Application to Safety Assessment	Application of results to performance criteria.

LAWRENCE BERKELEY LABORATORY  
TECHNICAL INFORMATION DEPARTMENT  
1 CYCLOTRON ROAD  
BERKELEY, CALIFORNIA 94720