

Lawrence Berkeley National Laboratory

Recent Work

Title

MODES OF ACCELERATION OF IONS IN A THREE-DEE CYCLOTRON

Permalink

<https://escholarship.org/uc/item/6d02z466>

Authors

Jakobson, Mark
Heusinkveld, Myron
Ruby, Lawrence.

Publication Date

1956-04-04

UNIVERSITY OF
CALIFORNIA

*Radiation
Laboratory*

TWO-WEEK LOAN COPY

*This is a Library Circulating Copy
which may be borrowed for two weeks.
For a personal retention copy, call
Tech. Info. Division, Ext. 5545*

BERKELEY, CALIFORNIA

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.

UNIVERSITY OF CALIFORNIA

Radiation Laboratory
Berkeley, California

Contract No. W-7405-eng-48

MODES OF ACCELERATION OF IONS IN A THREE-DEE CYCLOTRON

Mark Jakobson, Myron Heusinkveld, and Lawrence Ruby

April 4, 1956

MODES OF ACCELERATION OF IONS IN A THREE-DEE CYCLOTRON

Mark Jakobson, Myron Heusinkveld, and Lawrence Ruby

Radiation Laboratory
University of California
Berkeley, California

April 4, 1956

ABSTRACT

Formulas are presented for the maximum energy gain per turn of ions in a fixed-frequency cyclotron with three identical dees symmetrically spaced. Calculations have been made for dees of general angle θ and specific angles 60° , 90° , and 120° . Dee excitations in which the dee voltages are all in phase or phased at 120° with respect to each other have been considered. The type of ions that can be accelerated is dependent upon the mode of excitation. In a 60° three-dee cyclotron with variable rf phasing protons, deuterons, and tritons can be accelerated in the nonrelativistic energy region at substantially the same magnetic field and oscillator frequency. A 20-inch cyclotron of this type has been operated successfully.

MODES OF ACCELERATION OF IONS IN A THREE-DEE CYCLOTRON

Mark Jakobson,^{*} Myron Heusinkveld,[†] and Lawrence Ruby

Radiation Laboratory
University of California
Berkeley, California

April 4, 1956

INTRODUCTION

It is possible for a symmetrical three-dee cyclotron to accelerate ions of differing q/m ratios below relativistic velocities without a change in the frequency of the electrical power supplied to the dees or the value of the magnetic field. This is demonstrated in the following article by calculating the energy gain per turn for various ions in a cyclotron with three identical dees of arbitrary widths. For these calculations it has been assumed that a step-function voltage change occurs at each edge of the dees.

^{*} Now at the University of Montana, Missoula, Montana

[†] Now at the University of California Radiation Laboratory, Livermore, California.

THEORY¹

Consider a three-dee cyclotron as schematically indicated in Fig. 1. The three dees of equal angles are labeled A, B, and C. The angular extent of each dee is θ . For the initial calculations the dee voltages are of equal amplitudes. The term "mode of acceleration" or, more simply, "mode" is used to describe the differing types of dee excitation, depending upon the relative phases of the dee voltages. This is in keeping with a previous publication.²

Calculations have been restricted to the cases where (a) the three dee voltages are all in phase, called the inphase mode; (b) the voltages are phased 120° with respect to each other, with the phase of B dee following that of A dee, and the phase of C dee following that of B dee, designated the ABC mode; and (c) the voltages are phased 120° from each other, but in the reverse sequence, namely ACB. A phasing of type (b) will be considered first in analyzing the possibilities for ion acceleration.

The dee voltages for this ABC mode can be expressed:

$$\begin{aligned} V_A &= V e^{i\omega t}, \\ V_B &= V e^{i(\omega t - 2\pi/3)}, \\ V_C &= V e^{i(\omega t - 4\pi/3)}. \end{aligned} \quad (1)$$

Here V is the amplitude of the dee voltages with respect to ground, ω is the angular frequency of the electrical power supplied to the dees, and t is time.

¹ It has been brought to the authors' attention that Professor Edwin M. McMillan has obtained similar results as a special case of a general multidee cyclotron calculation. This general solution is to appear in the forthcoming third volume of Experimental Nuclear Physics (published by Wiley).

² M. Jakobson and F. H. Schmidt, Phys. Rev. 93, 303 (1954).

As an ion of charge q and mass m moves along its quasi-circular path in the cyclotron, it completes a revolution in a time $T = \frac{2\pi m}{qB} = \frac{2\pi}{\Omega}$, where Ω is the ion's angular frequency.

An ion that passes through the center of A dee at a time t_0 will cross the edge of A dee at a time

$$t_1 = t_0 + \frac{\theta}{2\Omega} \quad (2)$$

It will enter B dee at a time

$$t_2 = t_0 + \frac{2\pi}{3\Omega} - \frac{\theta}{2\Omega} \quad (3)$$

The times of crossing of the other dee edges follow similarly. The energy received by the ion in crossing one dee edge is the product of the charge on the ion and the voltage on the dee at that instant. The energy received by the ion in going around the cyclotron once is the sum of the energy contributions at the six edges. Carrying out this sum, we have the energy gain per turn, ΔW , given by

$$\Delta W = 2qV \sin\left(\frac{\theta\omega}{2\Omega}\right) \operatorname{Re} \left[e^{i\phi_0} \sum_{r=0}^2 e^{irf} \right], \quad (4)$$

where $f = \frac{2\pi}{3} \left(\frac{\omega}{\Omega} - 1 \right)$; ϕ_0 is the initial phase angle ωt_0 of the ion with respect to the dee voltage.

After S turns the phase angle becomes

$$\phi = \phi_0 + 2\pi S \left(\frac{\omega}{\Omega} - 1 \right).$$

The term $\sin \frac{\theta\omega}{2\Omega}$ indicates the dependence of the energy gain per turn on the angular extent of the dees. The summation term expresses the dependence of the energy gain per turn on the 120° phasing of the similar dees. The term $e^{i\phi_0}$ indicates the dependence on the initial phase of the ion. Maximum energy gain occurs when the ion is at the center of any dee when the instantaneous voltage on that dee is zero. The gain drops to zero as the rf phase varies to $\pm \pi/2$, corresponding to $\pm \frac{\Omega\pi}{\omega}$ angular displacement of the ion from the center of the dee when the instantaneous voltage is zero. The angular extent of each ion bunch in the cyclotron is then $\frac{\Omega\pi}{\omega}$. Other factors, such as field fall-off with radius, would limit the angle to values less than this. The number of ion

bunches present per ion cycle is $\frac{\omega}{\Omega}$. The total energy gain for the S turns is

$$W = 2 qV \sin\left(\frac{\theta\omega}{2\Omega}\right) \operatorname{Re} \left[\sum_{r=0}^{3S-1} e^{i\phi} e^{irf} \right] \quad (5)$$

If, after the S turns, the ion reaches the center of A dee at an rf phase identical with that at which the energy summation was begun, the series can be terminated to give a unique value for the energy gain per revolution. If no such repeat interval exists, the series does not terminate and the average energy gain per turn approaches zero. If the ion does reach the center of the first dee at an rf phase identical to that at which the summation was begun, then $\phi - \phi_0 = 2\pi n$. However, not only must this repeat interval exist, but by inspection, the summation of Eq. (5) will be zero unless the series terminates at $S = 1$, which has the physical meaning that the ion makes one revolution in an integral number of rf cycles. In this case the summation is

$$e^{i\phi_0} \sum_{r=0}^2 e^{irf} = 3e^{i\phi_0} \quad (6)$$

and the quantity f is restricted to the value $f = 2\pi n$. The energy gain per revolution becomes

$$\Delta W = 6qV \sin\left(\frac{\omega}{\Omega} \frac{\theta}{2}\right) \cos \phi_0 \quad (7)$$

for those ions satisfying the equation $f = \frac{2\pi}{3} \left(\frac{\omega}{\Omega} - 1\right) = 2\pi n$, n an integer. The acceptable ratios $\frac{\omega}{\Omega}$ are thus found to be $\frac{\omega}{\Omega} = 3n + 1$ for this mode with the ions traveling in the ABC dee sequence.

For a given magnetic field, positive ions will circulate in one direction in the cyclotron and negative ions in the other, so that a given phase sequence ABC will be in the direction of rotation of the positive ions but opposite that of the negative ions. Consequently, the foregoing analysis is valid for positive ions when the rf phase sequence is ABC, and for negative ions when the phase sequence is ACB. The quantity n is positive for positive ions and negative for negative ions.

The geometric factor $\sin \frac{\omega}{\Omega} \frac{\theta}{2}$ will, in addition to the requirement $\frac{\omega}{\Omega} = 3n + 1$, further limit the types of ions that may be accelerated. It is a modulating factor for energy gain, which may be zero for a given dee angular width for some type of ion that would otherwise be accelerated.

For the case in which the ion travels in a direction opposite the previous phase sequence the foregoing analysis still holds, but with the redefinition of the quantity f :

$$f = \left(\frac{\omega}{\Omega} + 1 \right) \frac{2\pi}{3}.$$

Using the requirement that $f = 2\pi n$, we find that the permissible values of $\frac{\omega}{\Omega}$ are

$$\frac{\omega}{\Omega} = 3n + 2,$$

where n may take integral values including zero. This is valid for positive ions when the phase sequence is ACB or for negative ions when the sequence is ABC, using the convention established earlier that a positive ion passes through the A, B, and C dees in consecutive order. The energy gain per revolution is the same as for the ABC mode and is given by Eq. (7).

For the case in which the three dees are excited in phase, the quantity f becomes $f = \frac{\omega}{\Omega} \frac{2\pi}{3}$, and the types of ions accelerated are determined by the relation $\frac{\omega}{\Omega} = 3n$. In this case, except for direction of rotation, it is immaterial whether the ions are positive or negative. The energy gain per revolution is again that of Eq. (7).

RESULTS AND DISCUSSION

Table I gives the results of this analysis in tabular form, with numerical values computed for the maximum energy gain per revolution for 60° , 90° , and 120° dees. For dees of other angular widths or dees in which the fringing fields are included, the same $\frac{\omega}{\Omega}$ ratios will give the ions eligible for acceleration, but with other values of energy gain per revolution, including zero in particular cases, as indicated by the θ° column. Negative values of $\frac{\omega}{\Omega}$ indicate negative ions and positive values of $\frac{\omega}{\Omega}$ indicate positive ions.

Table I

Energy gain per turn for various ions in a three-dee cyclotron				
Dee Angle	Mode	Ions accelerated ω/Ω	Maximum energy gain per turn	
			n even	n odd
60°	ABC	3n + 1	3 qV	3 $\sqrt{3}$ qV
	ACB	3n + 2	3 $\sqrt{3}$ qV	3 qV
	Inphase	3n except 6n	6 qV	6 qV
90°	ABC	3n + 1 except 4n	3 $\sqrt{2}$ qV	6 qV
	ACB	3n + 2 except 4n	6 qV	3 $\sqrt{2}$ qV
	Inphase	3n except 4n	3 / 3qV	"
120°	ABC	3n + 1	3 $\sqrt{3}$ qV	3 $\sqrt{3}$ qV
	ACB	3n + 2	"	"
	Inphase	none	none	none
θ	ABC	3n + 1	6qV sin (3n + 1) $\frac{\theta}{2}$	
	ACB	3n + 2	6qV sin (3n + 2) $\frac{\theta}{2}$	
	Inphase	3n	6qV sin 3n $\frac{\theta}{2}$	

ω = rf angular frequency

Ω = ion frequency = $\frac{qB}{m}$

n = integer

Table II indicates the ions of hydrogen, deuterium, tritium, and helium that can be accelerated in the three modes of a three-dee cyclotron with 60° dees and rf frequency,

$$\omega = \Omega_{\text{proton}}$$

These calculations have been made for conditions of exact balance of amplitudes of the voltages and exact phase conditions. In practice these conditions are not ordinarily met; slight unbalances in amplitudes or deviations in phase may occur. However, any arbitrary voltage distribution among the three dees (either as to amplitude or as to phase) may be expressed as the sum of the three symmetrical components as analyzed earlier--the ABC mode, the ACB mode, and the inphase mode (termed in Reference 3 the forward mode, reverse mode, and neutral mode).

If the dee voltages are nearly balanced in one of the phase sequences, then the amplitudes of the other two components will be small. Since, to a first approximation, the effects of these voltages on accelerating ions are linear, each component can be considered separately, and the effect of the unbalanced dee voltages can be found by adding the separate effects of each component. It is observed from the formulas for different modes of acceleration that no ion can be accelerated by more than one of the three components, for a given magnetic field and electrical frequency.

These latter results are significant in that under identical operating conditions several different types of ions may be accelerated, either intentionally or as contamination products. For example, if the cyclotron is driven in phase sequence ABC to accelerate H^+ in its lowest mode ($\omega = \Omega$), then it will also accelerate He^{4+} and N^{14++} at the same time. In addition, if the voltages on the dees are unbalanced so that the ACB and inphase components are also present, then many other ions can be accelerated simultaneously. An ion with a nonintegral ratio of ω/Ω , however, such as He^{3++} , cannot be accelerated under these conditions of operation, but can be accelerated only if the magnetic field or the electrical frequency of the cyclotron is changed. Since submultiples of ω/Ω are excluded, if the cyclotron is adjusted to accelerate H_2^+ or D^+ in the lowest mode, then H^+ cannot be accelerated.

Table II

Hydrogen, deuterium, tritium, and helium ions that can be accelerated in a three-dee cyclotron with 60° dees with $\omega = \Omega_{\text{Proton}}$

Mode	Ion	Energy gain per turn	Energy at radius R	Relative threshold voltage
ABC	H^+	$3qV$	W	V_0
"	D_2^+	$3\sqrt{3}qV$	$\frac{W}{4}$	$\frac{V_0}{\sqrt{3}}$
"	He^+	"	"	"
"	D^-	"	$\frac{W}{2}$	"
ACB	H_2^+	"	"	"
"	D^+	"	"	"
"	He^{++}	"	W	"
"	H^-	$3qV$	W	V_0
Inphase	T^\pm	$6qV$	$W/3$	$\frac{V_0}{2}$

In practice the voltage will not change in a step-function manner at the dee edges, but will change gradually over a distance comparable to the vertical aperture of the dees. When this fringing distance is comparable to the distance that an ion travels in an rf cycle--which will be the case for modes of operation where ω/Ω is large--the ion will gain very little energy in crossing any of the dee edges, and there will be no significant acceleration of these ions relative to those of lower ω/Ω ratios.

In the foregoing analysis it has been assumed that the magnetic field is constant as a function of radius, resulting in a constant value of the ion frequency Ω . In order to focus the beam, however, the magnetic field ordinarily is decreased with increasing radius, resulting in a lowering of the ion frequency as the orbit of the ion expands. For an ion that is in resonance at the center of the cyclotron the phase angle ϕ is no longer constant but varies as the ion moves outward. The permissible limits of ϕ are $\pm 90^\circ$; outside these limits the ion will lose energy to the electric field. Since the total phase shift ϕ with respect to the electrical frequency is the sum of the increments per ion revolution, a certain threshold dee voltage is required to limit the number of revolutions necessary to obtain the desired energy with the phase angle ϕ within the limits given. The last column of Table II indicates the relative threshold voltages for various ions in a cyclotron with three 60° dees.

CONCLUSION

A three-dee three-phase 20-inch cyclotron with 60° dees has been constructed and operated successfully.^{3, 4} Stable operation was maintained with 6 ma of 1-Mev protons accelerated in the ABC mode. From programmed orbits the gain in energy per turn was measured to be 2.5 qV. The discrepancy between this value and the calculated value of 3 qV is probably due to the fringing electric fields at the dee edges. Grounded dummy dees were not used. If the phase sequence was changed from ABC to ACB, 6.5 ma of 0.5 Mev deuterons were obtained. With helium ions, in the ACB mode, 1.5 ma of 1-Mev alpha particles was obtained. The measured energy gain per turn for He^{4++} and D_2^+ ions in this mode was approximately 5 qV.

We thank Professor R. L. Thornton for his kind interest and assistance. This paper was a part of the Three-dee Three-phase Cyclotron Development under his supervision.

This work was done under the auspices of the U. S. Atomic Energy Commission.

³ Ruby, Heusinkveld, Jakobson, Smith, and Wright, Rev. Sci. Instr. (In Press)

⁴ B. H. Smith and K. R. Mackenzie, Rev. Sci. Instr. (In Press)

LEGEND

Fig. 1. A schematic of a three-dee cyclotron.

