Lawrence Berkeley National Laboratory

Recent Work

Title

Surfactants are Ineffective for Reducing Imbibition of Water-Based Fracturing Fluids in Deep Gas Reservoirs

Permalink

<https://escholarship.org/uc/item/7nq9r2hw>

Journal

Energy and Fuels, 35(14)

ISSN

0887-0624

Authors

Tokunaga, TK
Omosebi, OA
Wan, J

Publication Date

2021-07-15

DOI

10.1021/acs.energyfuels.1c01162

Peer reviewed

**Surfactants are ineffective for reducing imbibition of water-based fracturing fluids in deep
gas reservoirs**

Tetsu K. Tokunaga*, Omotayo A. Omosebi, and Jiamin Wan

Energy Geosciences Division, Lawrence Berkeley National Laboratory

Berkeley, California, USA

ABSTRACT: Minimizing loss of injected hydraulic fracturing fluids into shale along fracture-matrix boundaries is desired because imbibed water restricts gas production and wastes valuable water resources. This problem has motivated the addition of surfactants into water-based hydraulic fracturing fluids in order to reduce the capillary driving force for imbibition. Here, we show that reduction in interfacial tension and wettability alteration have negligible ability to reduce imbibition in deep gas reservoirs. The effectiveness of altering capillary forces acting at the wetting front also depends on the injection pressure acting at the fracture-matrix boundary. The pressure at the interface between the fracture and the shale matrix is constrained between the reservoir pore pressure and formation pressure (rock fracture pressure, also known as breakdown pressure of the rock) and increases with depth to magnitudes that greatly exceed that of capillary pressures. The analyses presented here show that even maximum alteration of interfacial properties that result in strongly hydrophobic interactions between the fracturing fluid and reservoir rock is incapable of significantly reducing imbibition in deep reservoirs. Instead of using surfactants, this analysis points to decreases in wellbore shut-in pressures and shut-in times as practical options for reducing imbibition losses of water-based fluids.

*Corresponding author: Tetsu K. Tokunaga, ttokunaga@lbl.gov

1. INTRODUCTION

Hydraulic fracturing for stimulating production of low-permeability shale gas reservoirs uses large volumes of water, often exceeding 10^4 m^3 per well, while competing for valuable water resources and incurring high costs for water supply and treatment of flowback water¹⁻³. In addition to these burdens, loss of water-based fracturing fluids into reservoir matrix rocks during shut-in impedes production through blocking pores and through structural damage within the wetted fracture-matrix interface zone^{1, 4-6}. The adverse effects of water imbibition into shales have motivated investigations on ways to minimize water loss within reservoirs through manipulating interfacial properties and capillary forces. Indeed, a key strategy advanced in stimulating unconventional gas reservoirs is to use surfactants in hydraulic fracturing fluids in order to reduce the capillary pressure driving imbibition and thereby decrease thicknesses of water-blocked zones at the fracture-matrix interface⁷⁻¹⁶. Indeed, in enhanced oil recovery (EOR), the applications of surfactants to reduce surface tension, stabilize microemulsions, and alter reservoir wettability to facilitate oil mobilization are well recognized¹⁷⁻²². It is worth noting that surfactants are also added into hydraulic fracturing fluids for controlling rheological properties. As essential components of foams and gelling agents, surfactants can help enhance viscosity, thereby increase fracture width and improve proppant delivery²³⁻²⁵.

Instead of revisiting the extensively studied and complex problem of surfactant applications in EOR, the analyses developed here reexamines the importance of changing capillary forces in the context of hydraulic fracturing in deep gas reservoirs. To the best of our knowledge, a critical limitation of all the previous studies on surfactant applications for controlling imbibition in shale gas reservoirs is that influences of high reservoir pressures and temperatures were not considered. For a typical depth of 2.5 km for a horizontal well²⁶, hydraulic

fracturing occurs at pressures and temperatures of about 35 MPa and 80 °C, and in the following we show that such conditions severely limit the extent to which changing capillary forces can influence frac fluid imbibition in gas reservoirs.

Before considering capillary effects, it is worth briefly noting that electric double layer expansion and osmotic potential gradients can also influence imbibition in clay-rich, saline sediments. Although correlations between clay content, salinity, and imbibition rates have been obtained²⁷⁻²⁹, and osmotic potentials associated with saline reservoir pore waters have been determined³⁰, challenges persist for quantifying their actual impacts under reservoir conditions. A limitation associated with interpreting how clay swelling impacts imbibition is that experiments to date have largely been conducted on unloaded or only uniaxially loaded cores. Lack of total confinement allows multidimensional sample expansion during hydration, producing highly transmissive microfracture networks that artificially enhance imbibition relative to that actually occurring under in-situ reservoir stresses. Indeed, such free swelling leads to artificial microfracturing and even break up of unconfined samples^{10, 28, 31}. The importance of applying confining stresses during imbibition tests on shales is underscored by closure of microfractures during hydration experiments conducted under isotropic confinement³².

The extent to which imbibition can be facilitated by osmotic forces also requires better understanding because shales are not ideal semi-permeable membranes. The osmotic pressure gradient driving imbibition is moderated by the osmotic efficiency, σ , which ranges from 0 to 1, and depends inversely on the product of characteristic pore-size times the square-root of salt concentration³³. The inverse dependence on the square-root of salinity diminishes σ to less than 0.01 as salinities increase above 1 mol L⁻¹ in monovalent waters³³⁻³⁷, and small fractions of divalent cations lower σ even further³⁸. Thus, measurements of σ for shale systems are needed in

order to evaluate the significance of osmotically driven imbibition³⁹, and confinement of shale samples during such measurements is again warranted for preventing microfracturing.

The analyses developed here compare two basic driving forces for imbibition, capillary forces acting at the imbibition front and the hydrostatic reservoir pressure acting at the fracture-matrix boundary. Through comparing both of these forces, the effectiveness of manipulating interfacial properties will be shown to have a strong dependence on both depth and permeability, such that surfactant use in deep reservoirs has negligible ability to reduce imbibition.

2. METHODOLOGY

Because a one-dimensional analysis of transient imbibition will be used to compare influences of matrix rock capillarity and pressures in fractures, we first provide justification for this simplification of the geometry of fluids entering reservoirs through complex networks of hydraulic fractures and natural fractures. A conceptual model of how fracturing fluids are distributed shortly after hydraulic fracturing is shown in Figure 1, with (a) the km scale overview of multiple hydraulic fractures within a single fracturing stage, (b) a m scale depiction of a region including both a hydraulic fracture and numerous secondary fractures (natural and stimulated) supplied with frac fluid via main hydraulic fractures, and (c) a mm scale close-up view of water imbibing into shale matrix from a vertical hydraulic fracture and secondary (natural or stimulated) horizontal fracture. In the days following fracturing and prior to gas production from reservoirs with matrix permeability k in the range of 10^{-21} to 10^{-17} m² (n-Darcy to 10 μ -Darcy), imbibition fronts only propagate beyond the fracture-matrix interface to distances in the range of mm to cm into the matrix⁴⁰. When such short penetration distances are small relative to characteristic distances between the fractures, water imbibition occurs locally as an

effectively one-dimensional process emanating from complex fracture networks. Therefore, in the analysis developed next, flow is represented as being effectively one-dimensional.

Figure 1. Conceptual model of hydraulic fracturing fluid injection into shale gas reservoir. (a) Cross-section along horizontal well showing water distribution via nominally vertically oriented hydraulic fractures. (b) Local region adjacent to a hydraulic fracture, showing water injected into network of horizontal and vertical fractures (both natural and stimulated). (c) Injected water imbibing into a portion of shale matrix bounded by a vertical hydraulic fracture and a secondary horizontal fracture, both with fluid pressure P_o . This close-up shows the orientation-dependent imbibition front distances $L_i(t)$ at which the capillary pressure is $P_{c,f}$.

At the local scale of shale matrix adjacent to a fracture (microfracture) supplied with hydraulic fracturing fluid, the pressure difference acting across the advancing wet matrix of thickness $L(t)$ is the sum of the pressure at the fracture-matrix interface P_o and the capillary pressure at the advancing wetting front, $P_{c,f}$. Because of strongly anisotropic k in shales⁴¹, $L(t)$ generally exhibits orientation-dependence as indicated in Figure 1c. We will show later that anisotropy can be included through use of k components perpendicular and parallel to bedding planes, but does not impact conclusions concerning alteration of $P_{c,f}$. Thus for simplicity, we consider isotropic k , and a pressure gradient acting across the expanding imbibition zone given by $(P_{c,f} + P_o)/L$. The transient Darcy equation for 1-dimensional flow in the step-function wetting zone approximation is

$$J = \frac{\Delta \theta dL}{dt} = \frac{k}{\mu} \frac{P_o + P_{c,f}}{L} \quad (1)$$

where J is the volumetric flow of water per unit area, $\Delta \theta$ is the volumetric water content increase within the wetted zone, t is time, and μ is the viscosity of the fracturing fluid. Rearrangement and integration of eq 1 gives the time-dependent thickness of the wet zone

$$L(t) = \sqrt{\frac{2k}{\mu \Delta \theta} (P_o + P_{c,f})} \sqrt{t} \quad (2)$$

Because the cumulative volumetric water flux per unit area $I(t) = \Delta \theta L(t)$, the local volumetric imbibition rate per unit area of fracture-matrix contact area is expressed in the Green-Ampt model^{40, 42, 43} as

$$I(t) = \sqrt{\frac{2 \Delta \theta k}{\mu} (P_{c,f} + P_o)} \sqrt{t} \quad (3)$$

The Green-Ampt equation results directly from Darcy's law applied to the migration of an imbibition front characterized by constant $P_{c,f}$, and precedes the practically identical Lucas-

Washburn equation describing flow in capillaries^{44, 45}, and an equivalent later model by Handy⁴⁶ that is commonly used in petroleum recovery research^{10, 47-50}. The Green-Ampt model also predates other studies on soils that have highlighted the square-root of time dependence of imbibition, where the first grouped square-root term on the right-hand side of eq 3 is the sorptivity S ⁵¹, a parameter now also coming into use for characterizing imbibition in hydrocarbon reservoir rocks⁵²⁻⁵⁴. In both the Green-Ampt and Handy models, the relative permeability function is not needed because early stages of imbibition under positive pressure (and especially at high pressure) at the Darcy continuum scale proceeds at rates close to that resulting from single phase flow. Recently, it was shown that imbibition measurements used to determine S also provide reasonable estimates of k over a range of measured k that spanned 10 orders of magnitude⁴⁰. The fact that the database used to develop the S - k correlation included shales suggests that osmotic effects did not significantly enhance imbibition rates into those very low k samples.

Given that k and $\Delta\theta$ of a given reservoir are relatively fixed, the controllable variables available for reducing imbibition are μ , P_{cf} , P_o , and t . While eq 3 clearly shows that thickeners used to increase μ for proppant transport cause decreases in fluid imbibition, rheological properties of fracturing fluids are largely designed with fracture generation and proppant transport in mind⁵⁵. Therefore, our focus here will be on examining the significance of potential changes to P_{cf} , particularly in comparison to P_o . From eq 3, P_{cf} and P_o act additively within the square-root term to drive imbibition. Thus, the magnitude of P_{cf} relative to P_o determines the relative importance of surfactant additions on reducing imbibition. It is worth noting that the equivalent effects that P_{cf} and P_o have in driving imbibition are evident from their additive influences in eq 3, and have been supported by experimental tests conducted over ranges of

150 elevated injection pressures^{56, 57}. For the purpose of this study, we focus on the relative
 151 magnitudes of P_{cf} and P_o under commonly employed laboratory spontaneous imbibition
 152 experiments and under field reservoir conditions.

153 Newly generated fractures experience elevated fracturing pressures that are depth-
 154 dependent. Following shut-in, P_o begins to decline back towards the reservoir pressure⁵⁸. Thus,
 155 values of P_o are depth-dependent, being greater than the reservoir pressure and less than the rock
 156 fracture pressure. For purposes of this study, the hydrostatic gradient for reservoir pressure was
 157 taken as 10 MPa km⁻¹, the fracture gradient was taken as 18 MPa km⁻¹⁵⁹, and the wellbore shut-in
 158 P_o was assigned values midway between these limiting pressures. Thus, a hypothetical shut-in
 159 gradient of 14 MPa km⁻¹ was assumed, with P_o declining towards the reservoir pressure in the
 160 limit of very long shut-in times (Figure 2). It is important to note that reservoir pressures are very
 161 high in deep reservoirs, hence P_o remains high prior to the production phase. Also included in
 162 Figure 2 are a lithostatic pressure gradient of 24.5 MPa km⁻¹ and geothermal gradient of 25 °C
 163 km⁻¹.

164

Figure 2. Depth profiles of reservoir pressure, bottom hole shut-in pressure P_o , formation fracture pressure, lithostatic pressure, and temperature. Surface pressures and temperature are 0 MPa and 15 °C, respectively.

The dependence of $P_{c,f}$ on k and depth was determined in three steps, for water-wet rock with negligible variation in contact angle. The impact of wettability will be examined later in this analysis. First, a correlation between k and the capillary pressure for air entry into hydrophilic water-saturated porous materials $P_{c,a}$ was determined using data from the literature on room temperature water-air systems (where interfacial tension $\gamma \approx 72$ mN/m)⁴⁰. The power-law correlation given by

$$P_{c,a}(0.1 \text{ MPa}, 20 \text{ }^\circ\text{C}) = (0.106 \text{ Pa m}^{0.72})k^{-0.36} \quad (4)$$

fits data on consolidated and unconsolidated media with a root mean-square deviation in $\log P_{c,a}$ of 0.71, for measurements spanning twelve orders of magnitude in k . In previous work, the same data set was scaled with interfacial tension to estimate the methane gas-entry capillary pressure $P_{c,g}$ for a reservoir at 70 °C and 20 MPa⁴⁰. Equation 4 was next multiplied by the previously determined linear correlation⁴⁰ $P_{c,f} = 1.21P_{c,a}$ to obtain the dependence of $P_{c,f}$ on k at the ground surface

$$P_{c,f}(z=0, 0.1 \text{ MPa}, 20 \text{ }^\circ\text{C}) = \alpha k^{-0.36} \quad (5)$$

where $\alpha = 1.21 \times 0.106 \text{ Pa m}^{0.72} = 0.128 \text{ Pa m}^{0.72}$.

The final step needed to predict how $P_{c,f}$ varies with both depth and k requires determining how the methane-water interfacial tension γ varies with depth z below the ground surface. This relation was obtained by interpolating values of methane-water γ from the

187 literature^{60, 61} over a range of pressure-temperature combinations that are compatible with the P_o
 188 and T depth profiles illustrated in Figure 2.

189

190

191

192 **Figure 3.** Depth-dependence of methane-water γ , given the estimated temperature and wellbore
 193 shut-in pressure profiles.

194

195 These depth-dependent methane-water $\gamma(z)$ values were fit to $\gamma(z) = 72.0 - 16.9z + 3.37z^2 -$
 196 $0.185z^3$ shown in Figure 3, then used to scale Equation 5 in order to estimate how P_{cf} depends on
 197 both k and z

198
$$P_{cf}(z, k) = [\gamma(z)/\gamma(0)]\alpha k^{-0.36} \quad (6)$$

199 where $\gamma(0) = 71.7 \text{ mN m}^{-1}$, the methane-water γ at the ground surface. Substituting the depth-
 200 dependent wellbore shut-in $P_o(z)$ and eq 6 into eq 3 gives:

$$I(t) = \sqrt{\frac{2 \Delta \theta k}{\mu} \left(\frac{\gamma(z)}{\gamma(0)} \alpha k^{-0.36} + Bz \right)} \sqrt{t} \quad (7a)$$

where $B = 14.0 \text{ MPa km}^{-1}$, the wellbore shut-in gradient. The impact of surfactants on $I(t)$ can then be expressed as

$$I(t) = \sqrt{\frac{2 \Delta \theta k}{\mu} \left(\frac{f\gamma(z)}{\gamma(0)} \alpha k^{-0.36} + Bz \right)} \sqrt{t} \quad (7b)$$

where f represents the fractional reduction in $\gamma(z)$ imparted by addition of surfactants. For example, reducing γ from 50 mN m^{-1} to 15 mN m^{-1} corresponds to $f = 0.3$. Thus, the impact of surfactant addition in reducing fracturing fluid imbibition relative to the unaltered fluid (with $f = 1$) is given by

$$1 - \frac{I(f, z)}{I_0(z)} = 1 - \left[\frac{\frac{f\gamma(z)}{\gamma(0)} \alpha k^{-0.36} + Bz}{\frac{\gamma(z)}{\gamma(0)} \alpha k^{-0.36} + Bz} \right]^{0.5} \quad (8)$$

which we term the capillary alteration effectiveness (CAE). The CAE can range from 0 where the imbibed fluid volume is unaffected by the addition of surfactant, up to 1 where surfactant addition prevents any fluid imbibition into the reservoir due to extremely strong hydrophobic interaction. Note that anisotropy can be accommodated for imbibition perpendicular to and parallel to shale bedding planes by using suitable directional components of k in eq 8. Here, it is also convenient to consider how changing wettability can be incorporated into eq 8. Recall that P_c in a straight capillary tube of radius R is given by the Young–Laplace equation

$$P_c = \frac{2\gamma \cos \theta}{R} \quad (9)$$

where θ is the contact angle. Although scaling of P_c by $\cos \theta$, in porous media is not generally accurate⁶², it serves as a useful approximation⁶³. By scaling P_c by both γ and $\cos \theta$, f can be

interpreted more generally to be the product of $\cos \theta$ times the relative reduction in γ . Such a generalization allows examining the implications of a hypothetical extremely hydrophobic interaction between the reservoir and fracturing fluid. Such a case, with $\theta = \pi$ and $\cos \theta = -1$ can then be examined with $f = -1$, and captures the theoretical maximum impact achievable for capillary alteration of imbibition. The full range of wetting behavior, including that of complex mixed-wet systems^{64, 65}, is encompassed by varying f from 1 (strongly hydrophilic) to -1 (strongly hydrophobic). In order to focus on the potential impacts that weakening the capillary driving force can have on imbibition, values of f that range from 0.3 to -1 will later be examined.

3. RESULTS AND DISCUSSION

The capillary pressure acting at the imbibition front, P_{cf} , depends on k , and decreases with depth as approximated by eq 4. The strong k -dependence of P_{cf} shown in Figure 4 reflects the power-law correlation with $k^{-0.36}$ (eq 5), which differs from $k^{-0.5}$ predicted from Leverett scaling^{40, 66}. Decreases in γ with depth (Figure 3) account for the depth-dependence of P_{cf} .

Figure 4. Depth-dependence of imbibition front $P_{c,f}$ for different k , showing that $P_{c,f}$ decreases with depth and is larger for lower k .

The CAE is both k - and depth-dependent, as illustrated in Figure 5, where depth profiles are plotted for $k = 10^{-15}$ (1 mDarcy), 10^{-18} (1 μ Darcy), and 10^{-21} m² (1 nDarcy), with interfacial tensions reduced by $f = 0.3$, 0.01, and -1. These three f values represent modest, very strong, and maximum possible decreases in the capillary driving force for imbibition, respectively. Influences of surfactant alteration can be more important in lower k reservoirs, e.g. shales, because their higher $P_{c,f}$ can be more effectively reduced with surfactant addition. However, capillary alteration effectiveness decreases with depth because the pressure at the fracture-matrix boundary P_o becomes large enough to be the dominant driving force, even in very low k reservoirs. The depths by which capillary alteration effectiveness diminishes to only 10% are reached where the profiles cross the vertical red line in Figure 5. Thus, even with interfacial tension reduced by $f = 0.01$, capillary alteration effectiveness is diminished by only 10% at

depths of 0.11 and 1.1 km, for 1 μ Darcy and 1 nDarcy reservoirs, respectively. At the much greater depths commonly stimulated with hydraulic fracturing, the effectiveness in reducing fluid imbibition with surfactants will be negligible. Figure 5 also shows that even if a 1 nDarcy reservoir was stimulated with a fluid that imparted extremely hydrophobic interactions ($\theta = \pi, f = -1$), the effectiveness in reducing imbibition would be limited to less than 10% at depths greater than 2.2 km. Because k is commonly larger parallel to shale bedding planes, Figure 5 shows that the CAE for imbibition from vertical fractures is far less than that for imbibition from horizontal fractures. Given that μ is generally optimized for proppant delivery, only decreases in P_o and t remain as controllable variables that have the capacity to significantly reduce imbibition during reservoir stimulation.

Figure 5. The effectiveness of altering interfacial forces in order to minimize fracturing fluid imbibition depends on reservoir k (1 mDarcy, 1 μ Darcy, 1 nDarcy) and depth. The parameter f in the legend represents the fractional reduction in water-gas surface tension achieved by addition

of surfactant. The cases with $f = -1$ represent the maximum reduction in capillary uptake achievable with extremely hydrophobic interactions.

The shallow limit of $z = 0$ km in Figure 5 represents typical laboratory imbibition tests, where water or fracturing fluids are commonly introduced with negligible pressure head, i.e. $P_o \approx 0$ MPa. Under negligible P_o , alteration of $P_{c,f}$ with surfactants results in clear decreases to imbibition rates shown in recent studies⁹⁻¹². It is noteworthy that the contrasting effects of high P_o (24 MPa) versus negligible P_o was recognized in comparisons of imbibition without and with surfactants in a previous laboratory study on imbibition of fracturing fluids⁶⁷. Our analyses generalizes such findings by showing how the depth-dependent P_o and k -dependent $P_{c,f}$ limit the effectiveness that alterations of interfacial tension and wettability can have on imbibition.

CONCLUSION

Thicknesses of water-blocked regions along fracture-matrix interfaces grow by interfacial tension-dependent capillarity acting at the advancing wetting front $P_{c,f}$, and by the fracturing fluid pressure acting at the fracture-matrix boundary, P_o . Therefore, it is important to understand the relative magnitudes of these driving forces in order to determine the effectiveness of surfactant additions aimed at reducing the capillary contributions to imbibition. Our analyses show the following.

- The extent to which surfactants can reduce imbibition is limited by the k -dependent magnitude of $P_{c,f}$ and has greater potential effect in lower k reservoirs.
- Magnitudes of P_o in deep reservoirs are in the range of tens of MPa, and are greater than $P_{c,f}$ values of even the lowest k reservoirs.

- Therefore, alteration of water-gas interfacial tension and wettability have negligible ability to reduce imbibition of water-based fracturing fluids in deep, unconventional reservoirs.
- Given that rheological properties of fracturing fluids are largely prescribed for the purpose of delivering proppants into fractures, the remaining operational options for minimizing imbibition and water block thicknesses are reducing shut-in times and reducing the magnitude of P_o .

296 AUTHOR INFORMATION

297 Corresponding Author

298 Tetsu K. Tokunaga – Energy Geosciences Division, Lawrence Berkeley National Laboratory,
299 Berkeley, California 94720, United States

300 Email: tktokunaga@lbl.gov

301 Authors

302 Omotayo A. Omosebi – Energy Geosciences Division, Lawrence Berkeley National Laboratory,
303 Berkeley, California 94720, United States

304 Jiamin Wan – Energy Geosciences Division, Lawrence Berkeley National Laboratory, Berkeley,
305 California 94720, United States

306

307 ACKNOWLEDGMENTS

308 This work was supported by the Assistant Secretary for Fossil Energy, Office of Oil and Natural
309 Gas, through the National Energy Technology Laboratory under the U.S. Department of Energy
310 Contract No. DE-AC02-05CH11231. We thank the two reviewers for their helpful comments on
311 the manuscript, John Selker (Oregon State University) for comments on a recent publication⁴⁰
312 that helped motivate this study, and Stephen Henry (NETL) for project management.

313

314 REFERENCES

- 315 1. Edwards, R. W. J.; Doster, F.; Celia, M. A.; Bandilla, K. W., Numerical modeling of gas
316 and water flow in shale gas formations with a focus on the fate of hydraulic fracturing fluid.
317 *Environmental Science & Technology* **2017**, *51* (23), 13779-13787.
- 318 2. Vengosh, A.; Jackson, R. B.; Warner, N.; Darrah, T. H.; Kondash, A., A critical review
319 of the risks to water resources from unconventional shale gas development and hydraulic
320 fracturing in the United States. *Environmental Science & Technology* **2014**, *48* (15), 8334-8348.
- 321 3. Rosa, L.; Rulli, M. C.; Davis, K. F.; D'Odorico, P., The water-energy nexus of hydraulic
322 fracturing: A global hydrologic analysis for shale oil and gas extraction. *Earths Future* **2018**, *6*
323 (5), 745-756.
- 324 4. Chenevert, M. E.; Osisanya, S. O., Shale swelling at elevated temperature and pressure.
325 In *Rock Mechanics, Proc. 33rd U.S. Symposium*, Tillerson, J. R.; Wawersik, W. R., Eds.
326 Balkema: Rotterdam, 1992; pp 869-878.
- 327 5. Holditch, S. A., Factors affecting water blocking and gas-flow from hydraulically
328 fractured gas wells. *Journal of Petroleum Technology* **1979**, *31* (12), 1515-1524.
- 329 6. Bennion, D. B.; Thomas, F. B., Formation damage issues impacting the productivity of
330 low permeability, low initial water saturation gas producing formations. *J Energ Resour-Asme*
331 **2005**, *127* (3), 240-247.
- 332 7. Chai, Y.; Li, X.; Jing, D., Application of surfactants in hydraulic fracturing for enhanced
333 oil/gas recovery. *Oil & Gas Research* **2019**, *5* (1), 1-10.
- 334 8. Hussien, O. S.; Elraies, K. A.; Almansour, A.; Husin, H.; Belhaj, A.; Ern, L.,
335 Experimental study on the use of surfactant as a fracking fluid additive for improving shale gas
336 productivity. *Journal of Petroleum Science and Engineering* **2019**, *183*.
- 337 9. Roychaudhuri, B.; Tsotsis, T. T.; Jessen, K., An experimental investigation of
338 spontaneous imbibition in gas shales. *Journal of Petroleum Science and Engineering* **2013**, *111*,
339 87-97.
- 340 10. Makhanov, K.; Habibi, A.; Dehghanpour, H.; Kuru, E., Liquid uptake of gas shales: A
341 workflow to estimate water loss during shut-in periods after fracturing operations. *Journal of*
342 *Unconventional Oil and Gas Resources* **2014**, *7*, 22-32.
- 343 11. Das, S.; Adeoye, J.; Dhiman, I.; Bilheux, H. Z.; Ellis, B. R., Imbibition of mixed-charge
344 surfactant fluids in shale fractures. *Energy & Fuels* **2019**, *33* (4), 2839-2847.
- 345 12. Sun, Y. P.; Bai, B. J.; Wei, M. Z., Microfracture and surfactant impact on linear
346 cocurrent brine imbibition in gas-saturated shale. *Energy & Fuels* **2015**, *29* (3), 1438-1446.
- 347 13. Gdanski, R., Modeling the impact of capillary pressure reduction by surfactants. In *SPE*
348 *International Symposium on Oilfield Chemistry*, Society of Petroleum Engineers: Houston, TX,
349 2007; p 7.
- 350 14. Chee, S. C.; Hidayat, B. M.; Mohshim, D. F.; Zain, Z. M.; Chai, I. C. H.; Borhan, N.;
351 Ismail, H. H.; Adam, M., Evaluation of anionic and non-ionic surfactant performance for
352 Montney shale gas hydraulic fracturing fluids. *Journal of Petroleum Exploration and Production*
353 **2021**, *11* (4).
- 354 15. Penny, G. S.; Pursley, J. T., Field study of completion fluids to enhance gas production in
355 the Barnett Shale. In *SPE Gas Technology Symposium*, Society of Petroleum Engineers: Calgary,
356 Alberta, Canada, 2006; p 10.

16. Liang, T. B.; Xu, K.; Lu, J.; Nguyen, Q.; DiCarlo, D., Evaluating the performance of surfactants in enhancing flowback and permeability after hydraulic fracturing through a microfluidic model. *SPE Journal* **2020**, *25* (1), 268-287.
17. Hirasaki, G. J.; Miller, C. A.; Puerto, M., Recent advances in surfactant EOR. *SPE Journal* **2011**, *December 2011*, 889-907.
18. Sheng, J. J., Status of surfactant EOR technology. *Petroleum* **2015**, *1*, 97-105.
19. Alzobaidi, S.; Da, C.; Tran, V.; Prodanovic, M.; Johnston, K. P., High temperature ultralow water content carbon dioxide-in-water foam stabilized with viscoelastic zwitterionic surfactants. *J. Colloid Interface Sci.* **2017**, *488*, 79-91.
20. Sheng, J. J., What type of surfactants should be used to enhance spontaneous imbibition in shale and tight reservoirs? *Journal of Petroleum Science and Engineering* **2017**, *159*, 635-643.
21. Levitt, D. B.; Jackson, A. C.; Heinson, C.; Britton, L. N.; Malik, T.; Dwarakanath, V.; Pope, G. A., Identification and evaluation of high-performance EOR surfactants. *Spe Reserv Eval Eng* **2009**, *12* (2), 243-253.
22. Burrows, L. C.; Haeri, F.; Cvetic, P.; Sanguinito, S.; Shi, F.; Tapriyal, D.; Goodman, A.; Enick, R. M., A Literature review of CO₂, natural gas, and water-based fluids for enhanced oil recovery in unconventional reservoirs. *Energy & Fuels* **2020**, *34* (5), 5331-5380.
23. Elsner, M.; Hoelzer, K., Quantitative Survey and Structural Classification of Hydraulic Fracturing Chemicals Reported in Unconventional Gas Production. *Environmental Science & Technology* **2016**, *50* (7), 3290-3314.
24. Montgomery, C., Fracturing fluid components. In *Effective and Sustainable Hydraulic Fracturing*, Bunger, A. P.; McLennan, J.; Jeffrey, R., Eds. InTech: Rijeka, Croatia, 2013; pp 25-45.
25. Al-Muntasheri, G. A., A critical review of hydraulic-fracturing fluids for moderate- to ultralow-permeability formations over the last decade. *Spe Prod Oper* **2014**, *29* (4), 243-260.
26. Jackson, R. B.; Lowry, E. R.; Pickle, A.; Kang, M.; DiGiulio, D.; Zhao, K. G., The depths of hydraulic fracturing and accompanying water use across the United States. *Environmental Science & Technology* **2015**, *49* (15), 8969-8976.
27. Yang, L.; Dou, N. H.; Lu, X. B.; Zhang, X. H.; Chen, X.; Gao, J.; Yang, C. W.; Wang, Y., Advances in understanding imbibition characteristics of shale using an NMR technique: a comparative study of marine and continental shale. *J Geophys Eng* **2018**, *15* (4), 1363-1375.
28. Ge, H. K.; Yang, L.; Shen, Y. H.; Ren, K.; Meng, F. B.; Ji, W. M.; Wu, S., Experimental investigation of shale imbibition capacity and the factors influencing loss of hydraulic fracturing fluids. *Petrol Sci* **2015**, *12* (4), 636-650.
29. Binazadeh, M.; Xu, M. X.; Zolfaghari, A.; Dehghanpour, H., Effect of electrostatic interactions on water uptake of gas shales: The interplay of solution ionic strength and electrostatic double layer. *Energy & Fuels* **2016**, *30* (2), 992-1001.
30. Zhou, Z.; Li, X. P.; Teklu, T. W., A critical review of osmosis-associated imbibition in unconventional formations. *Energies* **2021**, *14* (4), 835.
31. Dehghanpour, H.; Lan, Q.; Saeed, Y.; Fei, H.; Qi, Z., Spontaneous imbibition of brine and oil in gas shales: Effect of water adsorption and resulting microfractures. *Energy & Fuels* **2013**, *27* (6), 3039-3049.

32. Zhang, S. F.; Sheng, J. J.; Shen, Z. Q., Effect of hydration on fractures and permeabilities in Mancos, Eagleford, Barnett and Marcellus shale cores under compressive stress conditions. *Journal of Petroleum Science and Engineering* **2017**, *156*, 917-926.
33. Bresler, E., Anion exclusion and coupling effects in nonsteady transport through unsaturated soils .1. Theory. *Soil Science Society of America Journal* **1973**, *37* (5), 663-669.
34. Cey, B. D.; Barbour, S. L.; Hendry, M. J., Osmotic flow through a Cretaceous clay in southern Saskatchewan, Canada. *Canadian Geotechnical Journal* **2001**, *38* (5), 1025-1033.
35. Neuzil, C. E.; Person, M., Reexamining ultrafiltration and solute transport in groundwater. *Water Resour. Res.* **2017**, *53* (6), 4922-4941.
36. Barbour, S. L.; Fredlund, D. G., Mechanisms of osmotic flow and volume change in clay soils. *Canadian Geotechnical Journal* **1989**, *26* (4), 551-562.
37. Al-Bazali, T. M.; Zhang, J.; Chenevert, M. E.; Sharma, M. M., Factors controlling the membrane efficiency of shales when interacting with water-based and oil-based muds. In *SPE International Oil & Gas Conference and Exhibition in China*, Society of Petroleum Engineers: Beijing, China, 2006; p 11.
38. Tremosa, J.; Goncalves, J.; Matray, J. M., Natural conditions for more limited osmotic abnormal fluid pressures in sedimentary basins. *Water Resour. Res.* **2012**, *48*, W04530.
39. Fakcharoenphol, P.; Torcuk, M.; Kazemi, H.; Wu, Y. S., Effect of shut-in time on gas flow rate in hydraulic fractured shale reservoirs. *J Nat Gas Sci Eng* **2016**, *32*, 109-121.
40. Tokunaga, T. K., Simplified Green-Ampt model, imbibition-based estimates of permeability, and implications for leak-off in hydraulic fracturing. *Water Resour. Res.* **2020**, *56* (4), 12.
41. Gensterblum, Y.; Ghanizadeh, A.; Cuss, R. J.; Amann-Hildenbrand, A.; Krooss, B. M.; Clarkson, C. R.; Harrington, J. F.; Zoback, M. D., Gas transport and storage capacity in shale gas reservoirs – A review. Part A: Transport processes. *Journal of Unconventional Oil and Gas Resources* **2015**, *12*, 87-122.
42. Green, W. H.; Ampt, G. A., Studies on soil physics Part I - The flow of air and water through soils. *J Agr Sci* **1911**, *4*, 1-24.
43. Neuman, S. P., Wetting front pressure head in infiltration-model of Green and Ampt. *Water Resour. Res.* **1976**, *12* (3), 564-566.
44. Lucas, R., The time law of the capillary rise of liquids. *Kolloid Z* **1918**, *23* (1), 15-22.
45. Washburn, E. W., The dynamics of capillary flow. *Physical Review* **1921**, *17* (3), 273-283.
46. Handy, L. L., Determination of effective capillary pressures for porous media from imbibition data. *Transactions of the American Institute of Mining and Metallurgical Engineers* **1960**, *219* (5), 75-80.
47. Babadagli, T., Scaling capillary imbibition during static thermal and dynamic fracture flow conditions. *Journal of Petroleum Science and Engineering* **2002**, *33* (4), 223-239.
48. Mason, G.; Morrow, N. R., Developments in spontaneous imbibition and possibilities for future work. *Journal of Petroleum Science and Engineering* **2013**, *110*, 268-293.
49. Mehana, M.; Al Salman, M.; Fahes, M., Impact of salinity and mineralogy on slick water spontaneous imbibition and fFormation strength in shale. *Energy & Fuels* **2018**, *32* (5), 5725-5735.

50. Yang, R.; He, S.; Hu, Q. H.; Zhai, G. Y.; Yi, J. Z.; Zhang, L., Comparative investigations on wettability of typical marine, continental, and transitional shales in the Middle Yangtze Platform (China). *Energy & Fuels* **2018**, 32 (12), 12187-12197.
51. Philip, J. R., The theory of infiltration, 4. Sorptivity and algebraic infiltration equations. *Soil Science* **1957**, 84, 257-264.
52. Yang, R.; Guo, X. S.; Yi, J. Z.; Fang, Z. X.; Hu, Q. H.; He, S., Spontaneous imbibition of three leading shale formations in the Middle Yangtze Platform, South China. *Energy & Fuels* **2017**, 31 (7), 6903-6916.
53. Yang, J.; Leng, J. Y.; Qiao, L. K.; Wang, L. L.; Ding, J. D., Parameter prediction of water imbibition in unsaturated shales using the NMR method. *Geofluids* **2019**, 2019, 4254159.
54. Hatiboglu, C. U.; Karaaslan, U.; Akin, S., Spontaneous imbibition in low permeability carbonates. *Energy Source* **2005**, 27 (9), 839-846.
55. Montgomery, C., Fracturing Fluids. In *Effective and Sustainable Hydraulic Fracturing*, Bunger, A.; McLennan, J.; Jeffrey, R., Eds. Intech: Brisbane, Australia, 2013; p 23.
56. Yeh, W. W. G.; Franzini, J. B., Moisture movement in a horizontal soil column under influence of an applied pressure. *Journal of Geophysical Research* **1968**, 73 (16), 5151-5157.
57. Pagels, M.; Willberg, D. M.; Edelman, E.; Zagorski, W.; Frantz, J., Quantifying fracturing fluid damage on reservoir rock to optimize production. In *Unconventional Resources Technology Conference*, URTEC: Denver, Colorado, 2013; p 9.
58. Nolte, K. G., Principles of fracture design based on pressure analysis. *SPE Production Engineering* **1988**, (February), 22-30.
59. Bell, J. S.; Grasby, S. E., The stress regime of the Western Canadian Sedimentary Basin. *Geofluids* **2012**, 12 (2), 150-165.
60. Wiegand, G.; Franck, E. U., Interfacial tension between water and non-polar fluids up to 473 K and 2800 bar. *Berichte der Bunsengesellschaft für physikalische Chemie* **1994**, 98 (6), 809-817.
61. Ren, Q. Y.; Chen, G. J.; Yan, W.; Guo, T. M., Interfacial tension of (CO₂ + CH₄) + water from 298 K to 373 K and pressures up to 30 MPa. *J. Chem. Eng. Data* **2000**, 45 (4), 610-612.
62. Philip, J. R., Limitations on scaling by contact angle. *Soil Science Society America Proceedings* **1971**, 35, 507-509.
63. Parlange, J.-Y., Scaling by contact angle. *Soil Science Society America Proceedings* **1974**, 38, 161-162.
64. Salathiel, R. A., Oil recovery by surface film drainage in mixed-wettability rocks. *Journal of Petroleum Technology* **1973**, 25 (Oct), 1216-1224.
65. Morrow, N. R.; Mason, G., Recovery of oil by spontaneous imbibition. *Curr. Opin. Colloid Interface Sci.* **2001**, 6, 321-337.
66. Leverett, M. C., Capillary behavior in porous solids. *Transactions of the American Institute of Mining and Metallurgical Engineers* **1941**, 142, 152-169.
67. Roychoudhuri, B.; Xu, J.; Tsotsis, T. T.; Jessen, K., Forced and spontaneous imbibition experiments for quantifying surfactant efficiency in tight shales. In *SPE Western North American and Rocky Mountain Joint Regional Meeting*, Society of Petroleum Engineers: Denver, Colorado, USA, 2014; p 7.

487 **TOC Graphic**

488

489