Lawrence Berkeley National Laboratory
Lawrence Berkeley National Laboratory

Title
ION SOURCE GROUP SUMMARY

Permalink
https://escholarship.org/uc/item/85v4t4pk

Author
Clark, D.J.

Publication Date
1978-11-01

eScholarship.org Powered by the California Digital Library
University of California

Presented at the Workshop on Heavy Ion Inertial Fusion, Argonne National Laboratory, Argonne, Illinois, September 19-26, 1978

LBL-8415

ION SOURCE GROUP SUMMARY

D. J. Clark, and R. L. Seliger

November 1978

Prepared for the U. S. Department of Energy
under Contract W-7405-ENG-48



MASTER

Reference Designs

In Table 2 the sources for the various lab reference designs are summarized, giving estimated confidence levels for each one. The confidence levels are below "high" where the design calls for performance which is a significant extrapolation from standard demonstrated performance. It is quite likely that these lower confidence cases will rise after the coming year's R & D.

Measurement Description Guidelines

In our discussions of ion sources from various labs, we have found that it is sometimes difficult to make direct comparisons. So we make the following suggestions for future discussions and publications of ion source development work. Accurate measurements of beam current and emittance of these high current beams is not easy. Various methods are used at different labs. For beam current measurement, collector cups or plates are used, sometimes with a bias on the collector, sometimes with a bias ring upstream which is shielded from the beam and sometimes with magnetic suppression. Size on a phosphor and thermocouple readouts are also used. Electrical readouts can be misleading because of secondary electrons and plasma produced by the beam. For understanding and evaluation of the measurements the authors should describe the measuring system and also show data of beam vs. strength of electric or magnetic suppression, whenever they are used. Emittance measurements also have difficulties. They are made by slit and scanning systems which interrupt most of the beam, by beam size on a phosphor, or by beam through collimators into a cup. Here again the method should be described. Pulse width of the beam is important for estimating space charge compensation. The background pressure and the fraction of the beam converted to neutral atoms are also useful in understanding the transport. Authors of ion source papers should describe as many of the above parameters as possible.

References

1. ERDA Summer Study of Heavy Ions for Inertial Fusion. LBL-5543. (July 1976).

2. Proceedings of the Heavy Ion Fusion Workshop. BNL-50769. (Oct. 1977).

Table 1. Source Test Results.

Group	Source	Ion	No. Aper.	I (peak mA)	D.C. or Pulsed	Energy (keV)	Ions or Atoms	Transport Dist.	ϵ_n (cm-mr)	$B = I/\epsilon_n^2 \left[\frac{A}{(cm\text{-}mr)^2}\right]$	Accel.	Ref.
ANL/ Hughes	Penning	Xe^{1+}	1	2.5	D.C.& Pulsed	80	Ions	.3m	.001	2500		This Conf.
	"	Xe^{1+}	Mult.	100	Pulsed	2.5						"
	"	Xe^{1+}	1	30/100	"	100/200			<.01	<1000		"
*	"	Xe^{1+}, Hg^{1+}	1	[illegible]	"	200	Ions	Source on Column	<.01		1.5 MV Column	"
BNL	Duoplas.	Xe^{1+}	1	2	Pulsed	500	Ions	"	.01	20	500 kV Column	This Conf.
*	New	Hg^{1+}		40	"		"	1m	.02	100	400 kV Column	"
LBL	LBL CTR +LLL Extr.	Xe^{1+}	13	35	Pulsed	20	Ions	1.4m	.035	29		This Conf.
	"	Xe^{1+}	13	60	"	500	"	1.2m To Column			500 kV Column	"
	Contact ioniz.	Cs^{1+}	1	400/1000	"	200/500	"		.01 Thermal	10,000	Drift Tube	"
*	"	Cs^{1+}	1	7500	"	5000	"				"	"
LBL-Mobley	LBL CTR (Slit Extr.)	Xe^{1+}	105/3	6500/180	Pulsed	35	Ions + Atoms	3.3m	.28&.013/.01	1800		Ref. 1, p. 50; This Conf.
LLL-Osher	MATS III	Kr^{1+}	25	75	D.C.	20	Ions + Atoms	1.1m	<.02	190		Ref. 2 p. 92

*Planned
A/B = Measured/Expected

Table 2. Sources for Reference Designs.

	Source				Pre. Accel.	
Lab	Ion	I (peak mA)	Type	Confidence Level	Type	Confidence Level
ANL-2	Hg^{1+}	50	Hughes Penning	High	1500 kV Column	Medium
ANL-3	Xe^{1+}	20	Hughes Penning	High	1500 kV Column	Medium
BNL	U^{1+} (Hg^{1+})	40		U^{1+} Low Hg^{1+} High	500 kV Column	High
LBL	U^{1+}	4000	Surface Ioniz.	Low, Needs R&D	Drift Tubes	Low Needs R&D