Lawrence Berkeley National Laboratory

Recent Work

Title

EARTHQUAKE SLOSHING IN ANNULAR AND CYLINDRICAL TANKS

Permalink

<https://escholarship.org/uc/item/8q90t3bn>

Author

Aslam, Mohammad

Publication Date

1978-05-01

Earthquake Sloshing in Annular and Cylindrical Tanks

*Mohammad Aslam,
William G. Godden, and
D. Theodore Scalise*

RECEIVED
LAWRENCE
BERKELEY LABORATORY

JUL 10 1978

LIBRARY AND
DOCUMENTS SECTION

Lawrence Berkeley Laboratory
Berkeley, California 94720

May 1978

TWO-WEEK LOAN COPY

*This is a Library Circulating Copy
which may be borrowed for two weeks.
For a personal retention copy, call
Tech. Info. Division, Ext. 6782*

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.

EARTHQUAKE SLOSHING IN ANNULAR AND CYLINDRICAL TANKS

by

Mohammad Aslam,¹ A.M. ASCE; William G. Godden,² M. ASCE
and
D. Theodore Scalise³

SUMMARY

This paper presents an analytical and experimental study of the earthquake induced sloshing response of water in annular tanks which are being use in Boiling Water Reactors. The theory developed here is equally applicable to cylindrical tanks.

¹Associate Engineer, Dept. of Civ. Engrg., Univ. of California, Berkeley, CA.

²Professor, Dept. of Civ. Engrg., University of California, Berkeley, CA.

³Dept. Head, Engineering Sciences Dept., Lawrence Berkeley Laboratory, University of California, Berkeley, CA.

KEYWORDS

Annular tanks; Boiling Water Reactors (BWR); Cylindrical tanks; Dynamic pressures; Earthquake response; Irrotational flow; Nuclear reactors; Pressure-Suppression pool; Sloshing response; Velocity potential.

ABSTRACT

The sloshing response of water in annular as well as in cylindrical tanks under horizontal earthquake ground motions is studied. A linear analysis, developed for the general annular tank problem is based on potential flow theory; and the predicted values of natural frequencies, surface displacements, and dynamic pressures are compared with measured data from shaking table tests. Experimental studies were conducted on 1/80th and 1/15th scale models of a 120 ft. (36.6 m) annular tank, and correlation data is presented for both sinusoidal and simulated earthquake motions. Test results from the sloshing of water in a 12 ft. (3.66 m) diameter cylindrical tank show that the annular tank solution is also applicable in this case. The range of surface displacement within which linear theory gives satisfactory results was established experimentally.

INTRODUCTION

The problem of the sloshing of a liquid in an annular cylindrical tank (Fig. 1) under horizontal ground motions is encountered in the possible effect of an earthquake on water surface level in the pressure-suppression pool of a Boiling Water Reactor (BWR). A cross-section through the annulus of a typical suppression pool design is shown in Figure 2; the inner and outer diameters of the pool are 80 ft. (24.4 m) and 120 ft. (36.6 m) respectively, the water depth is approximately 20 ft. (6.1 m), and the highest inlet opening is 5 ft. 10 in. (1.8 m) below the water surface. The sloshing problem arises due to the danger of superheated steam escaping if under dynamic conditions the water level at the inner wall were to drop low enough to expose the inlet pipe (level c-c in Figure 2). Hence it is important to be able to predict the maximum water surface displacements for any prescribed earthquake, particularly how far it may drop.

The sloshing of liquid in simple cylindrical tanks has received considerable attention, and both experimental and theoretical studies have been reported in the literature (1-4, 6,8-10, 12-15). Most of this deals with steady-state response and little with response under arbitrary ground motions. The annular tank problem has not been studied to this extent. Bauer's analysis (5) deals with steady-state harmonic ground motion, but neither analytical nor experimental data has been found for the arbitrary ground motion problem of the kind that exists under earthquake conditions.

This investigation presents the results of both analytical and experimental studies on the sloshing of liquid in annular tanks subjected to both harmonic and arbitrary ground motions. The primary object of the study was to determine the time-history of water surface displacements for any applied ground motion; as in the BWR suppression-pool this represents the greatest potential danger in an earthquake. Experimentally the response characteristics were first studied on a 1/80th scale plexi-glass tank mounted on a small table capable of applying horizontal sinusoidal motions (Figure 5a). Subsequently a 1/15th scale steel model with glass viewing windows was used on a large shaking table to study the response of the water to seismic-type horizontal ground motions (Figure 5b). The analytical study is based on linear theory, and the limits for small-displacement response were studied experimentally.

ANALYSIS

Assumptions

The following analysis is based on three assumptions:

1. Displacements are small and hence linear theory is applicable.
2. The tank is assumed to be rigid, the heavy structures used for suppression pools makes this a realistic assumption and even in more flexible tanks the assumption may still be valid as the primary sloshing response is a low frequency phenomenon.
3. Water is assumed to be an incompressible and non-viscous fluid, and thus the flow remains irrotational.

Basic Equations and Boundary Conditions

As the flow is assumed to be irrotational, there exists a velocity potential ϕ which will satisfy the Laplace equation which in a 3-D cylindrical coordinate system (Figure 1) is

$$\frac{\partial^2 \phi}{\partial r^2} + \frac{1}{r} \frac{\partial \phi}{\partial r} + \frac{1}{r^2} \frac{\partial^2 \phi}{\partial \theta^2} + \frac{\partial^2 \phi}{\partial z^2} = 0 \quad \dots \dots \dots (1)$$

Let a and b be the outer and inner radii of the annular tank and h be the depth of water, then the following boundary conditions must be satisfied

$$\left. \frac{\partial \phi}{\partial r} \right|_{r=a} = \dot{x} \cos \theta \quad \dots \dots \dots (2)$$

$$\left. \frac{\partial \phi}{\partial r} \right|_{r=b} = \dot{x} \cos \theta \quad \dots \dots \dots (3)$$

$$\left. \frac{\partial \phi}{\partial z} \right|_{z=-h} = 0 \quad \dots \dots \dots (4)$$

where $\dot{x} = \frac{dx}{dt}$ = tank wall velocity, and t = time. Also, the linearized free-surface boundary condition is given by the following equation [16]

$$\frac{\partial^2 \phi}{\partial t^2} + g \frac{\partial \phi}{\partial z} = 0 \quad \text{at} \quad z = 0 \quad \dots \dots \dots (5)$$

where g is the acceleration of gravity.

Solution of the Eigenvalue Problem

To determine the natural sloshing frequencies and mode shapes, it is necessary to solve the free vibration problem with homogeneous boundary conditions but non-zero initial conditions.

Assuming

$$\phi = R(r) \Theta(\theta) Z(z) T(t) \dots \dots \dots (6)$$

in which $T(t)$ is harmonic. The solution to Eq. (1) (substituting for ϕ into Eq. (1) and using separation of variables) subject to the following boundary conditions

$$\left. \frac{\partial \phi}{\partial r} \right|_{r=a} = \left. \frac{\partial \phi}{\partial r} \right|_{r=b} = \left. \frac{\partial \phi}{\partial z} \right|_{z=-h} = 0 \dots \dots \dots (7)$$

is given by the following equation.

$$\phi = \sum_{m=0}^{\infty} \sum_{n=0}^{\infty} e^{i\omega_{mn}t} [C_{mn} \sin(m\theta) + D_{mn} \cos(m\theta)] \frac{\cosh \xi \left(\frac{z}{a} + \frac{h}{a} \right) C_m \left(\xi_{mn} \frac{r}{a} \right)}{\cosh \left(\xi_{mn} \frac{h}{a} \right) Y'_m(\xi_{mn})} \dots \dots \dots (8)$$

in which

$$C_m \left(\xi_{mn} \frac{r}{a} \right) = J_m \left(\xi_{mn} \frac{r}{a} \right) Y'_m(\xi_{mn}) - J'_m(\xi_{mn}) Y_m \left(\xi_{mn} \frac{r}{a} \right) \dots \dots \dots (9)$$

and $T(t) = e^{i\omega_{mn}t}$. The values of ξ_{mn} are given by

$$J'_m(\xi_{mn}) Y'_m(K\xi_{mn}) - Y'_m(\xi_{mn}) J'_m(K\xi_{mn}) = 0 \dots \dots \dots (9a)$$

in which $K = b/a$

To determine the natural frequencies, we apply the free-surface boundary condition

$$\frac{\partial^2 \phi}{\partial t^2} + g \frac{\partial \phi}{\partial z} = 0 \quad \text{at} \quad z = 0$$

Substituting for $\partial^2 \phi / \partial t^2$ and $\partial \phi / \partial z$, gives

$$\begin{aligned} & \sum_{m=0}^{\infty} \sum_{n=0}^{\infty} -\omega_{mn}^2 e^{i\omega_{mn}t} [C_{mn} \sin m\theta + D_{mn} \cos m\theta] \frac{C_m(\xi_{mn} \frac{r}{a})}{Y'_m(\xi_{mn})} \\ & + \frac{g}{a} \sum_{m=0}^{\infty} \sum_{n=0}^{\infty} e^{i\omega_{mn}t} \xi_{mn} [C_{mn} \sin m\theta + D_{mn} \cos m\theta] \frac{C_m(\xi_{mn} \frac{r}{a}) \tanh(\xi_{mn} \frac{h}{a})}{Y'_m(\xi_{mn})} = 0 \end{aligned}$$

and comparing the coefficients, this gives

$$\omega_{mn}^2 = \left(\frac{g}{a}\right) \xi_{mn} \tanh\left(\xi_{mn} \frac{h}{a}\right) \dots \dots \dots (10)$$

Equations (10) and (9) give sloshing frequencies and mode shapes of water in a circular annular tank. Equation (8) gives the velocity potential for free vibration and the values of the constants C_{mn} and D_{mn} will be determined by initial conditions. Equations (8), (9) and (10) are similar to the ones derived earlier in reference (5).

Velocity Potential Under Arbitrary Ground Motions

The general solution for sloshing response due to arbitrary horizontal ground motion is derived by solving equation (1) for the velocity potential ϕ for the boundary conditions given in equations (2), (3) and (4). ϕ can be used to derive displacements, velocities and pressures anywhere in the fluid.

As the boundary conditions are non-homogeneous, assume a solution of the form

$$\phi(r, \theta, z, t) = \phi_1(r, \theta, z, t) + \phi_c(r, \theta, t) \dots \dots \dots (11)$$

ϕ_c is taken independent of z because of the rigid tank walls.

$$\frac{\partial \phi}{\partial r} = \frac{\partial \phi_1}{\partial r} + \frac{\partial \phi_c}{\partial r} = \dot{x} \cos \theta \quad \text{at} \quad r=a \quad \text{and} \quad r=b$$

Let

$$\frac{\partial \phi_c}{\partial r} = \dot{x} \cos \theta$$

then

$$\frac{\partial \phi_1}{\partial r} = 0 \quad \text{at} \quad r=a \quad \text{and} \quad r=b$$

Substituting Eq. (11) into Eq. (1), we have

$$\left[\frac{\partial^2 \phi_1}{\partial r^2} + \frac{\partial^2 \phi_c}{\partial r^2} \right] + \frac{1}{r} \left[\frac{\partial \phi_1}{\partial r} + \frac{\partial \phi_c}{\partial r} \right] + \frac{1}{r^2} \left[\frac{\partial^2 \phi_1}{\partial \theta^2} + \frac{\partial^2 \phi_c}{\partial \theta^2} \right] + \frac{\partial^2 \phi_1}{\partial z^2} = 0$$

or

$$\frac{\partial^2 \phi_1}{\partial r^2} + \frac{1}{r} \frac{\partial \phi_1}{\partial r} + \frac{1}{r^2} \frac{\partial^2 \phi_1}{\partial \theta^2} + \frac{\partial^2 \phi_1}{\partial z^2} = 0 \quad \dots \dots \dots (12)$$

with the boundary conditions

$$\left. \frac{\partial \phi_1}{\partial r} \right|_{r=a} = \left. \frac{\partial \phi_1}{\partial r} \right|_{r=b} = \left. \frac{\partial \phi_1}{\partial z} \right|_{z=-h} = 0 \dots \dots \dots (13)$$

and

$$\frac{\partial^2 \phi_c}{\partial r^2} + \frac{1}{r} \frac{\partial^2 \phi_c}{\partial r} + \frac{1}{r^2} \frac{\partial^2 \phi_c}{\partial \theta^2} = 0 \dots \dots \dots (14)$$

with the boundary conditions

$$\left. \frac{\partial \phi_c}{\partial r} \right|_{r=a} = \left. \frac{\partial \phi_c}{\partial r} \right|_{r=b} = \dot{x} \cos \theta \dots \dots \dots (15)$$

The solution satisfying equations (14) and (15) is given by

$$\phi_c = \dot{x} r \cos \theta \dots \dots \dots (16)$$

Now consider the free-surface boundary condition

$$\frac{\partial^2 \phi}{\partial t^2} + g \frac{\partial \phi}{\partial z} = 0 \quad \text{at} \quad z = 0$$

$$\frac{\partial^2 \phi_1}{\partial t^2} + \frac{\partial^2 \phi_c}{\partial t^2} + g \frac{\partial \phi_1}{\partial z} = 0$$

$$\frac{\partial^2 \phi_1}{\partial t^2} + g \left. \frac{\partial \phi_1}{\partial z} \right|_{z=0} = - \frac{\partial^2 \phi_c}{\partial t^2} = - \ddot{x} r \cos \theta \dots \dots \dots (17)$$

Equation (12) must be solved with the additional boundary condition at the free surface given by Eq. (17).

Equation (12) is similar to Eq. (1) and the boundary conditions at the walls and bottom of the tank are homogeneous in both cases. Therefore the general form of the solution in these two cases will be similar except that the time function $T(t)$ will be different for the solution of Eq. (12) which was simply harmonic for the free vibration case. Thus the solution of Eq. (12) will be of the form

$$\phi_1 = \sum_{m=0}^{\infty} \sum_{n=0}^{\infty} [C_{mn} \sin m\theta + D_{mn} \cos m\theta] \frac{\cosh \xi_{mn} \left(\frac{z}{a} + \frac{h}{a} \right) c_m \left(\xi_{mn} \frac{x}{a} \right) T_{mn}(t)}{y'_m(\xi_{mn}) \cosh \left(\xi_{mn} \frac{h}{a} \right)} \dots \dots \dots (18)$$

This is the general solution and covers all types of modes. It should be noted, however, that the horizontal ground motion under consideration does not excite all types of modes. It will excite only antisymmetric modes which correspond to an m value equal to 1. Therefore the sum of m can be dropped and it is understood that all subsequent equations refer only to the class of modes which correspond to $m = 1$ and which are antisymmetric about an axis perpendicular to the axis of excitation. Thus ϕ_1 becomes

$$\phi_1 = \sum_{n=0}^{\infty} \frac{[C_n \sin \theta + D_n \cos \theta] \cosh \xi_n \left(\frac{z}{a} + \frac{h}{a} \right) c_1 \left(\xi_n \frac{x}{a} \right) T_n(t)}{y'_1(\xi_n) \cosh \left(\xi_n \frac{h}{a} \right)} \dots \dots \dots (19)$$

in which

$$c_1\left(\xi_n \frac{r}{a}\right) = J_1\left(\xi_n \frac{r}{a}\right) y_1'(\xi_n) - J_1'(\xi_n) y_1\left(\xi_n \frac{r}{a}\right) \dots \dots \dots (20)$$

and ξ_n are the roots of the equation.

$$J_1'(\xi) y_1'(\kappa\xi) - J_1'(\kappa\xi) y_1'(\xi) = 0 \dots \dots \dots (21)$$

$T_n(t)$ are the time functions yet to be determined. C_n and D_n are the constants to be determined from the initial conditions. Applying the free-surface ($z = 0$) boundary conditions given by Eq. (17), gathering like terms and dividing by a gives

$$\begin{aligned} & \frac{1}{a} \sum_{n=0}^{\infty} C_n \sin\theta c_1\left(\xi_n \frac{r}{a}\right) \frac{\left[\ddot{T}_n + \frac{g}{a} \xi_n \tanh\left(\xi_n \frac{h}{a}\right) T_n\right]}{y_1'(\xi_n)} \\ & + \frac{1}{a} \sum_{n=0}^{\infty} D_n \cos\theta c_1\left(\xi_n \frac{r}{a}\right) \frac{\left[\ddot{T}_n + \frac{g}{a} \xi_n \tanh\left(\xi_n \frac{h}{a}\right) T_n\right]}{y_1'(\xi_n)} = -\frac{r}{a} \cos\theta \ddot{x} \dots \dots \dots (22) \end{aligned}$$

Using the orthogonality property of Bessel functions

$$\frac{r}{a} = \sum_{n=0}^{\infty} A_n c_1\left(\xi_n \frac{r}{a}\right) \dots \dots \dots (23)$$

in which

$$A_n = \frac{2 \left[\frac{2}{\pi \xi_n} - KC_1 (K \xi_n) \right]}{\frac{4}{\pi^2} \xi_n^2 (\xi_n^2 - 1) + C_1^2 (K \xi_n) [1 - K^2 \xi_n^2]} \dots \dots \dots (24)$$

Substituting for r/a into Eq. (22), and comparing the coefficients,

$$\frac{D_n}{a} \frac{\left[\ddot{T}_n + \frac{g}{a} \xi_n \tanh \left(\xi_n \frac{h}{a} \right) T_n \right]}{Y_1'(\xi_n)} = -A_n \ddot{\ddot{x}} \dots \dots \dots (25)$$

$$\ddot{T}_n + \omega_n^2 T_n = -\frac{a}{D_n} Y_1'(\xi_n) A_n \ddot{\ddot{x}} = E_n \ddot{\ddot{x}} \dots \dots \dots (26)$$

in which

$$\omega_n^2 = \frac{g}{a} \xi_n \tanh \left(\xi_n \frac{h}{a} \right) \dots \dots \dots (27)$$

and

$$E_n = -\frac{a}{D_n} Y_1'(\xi_n) A_n \dots \dots \dots (28)$$

The general solution for $T_n(t)$ is given by

$$T_n(t) = \left[F_n \sin \omega_n t + G_n \cos \omega_n t + \frac{E_n}{\omega_n} \sin \omega_n t \int_0^t \ddot{\ddot{x}}(\tau) \cos \omega_n \tau d\tau \right. \\ \left. - \frac{E_n}{\omega_n} \cos \omega_n t \int_0^t \ddot{\ddot{x}}(\tau) \sin \omega_n \tau d\tau \right] \dots \dots \dots (29)$$

Thus the solution for ϕ_1 becomes

$$\phi_1 = \sum_{n=0}^{\infty} \frac{\cos \theta \cosh \xi_n \left(\frac{z}{a} + \frac{h}{a} \right) c_1 \left(\xi_n \frac{r}{a} \right) T_n(t)}{y_1'(\xi_n) \cosh \left(\xi_n \frac{h}{a} \right)} \dots \dots \dots (30)$$

Using Eqs. (11), (16) and (29)

$$\phi = r \cos \theta \dot{x} + \sum_{n=0}^{\infty} \frac{\cos \theta \cosh \xi_n \left(\frac{z}{a} + \frac{h}{a} \right) c_1 \left(\xi_n \frac{r}{a} \right)}{y_1'(\xi_n) \cosh \left(\xi_n \frac{h}{a} \right)} \cdot T_n(t) \dots \dots \dots (31)$$

Applying the initial ("at rest") conditions, namely $\phi(r, \theta, z, 0) = 0$ and $\frac{\partial \phi}{\partial t}(r, \theta, z, 0) = 0$, $F_n = G_n = 0$. Thus

$$T_n(t) = \left[\frac{E_n}{\omega_n} \sin \omega_n t \int_0^t \ddot{x} \cos \omega_n \tau d\tau - \frac{E_n}{\omega_n} \cos \omega_n t \int_0^t \ddot{x} \sin \omega_n \tau d\tau \right] \dots (32)$$

Substituting for E_n and rearranging Eq. (31)

$$\phi = \cos \theta \left\{ r \dot{x} - a \sum_{n=0}^{\infty} A_n \frac{\cosh \xi_n \left(\frac{z}{a} + \frac{h}{a} \right) c_1 \left(\xi_n \frac{r}{a} \right)}{\omega_n \cosh \left(\xi_n \frac{h}{a} \right)} \cdot T_n(t) \right\} \dots \dots \dots (33)$$

in which

$$T_n(t) = \left[\sin \omega_n t \int_0^t \ddot{x} \cos \omega_n \tau d\tau - \cos \omega_n t \int_0^t \ddot{x} \sin \omega_n \tau d\tau \right] \dots (34)$$

Equation (33) is the general expression for the velocity potential in an annular-circular tank.

Displacements, Velocities and Dynamic Pressures

Once the expression for the velocity potential is known, the fluid displacements, velocities, and dynamic pressures anywhere in the fluid can easily be derived. Let

δ = fluid displacement

U_r = fluid velocity in the direction of r

U_θ = fluid velocity in the direction of θ

U_z = fluid velocity in the direction of z

p = dynamic pressure

then

$$\delta(r, \theta, z, t) = -\frac{1}{g} \frac{\partial \phi}{\partial t}(r, \theta, z, t)$$

$$U_r(r, \theta, z, t) = \frac{\partial \phi}{\partial r}(r, \theta, z, t)$$

$$p(r, \theta, z, t) = -\rho \frac{\partial \phi(r, \theta, z, t)}{\partial t}$$

in which ρ = density of the fluid. From Eq. (33) we have the following general expressions for δ and p

$$\delta(r, \theta, z, t) = -\frac{\cos \theta}{g} \left\{ r\ddot{x} - a \sum_{n=0}^{\infty} A_n \frac{\cosh \xi_n \left(\frac{z}{a} + \frac{h}{a} \right) C_1 \left(\xi_n \frac{r}{a} \right)}{\cosh \left(\xi_n \frac{h}{a} \right)} \cdot \left[\cos \omega_n t \int_0^t \ddot{x} \cos \omega_n \tau d\tau + \sin \omega_n t \int_0^t \ddot{x} \sin \omega_n \tau d\tau \right] \right\} \dots \dots \dots (35)$$

$$p(r, \theta, z, t) = -\rho \cos \theta \left\{ r \ddot{x} - a \sum_{n=0}^{\infty} A_n \frac{\cosh \xi_n \left(\frac{z}{a} + \frac{h}{a} \right) c_1 \xi_n \frac{r}{a}}{\cosh \left(\xi_n \frac{h}{a} \right)} \right. \\ \left. \cdot \left[\cos \omega_n t \int_0^t \ddot{x} \cos \omega_n \tau d\tau + \sin \omega_n t \int_0^t \ddot{x} \sin \omega_n \tau d\tau \right] \right\} \dots \dots \dots (36)$$

Similar expressions can be derived for velocity components U_r , U_θ and U_z .

Steady-State Response

Let the ground acceleration $\ddot{x} = x_o \sin \omega_o t$, where x_o = amplitude of the ground acceleration, and ω_o = circular frequency of the ground motion. Substituting for $\ddot{x}$ in Eq. (35) and simplifying, gives

$$\delta(r, \theta, z, t) = -\frac{\cos \theta}{g} \left\{ r \ddot{x} - a \sum_{n=0}^{\infty} A_n \frac{\cosh \xi_n \left(\frac{z}{a} + \frac{h}{a} \right) c_1 \left(\xi_n \frac{r}{a} \right)}{\cosh \left(\xi_n \frac{h}{a} \right)} \right. \\ \left. \cdot \left[-\frac{x_o \sin \omega_o t}{\left(\frac{\omega_n}{\omega_o} \right)^2 - 1} + \frac{x_o \sin \omega_n t}{\frac{\omega_n}{\omega_o} - \frac{\omega_o}{\omega_n}} \right] \right\} \dots \dots \dots (37)$$

If the transient term in the above equation is neglected, the expression for the steady state displacement response δ becomes

$$\delta(r, \theta, z, t) = -\frac{\cos \theta}{g} \left\{ r x_o \sin \omega_o t - a \sum_{n=0}^{\infty} A_n \frac{\cosh \xi_n \left(\frac{z}{a} + \frac{h}{a} \right) c_1 \left(\xi_n \frac{r}{a} \right)}{\cosh \left(\xi_n \frac{h}{a} \right)} \right. \\ \left. \cdot \left[-\frac{x_o \sin \omega_o t}{\left(\frac{\omega_n}{\omega_o} \right)^2 - 1} \right] \right\} \dots \dots \dots (38)$$

Similarly, the steady-state pressure response will be given by

$$p(r, \theta, z, t) = -\rho \cos \theta \left\{ r x_o \sin \omega_o t - a \sum_{n=0}^{\infty} A_n \frac{\cosh \xi_n \left(\frac{z}{a} + \frac{h}{a} \right) C_1 \left(\xi_n \frac{r}{a} \right)}{\cosh \left(\xi_n \frac{h}{a} \right)} \right. \\ \left. \cdot \left[- \frac{x_o \sin \omega_o t}{\left(\frac{\omega_n}{\omega_o} \right)^2 - 1} \right] \right\} \dots \dots \dots (39)$$

Mode Shapes and Sloshing Response Analysis

A time-history analysis of sloshing and pressure response under earthquake ground motions was carried out by computer. A program was written to solve for mode shapes and frequencies as well as to print and plot the time-history response of water displacements and pressures along the axis of ground excitation.

Figure 3a shows the first and second anti-symmetric mode shapes and Figure 3b gives the associated water surface profiles for an annular tank in which $h:b:a = 1:2:3$ at Section A-A Figure 1. The profile at any other section can be determined by multiplying with $\cos \theta$. For a typical prototype structure [$a = 60$ ft. (18.3 m), $b = 40$ ft. (12.2 m), $h = 20$ ft. (6.1 m)], the first and second natural frequencies are 0.079 and 0.36 Hz respectively. Figure 4a shows the time-history of water displacements at the inner and outer walls of the prototype tank under El Centro 1940 earthquake. Similar plots were obtained for the pressure response and Figure 4b shows the impulsive dynamic pressure variation with depth at the inner and outer walls of the prototype structure at the time of peak ground acceleration of 0.34 g.

MODEL STUDY

To verify the analytical results, tests were carried out on both small and large scale models as follows:

1. Small Scale Models

These tests were conducted on a 3 x 4 ft. (.92 x 1.22 m) shaking table capable of applying harmonic motions (Fig. 5a). Two 18 in. (45.71 cm) outside diameter plexiglass models were studied: model 1 had an inside diameter of 12 in. (30.5 cm) and was thus a 1/80th scale model of the prototype; model 2 had an inside diameter of 6 in. (15.24 cm). In both tests the water depth was 3 in. (7.62 cm).

The models were instrumented to measure the surface wave heights near the inner walls. The frequency of the table motion was known from the function generator and the amplitude of table motion was measured with an accelerometer. Natural sloshing frequencies and water displacements under steady state sinusoidal table motion were determined and the measured and equivalent analytical results are given in Tables 1 and 2. These forced vibration tests show a good agreement with the analytical values.

2. Large Scale Tests

These tests were conducted on the 20 ft. x 20 ft. (6.1 x 6.1 m) shaking table at the Earthquake Engineering Research Center at the University of California, Berkeley (Figure 5b). An 8 ft. (2.44 m) diameter steel tank with plexiglass observation windows and an inside diameter of 5 ft. 6 in. (1.67 m) represented a 1/15th scale model of the prototype suppression pool. Tests were conducted using time-scaled accelerograms of the El Centro (1940) and Parkfield earthquakes. Wave

heights and dynamic pressures were recorded at the locations shown in Figures 6 and 7 at a sampling speed of 100 per second.

Figures 8, 9, and 10 show the wave-height comparisons for increasing intensities of the El Centro earthquake, the form and duration of the earthquake remaining the same in all cases and the peak accelerations for the three tests being 0.24g, 0.31g, and 0.44g respectively. Figure 11 shows the computed and measured dynamic pressures at gage 1 at the bottom of the outer wall for the El Centro earthquake with 0.31g peak acceleration.

The wave-height tests indicate that even for a strong earthquake of the form of the El Centro accelerogram with significant long period energy the linear theory provides a reasonably accurate means of computing water surface displacements. In Figure 8 for a peak acceleration of 0.24g the correlation is extremely good indicating that the response is well within the linear range. In Figure 9, at the actual El Centro intensity, the results are still acceptable even though the effect of a slight nonlinearity is beginning to show: the response is not as sinusoidal in that the positive upward displacements are greater than the downward and there is a slight increase in period with amplitude. This effect is even more noticeable in Figure 10 which shows the response due to a ground motion of intensity 40% above the actual El Centro motion. Even in this extreme case however the computed values may be adequate for design purposes remembering that the most important response value is the maximum downward displacement at the inner wall.

The range of linear behavior will, of course, depend on the pre-dominant response mode as well as on the geometry of the tank, and the

values shown for the El Centro earthquake indicate the range of linearity for one particular tank when the response is primarily in the second mode. The maximum water surface gradient in this case taken as $2\delta_{\max}/(a-b)$ is approximately 1/5 which would indicate a linearity range for cases where radial modes predominate.

APPLICATION TO SIMPLE CYLINDRICAL TANKS

The theoretical results for the general annular tank problem can also be applied to a cylindrical tank as this is a limiting case of an annular tank as the inner radius approaches zero.

In order to check the validity of this solution, a comparison was made with test results obtained from another study(7) conducted on flexible cylindrical tanks. In this study the flexibility of the tanks, though having a significant influence on the stresses in the tank walls, had little effect on the overall sloshing response of the liquid. The test results shown in Figure 12 are for a 12 ft. (3.66 m) diameter tank, and for a water depth of 5 ft. (1.53 m). Both measured and computed time-histories are shown for the water-surface at the outer wall for the El Centro earthquake increased in intensity to a peak of 0.5g. The correlation between the two is very close indicating that the general annular tank solution is applicable to this case also and that the response is essentially within the linear range. It should be noted that in this analysis the inner radius cannot be made zero, and in the solution given it was made small enough (0.1 in.) to have a negligible effect on the overall response.

CONCLUSIONS

A good correlation between the test and computer results shows that the linearized small displacement theory can accurately predict the sloshing displacements and dynamic pressures in annular cylindrical as well as simple cylindrical tanks under earthquake motions. The range of linearity is quite large even in annular tanks of the type under consideration and the analysis gives satisfactory results as long as displacements remain within approximately 30 in. (76.2 cm) for the prototype being studied. The linearity range for simple cylindrical tanks of the same size is much larger.

The second mode is the dominant sloshing mode of vibration in the prototype tank for all of the earthquake motions studied, namely El Centro, Pacoima Dam and Housner's (11) artificial accelerogram A1, A2, B1, B2. The maximum displacement always occurs at the inner wall.

ACKNOWLEDGEMENTS

This investigation was sponsored by the United States Nuclear Regulatory Commission and the Lawrence Berkeley Laboratory and was done with support from the United States Department of Energy. The opinions, findings, and conclusion expressed in this paper are those of the writers and not necessarily of the sponsors.

TABLE I. Test and analytical frequencies of Models 1 and 2 for Depth of Water $h = 3$ in.

Mode Number	Model 1		Model 2	
	Test	Theory	Test	Theory
1	0.70	0.70	0.90	0.88
2	3.20	3.17	2.30	2.31
3	4.50	4.47	3.20	3.22
4	5.50	5.47	3.90	3.92

TABLE 2. Sloshing response of water in Models 1 and 2 under sinusoidal ground accelerations ($h = 3$ in.).

Frequency (Hz)	Acceleration (g)	Maximum Displacement at Inner Wall (Inches)			
		Model 1		Model 2	
		Test	Theory	Test	Theory
0.6	0.00585	0.167	0.153	0.040	0.042
1.2	0.0312	0.184	0.180	0.308	0.321
2.0	0.0530	0.168	0.174	0.580	0.586
3.7	0.0742	0.271	0.237	0.196	0.201

FIG. 1 ANNULAR TANK SHOWING COORDINATE SYSTEM

XBL 782-7210

FIG. 2 CROSS-SECTION THROUGH THE ANNULUS OF A
TYPICAL PRESSURE SUPPRESSION POOL OF
A BOILING WATER REACTOR (MARK III)
(1 FT. = 0.305 M)

XBL 782-7217 A

(a)

(b)

FIG. 3 FIRST AND SECOND ANTI-SYMMETRIC
MODE SHAPES

XBL 782-7212 A

Fig. 4a SLOSHING RESPONSE OF WATER IN ANNULAR TANK (INNER RADIUS = 480 IN., OUTER RADIUS = 720 IN., DEPTH OF WATER = 240 IN.) UNDER EL CENTRO 1940 EARTHQUAKE (1 IN. = 2.54 cm).

XBL783-500

FIG. 4b PRESSURE DISTRIBUTION IN PROTOTYPE
(1 IN. = 2.54 cm, 1 LB. = 4.5 N)

XBL782-7208

CBB 762-1195A

FIG. 5a. TEST SET-UP FOR SMALL SCALE MODEL TESTS

FIG 5b. 8 FT. STEEL TANK ON 20 × 20 FT.
SHAKING TABLE (1 FT. = 0.305 M)

XBB 779-8772 A

FIG. 6 LOCATION OF WATER DISPLACEMENT GAGES (1 IN. = 2.54 cm)

FIG. 7 LOCATION OF PRESSURE GAGES (1 IN. = 2.54 cm)

XBL 782-7215 A

FIG. 8 SLOSHING RESPONSE OF WATER IN ANNULAR TANK (INNER RADIUS = 33.2 IN., OUTER RADIUS = 48.0 IN., DEPTH OF WATER = 16.0 IN.) UNDER EL CENTRO EQ. 1940 (COMPARISON OF THEORY AND TEST 211276.1 (1 IN. = 2.54 cm)

XBL782 7209A

FIG. 9. SLOSHING RESPONSE OF WATER IN ANNULAR TANK (INNER RADIUS = 33.2 IN., OUTER RADIUS = 48.0 IN., DEPTH OF WATER = 16.0 IN.) UNDER EL CENTRO EARTHQUAKE (COMPARISON OF THEORY AND TEST 201276.21) (1 IN. = 2.54 cm)

XBL783-501

FIG. 10. SLOSHING RESPONSE OF WATER IN ANNULAR TANK (INNER RADIUS = 33.2 IN., OUTER RADIUS = 48.0 IN., DEPTH OF WATER = 16.0 IN.) UNDER EL CENTRO EARTHQUAKE 1940 (COMPARISON OF THEORY AND TEST 2112762) (1 IN. = 2.54 cm)

XBL782-7216A

FIG.II PRESSURE RESPONSE OF WATER IN ANNULAR TANK (INNER RADIUS = 33.2 IN., OUTER RADIUS = 48.0 IN., DEPTH OF WATER = 16.0 IN.) UNDER EL CENTRO EARTHQUAKE 1940 (COMPARISON OF THEORY AND TEST 201276.21) (1 IN. = 2.54 cm, 1 LB. = 4.45 N).

FIG. 12 SLOSHING RESPONSE OF WATER IN ANNULAR TANK (INNER RADIUS = 0.1 IN., OUTER RADIUS = 72.0 IN., DEPTH OF WATER = 60.0 IN.) UNDER EL CENTRO EARTHQUAKE (1940)
TIME SCALE = 1.73 (1 IN. = 2.54 cm)

XBL 782-7213A

APPENDIX I.—REFERENCES

1. Bauer, H.F. "Fluid Oscillations in a Circular Cylindrical Tank," American Boilers Manufacturers Association (ABMA), Report DA-TR-1-58.
2. Bauer, H.F., "Fluid Oscillations in a Cylindrical Tank with Damping," ABMA Report DA-TR-4-58.
3. Bauer, H.F., "Fluid Oscillations in a Circular Cylindrical Tank Due to Bending of Tank Walls," ABMA Report DA-3-58.
4. Bauer, H.F., "Damped Fluid Oscillations in a Circular Cylindrical Tank Due to Bending Walls," ABMA Report DA-9-58.
5. Bauer, H.F., "The Dynamic Behavior of Liquids in Moving Containers," National Aeronautics and Space Administration, Washington, D.C., 1966, edited by H. Norman Abramson.
6. Budiansky, B., "Sloshing of Liquids in Circular Canals and Spherical Tanks," Lockheed Aircraft Corp. LMSD-5151, Dec. 1958.
7. Clough, D.P., "Experimental Evaluation of Seismic Design Methods for Broad Cylindrical Tanks," Ph.D. Dissertation, University of California, Berkeley, 1976.
8. Graham, E.W., and Rodriguez, A.M., "The Characteristics of Fuel Motion which Affect Airplane Dynamics," Journal of Applied Mechanics, Vol. 19, No. 3, Sept. 1952.
9. Jacobson, L.S. and Ayre, R.S., "Hydrodynamic Experiments with Rigid Cylindrical Tanks Subjected to Transient Motions," Bulletin of Seismological Society of America, Vol. 41, Oct. 1951.
10. Jacobson, L.S. and Ayre, R.S., "Hydrodynamic Experiments with Rigid Cylindrical Tanks Subjected to Transient Motions, Bull. Seism. Soc. of America, Vol. 41, 1952.

11. Jennings, P.C., Housner, G.W., and Tsai, N.C., "Simulated Earthquake Motions," California Institute of Technology, Pasadena, CA, April 1968.
12. Kachigan, K., "Forced Oscillations of a Fluid in a Cylindrical Tank," Convair Report ZU-7-046, Oct. 1956.
13. Miles, J., "On the Sloshing of Liquid in a Flexible Tank, ASME, Paper No. 57-A-12, 1957.
14. Miles, J., "On the Sloshing of a Liquid in a Cylindrical Tank," Ramo-Wooldridge AM-6-5, CM-TR-18, 1956.
15. Schmitt, A.F., "Forced Oscillations of a Fluid in a Cylindrical Tank Undergoing Both Translation and Rotation," Convair Report ZU-7-069, Oct. 1956.
16. Stoker, J.J., "Water Waves," Interscience Publishers, Inc., New York, 1957.

APPENDIX II—NOTATION

a	=	Outer radius of the tank
b	=	Inner radius of the tank
g	=	Acceleration of gravity
h, H	=	Depth of water in the tank
J_m	=	Bessel functions of first kind and order m
J'_m	=	Derivative of J_m
p	=	dynamic pressure
r	=	Radius
t	=	Time
U_r	=	Velocity in r direction
U_θ	=	Velocity in θ direction

U_z	=	Velocity in z direction
x	=	Ground displacement
$\dot{x}$	=	Ground velocity (dx/dt - dot means derivative w.r.t.t)
Y_m	=	Bessel functions of second kind and order m
z	=	z-Coordinate direction
ϕ	=	Velocity potential
θ	=	θ -Coordinate direction
ω_n	=	Sloshing frequency (circular)
ω_o	=	Ground frequency (circular)
δ	=	Water displacement
$\delta_{\max}$	=	Maximum water displacement

This report was done with support from the Department of Energy. Any conclusions or opinions expressed in this report represent solely those of the author(s) and not necessarily those of The Regents of the University of California, the Lawrence Berkeley Laboratory or the Department of Energy.

TECHNICAL INFORMATION DEPARTMENT
LAWRENCE BERKELEY LABORATORY
UNIVERSITY OF CALIFORNIA
BERKELEY, CALIFORNIA 94720