Lawrence Berkeley National Laboratory

Recent Work

Title

Extreme compression of heavy ion beam pulses: Experiments and modeling

Permalink

<https://escholarship.org/uc/item/903923gj>

Authors

Sefkow, A.B.
Davidson, R.C.
Efthimion, P.
et al.

Publication Date

2008-11-01

Extreme Compression of Heavy Ion Beam Pulses: Experiments and Modeling

- * A. B. Sefkow, R. C. Davidson, P. Efthimion, E. P. Gilson, I. Kaganovich
PPPL, Princeton, New Jersey
- * J. J. Barnard
LLNL, Livermore, California
- * J. E. Coleman, P. K. Roy, P. A. Seidl
LBNL, Berkeley, California
- * D. R. Welch
Voss Scientific, Albuquerque, New Mexico

Funding: Research supported by the U. S. Department of Energy.

Intense heavy ion beam pulses need to be compressed in both the transverse and longitudinal directions for warm dense matter and heavy ion fusion applications. Previous experiments and simulations utilized a drift region filled with high-density plasma in order to neutralize the space-charge and current of a 300 keV K⁺ beam, and achieved transverse and longitudinal focusing separately to a radius < 2 mm and pulse width < 5 ns, respectively. To achieve simultaneous beam compression, a strong solenoid is employed near the end of the drift region in order to transversely focus the beam to the longitudinal focal plane. Simulations of near-term experiments predict that the ion beam can be focused to a sub-mm spot size coincident with the longitudinal focal plane, reaching a peak beam density in the range 10^{12} - 10^{13} cm⁻³, provided that the plasma density is large enough for adequate neutralization. Optimizing the compression under the appropriate experimental constraints offers the potential of delivering higher intensity per unit length of accelerator to the target, thereby allowing more compact and cost-effective accelerators and transport lines to be used as ion beam drivers.

Supported by the U.S. Department of Energy under Contract No. DE-AC02-05CH11231.