# Lawrence Berkeley National Laboratory

**Recent Work** 

Title

THE INSTABILITY OF FRONTS IN A POROUS MEDIUM

**Permalink** https://escholarship.org/uc/item/9wm3j66c

**Author** Chorin, A.J.

Publication Date 1983-04-01

LBL-15893 Preprint

R-15843

# Lawrence Berkeley Laboratory

UNIVERSITY OF CALIFORNIA

# Physics, Computer Science & Mathematics Division

LIBRARY AND

DOCUMENTS SECTION

RF

Submitted for publication

THE INSTABILITY OF FRONTS IN A POROUS MEDIUM

A.J. Chorin

April 1983

# TWO-WEEK LOAN COPY

This is a Library Circulating Copy which may be borrowed for two weeks. For a personal retention copy, call Tech. Info. Division, Ext. 6782.



Prepared for the U.S. Department of Energy under Contract DE-AC03-76SF00098

#### DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California. LBL-15893 PAM-149

## THE INSTABILITY OF FRONTS IN A POROUS MEDIUM<sup>1</sup>

#### Alexandre Joel Chorin<sup>2</sup>

#### Department of Mathematics and Lawrence Berkeley Laboratory University of California Berkeley, California 94720

#### **April 1983**

<sup>&</sup>lt;sup>1</sup>This work was supported in part by the Director, Office of Energy Research, Office of Basic Energy Sciences, Engineering, Mathematical, and Geosciences Division of the U.S. Department of Energy, under Contract DE-AC03-76SF00098, and in part by the Office of Naval Research, under Contract N00014-76-C-0316.

<sup>&</sup>lt;sup>2</sup>The work was performed while the author was a Miller Research Professor at the University of California at Berkeley.

#### Abstract

We use a random choice numerical method to analyze the instability of a front separating two fluids in a porous medium. We observe a linear instability and a catastrophic finite amplitude instability. A qualitative analogy with problems involving a transition to turbulence is pointed out.

#### Introduction

The goal of this paper is to present an analysis of the onset of instability in a front separating two fluids in a porous medium. The analysis will be based on Glimm's (random choice) numerical method. The front is known to be unstable for sufficiently large values of a parameter  $\mu$ , the viscosity ratio. We shall show that there exist two kinds of instability: for  $\mu \ge \mu_0 = 3$ , small perturbations that are spatially smooth will grow slowly; for  $\mu \ge \mu_1 < \mu_0$ , perturbations of large enough amplitude grow catastrophically. The two types of instability can interact.

The results and the numerical method are of practical significance in problems of oil flow and reservoir engineering. A random choice method [13], [3], [4] has been previously applied to such problems by Concus et al. [1], [10], Glimm et al. [14], [15], and Lotstedt [19]. Our method differs from earlier work in several respects, the most important of which is the fact that we keep some two dimensional information in order to reduce the possibility that one dimensional sweeps misinterpret the nature of waves moving diagonally across the grid. The possibility of large errors in this situation has been pointed out by Crandall and Majda [11], [12] and by Colella [9]. We do not track fronts.

The results regarding the different kinds of instability resemble strongly other phenomena previously observed in hydrodynamics (see e.g. [5],[7],[22]). We have a continuum of unstable modes which can combine strongly to generate phenomena reminiscent of turbulence and intermittency. The present calculation may be helpful in explaining the gap between linearized stability theory and experiment in more difficult problems. These questions are discussed in the

concluding section of the paper.

#### The equations of motion, the Riemann problem, and linearized stability theory

The incompressible flow of two immiscible fluids in a porous medium can be described by the following equations (see [24],[16],[21]):

$$\mathbf{s}_t + \mathbf{u} \cdot \nabla f(\mathbf{s}) = 0 \tag{1a}$$

$$\nabla \cdot \mathbf{u} = 0 \tag{1b}$$

$$\mathbf{u} = -\lambda(s) \nabla p , \qquad (1c)$$

where s is the saturation of one of the fluids (which we shall think of as being "water"), t is the time,  $\mathbf{x} = (x,y)$  is the spatial coordinate,  $\mathbf{u} = (u,v)$  is the velocity, p is the pressure,  $\lambda$  is the total mobility, and f is the fractional flow function (for explanations of those terms see [24]). Equation (1a) is known as the Buckley-Leverett equation, (1b) expresses incompressibility, and (1c) is Darcy's law. We shall pick

$$\lambda(s) = s^2 + (1-s)^2 / \mu , \qquad (2a)$$

$$f(s) = s^2 / \lambda(s)$$
 (2b)

where  $\mu$  is the viscosity ratio between the two fluids. (We shall think of the one which is not "water" as being "oil".) These choices correspond to immiscible flow. Note that f is not a convex function of s.

We shall be solving these equations in the square  $0 \le x \le 1$ ,  $0 \le y \le 1$ , subject to the boundary conditions:

$$\frac{\partial s}{\partial x} = 0 , \quad \frac{\partial p}{\partial x} = 0 \text{ on } x = 0.1 ,$$

$$\frac{\partial s}{\partial y} = 0 , \quad p = 1 \text{ on } y = 0 ,$$

$$\frac{\partial s}{\partial y} = 0 , \quad p = 0 \text{ on } y = 1 ,$$
(3)

and a variety of initial conditions s(x, y, 0).

The solutions of equations (1) develop discontinuities, and we assume that discontinuities in two space dimensions satisfy jump conditions identical to those which arise in the scalar problem

$$\mathbf{s}_t + u f_x = 0 \quad , \quad f = f(\mathbf{s}) \quad (4)$$

where x denotes the variable normal to the discontinuity. We shall now summarize some facts about equation (4); a detailed presentation is available in [10].

Let  $u \equiv 1$  in equation (4). Let  $s_l, s_r$  be the values of s to the left and to the right of a jump discontinuity. The solution of (4) is unique and depends continuously on the data only if the jump in s satisfies Oleinik's condition (E):

$$\frac{f(s_r) - f(s)}{s_r - s} \le \frac{f(s_r) - f(s_l)}{s_r - s_l}$$
(E)

for all s between  $s_l$  and  $s_r$ . (For an elementary discussion, see [8].)

Consider the Riemann problem for equation (4),  $u \equiv 1$ , i.e., equation (4) subject to the initial data

$$s = \begin{cases} s_l & \text{for } x < 0 \\ s_r & \text{for } x > 0 \end{cases}$$

The states  $s_l, s_r$  will be connected by either a shock, or a rarefaction wave, or a combined shock and rarefaction. All shocks must obey condition (E), which determines uniquely the allowed connecting waves.

If the chord connecting the points  $(s_l, f(s_l))$  and  $(s_r, f(s_r))$  in the (s, f)plane nowhere intersects the graph of f, then if  $a(s_l) > a(s_r)$ ,  $a \equiv \frac{df}{ds}$ , the connecting wave is a shock with speed  $\frac{dx}{dt} = (f(s_r) - f(s_l))/(s_r - s_l)$ ; if, on the other hand,  $a(s_l) \le a(s_r)$ , the connecting wave is a rarefaction. If the chord connecting  $(s_l, f(s_l))$  and  $(s_r, f(s_r))$  does intersect the graph of f, which can happen since f is not convex, there are again two possibilities. If  $s_l > s_r$ , we construct the convex hull of f in  $[s_l, s_r]$ , i.e., the smallest convex function  $H(s) \ge f(s)$ . Our f has a single inflection point and thus H consists of a straight line of slope S and a portion of the graph of f, the two being tangent to each other at a point  $(s_0, f(s_0))$ . If  $s_r = 0$ ,  $s_0 = (1+\mu)^{-\frac{\pi}{2}}$ . The wave connecting  $s_l$  and  $s_r$  is a shock moving with speed S followed by a suitable rarefaction wave (see fig. 1a). If, on the other hand,  $s_l < s_r$ , we construct the concave hull of f and determine the wave structure from its shape (fig. 1b). For full details, see [10].

Consider a physical problem in which water and oil are coexisting in a porous medium without mixing (a description of the physics can be found in [24]). In the region occupied by oil s = 0, in the region occupied by water s > 0. The discussion in the preceding paragraph indicates that if water is displacing oil the convex hull of f is used to determine the solution, which consists of a shock followed by rarefaction. If oil is displacing water, the concave hull is used, with analogous conclusions. This construction has been worked out in [24] by physical arguments with no explicit use of condition (E).

Suppose  $u \neq 1$ , u > 0, in equation (4); the wave speeds are merely scaled by u. If u < 0, the roles of  $s_l, s_r$ , are interchanged in the discussion above; i.e., if the driving velocity changes sign, the displaced fluid becomes the displacing fluid.

Consider a water/oil front coinciding with the x axis, moving steadily in the direction of increasing y (fig. 2), with water below the x axis and oil above. We wish to consider the stability of the front to small perturbations. The suffix "-" refers to quantities defined in the water and the suffix "+" to qualities defined in the oil.

In the oil phase  $s = s_{\pm} = 0$ . At the front,  $s_{\pm} = s_0 = (1+\mu)^{-\frac{1}{2}}$ . The quantity  $\lambda(s_0)/\lambda(0) \equiv M$  is called the mobility ratio. Write  $p_{\pm} = P_{\pm} + p'_{\pm}$ ,  $s_{\pm} = S_{\pm} + s'_{\pm}$ ,  $v_{\pm} = V_{\pm} + v'_{\pm}$ , etc., where the capitals denote unperturbed quantities and the primes denote perturbations. Let  $\nabla P_{\pm} = (0, G_{\pm})$ . From equations (1b),(1c), we find

$$G_{+}\lambda(0) = G_{-}\lambda(s_{0})$$
,  $G_{+}, G_{-} > 0$ ,  
 $P_{+} = G_{+}y$ ,  $P_{-} = G_{-}y$ .

Substitution into equation (1a) yields, to first order in small quantities,

$$(s'_{-})_{t} + V_{-}a(S_{-})(s'_{-})_{y} = A s'_{-}, a \equiv \frac{df}{ds}.$$

where A is a function of  $S_{-}$ . On the front itself  $s_{-}=s_{0}$ ,  $s'_{-}=0$ , and thus  $s'_{-}\equiv 0$  everywhere.

From this point on, the analysis follows Chuoke's argument, published by Saffman and Taylor [23]: From equations (1b),(1c), we find

$$\Delta p'_{+} = 0 , \qquad \nabla \cdot \lambda(S_{-}) \nabla p'_{-} = 0$$

with p and v continuous across the front.

Since the saturation  $s_{-}$  below the front forms a rarefaction, the values of  $s_{-}$  approach  $s_{0}$ , and it is natural to look at the simpler problem with  $s_{-} \equiv s_{0}$ , and thus

$$\Delta p'_{-} = 0$$

We now perturb the front so that it coincides with the curve

$$y = \varepsilon \exp(i\alpha x + \sigma t)$$
.

An appropriate choice of the forms of  $p'_{-},p'_{+}$  yields

$$p'_{\pm} = C_{\pm}e^{\pm ay} \exp(i\alpha x + \sigma t)$$
,  $C_{\pm}, C_{\pm} \text{ constants}$ .

The boundary conditions yield, after some manipulation,

$$\frac{\sigma}{\alpha} \left( \frac{1}{\lambda(s_0)} + \frac{1}{\lambda(0)} \right) = G_+(M-1) , \quad M = Mobility \ ratio; \tag{5}$$

For M > 1,  $\sigma > 0$  for all  $\alpha$  and the front is unstable. M > 1 if  $\mu > 3$ . Note that  $\sigma$  is proportional to  $\alpha$ , suggesting that the instability is very strong; (compare with the instability of a vortex sheet [18].) There is a continuum of unstable modes.

#### The numerical method

We shall be solving equations (1) by a generalization of the random choice method [13],[3],[4],[10],[15]. The time t is discretized into steps of length k. The quantities p, s, u, v are defined on a staggered grid of mesh length h (fig. 3), following [17]: p and s are defined at (ij, jh), i.j integers, u is defined at  $((i+\frac{1}{2})h, jh), v$  is defined at  $(ih, (j+\frac{1}{2})h)$ ; we write  $s(ih, jh) = s_{i,j}$  etc. The boundary conditions (3) are approximated in the obvious manner.

At the beginning of the (n+1)st time step, it is assumed that the quantities p.s.u.v are known. Equation (1a) is used to calculate  $s_{i,j}^{n+1} = s_{i,j}$  at the new time via the random choice method. Equation (1b),(1c) are then used to update p and u.

The one dimensional version of the random choice method can be described as follows: consider the equation

$$s_t + uf_x$$
,  $f = f(s)$ ,  $u$  given.

At time t the saturation s is assumed known at the points ih, i integer; s is extended to a function constant on the intervals  $[(i-\frac{1}{2})h,(i+\frac{1}{2})h]$ . The resulting initial value problem is solved exactly; the solutions consists of independent Riemann solutions if the CFL condition is satisfied:

$$\boldsymbol{k} \leq h \max(|\boldsymbol{u}|\boldsymbol{a}(s_i,s_{i+1}))),$$

where  $\alpha(s_i, s_{i+1})$  is the largest velocity which can occur in the solution of the Riemann problem separating  $s_i$  and  $s_{i+1}$ . We shall assume that this condition is satisfied. The Riemann solutions are then sampled to obtain new values of s. The sampling strategy determines the accuracy of the calculation. Following Colella [9], we use a sampling based on van der Corput sequences. We modify the sequence when necessary to ensure that if  $\vartheta_n \cdot \vartheta_{n+1}$  are successive samples,  $-\frac{1}{2} < \vartheta_n \cdot \vartheta_{n+1} < +\frac{1}{2}$ , then  $\vartheta_n \cdot \vartheta_{n+1} > 0$ . (The reasons are explained in [4].) Furthermore, we also follow Colella's modification of the sampling which allows the values of s to be defined on a fixed spatial grid without staggering; when this is done, it is natural to define u in equation (4) at the points  $(i+\frac{1}{2})h$ , as will be done in our two dimensional grid.

The natural way to generalize this scheme to two space dimensions is to solve successively the problems

$$s_t + uf_x = 0 \quad , \quad s_t + vf_v = 0 \quad .$$

The flaw in that procedure, pointed out by Colella [9] and Majda [11],[12], lies in the fact that a front which lies diagonally across the grid can be interpreted in one of the directional sweeps as representing water displacing oil and in the other sweep as oil displacing water. Examples of errors which arise in such situations can be found in [11], and the construction which follows is designed to avoid them. Other authors [16],[19], have tried to avoid this difficulty by tracking the fronts.

The general idea is to decide which kind of front is really occurring by using some local two-dimensional information in the one-dimensional sweeps. One can require, without loss of accuracy, that the sampling numbers used in the two directional sweeps be always either both positive or both negative. Assume this has been done. Consider the *x*-sweep, i.e., the sweep in which the equation being solved is  $s_t + uf_x = 0$ . For the full equation (1a), if  $\mathbf{u} \nabla f < 0$ , water is

displacing oil and the convex hull of the function f determines the Riemann solution. The opposite is true if if  $\mathbf{u} \cdot \nabla f > 0$ . Consider the point (i,j), assume  $u_{i-\chi_i j} > 0, v_{i,j-\chi} > 0$ , and evaluate the quantities

$$\rho_{1} = u_{i \to j} (f(s_{i,j}) - f(s_{i-1,j})) ,$$
  
$$\rho_{2} = v_{i,j \to j} (f(s_{i,j}) - f(s_{i,j-1})) ,$$

If  $\rho_1\rho_2 \ge 0$ , the wave is interpreted in the same way in both the sweep we are performing and in a hypothetical y-sweep, and the x-sweep does not have to be modified. The level lines of s are likely to look as in fig. 4a or fig. 4b.

Suppose  $\rho_1 \rho_2 < 0$ . The likely level lines look as in fig. 4c. Evaluate

$$\rho'_{2} = v_{i-1,j-\frac{j}{2}}(f(s_{i-1,j}) - f(s_{i-1,j-1})).$$

Let  $\rho = \rho_1 + \rho'_2$ . If  $\rho \le 0$  water is displacing oil, and if  $\rho > 0$ , oil is displacing water. If  $\rho \le 0$  and  $s_{i-1,j} \ge s_{i,j}$  or  $\rho > 0$  and  $s_{i-1,j} \le s_{i,j}$  the one dimensional sweep is interpreting the wave correctly. In the other cases the sweep is misinterpreting the nature of the wave and the roles of convex and concave hulls have to be interchanged. This is easily done: one exchanges the roles of  $s_i, s_r$  in the Riemann solver and replaces  $\vartheta$  by  $-\frac{1}{2}-\vartheta$  if  $\vartheta$  is negative, by  $\frac{1}{2}-\vartheta$  if  $\vartheta$  is positive. Note that the one-dimensional sweep may now violate condition (E).

There are three analogous cases to be considered:  $u_{i-\frac{n}{2},j} > 0$ ,  $v_{i,j+\frac{n}{2}} < 0$ , then  $u_{i+\frac{n}{2},j} < 0$ ,  $v_{i,j-\frac{n}{2}} > 0$  and finally  $u_{i-\frac{n}{2},j} < 0$ .  $v_{i,j+\frac{n}{2}} < 0$ . Similarly, there are four cases to consider in the *y*-sweep. Note that the decision process we have just described is not unambiguous: it may well happen that  $v_{i,j-\frac{n}{2}} > 0$  but  $v_{i,j+\frac{n}{2}} < 0$ . Such cases are presumably rare, the corresponding values of v small, and in practice the ambiguity presents no problem.

Finally, given  $s^{n+1}$ , the new values of p and u are found by approximating (1b) by

$$u_{i+\frac{1}{2},j} = \frac{1}{2} (\lambda(s_{i+1,j}) + \lambda(s_{i,j})) (p_{i+1,j} - p_{i,j}) / h$$

with a similar expression for v, and approximating  $\nabla \mathbf{u}$  by  $D\mathbf{u}$  given by

$$hDu = u_{i+\chi_j} - u_{i-\chi_j} + v_{i,j+\chi} - v_{i,j-\chi}$$

The resulting elliptic equation for p is self-consistent in the sense of [2], and thus there are no fictitious sources of s in the domain of integration. Also, the flux of s is conserved, and the natural discrete form of  $\nabla \times \nabla p = 0$  is satisfied. This guarantees that we are finding the correct weak solutions of our elliptic equation (see the analysis in [14]). There is no need to worry about the legitimacy of differencing across the front.

The algebraic equations which arise from equations (1b),(1c) can be solved in a variety of ways (see e.g. [11],[16]). We have obtained satisfactory results by an overrelaxation method with a position dependent relaxation factor.

The method has been successfully tested on several test problems whose solution is known. The calculations presented in the next section also act as a check.

#### Numerical results

#### (a) Growth of small perturbations

The linearized stability theory we have presented predicts that for  $\mu > 3$ small perturbations will grow exponentially. The rate of growth is however relatively small. If we assume  $\alpha = \pi$ , then  $\sigma^{-1}$ , the *e*-folding time as predicted by equation (5), will be ~160 for  $\mu = 3.1$ . Even if we consider the smallest  $\alpha$  which can be represented on an economical grid, the corresponding rate of growth is hard to observe in view of the stronger instability we shall discuss in the next section. Note that during the time it takes for a perturbation of small amplitude to grow the front is likely to leave our computational domain. This can be remedied by performing a translation of the form s'(x,y,t) = s(x,y + Y,t). Y = constant, whenever needed.

As a way of exhibiting the linearly unstable modes, consider the initial conditions:  $s(x,y,0) = s_0$  for  $0 \le x \le 1/3$  and  $0 \le y \le 1/2$ ,  $s = s_0$  for  $1/3 \le x \le 2/3$  and  $0 \le y \le 1/2 + 1/12$ ,  $s = s_0$  for  $2/3 \le x \le 1$  and  $0 \le y \le 1/2$ , s = 0 otherwise (this is a front with an extrusion in its middle third). In Table I we display the values of the vertical velocity v on the line y = 1/2 for  $\mu = 2.9$  and  $\mu = 3.1$ . For  $\mu = 2.9 v$  is smaller in the region of the extrusion, thus reducing its size; the opposite is true for  $\mu = 3.1$ .  $\mu = 3.0$  is then seen to be the dividing point between stable and unstable behavior. Note that the differences in v are in the fourth significant digit.

We have run some initial value problems with s in the water close to  $s_0$  and  $\mu$  close to 3,  $\mu > 3$ , and observed a growth of perturbations on a time scale compatible with linear theory. We omit the pictures which are singularly undramatic.

#### (b) Growth of finite amplitude perturbations

In figs. 5 and 6 we display the flow that arises from the front perturbed as depicted for various values of  $\mu$ . In each point occupied by water we print the integer [10s], where the square bracket denotes the integer part. When s = 1, we print 9. This device is similar to the one used by Glimm [15] and is necessary because it has not proved possible to design a contour plotter which gives a good account of the complexity of the flow.

In fig. 5 the initial perturbation has a very small physical extent. For  $\mu < 2.8$  the flow is stable in the simplest way: the perturbation simply disappears. For  $\mu$  between 2.8 and 3.5 we observe a paradoxical effect. An initial extrusion of water becomes an intrusion of oil with a little "foam" in front. The particular structure of the foam is quite likely to be a numerical artifact. The reason for this phenomenon is quite obvious: since x is not convex (see fig. 1), and s is

larger behind the extrusion, the velocity of water is smaller there. If the values of v are not large enough to make up for this effect, oil will intrude. After that intrusion the flow changes very slowly; presumably, if  $\mu > 3$ , the perturbation will grow on a time scale consistent with the linearized theory. When  $\mu \cong 3.6$  the paradoxical effect disappears, and for  $\mu \ge 3.6$  we see the rapid growth of a thin finger. The eventual complexity of the flow can be seen in fig. 5i.

In fig. 6 the initial perturbation has a larger lateral extent and thus more energy for overcoming the paradoxical effect. Note that the perturbation is growing rapidly even for  $\mu = 2.8$ , below the critical value of the linearized theory.

The perturbation has a better chance of growing if: (i) its amplitude is increased, (ii) its physical extent is increased, (iii)  $\mu$  is increased, and (iv) the gradients of s below the front are increased. We have not been able to characterize the successful perturbations in a mathematical reasonable way, nor to relate the finite amplitude catastrophic instability to the linear theory. Clearly, when finite amplitude perturbations are allowed, the larger values of s below the front can affect the front and create a large "eddy" mobility ratio. Note that the main new feature of our numerical method, i.e., the modification of the splitting, has little bearing on the analysis of the early stages of finite amplitude instability in our geometry. The important balance is between the solution of the elliptic equations (1b).(1c) and the properties of the one dimensional Riemann solution. The fingers we are seeing are of the same kind as the ones previously observed by Concus, Glimm, and Lotstedt. For experimental results, see e.g. [14].

The results regarding stability are compatible with those in [13] and [19]: the front is stable for  $\mu = 2$  (M = .845) and dramatically unstable for  $\mu = 4$ (M = 1.105). A finite amplitude perturbation is needed to generate an instability that can be discerned in a reasonable time. It remains to see whether our amplitudes are comparable with those in [15],[16], since previous authors provide few data around  $\mu = 3$ . Above  $\mu = 4$ , the amplitude needed may well be comparable with truncation and round-off error.

One can also display interesting runs in which a small perturbation grows for a while as per the linearized theory and, once some threshold is crossed, begins to grow at a much faster rate. Finally, even when  $s=s_0$  below the front, large enough perturbations grow much faster than the linear theory predicts.

Note that the range of mobility ratios in which these phenomena occur is very small: below M = .97 all perturbations decay both in the linearized mode and in the short run for large perturbations; above M = 1.06 our calculation show a catastrophic growth of perturbations whose physical extent is a single mesh cell in a 20×20 grid. As far as we know, ours is the first calculation in which the onset of instability is computed reliably.

#### (c) Fractalization

It is natural to wonder what happens to the front beyond the onset of instability. A look at fig. 5i and the much more complex figures which are obtained with a finer grid, as well as the fact that equations (1) are invariant under changes of time and length scales, suggest that the front eventually approximates a fractal set (i.e., a set of non-integer Hausdorff dimension; see e.g. [20]).

To test this conjecture we proceed as follows: At t = 0 assume the front is flat, represent it on an  $n_1 \times n_1$  grid, and give it a random perturbation. This is easily done by adding to the  $\vartheta$ 's in the random choice method a small random component which is a function of  $\mathbf{x}$  and t (such a device was already used in [16]). Turn off the perturbation when the front has changed its length and the instability has set in, and compute up to a time  $T_1$ . Suppose that at time  $T_1$  the number of cells which lie on the boundary between water and oil is  $l_1$ . Suppose we were to restart the calculation on an  $n_2 \times n_2$  grid, and run up to the same time  $T_1$ , with  $n_2 > n_1$ . We would get more detail, and if the number  $l_2$ of boundary points is larger than  $l_1 \times (n_2/n_1)$  we have grounds for the belief that the boundary is a fractal set.

Once we reach the time  $T_1$  with the second calculation, we can take the subsquare  $0 \le x \le \beta$ ,  $0 \le y \le \beta$ ,  $\beta = n_1/n_2$ , expand it to fill the whole square and increase the time scale by the factor  $1/\beta$ . Since the equations are invariant under simultaneous changes of scale in time and space, the resulting configuration could have been obtained by running the initial calculation up to a time  $T_1/\beta$ . (There are some minor differences at the boundaries of the domain which are presumably insignificant; a similar device was used in [6]). Thus we can obtain estimate of the Hausdorff dimension D of the boundary between oil and water by comparing the results of a single calculation at different times. If  $l_i$  is the number of boundary points at time  $T_i$ , and  $l_{i+1}$  is the number of boundary points at time  $T_i$  and  $l_i$  is the dimension D is approximated by

 $D \sim [\log L_{i+1}/L_i) / \log (T_{i+1}/T_i)] + 1$ 

We pick  $T_i = i \ 20k_0$ , where  $k_0$  is a typical time step; in Table II we list some computed values of D. The calculations have to be stopped whenever the boundary set fails to fit into our computational domain. The validity of the calculation is not obvious, in particular because it is far from obvious that it is legitimate to compute when the fingers are one mesh width thick, and because it is unclear that the neglected detail at any stage of the computation should not have an effect on what is actually seen. One could speculate that the results in Table II suggest a value  $D \sim 1.5$  for  $\mu$  large enough.

If indeed a process of fractalization does occur, it is obvious that the numerical results obtained from equations (1) in the unstable regime are wholly

unreliable and other effects, such as capillary pressure, must be taken into account in practical problems. Finally, in fig. 7 we show a typical detail of the flow with  $\mu = 28$ . This should be compared with the photographs in [25].

#### Conclusions

The application of our method to flow problems of direct interest in petroleum reservoir engineering will be presented elsewhere. We would like to emphasize here the broader significance of the results:

We have seen that linearized stability theory for the fronts described by equations (1) predicts a continuum of linearly unstable modes. These modes can be detected if a calculation is done carefully enough, but the important feature of the real instability is the catastrophic growth of localized finite amplitude perturbations which is accompanied by "chaos" in physical space. This situation parallels the transition to turbulence in a boundary layer (see e.g. [5] and the references therein, in particular [22]). In the case of a boundary layer, the unstable modes of the linearized theory are the Tollmien-Schlichting waves, and the analogues of the fingers are the "bursts" connected with the catastrophic stretching of horseshoe vortices. Similar scenarios arise also in the analysis of three dimensional vortex motion [7]. Equations (1) may thus provide a simple model of transition to turbulence in problems where the number of active modes is not restricted by the effects of buoyancy or imposed rotation.

**Note:** The programs used in the calculations above are available from the author.

Acknowledgment: I would like to thank Professor A. Majda for many illuminating discussions.

#### References

- [1] N. Albright, P. Concus, and W. Proskurowski, SPE paper 7681 (1979).
- [2] A.J. Chorin, Math. Comp., 22, 745-762 (1969).
- [3] A.J. Chorin, J. Comp. Phys., 22, 517-533 (1976).
- [4] A.J. Chorin, J. Comp. Phys., 25, 253-272 (1977).
- [5] A.J. Chorin, SIAM J. Sci. Stat. Comp., 1, 1-21 (1980).
- [6] A.J. Chorin, Comm. Pure Appl. Math., 34, 853-866 (1981).
- [7] A.J. Chorin, Comm. Math. Phys., 83, 517-535 (1982).
- [8] A.J. Chorin and J.E. Marsden, A mathematical introduction to fluid mechanics, Springer, N.Y. (1979).
- [9] P. Colella, SIAM J. Sci. Stat. Comp., 3, 76-110 (1982).
- [10] P. Concus and W. Proskurowski, J. Comp. Phys., 30, 153-166 (1979).
- [11] M. Crandall and A. Majda, Numerische Math., 34, 285-314 (1980).
- [12] M. Crandall and A. Majda, Math. Comp., 34, 1-14 (1980).
- [13] J. Glimm, Comm. Pure Appl. Math., 18, 697-715 (1965).
- [14] J. Glimm and D. Marchesin, J. Comp. Phys., 38, 179-200 (1981).
- [15] J. Glimm, D. Marchesin, and O. McBryan, Comm. Math. Phys., 74, 1-13 (1980).
- [16] J. Glimm, D. Marchesin, and O. McBryan, Comm. Pure Appl. Math., 24, 53-75 (1981).
- [17] F. Harlow and J. Welch, *Phys. Fluids*, 8, 2182-2188 (1965).
- [18] L. Landau and E. Lifshitz, Fluid mechanics, Pergamon, London (1959).
- [19] P. Lotstedt, J. Comp. Phys., 47, 211-228 (1982).
- [20] B. Mandelbrot, Fractals: form, chance and dimension, Freeman, San Francisco (1975).

- [21] D.W Peaceman, Fundamentals of numerical reservoir simulation. Elsevier. Amsterdam/N.Y. (1977).
- [22] H.L. Rogler and E. Reshotko, SIAM J. Appl. Math., 28, 431-441 (1975).
- [23] P. Saffman and G. Taylor, Proc. Roy. Soc., A. 245, 312-322 (1958).
- [24] A.E. Scheidegger, The physics of flow in porous media, University of Toronto Press, Toronto (1974).

[25] R.A. Wooding, J. Fluid Mech., 39, 477-495 (1969).

## Table I

# Vertical Velocity in Slightly Perturbed Flows

x	μ=2.9	$\mu = 3.1$
1/2	.3427	.3245
2/12	.3427	.3245
3/12	.3427	3245
4/12	.3426	.3249
5/12	.3422	.3250
6/12	.3421	.3249
7/12	.3422	.3246
8/12	.3426	.3245
9/12	.3427	. <b>32</b> 45
10/12	.3427	.3245
11/12	.3427	.3245

## Table II

#### Estimates of D

μ=28, 30×30 grid: 1.33 1.79 1.71 1.01 0.68 1.24 average: 1.30	$\mu = 28$ , 40×40 grid: 1.35 1.35 1.83 0.91 1.54 1.99 1.48 1.79 1.00 average: 1.44							
$\mu = 10, 30 \times 30 \text{ grid}:$ 1.26 1.36 1.52 1.31 2.27 1.51 1.33 2.35 1.46 average: 1.59	$\mu = 10, 40 \times 40 \text{ grid}:$ 1.32 1.60 1.36 0.31 0.88 1.45 1.07 1.35 1.33 1.85 1.21 average: 1.25							
μ = 5, 30×30 grid: 1.28 1.44 1.33 1.66 1.16 1.38 0.91 1.10 1.33 1.54 1.00 2.08 1.06 1.30 1.46 1.64 1.64 1.49	μ = 5, 40×40 grid: 1.25 0.97 1.16 1.89 1.46 1.28 1.45 1.45 1.44 1.57 1.22 1.23 2.68 2.86 1.61 0.88 2.03 2.26 1.00							

average: 1.38

2.75 average: 1.60

#### List of Figure Captions

Figures 1a,b: Convex and concave hulls of f.

Figure 2: The perturbation analysis.

Figure 3: The computational grid.

Figures 4a,b,c: The front relative to the two-dimensional grid.

Figures 5a,b,c,d,e,f,g,h,i: Effects of a small perturbation.

Figures 6a,b,c,d,e: Effects of a larger perturbation.

Figure 7: Partial view of a computed front,  $\mu = 28$ .



Figure la



Figure lb







b

Figure 3











# Figure 4c

 $\mu = 2.8, t = .90$ 

#### 

¥

#### Initial Perturbation

 $\mu = 2, t = .98$ 

 $\mu = 3.0, t = 1.06$ 

4	4
44444 444444	
555554 44 5555555	4444444444444444444444444
555554444444 55555555	444444444444444444444444444444444444444
66666444444445666666	555555555555555555555555555555555555555
6666655555555666666	666666666666666666666666666666666666666
666665555556556666666	666666666666666666666666666666666666666
77777666666666777777	666666666666666666666666666666666666666
9999977777777999999	77777777777777777777777777
999999999999999999999	9999999999999999999999999
999999999999999999 <u>99</u> 9	99999999999999999999999999
9999999999999999999999	9999999999999999999999999
y = 3.2 + = .96	$\mu = 3.6, t = .95$

 $\mu = 3.2, t = .96$ 

	44
	544
	555
	55
	444
	544
5	4444444555444444444
55	555555565555555555555555555555555555555
7	555555566655555555555555555555555555555
9	555555566655555555555555555555555555555
9	555555566655555555555555555555555555555
4444444494444444444	666655557775555555555
666666666666666666666666666666666666666	7666666999666666666
999999999999999999999	999999999999999999999999
999999999999999999999	9999999999999999999999999

 $\mu = 3.7, t = .51$ 

 $\mu = 4$ , t = .97

= .95

Figures 5e, f, g, h

 $\mu = 20$ , t = 1.50

5555 55555 

μ = 2	.7,	t =	.51
and the second s			

#### initial perturbation

5	55555 555
55	55555 5555
555	55555555
5566	55 666656665 555
555555557755555555	55555777755575555555
666666666666666666	66666588868885555888
777766666696677677777	66666699979996666666
77777777977777777777	7777799999997777777
99998888898888899999	99999999999999999999999999999999999999
9999999999999999999999	99999999999999999999999999
9999999999999999999999	99999999999999999999999999
YYY999999999999999999999	9999999999999999999999999

 $\mu = 2.8, t = .66$ 

#### $\mu = 2.9, t = .69$

#### Figures 6a,b,c,d

. .

					5	5	5				5	5							
				5	5	5	5				5	5	5						
					5	5	5	5	5	5	5	5	5						
5	5				6	6	6	5	5	5	6	6	6					5	5
5	5	5	5	5	7	7	7	6	6	6	6	6	7	5	5	5	5	5	5
6	6	6	6	5	5	8	8	6	6	6	6	6	5	5	6	6	6	6	6
6	6	6	6	6	6	9	9	7	7	7	9	9	6	6	6	6	6	6	6
7	7	7	7	7	7	9	9	9	9	9	9	9	7	7	7	7	7	7	7
9	9	9	9	9	9	9	9	9	9	9	9	9	8	8	9	9	9	9	9
9	9.	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9
9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9
99	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9

$$\mu = 3.0, t = .69$$

Figure 6e

																					9					
	99	1		9				9	9	)								9			9					
	99	9		99	99	9	•	9	9	9	ł	9	9		9	9		9			9		9		9	
	99			4	99	9	. '	9	9	99		9	9		9	9		9			9	9	9		9	
9	99			ç	99	9	9	9	9	9		9	9		9	9		9			9	9	9		9	
9	99				9	9	99	9	9	9	9	9	9	9	9	9	9	9			9	9	9		9	
9	99	99	9	99	99	9	99	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	
9	99	99	9	99	99	9	99	9	39	9	9	9	9	9	9	9	9	9	99	9	9	9	9	9	9	
9	99	99	99	99	9	9	99	)	99	9	9	9	9	9	9	9	9	9	99	9	9	9	9	9	9	

# $\mu$ = 28, t = .91, 40 × 40 grid (detail)

Figure 7

This report was done with support from the Department of Energy. Any conclusions or opinions expressed in this report represent solely those of the author(s) and not necessarily those of The Regents of the University of California, the Lawrence Berkeley Laboratory or the Department of Energy.

Reference to a company or product name does not imply approval or recommendation of the product by the University of California or the U.S. Department of Energy to the exclusion of others that may be suitable.

TECHNICAL INFORMATION DEPARTMENT LAWRENCE BERKELEY LABORATORY BERKELEY, CALIFORNIA 94720 UNIVERSITY OF CALIFORNIA Í