

Lawrence Berkeley National Laboratory

Recent Work

Title

RADIOACTIVITY OF GEOTHERMAL SYSTEMS

Permalink

<https://escholarship.org/uc/item/9zh5z5ck>

Author

Wollenberg, Harold A.

Publication Date

1975-05-01

0 0 0 0 4 2 0 2 5 5 7

Presented at the Second United Nations
Symposium on the Development and Use
of Geothermal Resources, San Francisco, CA,
May 19 - 29, 1975

LBL-3232
c.1

RADIOACTIVITY OF GEOTHERMAL SYSTEMS

Harold A. Wollenberg


May 1975

RECEIVED

OCT 2 1975

Prepared for the U. S. Energy Research and
Development Administration under Contract W-7405-ENG-48

For Reference
Not to be taken from this room



LBL-3232
c.1

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.

RADIOACTIVITY OF GEOTHERMAL SYSTEMS*

Harold A. Wollenberg

Lawrence Berkeley Laboratory
University of California
Berkeley, California 94720

ABSTRACT

Radioactivity anomalies associated with hot spring systems have been recognized and documented for many decades. The most observable radioelements in hot waters are radium-226 and radon-222, both members of the uranium-238 decay series. An examination of hot spring waters in Nevada indicates the presence of these radioelements, in varying abundances, in spring systems where CaCO_3 is the predominant material being deposited. Systems where silica predominates are relatively low in radioactivity. At a hot spring site in north-central Nevada where CaCO_3 predominates, gamma-ray levels from 0.25 to 0.5 milliroentgens per hour were measured over an enclosed warm pool. At other systems where SiO_2 predominates, gamma exposure rates are nearly two orders of magnitude lower.

The emanation of ^{222}Rn from thermalized fault zones is a possible exploration tool in locating a geothermal resource. An alpha-track detector survey within a potential resource area indicates anomalously high Rn associated with hot pools, but a rather featureless Rn pattern in valley alluvium away from the hot springs.

Results of studies combining neutron activation analyses of hot and cold waters in a region, and radiometric analyses of the waters and hot spring deposits, suggest that uranium entering a geothermal system is localized at depth by (1) a reducing environment afforded by H_2S and (2) precipitation of uranyl carbonate. The presence of the U at depth is indicated at the surface by its daughter products, Ra and Rn, in hot spring waters and deposits.

Along with these geochemical aspects, an understanding of the radioactivity of a geothermal resource is necessary to evaluate the environmental impact of its possible future development.

*Work performed under the auspices of the U. S. Energy Research and Development Administration.

INTRODUCTION

Radioactive anomalies associated with mineral- and hot-spring systems have been recognized and documented by many scientists. For example, Pöhl-Rüling and Scheminzky (1972) described the radium- and radon-rich environment of Bad Gastein, an Austrian spa celebrated for decades for its healing hot radioactive air, waters, and muds. Earlier, Belin (1959) described the occurrence of radon in New Zealand geothermal regions, and Mazor (1962) related radium and radon in Israeli water sources with oil, gas, and brine reservoirs of the Rift Valley. Since the late 1940's several Japanese scientists, among them Kimura (1949), Kikkawa (1954), and Hitaye (1962), have reported on the association of radioelements and hot- and mineral-spring systems. Scott and Barker (1962) made a comprehensive tabulation of uranium and radium contents of ground waters of the United States. Most recently, Stoker and Kruger in these Proceedings, describe the radon environment of geothermal reservoirs.

Hot spring areas in northern Nevada, USA, have been visited to evaluate sites for a geothermal energy program (Mirk and Wollenberg, 1974). The radioactivity of the spring systems is being studied (Wollenberg, 1974a), with the expectation that knowledge of the distribution and abundance of their radioelement contents helps define the plumbing systems operating beneath the springs; equally important, an assessment of the environmental impact of potential geothermal resource sites requires an understanding of their radioactive setting.

This paper is comprised of three parts: the first describes radioactivities and radioelements in and around some hot spring areas; second is a speculative assessment of the mechanism and magnitude of concentration of uranium at depth within some geothermal systems; and finally, the application of a relatively new method of radon detection as a geothermal exploration technique is described. The methods and concepts covered here, though applied to occurrences in the Great

Basin of the western United States, may also be relevant to geothermal systems in similar tectonic settings, parts of the earth's crust undergoing extension, characterized by normal faulting.


HOT SPRING RADIOACTIVITIES

Location

The hot-spring areas examined are shown on the location map (Fig. 1) and are listed by name on Tables I and II. At the sites field gamma radioactivity was measured with a portable NaI(Tl) scintillation detector 7.6 cm in diameter and 7.6 cm thick, coupled to a count-rate meter (the instrumentation is shown in Fig. 2). Field radioactivities were measured over hot pools, sinter (SiO_2 -rich), and tufa (CaCO_3 -rich) deposits, and also away from the spring areas to obtain background values. Figure 3 shows typical measurement conditions at a hot spring in Ruby Valley, Nevada. Samples of spring-deposit tufa, sinter, spring-wall muck, and water were collected at all sites, and on return to the laboratory, were analyzed for uranium-238, thorium-232, their daughter products, and potassium-40 by gamma-ray spectrometry.

Field Measurement Results

Results of field measurements and laboratory gamma-ray spectrometric analyses are shown on Tables I and II. Table I summarizes the field radiometric data; radioactivities are expressed in microrentgens per hour ($\mu\text{R/hr}$), based on calibration of the field instrument (counts/sec to $\mu\text{R/hr}$) with a radium source of known strength. Immediately apparent is the association of high radioactivities, "anomalies," with CaCO_3 -rich spring deposits; with one exception, Lee Hot Springs, silica-rich deposits have no anomalies. The greatest radioactivities, 250-500 $\mu\text{R/hr}$, were observed over hot pools (75-90°C) at Kyle Hot Springs, while the lowest values, two orders of magnitude lower than at Kyle, were measured over hot and boiling pools and sinter at Beowawe Hot Springs. In no case was there any apparent connection



XBL7410-4334

Fig. 1

0 0 0 0 4 2 0 2 5 6 0

-5-



CBB 741-134

Fig. 2



CBB 739-5185

Fig. 3

between surface spring temperature and radioactivity. Among the spring systems where CaCO_3 predominates there were no anomalies associated with blowing wells, nor with the fast-flowing spring at Fly Ranch. A strong radioactivity contrast exists at Darroughs Hot Springs where there is no apparent anomaly in the vicinity of a moderately blowing well, while approximately 200 meters away 75 $\mu\text{R/hr}$ was observed over a still pool. Thus, radioactive anomalies in the hot-spring areas appear to be associated with low-flowing CaCO_3 -rich systems. An inverse correlation of radioactivity with flow rate was observed by Vincenz (1959) at a mineral spring in Jamaica.

Where tufa and sinter are both present in a deposit, the calcareous material is highest in radioactivity. This is exemplified at Lee Hot Springs where sinter is the predominant spring deposit material; spotty zones of high radioactivity were observed over intermixed patches of tufa, while neighboring sinter was comparatively low. Similarly, tufa is highest in radioactivity at Gerlach Hot Springs where siliceous and calcareous zones intermingle.

At Buffalo Valley and Kyle Hot Springs, CaCO_3 -rich sites, sharp field-radiometric anomalies were detected downwind from pools, indicating the emanation of ^{222}Rn from the waters and spring walls.

Laboratory Measurement Results

Spring Deposits

Table II summarizes laboratory gamma-spectrometric analyses of spring-deposit materials. As with the field data, the high radioactivities, attributable primarily to equivalent U are associated with the calcareous hot-spring deposits. Siliceous deposits are comparatively low in U and Th, and most have Th/U ratios similar to those of ordinary siliceous rocks. Exceptions are the mixed tufa and sinter soil at Lee Hot Springs, where the tufa introduces relatively high equivalent U, and the low-radioactivity sinter terrace at Steamboat Hot Springs.

Table I. Field gamma radiometry of spring areas.

Location	Gamma exposure rates ($\mu\text{R/hr}$)		Remarks
	General background	Anomalously high radioactivity	
<i>Spring systems where CaCO_3 is the predominant deposit</i>			
Gerlach	6.25 - 7.5	60 - 65	Tufa, high rad. zone
Gerlach	--	20 - 25	Mixed sinter and tufa
Fly Ranch	6.25 - 8.75	None apparent	Travertine
Kyle	12.5 - 25	250 - 500	Over radioactive pools
Elko	7.5 - 10	19	Tufa at edge of pool
Buffalo Valley	6.25 - 7.5	30 - 38	Tufa mounds
Spencers	5 - 10	19	Tufa at edge of pools
Diana's Punchbowl	5 - 10	16	Springs at base of tufa mound
Wabuska	3.75 - 6.25	None apparent	Blowing wells
Darroughs	15 - 20	75	Edge of fenced pool
Darroughs	10 - 12.5	None apparent	Moderately blowing well
Golconda	12.5 - 17.5	37.5 - 175	Pools and interconnecting streams
Pumpnickel	7.5 - 10	17.5 - 22.5	Small pool
Pumpnickel	15	17.5	Outflow stream
<i>Spring systems where SiO_2 is the predominant deposit</i>			
Brady's	5 - 7.5	--	Sinter soil
Beowawe	2 - 2.5	--	Sinter apron
Beowawe	13.8 - 17.5	--	Andesite, escarpment above blowing wells
Big Sulfur (Ruby V.)	2.5 - 5	--	Sinter
Leach	5 - 7.5	--	Sinter
Lee	5 - 7.5	20 - 25	Tufa and sinter
Lee	--	10	Edge of pool
Steamboat	2.5 - 4	--	Main terrace sinter
Steamboat	6.9	--	Altered granitics, west area, blowing well

Table II. Laboratory gamma spectrometry of spring deposits.


Location	Description	Th (ppm)	Equivalent U			Th/U
			U (ppm)	K (%)	$^{226}\text{Ra}^*$ (pCi/g)	
<i>Spring systems where CaCO_3 is the predominant deposit</i>						
Gerlach	Tufa, high radioactivity zone	13.41	109.25	1.02	39	0.12
	Predominantly Si sinter, some tufa	2.38	33.3	0.41	12	0.07
Fly Ranch	Travertine	2.14	10.99	0.02	4	0.19
Kyle	Calcareous muck from spring walls	11.62	76.32	0.16	27	0.15
	Travertine away from active springs	0.19	4.06	0.09	1.5	0.05
Elko	Tufa	3.12	7.60	0.07	2.7	0.41
Buffalo Valley	Calcareous muck from a small mound	45.89	25.49	0.21	9.2	1.80
	Predominantly tufa, some Si sinter	6.20	65.67	0.35	23.7	0.09
Spencers	Predominantly calcareous mud	10.92	11.54	1.51	4.1	0.95
Golconda	Spring wall tufa	31.20	469.6	--	169	0.07
Pumpnickel	Calcareous muck from small pool	6.33	8.19	0.46	2.9	0.77
<i>Spring systems where SiO_2 is the predominant deposit</i>						
Brady	Mud from hot vent	6.32	2.93	0.41		2.15
Beowawe	Andesite, escarpment above blowing wells	15.99	3.28	3.74		4.88
	Sinter soil, vicinity of hot pools	0.91	0.37	0.40		2.43
Big Sulfur (Ruby Valley)	Sinter	0.18	0.11	0.16		1.60
Leach	Sinter	1.08	0.72	0.35		1.50
Lee	Sinter	4.76	2.49	1.11		1.91
	Tufa and sinter	3.71	11.67	0.51		0.31
Steamboat	Sinter, main terrace	0.30	1.42	0.13		0.21
	Sinter and altered granitics, west area	8.10	4.90	1.13		1.65

* Calculated from activities ratio, $^{226}\text{Ra}/^{238}\text{U} = 2.78 \times 10^6$.

For guidance in the following discussion the uranium decay series is shown in Fig. 4. The uranium values in Table II are listed as equivalent because they are based on the gamma-ray peaks of ^{214}Bi , one of the radioactive decay products of ^{226}Ra . Radium-226, in some chemical environments, may be completely separated from its parent ^{238}U , transported in bicarbonate-rich waters, and deposited with CaCO_3 on spring walls in the upper portions of a spring system (Tanner, 1964). Therefore, the high equivalent U in samples of calcareous deposits actually indicates ^{226}Ra anomalies. Uranium-238 or its decay products higher in atomic mass number than ^{226}Ra are missing. This was disclosed by examining high-resolution gamma-ray spectra of the calcareous samples, counted on a Ge(Li) detector system. Figure 5 displays superimposed gamma-ray spectra, in the X-ray energy region, of a ^{226}Ra source, calcareous muck from Kyle Hot Springs, and an equilibrium ^{238}U standard. The muck and ^{226}Ra source spectra match peak for peak. The U-standard spectrum shows the characteristic Bi and Pb X-ray peaks, as well as peaks from precursors to Ra in the U decay series. Corroborative evidence for radon anomalies in the calcareous material is furnished by comparison of the intensities of peaks at 186 and 352 keV (not shown on Fig. 5) in the equilibrium and Ra spectra. In the U spectrum 62% of the 186-keV peak is from ^{226}Ra , 38% from ^{235}U , while all of the 352-keV peak is from ^{214}Po , a Ra daughter; the ratio of counts in the 352-keV peak to counts in the 186-keV peak is approximately 2. In samples of Ra-rich spring deposits the corresponding peak ratios are approximately 3, indicating the absence of the ^{235}U component in the 186-keV peak.


Waters

Samples of water, approximately 550 ml, were collected from all of the springs for subsequent laboratory gamma-ray spectrometry. Radon-222 was indicated by the presence of the 1.76-MeV peak of ^{214}Bi in the gamma spectra of seven of the water



XBL741- 2101

Fig. 4



XBL7311 - 4599

Fig. 5

samples. Several days elapsed between collection and laboratory analyses of the samples. Therefore, it is expected that in some of the samples ^{222}Rn activity (a 3.8-day half-life) had decayed below detectability. Repeated gamma counting of the samples from Buffalo Valley, Kyle, and Gerlach Hot Springs showed that the ^{214}Bi activity decayed with the Rn half-life, indicating that there was little or no ^{226}Ra in these waters. Otherwise, Ra would have resupplied Rn, eventually achieving radioactive equilibrium between these isotopes. The ^{214}Bi activities of the measurable water samples and their calculated ^{222}Rn contents are listed in Table III. There is no apparent correlation between the radioactivities of the waters and those of the calcareous hot-spring deposits. The comparatively high radioactivities of the waters from Pumpnickel and Lee Hot Springs, compared with the relatively low activities of corresponding spring deposit material, suggests that these waters may contain radon from sources other than the radium on near-surface spring walls. Planned sampling of hot-spring waters shall include on-site radon analyses and chemical separation of radium, which, coupled with subsequent laboratory analyses, should determine the component of radon from radium in the waters and the component emanating from radium deposited near the surface.

Table III. Radioactivity and radon content of hot-spring waters.


Location	Net radioactivity in 1.76 MeV peak of ^{214}Bi (counts $\text{min}^{-1} \text{g}^{-1}$) ^a	Calculated ^{222}Rn content (pCi ℓ^{-1})
Gerlach	0.0117	258
Kyle	0.0179	587
Buffalo Valley	0.0034	73
Golconda	0.0070	207
Pumpnickel:		
Small pool	0.0362	1299
Outflow	0.0162	543
Lee	0.0166	556

^aCorrected for 3.8-day half life of ^{222}Rn .

GEOHERMAL CONCENTRATION OF URANIUM

Uranium contents of hot- and cold-spring waters, and springflow volumes can be combined to furnish an estimate of the amount of uranium which may be concentrating at depth within a geothermal system. At this stage of our studies, such estimates must be treated as speculative. Speculations are based on several assumptions, not the least tenuous of which is the model of a geothermal system, illustrated in Fig. 6. In this model it is assumed that meteoric waters enter a geothermal system after transversing country-rock aquifers of varying intrinsic U contents. The geothermal system is provided by convection cells within a permeable fault zone, penetrating deeply (3 to 5 km) into a region where geothermal gradients may range from 30 to over $50^{\circ}\text{C km}^{-1}$. In northern Nevada, uranium contents of bedrock terranes vary from 1 to a few ppm in Tertiary basaltic and Mesozoic clastic and carbonate rocks, up to 10 to 20 ppm in Tertiary acidic volcanic rocks and Mesozoic plutons. These variations in uranium are similar to variations in many other terranes throughout the world.

Chemical contents of cold springs in these bedrock terranes may be indicative of chemistries of groundwaters percolating into geothermal fault zone systems. Such data are described in another paper in this Symposium (Bowman et al., 1975). Hot- and cold-spring uranium contents (by neutron activation analysis) are summarized on Table IV. Inspection of Table IV indicates that uranium contents of cold spring waters are appreciable (1 to over 3 ppb), while hot springs have very little uranium. But, as has been pointed out in earlier sections, spring systems depositing CaCO_3 , such as Kyle and Buffalo Valley hot springs, have appreciable contents of uranium daughters in waters and deposits. At these locations, one can postulate that uranium may be concentrating at depth within the geothermal systems. (It may also be concentrating at depth in systems dominated by SiO_2 , but its presence is not obvious because U-daughters are not



CBB 743-1509

Fig. 6

abundant in these springs.) The mechanism of concentration is twofold. Uranium, as the uranyl (U^{+6}) ion is fairly mobile in an oxidizing environment. Uranyl carbonate may be transported in groundwater into a geothermal system, where it is reduced to U^{+4} in a reducing environment afforded to a large part by H_2S , a ubiquitous component of hot springs. Uranyl carbonate, as is the case with most carbonates, has retrograde solubility; it precipitates at high temperature (Blake et al., 1956). Thus, the presence of a high-temperature, reducing environment favors concentration of U, as it is reduced from U^{+6} to U^{+4} , and the carbonate is precipitated.

The amounts of uranium concentrating at depth in the systems at Kyle, Leach, and Buffalo Valley Hot Springs are estimated on Table IV. Estimates are based on flow rates of the hot springs (Olmsted et al., 1975), U contents of hot- and cold-spring waters, and the assumption that U contents of cold spring waters represent U contents of groundwaters entering the geothermal systems. These estimates suggest that uranium concentrations of the order of several tens of Kg may have formed over several thousand years. Such time spans are not unreasonable, considering the ephemeral nature of hot springs in this region of tectonic instability, the Basin and Range geomorphic province.

Table IV. Estimation of uranium deposition rates in three hot-spring systems.

Location	Mean U content (ppb)		Difference	Flow rate (ml y^{-1})*	U deposition (g y^{-1})
	Cold waters	Hot waters			
Buffalo Valley	1.3	~ 0.1	1.2	2.1×10^{11}	2.52×10^2
Kyle	3.07	~ 0.5	2.6	1.05×10^{10}	2.73×10^1
Leach	1.52	~ 0.2	1.3	3.5×10^{11}	4.52×10^2

* from Olmsted et al. (1975) for Buffalo Valley and Leach; Mariner et al. (1974) for Kyle.

RADON ALPHA-TRACK SURVEY

The registration of alpha particles in plastics has been applied to the search for uranium in recent years. The basic track etch concept (Fleischer et al., 1972) was modified and patented by scientists of the Terradex Corporation (Alter, 1972)

and the General Electric Vallecitos Laboratory to detect alpha particles from the decay of radon-222, a gaseous daughter product of uranium-238. Inverted plastic cups with a specially treated dielectric alpha-track detector attached inside are placed, each in an approximately 0.5 m-deep hole, in arrays of varying extent. The walls of the cup are thick enough to exclude alpha particles from radon in the air surrounding the cup; the only contribution is from radon emanating from soil directly beneath the mouth of the inverted cup. After exposure of several weeks, the cups are retrieved, the detectors removed and etched, revealing track densities proportional to the emanating radon flux. Significant uranium ore bodies, not detected by more traditional gamma-ray surveys, have been discovered by this method (Gingrich, 1974). It has been shown that radon travels through several tens of meters of overburden, which otherwise conceals an ore deposit by shielding its gamma radiation.

Earlier in this paper the association was described of radon emanations with some hot spring systems, especially those where calcium carbonate predominates. It was considered that an array of radon alpha-track detectors near and away from a radioactive spring system might indicate fault zones along which warm, radon- and radium-enriched waters were migrating. Israël and Björnsson (1967) described high concentrations of soil-gas radon associated with such fault zones in the vicinities of Bad Nauheim and Aachen.

Procedures

For the Nevada studies, a good test site was afforded by hot springs in Buffalo Valley in the north-central part of the state (site #7 on location map, Fig. 1). Because of the sharply varying gamma-ray fields measured at the springs, a set of alpha-track detectors was installed in their immediate area (a map of the hot springs area, showing detector locations, comprises Fig. 7). Also, an array of detectors, covering a much larger area, was installed in the valley surrounding the hot springs; detector locations and track density contours are shown in Fig. 8. The track etch

detectors, mounted in plastic cups, were generously provided and processed by the Terradex Corporation (a track etch service corporation affiliate of General Electric).

Uranium and Radon

Comparison of track densities and uranium content of surficial material provides a qualitative indicator of the effect, if any, of soil uranium on the observed track densities. Therefore, to determine the uranium content of the soil directly beneath and surrounding the cups, samples of soil from the cup holes were collected and later analyzed for natural radioelement contents by gamma spectrometry at Lawrence Berkeley Laboratory. There is no apparent correlation between near-surface uranium content and track density (Wollenberg, 1974b). Frequency distributions of U and track densities are shown as histograms in Fig. 9. The ranges of U content are not nearly so broad as the range in track densities.

Radon Emanation in the Vicinity of the Hot Springs

Inspection of the map (Fig. 7) shows that the small pools and mounds at Buffalo Valley Hot Springs, from which radon emanates, are associated with high track densities (several hundred to several thousand tracks/mm²) in detectors placed nearby. However, at some locations only a few tens of meters away from the mounds and pools, well within the springs area, track densities are "normal" (tens of tracks/mm²), while at other locations, roughly equidistant from the radioactive pools, densities are appreciably greater than normal. Therefore, radon emanations vary sharply within the springs area, though a general north-south-trending "high" is indicated on Fig. 7.

At sample locations in the hot springs area, total gamma radioactivity was measured by a 3-inch-diameter by 3-inch-thick NaI(Tl) detector, on the surface and within the approximately 15 cm-diameter holes dug for the radon detectors. The contribution of emanating radon to the observed gamma radioactivity was estimated

by subtracting the count rate calculated from the U, Th, and K contents of soil samples, from the total observed count rate. (Calculations were based on concentration-to-exposure rate conversion factors in Beck et al. (1968), and the exposure rate-to-count rate calibration for the field gamma-ray detector.) Background count rates for the in-hole configuration were estimated by scaling up calculated surface background count rates proportionately to the ratios of radioactivities measured in-hole and on the surface. Results are listed on Table V, and indicate that high measured count rates (>500 c/sec) were predominantly from radon, while lower rates were mainly from U, Th and K in near-surface soil.

Radon Emanation in the Valley Away from the Springs

With the exception of one location, #54, the track density contour pattern is explained by the lithology of the valley-fill and sub-alluvial material in Buffalo Valley. Relatively high track densities on the east and southeast sides of the valley reflect the relatively thin veneer of alluvium covering rhyolitic ash flow tuffs, whose uranium contents range from 10 to 15 ppm and thorium from 30 to 50 ppm (unpublished data). These tuffs were deposited by volcanism associated with an active caldera 20 to 25 million years ago (McKee, 1970). A large proportion of the Tertiary and Quaternary sediments in the east and southeast sections of Buffalo Valley is tuffaceous material derived from the Fish Creek Mountains. The radioelement contents of near-surface soil samples in this area are similar to those in other areas of the valley, indicating that the high track densities observed are from radon emanating from deeper alluvial material, or from the tuffs themselves. The basalt cinder cones and flows bordering the east side of Buffalo Valley, of considerably lower radioactivity than the tuffs, are more limited in extent, and are considerably younger (age about 3 million years), than the tuffs. The basalt, therefore, has not contributed as much material to the deeper alluvium. Relatively low track densities in the rest of the area covered reflect the deep alluvial material, where debris predominates from Paleozoic and Mesozoic sedimentary terranes in the Tobin Range and northern Fish Creek Mountains.

Table V . Observed, background and net gamma radioactivities from ^{222}Rn in counts per second, in Buffalo Hot Springs area.

Tracks/mm ²	Observed		Background from U,Th,K in soil		Net, from Rn	
	Surface	In-hole	Surface	In-hole	Surface	In-hole
2598	2000	3500	210	368	1890	3132
--	750	1700	240	544	510	1156
27	400	575	335	481	65	94
355	1200	2100	242	423	958	1677
429	1200	2900	186	450	1014	2450
30	500	750	417	625	83	125
56	575	750	490	639	85	111
112	320	430	283	380	37	50
332	420	550	300	392	120	158
225	300	300	137	137	163	163

CONCLUSIONS

Radium, and therefore, high radioactivity, preferentially associates with CaCO_3 in hot-spring deposits. Where sinter and tufa are mixed in a deposit, the calcareous material has the highest radioactivity. Low-flowing, CaCO_3 -dominated spring systems appear to be the most radioactive. Some of the ^{222}Rn measured in hot-spring waters is derived directly from ^{226}Rn deposited on the spring walls, some from U and Ra at depth.

Relatively high uranium contents of cold-spring waters, compared to low contents in surface waters of hot springs, within a hydrologic area, suggest that uranium may be concentrated at depth within geothermal systems. The most likely mechanisms are reduction of U^{+6} to U^{+4} as meteoric water enters the system, and the retrograde solubility of uranium carbonate.

Radon alpha-track detectors, presently used successfully to delineate concealed uranium deposits, are also sensitive to radon emanated from radioactive geothermal systems.







Fig. 7



CBB 742-8765

Fig. -8-



XBL7412-8380

Fig. 9

ACKNOWLEDGMENTS

Richard Hose of the U. S. Geological Survey provided valuable guidance in the field. Alan Smith of Lawrence Berkeley Laboratory performed much of the gamma-ray spectrometry and was very helpful in its interpretation. I thank Harry Bowman, Alvin Hebert and Frank Asaro of LBL for stimulating discussions on probable mechanisms of uranium concentration, and Daniel Lovett of General Electric and H. W. Alter and James Gingrich of Terradex Corporation for preparation and processing of alpha-track detectors. Most of the track detectors were emplaced and retrieved, and soil samples obtained, by R. Solbau of the LBL Geothermal Group, to whom the author is indebted.

REFERENCES

- Alter, H. W., et al., U. S. Patent No. 3,665,194 issued May 23, 1972, "Radon Detection Using Track-Registration Materials".
- Beck, H. and G. de Planque, 1968, The radiation field in air due to the distribution of gamma-ray sources in the ground; HASL-195, Health and Safety Lab., U. S. Atomic Energy Commission, New York.
- Belin, R. E., 1959, Radon in New Zealand geothermal regions; *Geochim. et Cosmochim. Acta*, 16, pp. 181-191.
- Blake, C. A., C. F. Coleman, K. B. Brown, D. G. Hill, R. S. Lowrie and J. M. Schmidt, 1956, Studies in the carbonate-uranium system; *J. Amer. Chem. Soc.* v. 78, p. 5978.
- Bowman, H. R., A. J. Hebert, H. A. Wollenberg and F. Asaro, 1975, Trace, minor, and major elements in geothermal waters and associated rock formations (north-central Nevada); Abstract, Second UN Symposium on the Development and Use of Geothermal Resources, May 20-29, 1975.
- Fleischer, R. L., H. W. Alter, S. C. Furman, P. B. Price and R. M. Walker, 1972, Particle track etching; *Science*, 178, pp. 255-263.
- Gingrich, J. E., 1974, Results from a new uranium exploration method; presented at the American Institute of Mining Engineers, February 24-28, 1974, Dallas, Texas.

- Hitaye, I., 1962, Radiochemical studies on radioactive mineral springs III; Shizouka University Liberal Arts and Sciences Faculty Reports, National Science Section 3, No. 3, pp. 135-143.
- Israël, H. and S. Björnsson, 1967, Radon (Rn^{222}) and thoron (Rn^{220}) in soil air over faults; Zeitschrift für Geophysik, Jahrg. 33, pp. 48-64.
- Kikkawa, K., 1954, Study on radioactive springs; Japanese Journal of Geophysics, 1, pp. 1-25.
- Kimura, K., 1949, Geochemical studies on radioactive springs in Japan; Proceedings of the Seventh Pacific Science Association Congress, 2, pp. 485-499.
- Mariner, R. H., J. B. Rapp, L. M. Willey and T. S. Presser, 1974, The chemical composition and estimated minimum thermal reservoir temperature of the principal hot springs of northern and central Nevada; U. S. Geological Survey open file report.
- Mazor, E., 1962, Radon and radium content of some Israeli water sources and a hypothesis on underground reservoirs of brines, oils and gases in the Rift Valley; Geochim. et Cosmochim. Acta, 26, pp. 765-786.
- McKee, E., 1970, Fish Creek Mountains Tuff and Volcanic Center, Lander County, Nevada; U. S. Geological Survey Professional Paper 681.
- Mirk, K. and H. A. Wollenberg, 1974, The Lawrence Berkeley Laboratory geothermal program in northern Nevada; in Proceedings of a Conference on Research for the Development of Geothermal Energy Resources, Jet Propulsion Laboratory, September 23-25, 1974.
- Olmsted, F., P. A. Glancy, J. R. Harrill, F.E. Rush, and A. S. VanDenburgh, 1975, Preliminary hydrogeological appraisal of selected hydrothermal systems in northern and central Nevada; U. S. Geological Survey open file report 75-56.
- Pöhl-Rüling, J. and E. Scheminzy, 1972, The natural radiation environment of Badgastein, Austria, and its biological effects; presented at the Second Symposium on the Natural Radiation Environment, Houston, Texas.
- Scott, R. C. and F. B. Barker, 1962, Data on uranium and radium in ground water in the United States; U. S. Geological Survey Professional Paper 426.
- Stoker, A. K., and P. Kruger, 1975, Radon in geothermal reservoirs; Abstract, Second UN Symposium on the Development and Use of Geothermal Resources, May 20-29, 1975.

- Tanner, A. B., 1964, Physical and chemical controls on distribution of radium-226 and radon-222 in ground water near Great Salt Lake, Utah; in The Natural Radiation Environment, J. A. S. Adams and W. M. Lowder, eds., University of Chicago Press.
- Vincenz, S. A., 1959, Some observations of gamma radioactivity emitted by a mineral spring in Jamaica; Geophys. Prospecting, 7, pp. 422-434.
- Wollenberg, H. A., 1974a, Radioactivity of Nevada hot-spring systems; Geophysical Research Letters, 1, pp. 359-362.
- Wollenberg, H. A., 1974b, Radon alpha-track survey of a potential geothermal resource area; Lawrence Berkeley Laboratory report LBL-3225.

FIGURE CAPTIONS

- Fig. 1. Location map of hot springs visited in Nevada. Numbered springs:
1) Big Sulfur, 2) Elko, 3) Beowawe, 4) Spencer, 5) Diana's Punchbowl,
6) Darrough, 7) Buffalo Valley, 8) Golconda, 9) Pumpnickel,
10) Leach, 11) Fly Ranch, 12) Gerlach, 13) Brady, 14) Lee,
15) Wabuska, 16) Steamboat, 17) Kyle.
- Fig. 2. Field gamma counter. The 3-in. by 3-in. NaI(Tl) scintillation crystal and photomultiplier tube are encased by the steel cylinder, and are connected to the accompanying count-rate meter.
- Fig. 3. Field gamma radioactivity and water-temperature measurements at Big Sulfur Hot Springs, Ruby Valley, Nevada.
- Fig. 4. The uranium-238 decay series, indicating half-lives.
- Fig. 5. Gamma-ray spectra in the energy region 40 to 100 keV. The spectra were taken on a high-resolution system, utilizing a $10 \text{ cm}^3 \text{ Ge (Li)}$ detector.
- Fig. 6. Schematic cutaway diagram of a geothermal system within a permeable fault zone. Meteoric water enters the fault zone where it intersects near-surface aquifers. Some of the water percolates downward to regions where temperatures reach 150 to 200°C, is heated and rises on the upward limb of a convection cell. Hot springs occur where the cell intersects the surface.
- Fig. 7. Sketch map of Buffalo Valley Hot Springs area, showing locations of some of the warm pools, temperatures, and normalized track densities.

FIGURE CAPTIONS (cont'd)

Fig. 8. Contours of radon alpha-track density (in tracks/mm, normalized to a 30-day exposure) in Buffalo Valley. Dotted numbers: locations.

Fig. 9. Frequency distribution of track densities normalized to a 30-day exposure (a), and (b), uranium contents of soils from track detector holes in Buffalo Valley.

LEGAL NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

TECHNICAL INFORMATION DIVISION
LAWRENCE BERKELEY LABORATORY
UNIVERSITY OF CALIFORNIA
BERKELEY, CALIFORNIA 94720