Lawrence Berkeley National Laboratory

Lawrence Berkeley National Laboratory

Title

NDCX-II injector with a 10.9-cm diameter Li+ ion source

Permalink

https://escholarship.org/uc/item/6q9500vd

Author

Roy, P. K.

Publication Date 2011-12-30

NDCX-II injector with a 10.9-cm diameter Li⁺ ion source

P. K. Roy¹, W. Greenway¹, D. P. Grote², J. Y. Jung¹, J. W. Kwan¹, P. A. Seidl¹, J. Takakuwa¹, J. L. Vay¹ and W. Waldron¹

¹Lawrence Berkeley National Laboratory (LBNL), Berkeley, CA

²Lawrence Livermore National Laboratory (LLNL), Livermore, CA

The Neutralized Drift Compression Experiment II (NDCX-II) is an accelerator facility for warm dense matter studies. It will generate a short Li^+ ion beam pulse (~ 1 ns) at up to a few MeV ion kinetic energy to uniformly heat thin targets to ~ 1 eV temperature. The NDCX-II induction linac has a 130-kV injector that produces ~ 100-mA, 0.5-µs ion current from a 10.9-cm diameter lithium alumino-silicate ion source. The fabrication and operation of the ion source is challenging due to the high current density required, the difficulty in coating the large emitter and the high operating temperature of 1275°C. Required power to heat the source is 3.4 kW and calculated temperature variation across the surface is 9.8°C. Details of the NDCX-II injector design and initial beam optics will be presented.

*This work was supported by the U.S Department of Energy, OFES, under contract DE-AC02-05CH11231.

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor the Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or the Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the Regents of the University of California.